

ETSI TS 138 101-1 V17.5.0 (2022-05)



**5G;
NR;**

**User Equipment (UE) radio transmission and reception;
Part 1: Range 1 Standalone
(3GPP TS 38.101-1 version 17.5.0 Release 17)**

<https://standards.iteh.ai/catalog/standards/sist/cfe2ec21-2d19-4597-aed6-0c227a76474f/etsi-ts-138-101-1-v17-5-0-2022-05>



Reference

RTS/TSGR-0438101-1vh50

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.

All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal notice

(standards.iteh.ai)

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal notice	2
Modal verbs terminology	2
Foreword	17
1 Scope	19
2 References	19
3 Definitions, symbols and abbreviations	20
3.1 Definitions	20
3.2 Symbols	21
3.3 Abbreviations	23
4 General	24
4.1 Relationship between minimum requirements and test requirements	24
4.2 Applicability of minimum requirements	24
4.3 Specification suffix information	24
5 Operating bands and channel arrangement	25
5.1 General	25
5.2 Operating bands	26
5.2A Operating bands for CA	28
5.2A.0 General	28
5.2A.1 Intra-band CA	28
5.2A.2 Inter-band CA	29
5.2A.2.1 Inter-band CA (two bands)	30
5.2A.2.2 Inter-band CA (three bands)	36
5.2A.2.3 Inter-band CA (four bands)	40
5.2A.2.4 Inter-band CA (five bands)	41
5.2B Operating bands for DC	41
5.2C Operating band combination for SUL	41
5.2D Operating bands for UL MIMO	43
5.2E Operating band for V2X	44
5.2E.1 V2X operating bands	44
5.2E.2 V2X operating bands for con-current operation	44
5.3 UE channel bandwidth	45
5.3.1 General	45
5.3.2 Maximum transmission bandwidth configuration	47
5.3.3 Minimum guardband and transmission bandwidth configuration	47
5.3.4 RB alignment	49
5.3.5 UE channel bandwidth per operating band	49
5.3.6 Asymmetric channel bandwidths	53
5.3A UE channel bandwidth for CA	54
5.3A.1 General	54
5.3A.2 Maximum transmission bandwidth configuration for CA	54
5.3A.3 Minimum guardband and transmission bandwidth configuration for CA	54
5.3A.4 Void	56
5.3A.5 UE channel bandwidth per operating band for CA	56
5.3E Channel bandwidth for V2X	57
5.3E.1 General	57
5.3E.2 Channel bandwidth for V2X concurrent operation	58
5.3I Channel bandwidth for RedCap	59
5.4 Channel arrangement	59
5.4.1 Channel spacing	59
5.4.1.1 Channel spacing for adjacent NR carriers	59
5.4.2 Channel raster	59
5.4.2.1 NR-ARFCN and channel raster	59

5.4.2.2	Channel raster to resource element mapping.....	60
5.4.2.3	Channel raster entries for each operating band	60
5.4.3	Synchronization raster	64
5.4.3.1	Synchronization raster and numbering.....	64
5.4.3.3	Synchronization raster entries for each operating band.....	64
5.4.4	TX–RX frequency separation	67
5.4A	Channel arrangement for CA.....	68
5.4A.1	Channel spacing for CA.....	68
5.4A.2	Channel raster for CA	69
5.4A.3	Synchronization raster for CA	69
5.4A.4	Tx-Rx frequency separation for CA.....	69
5.4B	Reserved	69
5.4C	Reserved	69
5.4D	Reserved	69
5.4E	Channel arrangement for V2X	69
5.4E.1	Channel spacing.....	69
5.4E.2	Channel raster	70
5.4E.2.1	NR-ARFCN and channel raster.....	70
5.4E.2.2	Channel raster to resource element mapping.....	70
5.4E.2.3	Channel raster entries for each operating band	70
5.4E.3	Synchronization raster for V2X	70
5.5	Void.....	70
5.5A	Configurations for CA.....	70
5.5A.0	General.....	70
5.5A.1	Configurations for intra-band contiguous CA.....	71
5.5A.2	Configurations for intra-band non-contiguous CA	76
5.5A.3	Configurations for inter-band CA.....	80
5.5A.3.1	Configurations for inter-band CA (two bands)	80
5.5A.3.2	Configurations for inter-band CA (three bands)	106
5.5A.3.3	Configurations for inter-band CA (four bands).....	171
5.5A.3.4	Configurations for inter-band CA (five bands).....	221
5.5B	Configurations for DC.....	225
5.5C	Configurations for SUL.....	230
6	Transmitter characteristics.....	236
6.1	General	236
6.1A	General	236
6.1F	General	236
6.2	Transmitter power	236
6.2.1	UE maximum output power.....	236
6.2.1I	Maximum output power for RedCap UE.....	238
6.2.2	UE maximum output power reduction.....	238
6.2.3	UE additional maximum output power reduction	241
6.2.3.1	General	241
6.2.3.2	A-MPR for NS_04	246
6.2.3.3	A-MPR for NS_10	247
6.2.3.4	A-MPR for NS_05 and NS_05U.....	247
6.2.3.5	A-MPR for NS_40	251
6.2.3.6	A-MPR for NS_43 and NS_43U.....	252
6.2.3.7	A-MPR for NS_03 and NS_03U.....	253
6.2.3.8	A-MPR for NS_37	253
6.2.3.9	A-MPR for NS_38	254
6.2.3.10	A-MPR for NS_39	254
6.2.3.11	A-MPR for NS_41	255
6.2.3.12	A-MPR for NS_42	255
6.2.3.13	A-MPR for NS_18	256
6.2.3.14	A-MPR for NS_21	256
6.2.3.15	A-MPR for NS_24	257
6.2.3.16	A-MPR for NS_27	258
6.2.3.17	A-MPR for NS_46	259
6.2.3.18	A-MPR for NS_47	260
6.2.3.19	A-MPR for NS_50	261

6.2.3.20	A-MPR for NS_44	263
6.2.3.21	A-MPR for NS_12	263
6.2.3.22	A-MPR for NS_13	264
6.2.3.23	A-MPR for NS_14	264
6.2.3.24	A-MPR for NS_15	265
6.2.3.25	A-MPR for NS_45	266
6.2.3.26	A-MPR for NS_48	266
6.2.3.27	A-MPR for NS_49	268
6.2.3.28	A-MPR for NS_51	270
6.2.3.29	A-MPR for NS_07	270
6.2.3.30	A-MPR for NS_56	271
6.2.4	Configured transmitted power	272
6.2A	Transmitter power for CA	274
6.2A.1	UE maximum output power for CA	274
6.2A.1.1	UE maximum output power for Intra-band contiguous CA	274
6.2A.1.2	UE maximum output power for Intra-band non-contiguous CA	275
6.2A.1.3	UE maximum output power for Inter-band CA	275
6.2A.1.4	Void	280
6.2A.1.5	Void	280
6.2A.2	UE maximum output power reduction for CA	280
6.2A.2.1	UE maximum output power reduction for Intra-band contiguous CA	280
6.2A.2.2	UE maximum output power reduction for Intra-band non-contiguous CA	283
6.2A.2.2.0	General	283
6.2A.2.2.1	MPR to meet -30dBm/MHz	284
6.2A.2.2.1.1	PC3 with indicating dualPA-Architecture supported	284
6.2A.2.2.1.2	PC2 with indicating dualPA-Architecture supported	285
6.2A.2.2.1.3	PC3 without indicating dualPA-Architecture supported	285
6.2A.2.2.1.4	PC2 without indicating dualPA-Architecture supported	285
6.2A.2.2.2	MPR to meet -13dBm/MHz	286
6.2A.2.2.2.1	PC3 with indicating dualPA-Architecture supported	286
6.2A.2.2.2.2	PC2 with indicating dualPA-Architecture supported	286
6.2A.2.2.2.3	PC3 without indicating dualPA-Architecture supported	286
6.2A.2.2.2.4	PC2 without indicating dualPA-Architecture supported	287
6.2A.2.3	UE maximum output power reduction for Inter-band CA	287
6.2A.2.4	Void	287
6.2A.3	UE additional maximum output power reduction for CA	287
6.2A.3.1.1	UE additional maximum output power reduction for Intra-band contiguous CA	287
6.2A.3.1.1.1	A-MPR for CA_NS_04	288
6.2A.3.1.2	UE additional maximum output power reduction for Intra-band non-contiguous CA	294
6.2A.3.1.3	UE additional maximum output power reduction for Inter-band CA	296
6.2A.4	Configured output power for CA	299
6.2A.4.1	Configured transmitted power level	299
6.2A.4.1.1	Configured transmitted power for Intra-band contiguous CA	299
6.2A.4.1.2	Configured transmitted power for Intra-band non-contiguous CA	301
6.2A.4.1.3	Configured transmitted power for Inter-band CA	304
6.2A.4.1.4	Void	307
6.2A.4.2	$\Delta T_{IB,c}$ for CA	307
6.2A.4.2.1	Void	307
6.2A.4.2.2	Void	307
6.2A.4.2.3	$\Delta T_{IB,c}$ for Inter-band CA (two bands)	307
6.2A.4.2.4	$\Delta T_{IB,c}$ for Inter-band CA (three bands)	314
6.2A.4.2.5	$\Delta T_{IB,c}$ for Inter-band CA (four bands)	325
6.2A.4.2.6	$\Delta T_{IB,c}$ for Inter-band CA (five bands)	329
6.2B	Transmitter power for NR-DC	329
6.2B.0	General	329
6.2B.1	UE maximum output power for NR-DC	329
6.2B.2	UE maximum output power reduction for NR-DC	330
6.2B.3	UE additional maximum output power reduction for NR-DC	330
6.2B.4.1	Configured transmitted power level for NR-DC	331
6.2B.4.2	$\Delta T_{IB,c}$ for NR-DC	335
6.2C	Transmitter power for SUL	335
6.2C.1	Configured transmitted power for SUL	335

6.2C.2	$\Delta T_{IB,c}$	336
6.2D	Transmitter power for UL MIMO	337
6.2D.1	UE maximum output power for UL MIMO.....	337
6.2D.2	UE maximum output power reduction for UL MIMO.....	339
6.2D.3	UE additional maximum output power reduction for UL MIMO.....	340
6.2D.4	Configured transmitted power for UL MIMO	340
6.2E	Transmitter power for V2X	341
6.2E.1	UE maximum output power for V2X	341
6.2E.1.1	General	341
6.2E.1.2	UE maximum output power for V2X con-current operation	342
6.2E.2	UE maximum output power reduction for V2X	343
6.2E.2.1	General	343
6.2E.2.2	MPR for Power class 2 and Power class 3 V2X UE	343
6.2E.2.3	MPR for Power class 2 and Power class 3 V2X con-current operation	345
6.2E.2.4	MPR for Power class 1 UE in n14	347
6.2E.3	UE additional maximum output power reduction for V2X.....	347
6.2E.3.1	General	347
6.2E.3.2	A-MPR for V2X UE by NS_33	348
6.2E.3.3	A-MPR for Power class 3 V2X UE by NS_52	351
6.2E.3.4	A-MPR for V2X con-current operation	352
6.2E.4	Configured transmitted power for V2X.....	353
6.2E.4.1	General	353
6.2E.4.2	Configured transmitted power for inter-band V2X con-current operation.....	353
6.2E.4.3	Configured transmitted power for intra-band V2X con-current operation.....	354
6.2F	Transmitter power for shared spectrum channel access	356
6.2F.1	UE maximum output power	356
6.2F.1A	UE maximum output power for CA	357
6.2F.1A.1	UE maximum output power for inter-band CA.....	357
6.2F.2	UE maximum output power reduction.....	358
6.2F.2A	UE maximum output power reduction for CA.....	359
6.2F.2A.1	UE maximum output power reduction for inter-band CA.....	359
6.2F.3	UE additional maximum output power reduction	359
6.2F.3.1	General	359
6.2F.3.2	A-MPR for NS_28	359
6.2F.3.3	A-MPR for NS_29	360
6.2F.3.4	A-MPR for NS_30	360
6.2F.3.5	A-MPR for NS_31	361
6.2F.3.6	A-MPR for NS_53	361
6.2F.3.7	A-MPR for NS_54	362
6.2F.3.8	A-MPR for NS_58	362
6.2F.3.9	A-MPR for NS_59	363
6.2F.3.10	A-MPR for NS_60	364
6.2F.3A	UE additional maximum output power reduction for CA.....	364
6.2F.3A.1	UE additional maximum output power reduction for inter-band CA.....	364
6.2F.4	Configured transmitted power	364
6.2G	Transmitter power for Tx Diversity.....	364
6.2G.1	UE maximum output power for Tx Diversity	364
6.2G.2	UE maximum output power reduction for Tx Diversity	364
6.2G.3	UE additional maximum output power reduction for Tx Diversity	365
6.2G.4	Configured transmitted power for Tx Diversity.....	365
6.2H	Transmitter power for CA with UL MIMO.....	365
6.2H.1	Transmitter power for intra-band UL contiguous CA for UL MIMO	365
6.2H.1.1	UE maximum output power for intra-band UL contiguous CA for UL MIMO.....	365
6.2H.1.2	UE maximum output power reduction for intra-band UL contiguous CA for UL MIMO	366
6.2H.1.3	UE additional maximum output power reduction for intra-band UL contiguous CA for UL MIMO	366
6.2H.1.4	Configured transmitted power for intra-band UL contiguous CA for UL MIMO	366
6.3	Output power dynamics.....	367
6.3.1	Minimum output power	367
6.3.2	Transmit OFF power.....	367
6.3.3	Transmit ON/OFF time mask	368
6.3.3.1	General	368

6.3.3.2	General ON/OFF time mask	368
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries.....	369
6.3.3.4	PRACH time mask.....	369
6.3.3.5	Void.....	371
6.3.3.6	SRS time mask	371
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	372
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	373
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	374
6.3.4	Power control.....	375
6.3.4.1	General	375
6.3.4.2	Absolute power tolerance.....	375
6.3.4.3	Relative power tolerance.....	375
6.3.4.4	Aggregate power tolerance.....	376
6.3A	Output power dynamics for CA	376
6.3A.1	Minimum output power for CA 6.3A.1.1..... Minimum output power for intra-band contiguous CA	376
6.3A.1.2	Minimum output power for intra-band non-contiguous CA	376
6.3A.1.3	Minimum output power for inter-band CA	376
6.3A.1.4	Void.....	377
6.3A.2	Transmit OFF power for CA.....	377
6.3A.2.1	Transmit OFF power for intra-band contiguous CA	377
6.3A.2.2	Transmit OFF power for intra-band non-contiguous CA	377
6.3A.2.3	Transmit OFF power for inter-band CA.....	377
6.3A.2.4	Void.....	377
6.3A.3	Transmit ON/OFF time mask for CA	377
6.3A.3.1	Transmit ON/OFF time mask for intra-band contiguous CA	377
6.3A.3.2	Transmit ON/OFF time mask for intra-band non-contiguous CA	378
6.3A.3.3	Transmit ON/OFF time mask for inter-band CA	378
6.3A.3.3.1	General	378
6.3A.3.3.2	Time mask for switching between two uplink carriers	378
6.3A.3.3.3	Time mask for switching between two uplink carriers with two transmit antenna connectors	379
6.3A.3.3.4	Time mask for switching between one uplink band with one transmit antenna connector and one uplink band with two transmit antenna connectors	380
6.3A.3.3.5	Time mask for switching between two uplink bands with two transmit antenna connectors	381
6.3A.3.4	Void.....	382
6.3A.4	Power control for CA.....	382
6.3A.4.1	Power control for intra-band contiguous CA	382
6.3A.4.1.1	Absolute power tolerance	382
6.3A.4.1.2	Relative power tolerance	382
6.3A.4.1.3	Aggregate power control tolerance.....	383
6.3A.4.2	Power control for intra-band non-contiguous CA	383
6.3A.4.2.1	Absolute power tolerance.....	383
6.3A.4.2.1.1	Minimum requirements	383
6.3A.4.2.2	Relative power tolerance	383
6.3A.4.2.2.1	Minimum requirements	383
6.3A.4.2.3	Aggregate power control tolerance	383
6.3A.4.3	Power control for inter-band CA.....	383
6.3A.4.4	Void.....	383
6.3B	Output power dynamics for NR-DC.....	383
6.3C	Output power dynamics for SUL	384
6.3C.1	Void	384
6.3C.2	Void	384
6.3C.3	Transmit ON/OFF time mask for SUL	384
6.3C.3.1	Time mask for switching between two uplink carriers.....	384
6.3C.3.2	Time mask for switching between two uplink carriers with two transmit antenna connectors	385
6.3C.3.3	Time mask for switching between one uplink band with one transmit antenna connector and one uplink band with two transmit antenna connectors	385
6.3C.3.4	Time mask for switching between two uplink bands with two transmit antenna connectors.....	386
6.3D	Output power dynamics for UL MIMO	387
6.3D.1	Minimum output power for UL MIMO	387
6.3D.2	Transmit OFF power for UL MIMO.....	387

6.3D.3	Transmit ON/OFF time mask for UL MIMO	387
6.3D.4	Power control for UL MIMO.....	388
6.3E	Output power dynamics for V2X	388
6.3E.1	Minimum output power for V2X.....	388
6.3E.1.1	General	388
6.3E.1.2	Minimum output power for V2X con-current operation.....	388
6.3E.2	Transmit OFF power for V2X	389
6.3E.2.1	General	389
6.3E.2.2	Transmit OFF power for V2X con-current operation	389
6.3E.3	Transmit ON/OFF time mask for V2X.....	389
6.3E.3.1	General	389
6.3E.3.2	General time mask.....	389
6.3E.3.3	S-SSB time mask	390
6.3E.3.4	Transmit ON/OFF time mask for V2X con-current operation.....	390
6.3E.4	Power control for V2X	391
6.3E.4.1	General	391
6.3E.4.2	Absolute power tolerance.....	392
6.3E.4.3	Power control for V2X con-current operation.....	392
6.3F	Output power dynamics for shared spectrum channel access.....	392
6.3F.1	Minimum output power	392
6.3F.2	Transmit OFF power.....	392
6.3F.3	Transmit ON/OFF time mask	392
6.3F.3.1	General	392
6.3F.3.2	General ON/OFF time mask	392
6.3F.3A	General ON/OFF mask for CA	393
6.3F.3A.1	General ON/OFF mask for inter-band CA	393
6.3F.4	Power control.....	393
6.3F.4.1	General	393
6.3F.4.2	Absolute power tolerance.....	393
6.3F.4.3	Relative power tolerance.....	393
6.3F.4.4	Aggregate power tolerance.....	393
6.3G	Output power dynamics for Tx Diversity.....	393
6.3G.1	Minimum output power for Tx Diversity.....	393
6.3G.2	Transmit OFF power for Tx Diversity.....	394
6.3G.3	Transmit ON/OFF time mask for Tx Diversity	394
6.3G.4	Power control for Tx Diversity.....	394
6.3H	Output power dynamics for intra-band UL contiguous CA for UL MIMO	394
6.3H.1	Minimum output power for intra-band UL contiguous CA for UL MIMO	394
6.3H.2	Transmit OFF power for intra-band UL contiguous CA for UL MIMO	394
6.3H.3	Transmit ON/OFF time mask for intra-band UL contiguous CA for UL MIMO	394
6.3H.4	Power control for intra-band UL contiguous CA for UL MIMO.....	394
6.4	Transmit signal quality	395
6.4.1	Frequency error.....	395
6.4.2	Transmit modulation quality.....	395
6.4.2.1	Error Vector Magnitude	395
6.4.2.1a	Error Vector Magnitude including symbols with transient period	396
6.4.2.2	Carrier leakage	397
6.4.2.3	In-band emissions	397
6.4.2.4	EVM equalizer spectrum flatness	398
6.4.2.4.1	Requirements for Pi/2 BPSK modulation.....	399
6.4A	Transmit signal quality for CA.....	400
6.4A.1	Frequency error for CA.....	400
6.4A.1.1	Frequency error for intra-band contiguous CA	400
6.4A.1.2	Frequency error for intra-band non-contiguous CA.....	400
6.4A.1.3	Frequency error for inter-band CA.....	400
6.4A.1.4	Void.....	401
6.4A.2	Transmit modulation quality for CA.....	401
6.4A.2.1	Transmit modulation quality for intra-band contiguous CA	401
6.4A.2.1.1	Error Vector Magnitude.....	401
6.4A.2.1.2	In-band emissions.....	401
6.4A.2.1.3	Carrier leakage.....	404
6.4A.2.2	Transmit modulation quality for intra-band non-contiguous CA	404

6.4A.2.2.0	General	404
6.4A.2.2.1	Error Vector Magnitude	404
6.4A.2.2.2	In-band emissions	405
6.4A.2.2.3	Carrier leakage.....	405
6.4A.2.3	Transmit modulation quality for inter-band CA.....	405
6.4A.2.4	Void.....	405
6.4B	Transmit signal quality for NR-DC.....	405
6.4D	Transmit signal quality for UL MIMO.....	405
6.4D.1	Frequency error for UL MIMO.....	405
6.4D.2	Transmit modulation quality for UL MIMO.....	406
6.4D.2.1	Error Vector Magnitude	406
6.4D.2.2	Carrier leakage	406
6.4D.2.3	In-band emissions	406
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO	406
6.4D.3	Time alignment error for UL MIMO	406
6.4D.4	Requirements for coherent UL MIMO	407
6.4E	Transmit signal quality for V2X.....	407
6.4E.1	Frequency error for V2X	407
6.4E.1.1	General	407
6.4E.1.2	Frequency error for V2X con-current operation	408
6.4E.2	Transmit modulation quality for V2X	408
6.4E.2.1	General	408
6.4E.2.2	Error Vector Magnitude for V2X.....	408
6.4E.2.3	Carrier leakage for V2X.....	408
6.4E.2.4	In-band emissions for V2X.....	408
6.4E.2.5	EVM equalizer spectrum flatness for V2X	408
6.4E.2.6	Transmit modulation quality for V2X con-current operation	408
6.4F	Transmit signal quality for shared spectrum channel access	409
6.4F.1	Frequency error.....	409
6.4F.2	Transmit modulation quality.....	409
6.4F.2.1	Error Vector Magnitude	409
6.4F.2.2	Carrier leakage	409
6.4F.2.3	In-band emissions	409
6.4F.2.4	EVM equalizer spectrum flatness	410
6.4F.2A	Transmit modulation quality for CA	410
6.4F.2A.1	Transmit modulation quality for inter-band CA	410
6.4G	Transmit signal quality for Tx Diversity	411
6.4G.1	Frequency error for Tx Diversity.....	411
6.4G.2	Transmit modulation quality for Tx Diversity	411
6.4H	Transmit signal quality for CA with UL MIMO	412
6.4H.1	Transmit signal quality for intra-band UL contiguous CA for UL MIMO	412
6.4H.1.1	Frequency error for intra-band UL contiguous CA for UL MIMO.....	412
6.4H.1.2	Transmit modulation quality for intra-band UL contiguous CA for UL MIMO.....	412
6.4H.1.2.1	Error Vector Magnitude.....	412
6.4H.1.2.2	Carrier leakage.....	412
6.4H.1.2.3	In-band emissions.....	412
6.4H.1.3	Time alignment error for intra-band UL contiguous CA for UL MIMO	412
6.4H.1.4	Coherent UL MIMO requirement for intra-band UL contiguous CA for UL MIMO	412
6.5	Output RF spectrum emissions.....	413
6.5.1	Occupied bandwidth	413
6.5.2	Out of band emission	413
6.5.2.1	General	413
6.5.2.2	Spectrum emission mask	413
6.5.2.3	Additional spectrum emission mask	414
6.5.2.3.1	Requirements for network signalling value "NS_35".....	414
6.5.2.3.2	Requirements for network signalling value "NS_04".....	414
6.5.2.3.3	Requirements for network signalling value "NS_03" and "NS_21"	415
6.5.2.3.4	Requirements for network signalling value "NS_06" or "NS_07"	415
6.5.2.3.5	Void.....	416
6.5.2.3.6	Void.....	416
6.5.2.3.7	Void.....	416
6.5.2.3.8	Requirements for network signalling value "NS_27"	416

6.5.2.4	Adjacent channel leakage ratio	416
6.5.2.4.1	NR ACLR.....	417
6.5.2.4.2	UTRA ACLR	417
6.5.3	Spurious emissions	418
6.5.3.1	General spurious emissions.....	418
6.5.3.2	Spurious emissions for UE co-existence.....	418
6.5.3.3	Additional spurious emissions	426
6.5.3.3.1	Requirement for network signalling value "NS_04"	426
6.5.3.3.2	Requirement for network signalling value "NS_17"	427
6.5.3.3.3	Requirement for network signalling value "NS_18"	427
6.5.3.3.4	Requirement for network signalling value "NS_05"	427
6.5.3.3.5	Requirement for network signalling value "NS_43"	427
6.5.3.3.6	Requirement for network signalling value "NS_37"	428
6.5.3.3.7	Requirement for network signalling value "NS_38"	428
6.5.3.3.8	Requirement for network signalling value "NS_39"	428
6.5.3.3.9	Requirement for network signalling value "NS_40"	428
6.5.3.3.10	Requirement for network signalling value "NS_41"	429
6.5.3.3.11	Requirement for network signalling value "NS_42"	429
6.5.3.3.12	Requirement for network signalling value "NS_21"	429
6.5.3.3.13	Requirement for network signalling value "NS_24"	430
6.5.3.3.14	Requirement for network signalling value "NS_27"	430
6.5.3.3.15	Requirement for network signalling value "NS_47"	430
6.5.3.3.16	Requirement for network signalling value "NS_50"	431
6.5.3.3.17	Requirement for network signalling value "NS_12"	431
6.5.3.3.18	Requirement for network signalling value "NS_13"	431
6.5.3.3.19	Requirement for network signalling value "NS_14"	432
6.5.3.3.20	Requirement for network signalling value "NS_15"	432
6.5.3.3.21	Requirement for network signalling value "NS_45"	432
6.5.3.3.22	Requirement for network signalling values "NS_48" and "NS_51"	433
6.5.3.3.23	Requirement for network signalling value "NS_49"	433
6.5.3.3.24	Requirement for network signalling value "NS_44"	433
6.5.3.3.25	Requirement for network signalling value "NS_46"	434
6.5.3.3.26	Requirement for network signalling value "NS_07"	434
6.5.3.3.27	Requirement for network signalling value "NS_56"	434
6.5.4	Transmit intermodulation	435
6.5A	Output RF spectrum emissions for CA.....	435
6.5A.1	Occupied bandwidth for CA	436
6.5A.1.1	Void.....	436
6.5A.1.1a	Occupied bandwidth for Intra-band contiguous CA	436
6.5A.1.2	Occupied bandwidth for Intra-band non-contiguous CA	436
6.5A.1.3	Occupied bandwidth for Inter-band CA	436
6.5A.2	Out of band emission for CA	436
6.5A.2.1	General	436
6.5A.2.2	Spectrum emission mask	436
6.5A.2.2.1	Spectrum emission mask for intra-band contiguous C	436
6.5A.2.2.2	Spectrum emission mask for intra-band non-contiguous CA	437
6.5A.2.2.3	Spectrum emission mask for Inter-band CA	437
6.5A.2.2.4	Void	437
6.5A.2.3	Additional spectrum emission mask for CA	437
6.5A.2.3.1	Additional spectrum emission mask for intra-band contiguous CA	437
6.5A.2.3.2	Additional spectrum emission mask for Intra-band non-contiguous CA	438
6.5A.2.3.3	Additional spectrum emission mask for Inter-band CA	438
6.5A.2.4	Adjacent channel leakage ratio	438
6.5A.2.4.1	NR ACLR.....	438
6.5A.2.4.2	UTRA ACLR	440
6.5A.3	Spurious emission for CA.....	440
6.5A.3.1	General spurious emissions.....	440
6.5A.3.2	Spurious emissions for UE co-existence	441
6.5A.3.2.1	Spurious emissions for UE co-existence for intra-band contiguous CA	441
6.5A.3.2.2	Spurious emissions for UE co-existence for intra-band non-contiguous CA	443
6.5A.3.2.3	Spurious emissions for UE co-existence for Inter-band CA	443
6.5A.3.2.4	Void	463

6.5A.3.2.5	Void.....	463
6.5A.3.2.6	Void.....	463
6.5A.3.3	Additional spurious emissions for CA	463
6.5A.3.3.1	Additional spurious emissions for intra-band contiguous CA.....	463
6.5A.4	Transmit intermodulation for CA	464
6.5A.4.2.1	Transmit intermodulation for intra-band contiguous CA	464
6.5A.4.2.2	Void.....	464
6.5B	Output RF spectrum emissions for NR-DC.....	464
6.5D	Output RF spectrum emissions for UL MIMO.....	465
6.5D.1	Occupied bandwidth for UL MIMO	465
6.5D.2	Out of band emission for UL MIMO	465
6.5D.3	Spurious emission for UL MIMO.....	465
6.5D.4	Transmit intermodulation for UL MIMO	465
6.5E	Output RF spectrum emissions for V2X	466
6.5E.1	Occupied bandwidth for V2X.....	466
6.5E.1.1	General	466
6.5E.1.2	Occupied bandwidth for V2X con-current operation.....	466
6.5E.2	Out of band emission for V2X.....	466
6.5E.2.1	General	466
6.5E.2.2	Spectrum emission mask.....	466
6.5E.2.2.1	General	466
6.5E.2.2.2	Spectrum emission mask for V2X con-current operation.....	466
6.5E.2.3	Additional Spectrum emission mask.....	467
6.5E.2.3.1	Requirements for network signalling value "NS_33".....	467
6.5E.2.3.2	Requirements for network signalling value "NS_52".....	467
6.5E.2.3.3	Requirements for network signalling value "NS_06".....	468
6.5E.2.4	Adjacent channel leakage ratio	468
6.5E.2.4.1	General	468
6.5E.2.4.2	ACLR for V2X con-current operation.....	468
6.5E.3	Spurious emissions for V2X.....	468
6.5E.3.1	General spurious emissions.....	468
6.5E.3.2	Spurious emissions for UE co-existence.....	468
6.5E.3.3	Spurious emissions for UE co-existence for V2X con-current operation	469
6.5E.3.4	Additional spurious emissions requirements for V2X.....	471
6.5E.3.4.1	General	471
6.5E.3.4.2	Requirements for network signalling value "NS_33".....	471
6.5E.3.4.3	Void.....	471
6.5E.4	Transmit intermodulation	471
6.5E.4.1	General	471
6.5E.4.2	Transmit intermodulation for V2X con-current operation	471
6.5F	Output RF spectrum emissions.....	472
6.5F.1	Occupied bandwidth	472
6.5F.2	Out of band emission.....	472
6.5F.2.1	General	472
6.5F.2.2	Spectrum emission mask for operation with shared spectrum channel access.....	472
6.5F.2.2.1	Spectrum emission mask for non-transmitted channels.....	473
6.5F.2.3	Additional spectrum emission mask	473
6.5F.2.4	Adjacent channel leakage ratio	473
6.5F.2.4.1	Shared spectrum channel access ACLR	473
6.5F.2.4.2	Additional requirement for network signaled value "NS_29".....	473
6.5F.3	Spurious emissions	474
6.5F.3.1	General spurious emissions.....	474
6.5F.3.2	Spurious emissions for UE co-existence.....	474
6.5F.3.3	Additional spurious emissions	474
6.5F.3.3.1	Requirement for network signalling value "NS_28"	474
6.5F.3.3.2	Requirement for network signalling value "NS_29"	474
6.5F.3.3.3	Requirement for network signalling value "NS_30"	476
6.5F.3.3.4	Requirement for network signalling value "NS_31"	477
6.5F.3.3.5	Requirements for network signalling value "NS_53" or "NS_54" or "NS_60".....	478
6.5F.3.3.6	Requirements for network signalling value "NS_58"	478
6.5F.4	Transmit intermodulation	478
6.5G	Output RF spectrum emissions for Tx Diversity	478

6.5G.1	Occupied bandwidth for Tx Diversity	478
6.5G.2	Out of band emission for Tx Diversity	478
6.5G.3	Spurious emission for Tx Diversity	479
6.5G.4	Transmit intermodulation for Tx Diversity.....	479
6.5H	Output RF spectrum emissions for CA with UL MIMO	479
6.5H.1	Output RF spectrum emissions for intra-band UL contiguous CA for UL MIMO	479
6.5H.1.1	Occupied bandwidth for intra-band UL contiguous CA for UL MIMO	479
6.5H.1.2	Out of band emission for intra-band UL contiguous CA for UL MIMO	479
6.5H.1.3	Spurious emission for intra-band UL contiguous CA for UL MIMO	479
6.5H.1.4	Transmit intermodulation for intra-band UL contiguous CA for UL MIMO.....	479
6.6	Void.....	480
6.6E	Time alignment error.....	480
7	Receiver characteristics	481
7.1	General	481
7.1A	General	481
7.1F	General	482
7.1I	General	482
7.2	Diversity characteristics	482
7.3	Reference sensitivity	482
7.3.1	General.....	482
7.3.2	Reference sensitivity power level	482
7.3.3	$\Delta R_{IB,c}$	490
7.3A	Reference sensitivity for CA	490
7.3A.1	General.....	490
7.3A.2	Reference sensitivity power level for CA	490
7.3A.2.1	Reference sensitivity power level for Intra-band contiguous CA	490
7.3A.2.2	Reference sensitivity power level for Intra-band non-contiguous CA	491
7.3A.2.3	Reference sensitivity power level for Inter-band CA	492
7.3A.2.4	Void.....	492
7.3A.3	$\Delta R_{IB,c}$ for CA	493
7.3A.3.1	General	493
7.3A.3.2	$\Delta R_{IB,c}$ for Inter-band CA	493
7.3A.3.2.1	$\Delta R_{IB,c}$ for two bands	494
7.3A.3.2.2	Void	498
7.3A.3.2.3	$\Delta R_{IB,c}$ for three bands	498
7.3A.3.2.4	$\Delta R_{IB,c}$ for four bands	506
7.3A.3.2.5	$\Delta R_{IB,c}$ for five bands	510
7.3A.3.3	$\Delta R_{IB,c}$ for Intra-band CA.....	510
7.3A.4	Reference sensitivity exceptions due to UL harmonic interference for CA.....	511
7.3A.5	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA	520
7.3A.6	Reference sensitivity exceptions due to cross band isolation for CA	547
7.3B	Reference sensitivity for NR-DC	551
7.3C	Reference sensitivity for SUL	551
7.3C.1	General.....	551
7.3C.2	Reference sensitivity power level for SUL	551
7.3C.3	$\Delta R_{IB,c}$ for SUL	554
7.3C.3.1	General	554
7.3C.3.2	SUL band combination	555
7.3C.3.2.1	$\Delta R_{IB,c}$ for two bands	555
7.3C.3.2.2	$\Delta R_{IB,c}$ for three bands	556
7.3D	Reference sensitivity for UL MIMO	556
7.3E	Reference sensitivity for V2X.....	556
7.3E.1	General.....	556
7.3E.2	Minimum requirements.....	556
7.3E.3	Reference sensitivity power level for V2X con-current operation.....	557
7.3F	Reference sensitivity for shared spectrum channel access	559
7.3F.1	General.....	559
7.3F.2	Reference sensitivity power level	559
7.3F.3	$\Delta R_{IB,c}$	560
7.3F.4	Intra-band contiguous shared spectrum channel access CA	560
7.3G.5	Inter-band CA with shared spectrum channel access.....	560

7.3G.5.1	Reference sensitivity exceptions due to UL harmonic interference	561
7.3G.5.2	Reference sensitivity exceptions due to receiver harmonic mixing	561
7.3G.5.3	Reference sensitivity exceptions due to cross band isolation.....	561
7.3I	Reference sensitivity for RedCap	562
7.3I.1	General.....	562
7.3I.2	Reference sensitivity power level	562
7.4	Maximum input level	567
7.4A	Maximum input level for CA	567
7.4A.1	Maximum input level for Intra-band contiguous CA.....	567
7.4A.2	Maximum input level for Intra-band non-contiguous CA	567
7.4A.3	Maximum input level for Inter-band CA	568
7.4B	Maximum input level for NR-DC	568
7.4D	Maximum input level for UL MIMO	568
7.4E	Maximum input level for V2X	568
7.4E.1	General.....	568
7.4E.2	Maximum input level for V2X con-current operation	568
7.5	Adjacent channel selectivity.....	569
7.5A	Adjacent channel selectivity for CA.....	571
7.5A.1	Adjacent channel selectivity for Intra-band contiguous CA	571
7.5A.2	Adjacent channel selectivity Intra-band non-contiguous CA	573
7.5A.3	Adjacent channel selectivity Inter-band CA	574
7.5B	Adjacent channel selectivity for NR-DC.....	574
7.5D	Adjacent channel selectivity for UL MIMO.....	574
7.5E	Adjacent channel selectivity for V2X	574
7.5E.1	General.....	574
7.5E.2	Adjacent channel selectivity for V2X con-current operation.....	576
7.5F	Adjacent channel selectivity.....	576
7.5F.1	General.....	576
7.5F.2	Intra-band contiguous shared spectrum channel access CA	577
7.6	Blocking characteristics	578
7.6.1	General.....	578
7.6.2	In-band blocking.....	578
7.6.3	Out-of-band blocking.....	580
7.6.4	Narrow band blocking	582
7.6A	Blocking characteristics for CA	583
7.6A.1	General.....	583
7.6A.2	In-band blocking for CA	583
7.6A.2.1	In-band blocking for Intra-band contiguous CA	583
7.6A.2.2	In-band blocking for Intra-band non-contiguous CA	585
7.6A.2.3	In-band blocking for Inter-band CA.....	585
7.6A.3	Out-of-band blocking for CA.....	586
7.6A.3.1	Out-of-band blocking for Intra-band contiguous CA	586
7.6A.3.2	Out-of-band blocking for Intra-band non-contiguous CA.....	587
7.6A.3.3	Out-of-band blocking for Inter-band CA	587
7.6A.4	Narrow band blocking for CA	589
7.6A.4.1	Narrow band blocking for Intra-band contiguous CA.....	589
7.6A.4.2	Narrow band blocking for Intra-band non-contiguous CA	589
7.6A.4.3	Narrow band blocking for Inter-band CA	589
7.6B	Blocking characteristics for NR-DC.....	590
7.6C	Blocking characteristics for SUL	590
7.6C.1	General.....	590
7.6C.2	In-band blocking for SUL	590
7.6C.3	Out-of-band blocking for SUL.....	590
7.6C.4	Narrow band blocking for SUL	591
7.6D	Blocking characteristics for UL MIMO	591
7.6E	Blocking characteristics for V2X	591
7.6E.1	General.....	591
7.6E.2	In-band blocking.....	591
7.6E.2.1	General	591
7.6E.2.2	In-band blocking for V2X con-current operation.....	592
7.6E.3	Out-of-band blocking.....	592
7.6E.3.1	General	592

7.6E.3.2	Out-of-band blocking for V2X con-current operation	593
7.6F	Blocking characteristics	593
7.6F.1	General.....	593
7.6F.2	In-band blocking.....	593
7.6F.2.1	General	593
7.6F.2.2	Intra-band contiguous shared spectrum channel access CA.....	594
7.6F.3	Out-of-band blocking.....	595
7.6F.3.1	General	595
7.6F.3.2	Intra-band contiguous shared spectrum channel access CA.....	596
7.7	Spurious response.....	597
7.7A	Spurious response for CA.....	598
7.7A.1	Spurious response for Intra-band contiguous CA	598
7.7A.2	Spurious response for Intra-band non-contiguous CA.....	598
7.7A.3	Spurious response for Inter-band CA.....	599
7.7B	Spurious response for NR-DC.....	599
7.7D	Spurious response for UL MIMO.....	599
7.7E	Spurious response for V2X	599
7.7E.1	General.....	599
7.7E.2	Spurious response for V2X con-current operation.....	600
7.7F	Spurious response for shared spectrum channel access.....	600
7.7F.1	General.....	600
7.7F.2	Intra-band contiguous shared spectrum channel access CA	600
7.8	Intermodulation characteristics	601
7.8.1	General.....	601
7.8.2	Wide band Intermodulation	601
7.8A	Intermodulation characteristics for CA	603
7.8A.1	General.....	603
7.8A.2	Wide band intermodulation for CA	603
7.8A.2.1	Wide band intermodulation for Intra-band contiguous CA.....	603
7.8A.2.2	Wide band intermodulation for Intra-band non-contiguous CA.....	604
7.8A.2.3	Wide band intermodulation for Inter-band CA	604
7.8B	Intermodulation characteristics for NR-DC	604
7.8D	Intermodulation characteristics for UL MIMO.....	605
7.8E	Intermodulation characteristics for V2X	605
7.8E.1	General.....	605
7.8E.2	Wide band Intermodulation	605
7.8E.2.1	General	605
7.8E.2.2	Wide band Intermodulation for V2X con-current operation.....	606
7.8F	Intermodulation characteristics for shared spectrum channel access	606
7.8F.1	General.....	606
7.8F.2	Wide band Intermodulation	606
7.9	Spurious emissions	607
7.9A	Spurious emissions for CA.....	608
7.9A.1	Void	608
7.9A.2	Void	608
7.9A.3	Spurious emissions for Inter-band CA.....	608
7.9B	Spurious emissions for NR-DC	608
Annex A (normative):	Measurement channels.....	609
A.1	General	609
A.2	UL reference measurement channels	609
A.2.1	General	609
A.2.2	Reference measurement channels.....	610
A.2.2.1	DFT-s-OFDM Pi/2-BPSK	610
A.2.2.2	DFT-s-OFDM QPSK.....	611
A.2.2.3	DFT-s-OFDM 16QAM.....	611
A.2.2.4	DFT-s-OFDM 64QAM.....	613
A.2.2.5	DFT-s-OFDM 256QAM.....	615
A.2.2.6	CP-OFDM QPSK	617
A.2.2.7	CP-OFDM 16QAM	619
A.2.2.8	CP-OFDM 64QAM	621