

SLOVENSKI STANDARD

oSIST prEN ISO 22476-9:2019

01-oktober-2019

Geotehnično preiskovanje in preskušanje - Preskušanje na terenu - 9. del: Terenski krilni preskus (FVT in FVT-F) (ISO/DIS 22476-9:2019)

Ground investigation and testing - Field testing - Part 9: Field vane test (FVT and FVT-F) (ISO/DIS 22476-9:2019)

Geotechnische Erkundung und Untersuchung - Felduntersuchungen - Teil 9:
Flügelscherversuche (FVT und FVT F) (ISO/DIS 22476 9:2019)

Reconnaissance et essais géotechniques - Essais en place - Partie 9: Essai au
scissomètre de chantier (ISO/DIS 22476-9:2019)

Ta slovenski standard je istoveten z: prEN ISO 22476-9

ICS:

93.020	Zemeljska dela. Izkopavanja. Gradnja temeljev. Dela pod zemljo	Earthworks. Excavations. Foundation construction. Underground works
--------	--	---

oSIST prEN ISO 22476-9:2019

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/b44dc48a-0948-4ec3-bdb5-408971f77b00/osist-pren-iso-22476-9-2019>

DRAFT INTERNATIONAL STANDARD

ISO/DIS 22476-9

ISO/TC 182

Secretariat: BSI

Voting begins on:
2019-08-01Voting terminates on:
2019-10-24

Ground investigation and testing — Field testing —

Part 9: Field vane test (FVT and FVT-F)

*Reconnaissance et essais géotechniques — Essais en place —
Partie 9: Essai au scissomètre de chantier*

ICS: 93.020

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/b44dc48a-0948-4ec3-bdb5-408971f77b00/osist-pren-iso-22476-9-2019>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

ISO/CEN PARALLEL PROCESSING



Reference number
ISO/DIS 22476-9:2019(E)

© ISO 2019

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/b44dc48a-0948-4ec3-bdb5-408971f77b00/osist-pren-iso-22476-9-2019>

**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 General	1
3.2 Symbols	4
4 Equipment	5
4.1 Test configurations	5
4.2 Vane	8
4.2.1 General	8
4.2.2 Dimensional requirements	8
4.3 Vane shaft and friction reducer	10
4.4 Slip coupling	10
4.5 Extension rods, protective casings, protection shoe	10
4.6 Equipment for applying rotation	11
4.7 Equipment for measuring rotation and torque	11
5 Selection of test and test configuration	11
5.1 Selection of shear strengths to be measured	11
5.2 Selection of equipment and procedures related to soil conditions	13
6 Test procedure	13
6.1 Equipment checks and calibrations	13
6.2 Position and inclination of thrust machine	14
6.3 Test depths	14
6.4 Internal friction torque reading prior to testing	14
6.5 Methods for reaching the level for insertion of vane	14
6.6 Insertion of the vane	16
6.7 External friction torque reading	16
6.8 Vane shear test	16
6.9 Internal friction torque reading after the test	17
7 Test results	17
8 Reporting	18
8.1 General	18
8.2 Reporting of test results	19
8.2.1 General information	19
8.2.2 Location of the test	19
8.2.3 Test equipment	20
8.2.4 Test procedure	20
8.2.5 Test results	20
8.3 Presentation of test plots	20
Annex A (informative) Example of field record for field vane test	22
Annex B (normative) Maintenance, checks and calibration	24
Annex C (informative) Uncertainties in field vane testing	27
Annex D (normative) General interpretation and explanation for tapered and rectangular vanes with H/D ratios differing from 2	29
Annex E (informative) Interpretation and explanation for a rectangular vane with rounded corners	32
Annex F (normative) Calculation of test depth	34

ISO/DIS 22476-9:2019(E)

Annex G (informative) Example of estimation of post-peak behaviour	35
Bibliography	36

iTeh STANDARD PREVIEW
(standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/b44dc48a-0948-4ec3-bdb5-408971f77b00/osist-pren-iso-22476-9-2019>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 182, *Geotechnics*.

A list of all parts in the ISO 22476- series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The field vane test is used to determine the vane shear strength of soils in the undrained condition, by insertion of a rectangular vane into fine-grained soil and rotating it. During rotation, the torque and rotation can be measured, depending on the test configuration. From the measured torque and the dimensions of the vane, the peak shear strength, an indication of post-peak behaviour and the remoulded shear strength can be derived by limit equilibrium analysis. Soil sensitivity can be ascertained if peak and remoulded shear strengths have been determined.

The tests are carried out in boreholes, in trial pits and with pushed-in equipment. Torque and rotation are measured either above the ground surface using extension rods; or directly above the vane.

The field vane test is mainly applicable to saturated fine-grained soil. The vane shear strength determined by the test is commonly corrected before geotechnical analysis, using factors based on local experience.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/b44dc48a-0948-4ec3-bdb5-408971f77b00/osist-pren-iso-22476-9-2019>

Ground investigation and testing — Field testing —

Part 9: Field vane test (FVT and FVT-F)

1 Scope

This standard deals with the equipment requirements, execution and reporting of field vane tests for the measurement of peak and remoulded vane shear strength together with the sensitivity of fine-grained soils. In addition, post-peak shear strength behaviour can be evaluated. Two types of field vane test are described; the ordinary field vane test (FVT) and the fast field vane test (FVT-F).

The uncertainties of the vane test result are described in [Annex C](#).

NOTE 1 This part of ISO 22476 fulfils the requirements for field vane tests as part of the geotechnical investigation and testing according to EN 1997-1 and EN 1997-2

NOTE 2 This part of ISO 22476 covers onshore and nearshore field vane testing

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10012:2003, *Measurement management systems — Requirements for measurement processes and measuring equipment*

ISO 14688-1, *Geotechnical investigation and testing — Identification and classification of soil — Part 1: Identification and description*

ISO 14688-2, *Geotechnical investigation and testing — Identification and classification of soil — Part 2: Principles for a classification*

ISO 22475-1, *Geotechnical investigation and testing – Sampling methods and groundwater measurements – Part 1: Technical principles for execution*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 General

3.1.1

Cased extension rod

Extension rods that are sleeved inside of protective casings during vane testing.

3.1.2

Cased borehole

Borehole that is cased to prevent collapse and minimize friction between the extension rods and soil.

3.1.3

Centralizer

Equipment to keep the extension rods straight and prevent buckling.

ISO/DIS 22476-9:2019(E)

3.1.4

Data acquisition system

Measuring system, which converts physical quantities to digital format.

Note 1 to entry: The system typically includes sensors, signal conditioning, AD converter and recording unit.

3.1.5

Downhole test

Test configuration whereby the torque is measured close to the vane. The rotation can be measured close to the vane or above the ground surface.

3.1.6

External friction torque

Torque due to friction outside the measuring equipment during rotation excluding torque caused by shearing of soil. External friction is mainly caused by friction acting on extension rods and it can be estimated with a slip coupling immediately before engagement of the vane.

3.1.7

Friction reducer

A ring inserted between the vane and the extension rods to reduce friction along uncased extension rods.

3.1.8

Insertion length

Distance from the ground surface or base of (bore)hole or trial pit to mid-height of the vane, measured along the axis of the extension rods.

3.1.9

Internal friction torque

Torque due to friction inside the measuring equipment during rotation when there is no torque acting on the vane and no friction acting on the extension rods.

3.1.10

Penetration length

Sum of the lengths of the extension rods, the vane shaft and the distance to mid-height of the vane, relative to a fixed horizontal plane (normally the ground surface).

3.1.11

Protection shoe

Equipment to protect the vane while pushing into the soil. It assists with the insertion of the vane without drilling. Usually, the tip of the protection shoe consists of four plate slots allowing the vane plates to retract inside of the protective casing.

3.1.12

Protective casing

Tubes that isolate the extension rods from the soil and give support against buckling.

3.1.13

Protrusion length

Distance between the bottom of the protective casing/shoe and the mid-height of the vane when pushed to the test depth, measured along the axis of the rods.

3.1.14

Push-in equipment

Equipment to push the vane into the soil without predrilling.

3.1.15

Rotation

Change of angle by the circular movement of the vane around its axis.

Note 1 to entry: Apparent rotation is the rotation recorded by the rotation measurement equipment.

3.1.16**Rotation rate**

Rate of angular rotation of the vane.

3.1.17**Slip coupling**

Mechanism that allows the extension rods to rotate freely while the vane remains stationary.

3.1.18**Test depth**

Vertical distance from the ground surface, reference level or datum to mid-height of the vane.

Note 1 to entry: According to [Annex F](#), the penetration length can be corrected with inclinometer measurements to correspond the test depth. Otherwise, the test depth is based on the penetration length owing to the uncertainty of inclination.

3.1.19**Test location**

Plan position of a test or series of tests.

3.1.20**Test type**

Two types of field vanes test can be distinguished; ordinary field vane test (FVT) and fast field vane test (FVT-F).

3.1.21**Time to failure**

Time from the beginning of application of torque to the vane until the maximum torque is reached.

3.1.22**Uncased extension rods**

Extension rods that are not protected by protective casing allowing friction to develop between the extension rods and the soil.

3.1.23**Uncased vane**

The vane pushed into the ground without protection.

3.1.24**Uphole test**

Test configuration whereby the torque is measured above the ground surface. The rotation is applied and measurements registered above the ground surface.

3.1.25**Vane**

Four vane plates fixed at 90° to each other.

3.1.26**Vane plate**

Thin and flat rectangular plate.

Note 1 to entry: Most vanes have a (nearly) rectangular shape. For practical reasons, vanes without protection shoes often have slightly tapered lower ends of the vane plates or with rounded corners. Some equipment using uncased extension rods and a slip coupling to separate the rod friction from the torque on the vane are designed with slightly tapered, sharpened, pointed or conical, vane plates in order to disengage the slip coupling during the pushing stroke.

3.1.27**Vane shaft**

Cylindrical element of the vane to which the vane plates are fixed. The vane shaft may be connected directly to the force or torque measurement equipment in a downhole test or connected to it via extension rods in an uphole test.

ISO/DIS 22476-9:2019(E)

3.1.28

Waiting time

Time between reaching the test depth and beginning of application of the torque to the vane.

3.1.29

Zero shift

Difference between the internal friction torque readings of the measuring equipment prior and after completion of the test.

3.1.30

Sensitivity

The ratio between the undisturbed and remoulded undrained shear strengths.

3.2 Symbols

Symbol	Name	Description	Unit
$A_{cone,bott}$		Lateral shear surface area of the bottom cone	mm ²
$A_{cone,top}$		Lateral shear surface area of the top cone	mm ²
$A_{cylinder}$		Lateral shear surface area of the cylinder	mm ²
c_u	Undrained shear strength	Shear resistance of fine-grained soils in the undrained condition	kPa
c_{fv}	Field vane strength	Peak shear strength of soil, derived from the maximum torque measured by field vane test	kPa
c_{pv}	Post-peak field vane strength	Post-peak shear strength of soil, selected after desired rotation after field vane strength	kPa
c_{rv}	Remoulded field vane strength	Shear strength, as measured by field vane test, after remoulding the soil	kPa
c_{fv-f}	Fast field vane strength	Peak shear strength of soil, derived from the maximum torque measured by fast field vane test	kPa
D		Diameter of the vane	mm
d		Diameter of vane shaft immediately behind vane	mm
D_c		Diameter of lower end of protective casing	mm
D_{ps}		Diameter of protection shoe	mm
H		Height of the vane	mm
H_t		The height of the vertical side of the tapered vane excluding the height influence of tapering(s).	mm
i_T		Angle of taper at vane top	°
i_B		Angle of taper at vane bottom	°
l	Penetration length	sum of the lengths of the extension rods, the vane shaft and the distance to mid-height of the vane, relative to a fixed horizontal plane	m
R_a	Area ratio	Cross sectional area ratio of vane and vane shaft compared to circular shear surface	-
r		Radius of rounded corner of the vane plate	mm
$r_{cone,bott}$		Lever arm of lateral surface of the bottom cone of shear surface	mm
$r_{cone,top}$		Lever arm of lateral surface of the top cone	mm
$r_{cylinder}$		Lever arm of lateral surface of the cylinder	mm
s_{fv}	Field vane sensitivity	The ratio between the field vane and remoulded field vane strengths	-
s		Thickness of the vane plates	mm
T_{int}	Internal friction torque reading prior to test	Stable output of a measuring equipment during rotation when there is no torque acting on the vane and no friction acting on the extension rods	Nm