# ETSI TS 132 584 V17.0.0 (2022-04)



Universal Mobile Telecommunications System (UMTS);
Telecommunication management;
Home Node B (HNB) Operations, Administration, Maintenance and Provisioning (OAM&P);
XML definitions for Type 1 interface HNB to HNB Management
https://standards.System (HMS)s/sist/b7a30d80(3GPP TS 732.584 version 17.0.0 Release 17)



# Reference RTS/TSGS-0532584vh00 Keywords UMTS

#### **ETSI**

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° w061004871

#### Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at <a href="https://www.etsi.org/deliver">www.etsi.org/deliver</a>.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <a href="https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx">https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx</a>

If you find errors in the present document, please send your comment to one of the following services: <a href="https://portal.etsi.org/People/CommitteeSupportStaff.aspx">https://portal.etsi.org/People/CommitteeSupportStaff.aspx</a>

If you find a security vulnerability in the present document, please report it through our 63a-467 Coordinated Vulnerability Disclosure Program: 17-0-0-https://www.etsi.org/standards/coordinated-vulnerability-disclosure

### Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

## **Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022. All rights reserved.

# Intellectual Property Rights

#### **Essential patents**

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### **Trademarks**

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup>, **UMTS**<sup>TM</sup> and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP**<sup>TM</sup> and **LTE**<sup>TM</sup> are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M**<sup>TM</sup> logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**<sup>®</sup> and the GSM logo are trademarks registered and owned by the GSM Association.

# **Legal Notice**

# (standards.iteh.ai)

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables -132-584-v17-0-0-

The cross reference between 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

# Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

# Contents

Intelle	ectual Property Rights	2
Legal	Notice	2
Moda	l verbs terminology	2
Forew	ord	4
Introd	uction	4
	Scope	
	References	
	Definitions and abbreviations.	
3.1	Definitions and abbreviations	
3.2	Abbreviations	
4	CM data format definition	6
4.1	File content description	6
4.2	XML schema based CM data file format definition	
4.2.1	CM data file XML diagram	
4.2.2	CM data file XML schema	
4.2.3	CM data file XML header	21
5	CM data file XML header. PM data format definition	21
5.1		
5.2	Mapping tableXML schema based PM data file format definition	23
5.2.1	PM data file XML diagram	23
5.2.2	PM data file XML diagram  PM data file XML schema tandards itch ai  PM data file XML header	23
5.2.2	PM data file XML header	23
Anne	x A (informative): Examples 75.132.584.W17:0.0 (2022-04)	24
A.1	XML schema based CM/data fileds itch.ai/catalog/standards/sist/h7a30d80	24
	XML schema based PM data file 2022-04	
Anne	x B (informative): Void	25
Anne	x C (informative): Change history	26
Histor		27

## **Foreword**

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

# Introduction

# <del>iTeh STANDARD</del>

The present document is part of a TS-family covering the 3<sup>rd</sup> Generation Partnership Project Technical Specification Group Services and System Aspects, Telecommunication Management; as identified below:

- 32.581: "Telecommunications management; Home Node B (HNB) Operations, Administration, Maintenance and Provisioning (OAM&P); Concepts and requirements for Type 1 interface HNB to HNB Management System (HMS)"

  ETSLTS 132 584 V17.0.0 (2022-04)
- https://standards.iteh.ai/catalog/standards/sist/b7a30d8032.582: "Telecommunications management: Home Node B (HNB) Operations, Administration, Maintenance and Provisioning (OAM&P); Information model for Type 1 interface HNB to HNB Management System (HMS)"
- 32.583: "Telecommunications management; Home Node B (HNB) Operations, Administration, Maintenance and Provisioning (OAM&P); Procedure flows for Type 1 interface HNB to HNB Management System (HMS)"
- 32.584: "Telecommunications management; Home Node B (HNB) Operations, Administration, Maintenance and Provisioning (OAM&P); XML definitions for Type 1 interface HNB to HNB Management System (HMS)"

# 1 Scope

The present document describes the data format for Configuration Management and Performance Management for Home Node B (HNB). The XML definitions captured in this document shall be met via Type 1 interface between HNB and HNB Management System (HMS).

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- 3GPP TR 21.905: "Vocabulary for 3GPP Specifications". [1] [2] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements". 3GPP TS 32.102: "Telecommunication management; Architecture". [3] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name [4] convention for Managed Objects". standards.iteh.ai) Void. [5] 3GPP TR R3.020, Home (e)NodeB [6] 4 V17.0.0 (2022-04) [7] TR-069 Amendment 2, CPE WAN Management Protocol v1-1, Broadband Forum 3GPP TS 32.435: "Telecommunication management; Performance measurement: eXtensible [8] Markup Language (XML) file format definition" [9] 3GPP TS 32.582: "Telecommunications management; Home Node B (HNB) Operations, Administration, Maintenance and Provisioning (OAM&P); Information model for Type 1 interface HNB to HNB Management System (HMS)" [10] W3C REC-xml-20001006: "Extensible Markup Language (XML) 1.0 (Second Edition)". W3C REC-xmlschema-0-20010502: "XML Schema Part 0: Primer". [11] [12] W3C REC-xmlschema-1-20010502: "XML Schema Part 1: Structures". W3C REC-xmlschema-2-20010502: "XML Schema Part 2: Datatypes". [13] W3C REC-xml-names-19990114: "Namespaces in XML". [14] TR-157 Amendment 1 "Component Objects for CWMP", Broadband Forum. [15] [16] TR-098 Amendment 2, "Internet Gateway Device Data Model for TR-069", Broadband Forum 3GPP TS 32.622: "Telecommunication management; Configuration Management (CM); Generic [17] network resources Integration Reference Point (IRP): Network Resource Model (NRM)".

Reference Point (IRP); Information Service (IS)"

3GPP TS 32.772: "Telecommunication management; Home Node B (HNB) Subsystem (HNS); Integration

[20] 3GPP TS 32.432: "Telecommunication management; Performance measurement: File format definition"

## 3 Definitions and abbreviations

## 3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

**Home NodeB:** These terms, their derivations and abbreviations are used synonymously throughout this document.

## 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

DM	Domain Manager
EM	Element Manager Teh STANDARD
FFS	For Further Study
HNB	Home Node B
HMS	HNB Management System REVIEW
IP	Total and A Direction of
LTE	Long Term Evolution and ards.iteh.ai) Mobile Management Entity
MME	Mobile Management Entity
NGMN	Next Generation Mobile Networks
PnP	Plug and Play <u>ETSI TS 132 584 V17.0.0 (2022-04)</u>
SAE	System Architecture Eyolution ai/catalog/standards/sist/b7a30d80-Self-Organising Networks To Be Discussed
SON	Self-Organising Networks 342 a 60 fbd/atai to 122 584 v17 0 0
TBD	To Be Discussed
UMTS	Universal Mobile Telecommunications System
UTRAN	UMTS Radio Access Network

# 4 CM data format definition

This clause describes the format of Configuration Management data.

# 4.1 File content description

Table 4.1 lists all the file content items, provides and explanation of the individual items, and maps the file content items to those used in the XML schema based file format definitions. XML tag attributes are useful where data values bind tightly to its parent element. They have been used where appropriate.

Table 4.1 File Content Description and Mapping of File Content Items to XML tags

File Content Item	XML schema based XML tag	Description
configDataCollection	configDataFile	This is the top-level tag, which identifies the file as a collection of config data. The file content is made up of a header ("configFileHeader"), the collection of configuration items ("configData"), and a configfile footer ("configFileFooter").
configFileHeader	fileHeader	This is the configuration data file header to be inserted in each file. It includes a version indicator, the sendor name, and vendor name of the sending network node.

	The "configData" construct represents the sequence of zero or more configuration parameter items contained in the file.  Each "configData" element contains the name of the NE ("nEId") and the list of parameters to be created, modified or deleted
	which pertaining to that NE The "configData" consists of DeviceData, DiagnosticsData, and FAPServiceData
	The configuration data file footer to be inserted in each file. It includes a time stamp, which refers to the time when the file is closed for sending to the NE.
	This parameter identifies the file format version applied by the sender. The format version defined in the present document shall be the abridged number and version of this 3GPP document (see below).  The abridged number and version of a 3GPP document is constructed from its version specific full reference "3GPP [] (yyyy-mm)" by: - removing the leading "3GPP TS" - removing everything including and after the version third digit, representing editorial only changes, together with its preceding dot character - from the resulting string, removing leading and trailing white space, replacing every multi character white space by a single space character and changing the case of all characters to uppercase.
ileHeader senderName PR (stands  ETSLTS 132 tps://standards.iteh.ar	e.g. /32.584 V8.0"  If this is a downloaded file from HMS to HNB, then this attribute shall hold the DN of HMS whose name hierarchy is defined section 6.2.1 of TS 32.772 [18].  Example: "DC=a1:companyNN:com,SubNetwork=1,ManagementNode=6, HMSFunction=H3WT2"  If this is an uploaded file from HNB to HMS, then this attribute shall hold the DN of HNB; See Note 3 of Table 5.1  2.60 fbd/etsi-13.2-584-v17-0-0- See TS 32.300 [4] for definition of DN.
ileHeader vendorName	The "vendorName" identifies the vendor of the equipment that provided the measurement file. The string may be empty (i.e. string size =0) if the "vendorName" is not configured in the sender.  For the XML schema based XML format, XML attribute specification "vendorName" may be absent in case the "vendorName" is not configured in the sender.
	The unique identification of the NE in the system. It includes the user name ("nEUserName"), the distinguished name ("nEDistinguishedName") and the software version ("nESoftwareVersion") of the NE.
userLabel	This is the user definable name ("userLabel") defined for the NE in 3GPP TS 32.622 [17]. The string may be empty (i.e. string size =0) if the "nEUserName" is not configured in the CM applications.  For the XML schema based XML format, XML attribute specification "userLabel" may be absent in case the "nEUserName" is not configured in the CM applications.
managedElement ocalDn	This attribute shall hold the DN of HNB. See Note 1 of Table 5.1.  See TS 32.300 [4] for definition of DN.
ii Tru	leHeader leFormatVersion  IeHeader senderName PR (stands  ETSI TS 132  ps://standards.iteh.as 3a-4678-9df2-cead4  IeHeader vendorName  managedElement  managedElement  managedElement

	managedElement swVersion	This is the software version ("swVersion") defined for the NE in 3GPP TS 32.622 [17]. This is an optional parameter which allows post-processing
		systems to take care of vendor specific measurements modified between software versions.  For the XML schema based XML format, XML attribute specification "swVersion" may be absent in case the "nESoftwareVersion" is not configured in the CM applications.
Modifier	configData modifier	This element is present if the HMS is required to inform the NE whether the parameter information should be used to create, update or delete an specific object instance on the HNB  If not present the NE will assume the modification action is update
F F F F F	configData DeviceInfo configData ManagementServer configData Time FAPService DNPrefix FAPControl FAPService AccessMgmt FAPService CellConfig FAPService Transport FAPService REM FAPService GPS	These elements are present if the HMS requires to modify the specific configuration parameters  The XML file format definitions implement the configuration structure and parameter definitions defined in broadband forum 3GPP TS 32.582 [9] and TR-098 Amendment 2 [16].
timestamp f	fileFooter dataTime	יו קוו/יקו

A vendor MAY extend the standardized parameter list with vendor-specific parameters and objects. Vendor-specific parameters and objects MAY be defined either in a separate naming hierarchy or within the standardized naming hierarchy of the XML File Format.

The name of a vendor-specific parameter or object not contained within another yendor-specific object MUST have the following form to align with the Vendor Specific Parameter Definition of TR-098 Amendment 2 [16].

• X\_<VENDOR>\_VendorSpecificName\_teh.ai/catalog/standards/sist/b/a30d80-

• X\_<VENDOR>\_VendorSpecificName.iten.ai/catalog/standards/sist/b/a30d80-663a-4678-9df2-cead42c60fbd/etsi-ts-132-584-v17-0-0-2022-04

## 4.2 XML schema based CM data file format definition

## 4.2.1 CM data file XML diagram

Figure 4.1 describes the XML element structure of the CM data file.




Figure 4.1: XML diagram of the configuration data file

## 4.2.2 CM data file XML schema

The following XML schema configData.xsd is the schema for CM data XML files:

```
<?xml version="1.0" encoding="UTF-8"?>
  3GPP TS 32.584 Configuration Data XML file format definition
  data file XML schema
 configData.xsd
<schema xmlns:cd="http://www.3gpp.org/ftp/specs/archive/32_series/32.584#configData"</pre>
xmlns="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.584#configData"
elementFormDefault="qualified">
    <!-- Config data XML elements -->
    <element name="AccessMode">
        <simpleType>
            <restriction base="string">
                <enumeration value="Open Access"/>
                 <enumeration value="Closed Access"/>
                <enumeration value="Hybrid Access"/>
            </restriction>
        </simpleType>
    </element>
    <element name="BandIndicator">
        <simpleType>
            <restriction base="string">
                 <enumeration value="GSM 850"/>
                <enumeration value="GSM 900"/>
<enumeration value="DCS 1800"/>
<enumeration value="PCS 1900"/>
            </restriction>
                                        PREVIEW
        </simpleType>
    </element>
    <element name="InServiceHandling">
            pleType> < restriction base="string" and ards.iteh.ai)
        <simpleType>
                <enumeration value="Immediate"/>
                <enumeration value="Delayed"/>
                                 ETSI TS 132 584 V17.0.0 (2022-04)
            </restriction>
        </simpleType>
                      https://standards.iteh.ai/catalog/standards/sist/b7a30d80-
    </element>
    <element name="Measurement@uantity-Inter42c60fbd/etsi-ts-132-584-v17-0-0-</pre>
        <simpleType>
                                                2022-04
            <restriction base="string">
                <enumeration value="CPICH Ec/No"/>
                 <enumeration value="CPICH RSCP"/>
            </restriction>
        </simpleType>
    </element>
    <element name="MeasurementQuantity-Intra">
        <simpleType>
            <restriction base="string">
                <enumeration value="CPICH Ec/No"/>
                 <enumeration value="CPICH RSCP"/>
                <enumeration value="Pathloss"/>
            </restriction>
        </simpleType>
    </element>
    <element name="Modifier">
        <simpleType>
            <restriction base="string">
                 <enumeration value="create"/>
                 <enumeration value="delete"/>
                <enumeration value="update"/>
            </restriction>
        </simpleType>
    </element>
    <element name="NonCSGUEAccessDecision">
        <simpleType>
            <restriction base="string">
                <enumeration value="Local"/>
                 <enumeration value="Query FAP-GW"/>
                <enumeration value="By Core"/>
            </restriction>
        </simpleType>
```