
**Acoustics — Hearing protectors —
Part 1:
Subjective method for the
measurement of sound attenuation**

Acoustique — Protecteurs individuels contre le bruit —

*Partie 1: Méthode subjective de mesurage de l'affaiblissement
acoustique*

(<https://standards.iteh.ai>)
Document Preview

ISO 4869-1:2018

<https://standards.iteh.ai/catalog/standards/iso/43213261-f72f-44b8-8cc4-57edde42e225/iso-4869-1-2018>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO 4869-1:2018

<https://standards.iteh.ai/catalog/standards/iso/43213261-f72f-44b8-8cc4-57edde42e225/iso-4869-1-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Measurement of the sound attenuation of hearing protectors	3
4.1 Test signals.....	3
4.2 Test site.....	3
4.2.1 General.....	3
4.2.2 Sound pressure level and sound pressure level variation	3
4.2.3 Reverberation time.....	4
4.2.4 Ambient noise level.....	4
4.3 Test equipment.....	5
4.4 Test subjects.....	6
4.5 General test procedure and instruction of the test subject	6
4.6 Determination of hearing protector attenuation	7
5 Application force	8
5.1 Earmuffs.....	8
5.2 Semi-aural earplugs.....	8
6 Test report	8
Annex A (normative) Uncertainty of hearing protector attenuation measurements	10
Annex B (informative) Evaluation of two hearing protector attenuation measurements	14
Annex C (informative) Minimum and maximum sound pressure levels for test signals	17
Bibliography	18

ISO 4869-1:2018

<https://standards.iteh.ai/catalog/standards/iso/43213261-f72f-44b8-8cc4-57edde42e225/iso-4869-1-2018>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This second edition cancels and replaces the first edition (ISO 4869-1:1990), which has been technically revised.

The main changes compared to the previous edition are as follows:

The revision includes changes mainly of the sound field requirements, specification of test equipment, test procedures and instructions to the test subjects, and uncertainty of the measurements. The sound field requirements are based on published and unpublished laboratory experience, especially [10] and [11] in the Bibliography.

A list of all parts in the ISO 4869 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Hearing protectors are commonly used to reduce the noise to which the ear is exposed. Hearing protectors are manufactured as earplugs, earmuffs or helmets. A standardized method of sound attenuation measurement allows comparison of performance data obtained in different locations under similar conditions.

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[ISO 4869-1:2018](https://standards.itih.ai/catalog/standards/iso/43213261-f72f-44b8-8cc4-57edde42e225/iso-4869-1-2018)

<https://standards.itih.ai/catalog/standards/iso/43213261-f72f-44b8-8cc4-57edde42e225/iso-4869-1-2018>

Acoustics — Hearing protectors —

Part 1: Subjective method for the measurement of sound attenuation

1 Scope

This document specifies a subjective method for measuring sound attenuation of hearing protectors at the threshold of hearing. The method is a laboratory method designed to yield reproducible values under controlled measurement conditions. The values reflect the attenuating characteristics of the hearing protector only to the extent that users wear the device in the same manner as did the test subjects.

For a more representative indication of field performance the methods of ISO/TS 4869-5 can be used.

This test method yields data which are collected at low sound pressure levels (close to the threshold of hearing) but which are also representative of the attenuation values of hearing protectors at higher sound pressure levels. An exception occurs in the case of amplitude-sensitive hearing protectors for sound pressure levels above the point at which their level-dependent characteristics become effective. At those sound pressure levels the method specified in this document is inapplicable, as it will usually underestimate sound attenuation for these devices.

NOTE Due to masking from physiological noise in the occluded ear tests, sound attenuations below 500 Hz can be overestimated by a few decibels.

2 Normative references

ISO 4869-1:2018

<https://standards.iteh.ai/catalog/standards/iso/43213261-f72f-44b8-8cc4-57edde42e225/iso-4869-1-2018>

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8253-2, *Acoustics — Audiometric test methods — Part 2: Sound field audiometry with pure-tone and narrow-band test signals*

IEC 60263, *Scales and sizes for plotting frequency characteristics and polar diagrams*

IEC 61260-1, *Electroacoustics — Octave-band and fractional-octave-band filters — Part 1: Specifications*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1
hearing protector

device worn by a person to prevent harmful effects from noise and other loud acoustic stimuli

Note 1 to entry: Hearing protectors can include electronic devices for communication, or devices designed to play an active role in the reduction of the noise level between the hearing protector and the eardrum.

3.2
 earmuff

hearing protector consisting of an ear-cup to be pressed against each pinna (supra-aural) or of an ear-cup to be pressed against the head, around the pinna (circumaural)

Note 1 to entry: The ear-cups can be pressed against the head with a special headband or neck band or by means of a device attached to a safety helmet or other equipment.

3.3
earplug

hearing protector worn within the external earcanal (aural) or in the concha against the entrance to the external earcanal (semi-aural)

3.4
helmet

device which covers a substantial part of the head

3.5
hearing level (of a pure tone)

difference between the sound pressure level of this pure tone produced by the earphone in a specified ear simulator or acoustic coupler and the appropriate reference equivalent threshold sound pressure level at a specified frequency, for a specified type of earphone and for a specified manner of application

Note 1 to entry: Values of reference equivalent threshold sound pressure levels are specified in ISO 389-1.

3.6
hearing threshold level (of a given ear)

threshold of hearing expressed as hearing level at a specified frequency and for a specified type of earphone

Note 1 to entry: For appropriate test conditions, see, for example, ISO 8253-1.

3.7
threshold of hearing

lowest sound pressure level at which, under specified conditions, a person gives a predetermined percentage of correct detection responses on repeated trials

Note 1 to entry: For the purpose of ISO 4869-1, the threshold of hearing is measured with and without the hearing protector. For appropriate test conditions, see ISO 8253-2.

3.8
sound attenuation

difference between the threshold of hearing with and without the hearing protector in place for a test subject for a given test signal

Note 1 to entry: The sound attenuation is given in decibels.

3.9
pink noise

random noise signal with a spectral density that decreases by 3 dB per octave, giving constant energy per octave

Note 1 to entry: The definition is often phrased as 'noise whose power spectral density is inversely proportional to frequency'.

[SOURCE: ISO 7240-24:2016, 3.1.11; modified: added Note 1 to entry]

3.10

reference point

fixed spatial position within the test chamber to which all objective measurements of the sound field characteristics are referenced and which coincides with the midpoint of a line connecting the test subject's earcanal openings when the test subject is seated for measurements

3.11

reverberation time

time required for the sound pressure level to decrease by 60 dB after the sound source has stopped

Note 1 to entry: See ISO 354 for information about measurement of reverberation time.

4 Measurement of the sound attenuation of hearing protectors

4.1 Test signals

The test signals shall consist of pink noise filtered through one-third-octave bands with centre frequencies in accordance with IEC 61260-1. Tests shall be performed at the following centre frequencies:

125 Hz, 250 Hz, 500 Hz, 1 000 Hz, 2 000 Hz, 4 000 Hz, 8 000 Hz.

Measurements at an additional centre frequency of 63 Hz are optional.

4.2 Test site

4.2.1 General

The sound field at the test site shall have sound incidence from many directions. Such a sound field is adequately approximated when the requirements of 4.2.2, 4.2.3 and 4.2.4 are met. The measurements of the sound field shall be conducted with the test subject and the subject's chair absent.

4.2.2 Sound pressure level and sound pressure level variation

- a) The sound pressure level at all test frequencies measured with an omnidirectional microphone at positions 15 cm from the reference point on the front-back, right-left and up-down axes shall deviate by no more than $\pm 2,5$ dB from the sound pressure level at the reference point. In addition, the difference between the right-left positions shall not exceed 3 dB. The orientation of the microphone shall be kept the same at each position.
- b) The directionality of the sound field shall be evaluated at the reference point for test signals with centre frequencies greater than or equal to 500 Hz. The measurements shall be conducted with a directional microphone with a typical free-field polar response at the one-third-octave test signals of at least 10 dB front-to-side rejection for a cosine microphone, or at least 10 dB front-to-back rejection for a cardioid microphone. The microphone shall be rotated at the reference point through 360° in the horizontal plane. The variation of the observed sound pressure levels in each test signal shall remain within the variation allowed in Table 1. The sound pressure levels can also be obtained by measuring at fixed 15 degree increments as the microphone is rotated.

Table 1 — Allowable variation of sound-field sound pressure levels for corresponding directional microphone free-field rejection

Microphone free-field rejection (FFR) dB	Allowable field variation dB
$25 \leq \text{FFR}$	20
$20 \leq \text{FFR} < 25$	15
$15 \leq \text{FFR} < 20$	10
$10 \leq \text{FFR} < 15$	5
$\text{FFR} < 10$	Microphone not suitable

NOTE The variation in microphone response as the microphone is rotated in a random incidence field is related to the directional characteristics of the microphone and the degree of randomness of the field being measured. Therefore, the allowable sound field response variations are related to the free-field directional response characteristics of the microphone. The microphone characteristics can be obtained from the microphone manufacturer or by measurement in a free field.

4.2.3 Reverberation time

The reverberation time in the test space, with the test subject and the test subject's chair absent, shall not exceed 1,6 s for each of the test signals.

4.2.4 Ambient noise level

The ambient noise level at the test site in the test room shall not exceed the values given in [Table 2](#). The ambient noise level shall be determined by measuring the sound pressure level with the test subject absent.

When the lowest test signal centre frequency is 125 Hz, the ambient noise requirement shall be met down to and including 63 Hz. When the lowest test signal centre frequency is 63 Hz, the ambient noise requirement shall be met down to and including 31,5 Hz.

NOTE The ambient noise level includes the noise present in the room and the possible noise from the test equipment while it is on and running, but in the absence of the test signals.

Table 2 — Maximum permissible ambient sound pressure level

Centre frequency Hz	One-third-octave-band sound pressure level (reference = 20 µPa) dB
31,5	57
40	43
50	31
63	25
80	21
100	18
125	14
160	11
200	9
250	6
315	4
NOTE The levels are set in relation to ISO 8253-1 for the purpose of testing down to -10 dB hearing threshold level.	