

SLOVENSKI STANDARD SIST EN 13001-3-1:2012+A2:2018

01-maj-2018

Žerjavi - Konstrukcija, splošno - 3-1. del: Mejna stanja in dokaz varnosti jeklene nosilne konstrukcije

Cranes - General Design - Part 3-1: Limit States and proof competence of steel structure

Krane - Konstruktion allgemein - Teil 3-1: Grenzzustände und Sicherheitsnachweis von Stahltragwerken

iTeh STANDARD PREVIEW

Appareils de levage à charge suspendue a Conception générale - Partie 3-1 : Etats limites et vérification d'aptitude des charpentes en acier

SIST EN 13001-3-1:2012+A2:2018

Ta slovenski standard je istoveten z: EN 13001-3-1:2012+A2:2018

ICS:

53.020.20 Dvigala Cranes

SIST EN 13001-3-1:2012+A2:2018 en,fr,de

SIST EN 13001-3-1:2012+A2:2018

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 13001-3-1:2012+A2:2018 https://standards.iteh.ai/catalog/standards/sist/07ce89c5-68e6-46af-a417-dd643f87ebf1/sist-en-13001-3-1-2012a2-2018 EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM EN 13001-3-1:2012+A2

January 2018

ICS 53.020.20

Supersedes EN 13001-3-1:2012+A1:2013

English Version

Cranes - General Design - Part 3-1: Limit States and proof competence of steel structure

Appareils de levage à charge suspendue - Conception générale - Partie 3-1 : Etats limites et vérification d'aptitude des charpentes en acier Krane - Konstruktion allgemein - Teil 3-1: Grenzzustände und Sicherheitsnachweis von Stahltragwerken

This European Standard was approved by CEN on and includes Amendment 2 approved by CEN on 30 October 2017.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom. Standards ich av catalog/standards/sist/0/ce89c3-68e6-46af-a417-dd643f87ebfl/sist-en-13001-3-1-2012a2-2018



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents		
1	Scope	7
2	Normative references	7
3	Terms ,definitions, symbols and abbreviations	9
3.1	Terms and definitions	9
3.2	Symbols and abbreviations	
4	General	
4.1	Documentation	
4.2	Materials for structural members	
4.2.1	Grades and qualities	
4.2.2	Impact toughness	
4.3	Bolted connections	
4.3.1	Bolt materials	
4.3.2	General	_
4.3.3	Shear and bearing connections	
4.3.4	Friction grip type (slip resistant) connections	19
4.3.5	Friction grip type (slip resistant) connections	19
4.4	Pinned connections	19
4.5	Pinned connections (standards.iteln.ai)	20
4.6	Proof of competence for structural members and connections	20
5	SIST EN 13001-3-1:2012+A2:2018 Proof of static strength tandards itch ai/catalog/standards/sist/07ce89c5-68e6-46af-a417-	21
5 5.1	General	21
5.2	Limit design stresses and forces	
5.2.1	General	
5.2.2	Limit design stress in structural members	
5.2.3	Limit design forces in bolted connections	
5.2.4	Limit design forces in pinned connections	
5.2.5	Limit design stresses in welded connections	
5.3	Execution of the proof	
5.3.1	Proof for structural members	
5.3.2	Proof for bolted connections	
5.3.3	Proof for pinned connections	39
5.3.4	Proof for welded connections	40
6	Proof of fatigue strength	40
6.1	General	
6.2	Limit design stresses	
6.2.1	Characteristic fatigue strength	
6.2.2	Weld quality	
6.2.3	Requirements for fatigue testing	
6.3	Stress histories	
6.3.1	General	
6.3.2	Frequency of occurence of stress cycles	
6.3.3	Stress history parameter	
6.3.4	Stress history classes S	
6.4	Execution of the proof	

$\begin{array}{cccccccccccccccccccccccccccccccccccc$	6.5	Determination of the limit design stress range	49
6.5.3Use of class S	6.5.1	A A	
6.5.4 Combined effect of normal and shear stresses	6.5.2		
7 Proof of static strength of hollow section girder joints 51 8 Proof of elastic stability 52 8.1 General 52 8.2 Lateral buckling of members loaded in compression 52 8.2.1 Critical buckling load 52 8.2.2 Limit compressive design force 54 8.3 Buckling of plate fields subjected to compressive and shear stresses 57 8.3.1 General 57 8.3.2 Limit design stress with respect to longitudinal stress σ_x 59 8.3.3 Limit design stress with respect to shear stress τ 63 8.3.4 Limit design stress with respect to shear stress τ 63 8.4.1 Members loaded in compression 64 8.4.2 Plate fields 64 Annex A (informative) Limit design shear force $F_{v,Rd}$ per bolt and per shear plane for multiple shear plane connections 66 Annex B (informative) Preloaded bolts 67 Annex B (informative) Design weld stresses $\sigma_{w,sd}$ and $\tau_{w,sd}$ 69 C.1 Butt joint 69 C.2 T-joint with fillet or partial penetration weld $\tau_{w,sd}$ 70	6.5.3		
8 Proof of elastic stability	6.5.4	Combined effect of normal and shear stresses	51
8.1 General	7	Proof of static strength of hollow section girder joints	51
8.1 General	8	Proof of elastic stability	52
8.2.1 Critical buckling load	8.1	General	52
8.2.2 Limit compressive design force	8.2	Lateral buckling of members loaded in compression	52
8.3 Buckling of plate fields subjected to compressive and shear stresses	8.2.1		
8.3.1 General			
8.3.2 Limit design stress with respect to longitudinal stress σ_x			
8.3.3 Limit design stress with respect to transverse stress σ_y			
8.3.4 Limit design stress with respect to shear stress τ			
8.4 Execution of the proof	8.3.3	Limit design stress with respect to transverse stress σ_y	61
8.4.1 Members loaded in compression	8.3.4	Limit design stress with respect to shear stress τ	63
8.4.2 Plate fields	8.4	Execution of the proof	64
Annex A (informative) Limit design shear force $F_{v,Rd}$ per bolt and per shear plane for multiple shear plane connections	8.4.1	Members loaded in compression	64
multiple shear plane connections	8.4.2	Plate fields	64
Annex B (informative) Preloaded bolts	Annex		
Annex B (informative) Preloaded bolts		multiple shear plane connections	66
C.1 Butt joint	Annex	B (informative) Preloaded bolts	67
C.2 T-joint with fillet or partial penetration weld $10^{10} = 10$	Annex	C (normative) Design weld stresses $\sigma_{W,Sd}$ and $\tau_{W,Sd}$	69
C.3 Effective distribution length under concentrated load	C.1		
C.3 Effective distribution length under concentrated load	C.2	T-joint with fillet or partial penetration weld	70
Annex D (normative) Values of slope constant m and characteristic fatigue strength $\Delta\sigma_c$, $\Delta\tau_c$	C.3	Effective distribution length under concentrated load	71
Δau_{c}	C.4	Other types of welds	72
Annex F (informative) Evaluation of stress cycles (example)	Annex		73
Annex G (informative) Calculation of stiffnesses for connections loaded in tension	Annex	E (normative) Calculated values of limit design stress ranges $\Delta\sigma_{Rd}$ and $\Delta\sigma_{Rd,1}$	94
Annex H (informative) Hollow Sections	Annex	F (informative) Evaluation of stress cycles (example)	96
Annex I (informative) Selection of a suitable set of crane standards for a given application 113 Annex ZA (informative) Relationship between this European Standard and the Essential	Annex	G (informative) Calculation of stiffnesses for connections loaded in tension	98
Annex ZA (informative) Relationship between this European Standard and the Essential	Annex	H (informative) Hollow Sections	. 101
	Annex	I (informative) Selection of a suitable set of crane standards for a given application	113
	Annex		114

European foreword

This document (EN 13001-3-1:2012+A2:2018) has been prepared by Technical Committee CEN/TC 147 "Cranes - Safety", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by July 2018, and conflicting national standards shall be withdrawn at the latest by July 2018.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document includes Amendment 1 approved by CEN on 11 May 2013.

This document includes Amendment 2 approved by CEN on 30 October 2017.

This document supersedes \triangle EN 13001-3-1:2012+A1:2013 \triangle .

The start and finish of text introduced or altered by amendment is indicated in the text by tags (standards.iteh.ai)

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

https://standards.iteh.ai/catalog/standards/sist/07ce89c5-68e6-46af-a417-

For relationship with EU Directive(s), see informative Annex ZA, which is an integral part of this document.

(A) CEN/TC 147/WG 2 has made a new edition of EN 13001-3-1 to adapt the standard as follows:

- Subclause 4.2.1 is changed in such a way that Table 2 is permanently valid and requirements for other materials are added, and
- editorial changes are done to improve the document. (A)
- (Example 2) CEN/TC 147/WG 2 has made a new consolidation of EN 13001-3-1 to adapt the standard as follows:
- New steel qualities from EN 10149-2 and stainless steels from EN 10088-2 added to 4.2.1.
- Application of bolt preloading scatter in 5.2.3.3 was modified.
- Table 8 changed to exclude matching material for ultra-high strength steel.
- Fatigue strength specific resistance factors were adjusted in 6.1.
- Requirements for fatigue testing were modified.
- Formula for assessing combined effect of normal and shear stresses was changed in 6.5.4.
- Annex C improved for calculation of fillet welds.

- Characteristic fatigue strengths modified for notch cases D.1.1, D.1.2, D.3.29 and D.3.30.
- Number of minor changes for reasons of editorial and technical accuracy. 🔄

This European Standard is one Part of EN 13001, *Cranes — General design*. The other parts are as follows:

- Part 1: General principles and requirements;
- Part 2: Load actions;
- Part 3-2: Limit states and proof of competence of wire ropes in reeving systems;
- Part 3-3: Limit states and proof of competence of wheel/rail contacts;
- Part 3-4: Limit states and proof of competence of machinery;
- Part 3-5: Limit states and proof of competence of forged hooks.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 13001-3-1:2012+A2:2018</u> https://standards.iteh.ai/catalog/standards/sist/07ce89c5-68e6-46af-a417-dd643f87ebf1/sist-en-13001-3-1-2012a2-2018

Introduction

This European Standard has been prepared to be a harmonized standard to provide one means for the mechanical design and theoretical verification of cranes to conform (A2) to (A2) the essential health and safety requirements of the Machinery Directive, as amended. This standard also establishes interfaces between the user (purchaser) and the designer, as well as between the designer and the component manufacturer, in order to form a basis for selecting cranes and components.

This European Standard is a type C standard as stated in EN ISO 12100.

The machinery concerned and the extent to which hazards, hazardous situations and events are covered are indicated in the scope of this standard.

When provisions of this type C standard are different from those which are stated in type A or B standards, the provisions of this type C standard take precedence over the provisions of the other standards, for machines that have been designed and built according to the provisions of this type C standard.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 13001-3-1:2012+A2:2018</u> https://standards.iteh.ai/catalog/standards/sist/07ce89c5-68e6-46af-a417-dd643f87ebf1/sist-en-13001-3-1-2012a2-2018

1 Scope

This European Standard is to be used together with EN 13001-1 and EN 13001-2 and as such they specify general conditions, requirements and methods to prevent mechanical hazards of cranes by design and theoretical verification.

NOTE Specific requirements for particular types of cranes are given in the appropriate European Standard for the particular crane type.

The following is a list of significant hazardous situations and hazardous events that could result in risks to persons during intended use and reasonably foreseeable misuse. Clauses 4 to 8 of this standard are necessary to reduce or eliminate risks associated with the following hazards:

- a) exceeding the limits of strength (yield, ultimate, fatigue);
- b) exceeding temperature limits of material or components;
- c) elastic instability of the crane or its parts (buckling, bulging).

This European Standard is not applicable to cranes which are manufactured before the date of its publication as EN and serves as reference base for the European Standards for particular crane types (see Annex I).

NOTE EN 13001-3-1 deals only with the limit state method in accordance with EN 13001-1. (standards.iteh.ai)

2 Normative references SIST EN 13001-3-1:2012+A2:2018

https://standards.iteh.ai/catalog/standards/sist/07ce89c5-68e6-46af-a417-

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

 A_2 deleted reference A_2

EN 1993-1-8:2005, Eurocode 3: Design of steel structures — Part 1-8: Design of joints

EN 10025-2:2004, Hot rolled products of structural steels — Part 2: Technical delivery conditions for non-alloy structural steels

EN 10025-3:2004, Hot rolled products of structural steels — Part 3: Technical delivery conditions for normalized/normalized rolled weldable fine grain structural steels

EN 10025-4:2004, Hot rolled products of structural steels — Part 4: Technical delivery conditions for thermomechanical rolled weldable fine grain structural steels

EN 10025-6:2004, Hot rolled products of structural steels — Part 6: Technical delivery conditions for flat products of high yield strength structural steels in the quenched and tempered condition

EN 10029:2010, Hot rolled steel plates 3 mm thick or above — Tolerances on dimensions and shape

 A_2 deleted references A_2

EN 10088-2:2014, Stainless steels — Part 2: Technical delivery conditions for sheet/plate and strip of corrosion resisting steels for general purposes

EN 10149-2:2013, Hot-rolled flat products made of high yield strength steels for cold forming — Part 2: Delivery conditions for thermomechanically rolled steels

EN 10149-3:2013, Hot-rolled flat products made of high yield strength steels for cold forming — Part 3: Delivery conditions for normalized or normalized rolled steels (A2)

EN 10160:1999, Ultrasonic testing of steel flat product of thickness equal or greater than 6 mm (reflection method)

EN 10163-1:2004, Delivery requirements for surface conditions of hot-rolled steel plates, wide flats and sections — Part 1: General requirements

EN 10163-2:2004, Delivery requirements for surface conditions of hot-rolled steel plates, wide flats and sections — Part 2: Plate and wide flats

EN 10163-3:2004, Delivery requirements for surface conditions of hot-rolled steel plates, wide flats and sections – Part 3: Sections

EN 10164:2004, Steel products with improved deformation properties perpendicular to the surface of the product — Technical delivery conditions

EN 13001-1, Cranes — General design — Part 1: General principles and requirements

EN 13001-2, Crane safety — General design — Part 2: Load actions

EN 20273:1991, Fasteners — Clearance holes for bolts and screws (ISO 273:1979)

A EN ISO 148-1:2016 Metallic materials Charpy pendulum impact test — Part 1: test method

EN ISO 286-2:2010, Geometrical product specifications (GPS) — ISO code system for tolerances on linear sizes — Part 2: Tables of standard tolerance classes and limit deviations for holes and shafts (ISO 286-2:2010)

EN ISO 898 1:2013, Mechanical properties of fasteners made of carbon steel and alloy steel — Part 1: Bolts, screws and studs with specified property classes — Coarse thread and fine pitch thread (ISO 898 1:2013) (A2)

EN ISO 5817:2014, Welding — Fusion-welded joints in steel, nickel, titanium and their alloys (beam welding excluded) — Quality levels for imperfections (ISO 5817:2014) (A2)

EN ISO 9013:2002, Thermal cutting — Classification of thermal cuts — Geometrical product specification and quality tolerances (ISO 9013:2002)

EN ISO 12100:2010, Safety of machinery — General principles for design — Risk assessment and risk reduction (ISO 12100:2010)

EN ISO 17659:2004, Welding — Multilingual terms for welded joints with illustrations (ISO 17659:2002)

ISO 4306-1:2007, Cranes — Vocabulary — Part 1: General

3 Terms ,definitions, symbols and abbreviations

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in EN ISO 12100:2010 [A] deleted text (A2] apply. For the definitions of loads, Clause 6 of ISO 4306-1:2007 applies.

3.2 Symbols and abbreviations

The symbols and abbreviations used in this Part of the EN 13001 are given in Table 1.

Table 1 — Symbols and abbreviations (1 of 4)

Symbols, abbreviations	Description
A	
	cross section
$A_{ m n}$	net cross section
$A_{ m S}$	stress area of a bolt
$A_{\mathcal{S}}$	shear area of the tear-out section (pinned connections)
a a	length of plate in buckling PREVIEW throat thickness of fillet welds
$a_{ m r}$	effective weldthickness rds.iteh.ai)
b	width of plate
c https://	SIST EN 13001-3-1:2012+A2:2018 edge stress ratio factor (buckling) standards lien arcadolysiandards 88t/07ce89c5-68e6-46af-a417-
Do, Di	outer in the diameter of hollow pin1-2012a2-2018
d	diameter (shank of bolt, pin)
d_{o}	diameter of hole
E	modulus of elasticity
$F_{ m b}$	tensile force in bolt
$F_{ m d}$	limit force
$A_1 F_k \langle A_1 \rangle$	characteristic value (force)
$F_{ m p}$	preloading force in bolt
$F_{ m Rd}$	limit design force
$F_{ m e}$	external force (on bolted connection)
$F_{ m b,Rd}$	limit design bearing force
$F_{ m b,Sd}$; $F_{ m bi,Sd}$	design bearing force
$F_{ m cs,Rd}$	limit design tensile force
$F_{ m p,d}$	design preloading force
$F_{ m cr}$	reduction in compression force due to external tension

Table 1 — Symbols and abbreviations (2 of 4)

Symbols, abbreviations	Description
$F_{t,Rd}$	limit design tensile force in bolt
$F_{t,Sd}$	external tensile force per bolt
$F_{ u}$, Sd	design shear force per bolt and shear plane
$F_{ m vp,Rd}$	limit design shear force per pin and shear plane
$F_{vp, Sd}$	design shear force per pin and shear plane
$F_{s,Rd}$	limit design slip force per bolt and shear plane
$F_{ m vs,Rd}$	limit design shear force of the connected part
F _{vd} , Sd	design force in the connected part
$F_{ m vt,Rd}$	limit design tensile force of the connected part
$F_{\sigma, au}$	acting normal/shear force
f	maximum imperfection
$f_{ m d}$	limit stress
$A_1 f_k \langle A_1 \rangle$	characteristic value (stress)
$f_{ m Rd}$	limit design stress
$f_{ m u}$	ultimate strength of material
$f_{ m ub}$	ultimate strength of bolts
$f_{ m w,Rd}$	limit design weld stress
f _y	yield stress of material, specified or measured
$f_{ m yb}$ $f_{ m yp}$	yield stress of bolts yield stress of pins, specified or measured (2). ai)
$\boxed{A_1} h_d$	distance between weld and contact level of acting load (4)
<i>I, I</i> _i	moments of inertia of members 01-3-1:2012+A2:2018
k K _b	stress concentration actor (printed collections) 89c5-68e6-46af-a417-stiffness of bolt 4643f87ebfl/sist-en-13001-3-1-2012a2-2018
K_{c}	stiffness of connected parts
k*	specific spectrum ratio factor
$k_{ m m}$	stress spectrum factor based on m of the detail under consideration
k_3	stress spectrum factor based on m = 3
$k_{\sigma x_{\prime}}, k_{\sigma y_{\prime}}, k_{\tau}$	buckling factors
L	element length (buckling)
$l_{ m m}$	gauge length
l_r	relevant weld length
l_W	weld length
M_{Rd}	limit design bending moment
M_{Sd}	design bending moment
m	slope constant of $\log \Delta \sigma / \log N$ -curve
N	compressive force (buckling)

Table 1 — Symbols and abbreviations (3 of 4)

Symbols,	Description
abbreviations	
NC N	notch class
N_k	critical buckling load
N_{ref} .	reference number of cycles
min σ, max σ	extreme values of stresses
P_{S}	probability of survival
p	penetration of weld
Q	shear (evaluation of stress cycles)
q_i	impact toughness parameter
α	cross section parameter (lateral buckling)
$lpha_b$	characteristic factor for bearing connection
$lpha_L$	load introduction factor (bolted connection)
$lpha_{ m w}$	characteristic factor for limit weld stress
$\gamma_{ m m}$	general resistance factor
$\gamma_{ m mf}$	fatigue strength specific resistance factor
γp	partial safety factor PD PREVIEW
γR	resulting resistance factor
γs	specific resistance factor.iteh.ai)
$\gamma_{ m Rb}$	resulting resistance factor of bolt 2018
γsbb, γsbs, γsbthttps://	specific resistance factors of bolted connections 17-
$\gamma_{ m Rm}$	resulting resistance factor of members
$\gamma_{ m sm}$	specific resistance factor of members
$\gamma_{ m Rp}$	resulting resistance factor of pins
$\gamma_{ m spm}$, $\gamma_{ m sps}$, $\gamma_{ m spb}$, $\gamma_{ m spt}$	specific resistance factors of pins
γ_{Rs}	resulting resistance factor of slip-resistance connection
γ_{ss}	specific resistance factor of slip-resistance connection
$\gamma_{ m Rc}$	resulting resistance factor for tension on section with holes
$\gamma_{ m st}$	specific resistance factor for tension on section with holes
$\gamma_{ m Rw}$	resulting resistance factor of welding connection
$\gamma_{ m sw}$	specific resistance factor of welding connection
$\delta_{ m p}$	elongation from preloading
ϕ_2	dynamic factor
κ	dispersion angle (wheel pressure)
K , K_x , K_y , $K_ au$	reduction factors (buckling)
λ	width of contact area in weld direction

Table 1 — Symbols and abbreviations (4 of 4)

Symbols, abbreviations	Description
λ_{x} , λ_{y} , λ_{τ}	non-dimensional plate slenderness (buckling)
Ψ	edge stress ratio (buckling)
$\it \Delta F_{ m b}$	additional force
$\Delta\delta_{t}$	additional elongation
μ	slip factor
ν	relative total number of stress cycles 街 deleted text 街
$\nu_{ ext{D}}$	ratio of diameters
$arDelta\sigma_{ extsf{c}}$	characteristic value of stress range (normal stress)
$\Delta au_{ m c}$	characteristic value of stress range (shear stress)
σ_e	reference stress (buckling)
$\sigma_{ m b}$	lower extreme value of stress range
$\sigma_{ m u}$	upper extreme value of stress range
$\sigma_{ m Sd}$	design stress (normal)
TSd	design stress (shear)
σ w, Sd	design weld stress (normal) DARD PREVIEW
₹w, Sd	design weld stress (shear) dards.iteh.ai)
$arDelta\sigma_{ m Rd}$	limit design stress range (normal)
$arDelta\sigma_{ m Rd,1}$	limit design stress tange for k*0±1-3-1:2012+A2:2018
$arDelta au_{ m Rd}$	littiss://standards.iteh.ai/catalog/standards/sist/07ce89c5-68e6-46af-a417- limit design stress range (shear) dd643f87ebt1/sist-en-13001-3-1-2012a2-2018
$arDelta\sigma_{ m Sd}$	design stress range (normal)
$arDelta au_{ m Sd}$	design stress range (shear)

4 General

4.1 Documentation

The documentation of the proof of competence shall include:

- design assumptions including calculation models,
- applicable loads and load combinations,
- material grades and qualities,
- weld quality levels, in accordance with EN ISO 5817,
- materials of connecting elements,
- relevant limit states,
- results of the proof of competence calculation. and tests when applicable.

4.2 Materials for structural members

4.2.1 Grades and qualities

European Standards specify materials and specific values. This standard gives a preferred selection.

For structural members, steel according to following European Standards should be used:

- a) Non-alloy structural steels EN 10025-2;
- b) Weldable fine grain structural steels in conditions:
 - 1) normalized (N) EN 10025-3;
 - 2) thermomechanical (M) EN 10025-4;
- c) High yield strength structural steels in the quenched and tempered condition EN 10025-6;
- d) High yield strength steels for cold forming in conditions:
 - 1) thermomechanical (M) EN 10149-2;
 - 2) normalized (N) EN 10149-3.

iTeh STANDARD PREVIEW

Austenitic stainless steels EN 10088-2.

(standards.iteh.ai)

Where stainless steels are welded, special attention should be given to the welding process and corrosion effects.

SIST EN 13001-3-1:2012+A2:2018

https://standards.iteh.ai/catalog/standards/sist/07ce89c5-68e6-46af-a417-

Table 2 shows specific values for the nominal value of strength f_{U} , f_{Y} . For limit design stresses f_{Rd} see 5.2. The values given are applicable for temperatures up to 100 °C for stainless steels and up to 150 °C for all other steels. For more information see the specific European Standard. \bigcirc

A_1 deleted text A_1

To allow the use of nominal values of plate thicknesses in the proof calculations, the minus tolerance of the plate shall be equal or better than that of class A of EN 10029:2010. Otherwise the actual minimum value of plate thickness shall be used. To allow the use of nominal dimensions for other steel products than plates, their minus tolerances shall be within those of the relevant European standards for those products.

- Grades and qualities other than those mentioned in the above standards and in Table 2 may be used if the mechanical properties and the chemical composition are specified in a manner corresponding to relevant European standard, and the following conditions are fulfilled:
- the design value of f_y is limited to $f_u/1,05$ for materials with $f_u/f_y < 1,05$;
- the percentage elongation at fracture $A \ge 7\%$ on a gauge length $L_0 = 5.65 \times \sqrt{S_0}$ (where S_0 is the original cross-sectional area);
- the weldability or non-weldability of the material is specified and, if intended for welding, weldability is demonstrated;
- if the material is intended for cold forming, the pertinent parameters are specified. (A)

NOTE Where it is deemed necessary to check for internal defects, classes of EN 10160 should be specified.