
Vtiči, vtičnice, konektorji in uvodnice na vozilih - Kabelsko napajanje električnih vozil - 3. del: Zahteve za dimenzijsko združljivost in izmenljivost za spojke na vozilih s trni in cevastimi kontakti za enosmerni (d.c.) in izmenični/enosmerni (a.c./d.c.) tok

Plugs, socket-outlets, vehicle connectors and vehicle inlets - Conductive charging of electric vehicles - Part 3: Dimensional compatibility and interchangeability requirements for DC and AC/DC pin and contact-tube vehicle couplers

Stecker, Steckdosen und Fahrzeugsteckvorrichtungen - Konduktives Laden von Elektrofahrzeugen - Teil 3: Anforderungen an und Hauptmaße für Stifte und Buchsen für die Austauschbarkeit von Fahrzeugsteckvorrichtungen zum dedizierten Laden mit Gleichstrom und als kombinierte Ausführung zum Laden mit Wechselstrom/Gleichstrom

Fiches, socles de prise de courant, prises mobiles de véhicule et socles de connecteur de véhicule - Charge conductive des véhicules électriques - Partie 3: Exigences dimensionnelles de compatibilité et d'interchangeabilité pour les connecteurs de véhicule à broches et alvéoles pour courant continu et pour courants alternatif et continu

Ta slovenski standard je istoveten z: prEN IEC 62196-3:2020

ICS:

29.120.30	Vtiči, vtičnice, spojke	Plugs, socket-outlets, couplers
43.120	Električna cestna vozila	Electric road vehicles

oSIST prEN IEC 62196-3:2020

en,fr,de



23H/462/CDV

COMMITTEE DRAFT FOR VOTE (CDV)

PROJECT NUMBER: IEC 62196-3 ED2	
DATE OF CIRCULATION: 2020-01-10	CLOSING DATE FOR VOTING: 2020-04-03
SUPERSEDES DOCUMENTS: 23H/446/CD,23H/451A/CC	

IEC SC 23H : PLUGS, SOCKET-OUTLETS AND COUPLERS FOR INDUSTRIAL AND SIMILAR APPLICATIONS, AND FOR ELECTRIC VEHICLES	
SECRETARIAT: France	SECRETARY: Mr Bertrand Doignon
OF INTEREST TO THE FOLLOWING COMMITTEES: TC 69	PROPOSED HORIZONTAL STANDARD: <input type="checkbox"/> Other TC/SCs are requested to indicate their interest, if any, in this CDV to the secretary.
FUNCTIONS CONCERNED: <input type="checkbox"/> EMC <input type="checkbox"/> ENVIRONMENT <input type="checkbox"/> QUALITY ASSURANCE <input type="checkbox"/> SAFETY	
<input checked="" type="checkbox"/> SUBMITTED FOR CENELEC PARALLEL VOTING Attention IEC-CENELEC parallel voting The attention of IEC National Committees, members of CENELEC, is drawn to the fact that this Committee Draft for Vote (CDV) is submitted for parallel voting. The CENELEC members are invited to vote through the CENELEC online voting system.	<input type="checkbox"/> NOT SUBMITTED FOR CENELEC PARALLEL VOTING

This document is still under study and subject to change. It should not be used for reference purposes.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

TITLE:

Plugs, socket-outlets, vehicle connectors and vehicle inlets - Conductive charging of electric vehicles - Part 3: Dimensional compatibility and interchangeability requirements for DC and AC/DC pin and contact-tube vehicle couplers

PROPOSED STABILITY DATE: 2025

NOTE FROM TC/SC OFFICERS:

If necessary, comments received will be reviewed in an MT 8 meeting in April 2020.

Copyright © 2019 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

CONTENTS

1		
2		
3	FOREWORD.....	4
4	INTRODUCTION.....	6
5	1 Scope.....	7
6	2 Normative references	7
7	3 Terms and definitions	8
8	4 General	8
9	5 Ratings.....	8
10	6 Connection between the power supply and the electric vehicle	8
11	7 Classification of accessories.....	10
12	8 Marking	11
13	9 Dimensions.....	11
14	10 Protection against electric shock	11
15	11 Size and colour of earthing conductors	12
16	12 Provision for earthing.....	12
17	13 Terminals	12
18	14 Interlocks.....	12
19	15 Resistance to aging of rubber and thermoplastic material	13
20	16 General construction	13
21	17 Construction of socket-outlets.....	13
22	18 Construction of plugs and vehicle connectors	13
23	19 Construction of vehicle inlets.....	13
24	20 Degrees of protection	13
25	21 Insulation resistance and dielectric strength	13
26	22 Breaking capacity	13
27	23 Normal operation	13
28	24 Temperature rise	14
29	25 Flexible cables and their connection	14
30	26 Mechanical strength.....	15
31	27 Screws, current-carrying parts and connections.....	15
32	28 Creepage distances, clearances and distances.....	15
33	29 Resistance to heat, to fire and to tracking.....	15
34	30 Corrosion and resistance to rusting	15
35	31 Conditional short-circuit current	15
36	32 Electromagnetic compatibility	15
37	33 Vehicle driveover	15
38	34 Thermal cycling	16
39	35 Humidity exposure	16
40	36 Misalignment test.....	16
41	37 Contact endurance test.....	16
42	Bibliography.....	58
43		
44	Table 301 – Overview of the DC vehicle interface	9

45	Table 302 – Overview of the combined AC/DC vehicle interface,	9
46	Table 303 – Interface Overview.....	11
47	Table 304 – Functionality of the contacts for configuration EE	30
48	Table 305 – Functionality of the contacts for DC configuration FF.....	43
49		
50		

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[SIST EN IEC 62196-3:2023](https://standards.iteh.ai/catalog/standards/sist/b9c032ed-1280-41dc-91a3-98da585c79e7/sist-en-iec-62196-3-2023)

<https://standards.iteh.ai/catalog/standards/sist/b9c032ed-1280-41dc-91a3-98da585c79e7/sist-en-iec-62196-3-2023>

51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PLUGS, SOCKET-OUTLETS, VEHICLE CONNECTORS AND VEHICLE INLETS – CONDUCTIVE CHARGING OF ELECTRIC VEHICLES –

Part 3: Dimensional compatibility requirements for DC and AC/DC pin and contact-tube vehicle couplers

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This amendment of International Standard IEC 62196-3 has been prepared by subcommittee 23H: Plugs, socket-outlets and couplers for industrial and similar applications, and for electric vehicles, of IEC technical committee 23: Electrical accessories.

This fourth edition cancels and replaces the third edition published in 2014 and constitutes a technical revision, with the following significant technical changes with respect to the previous edition:

- a) Increased ratings for all configurations.
- b) Reference to new tests in Part 1 (clauses 34, 35, 36 and 37)

105 The text of this amendment is based on the following documents:

FDIS	Report on voting
23H/---/FDIS	23H/---/RVD

106

107 Full information on the voting for the approval of this standard can be found in the report on
108 voting indicated in the above table.

109 This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

110 A list of all the parts in the IEC 62196 series, under the general title *Plugs, socket-outlets,*
111 *vehicle connectors and vehicle inlets – Conductive charging of electric vehicles*, can be found
112 on the IEC website.

113 This document is to be read in conjunction with IEC 62196-1. The clauses of the particular
114 requirements in Part 3 supplement or modify the corresponding clauses in Part 1. Where the
115 text indicates an "addition" to or a "replacement" of the relevant requirement, test specification
116 or explanation of Part 1, these changes are made to the relevant text of Part 1, which then
117 becomes part of the standard.

118 Subclauses, figures, tables or notes which are additional to those in IEC 62196-1 are
119 numbered starting from 301.

120 In this standard, the following print types are used:

- 121 – requirements proper: in roman type;
- 122 – *test specifications: in italic type;*
- 123 – notes: in smaller roman type.

124 The committee has decided that the contents of this publication will remain unchanged until
125 the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data
126 related to the specific publication. At this date, the publication will be

- 127 • reconfirmed,
- 128 • withdrawn,
- 129 • replaced by a revised edition, or
- 130 • amended.

131

132

133

134

INTRODUCTION

135 IEC 61851 series specifies requirements for EV conductive supply equipment.

136 IEC 62196 series specifies the requirements for plugs, socket-outlets, vehicle connectors,
137 vehicle inlets and cable assemblies as described in the IEC 61851 family of standards.

138 Charging using off-board DC charging equipment can be achieved by the direct connection of
139 an electric vehicle to DC EV supply equipment incorporating control and communication
140 circuits.

141 To support the connection of DC power for such vehicles, this standard provides the standard
142 interface configurations of DC vehicle couplers and accessories to be used in conductive
143 charging of electric vehicles, taking the most frequent charging situations into consideration.

144 IEC 62196 is divided into several parts as follows:

- 145 – Part 1: General requirements, comprising clauses of a general character.
- 146 – Part 2: Dimensional compatibility requirements for AC pin and contact-tube accessories.
- 147 – Part 3: Dimensional compatibility requirements for DC and AC/DC pin and contact-tube
148 vehicle couplers.
- 149 – Part 4¹: Dimensional compatibility requirements for DC pin and contact-tube accessories
150 for Class II or Class III applications.
- 151 – Part 6²: Dimensional compatibility requirements for DC pin and contact-tube couplers for
152 applications using a system of protective electrical separation.

153

154

iteh Standards
(<https://standards.iteh.ai>)
Document Preview

[SIST EN IEC 62196-3:2023](https://standards.iteh.ai/catalog/standards/sist/b9c032ed-1280-41dc-91a3-98da585c79e7/sist-en-iec-62196-3-2023)

<https://standards.iteh.ai/catalog/standards/sist/b9c032ed-1280-41dc-91a3-98da585c79e7/sist-en-iec-62196-3-2023>

1 Publication pending

2 Under consideration.

155 **PLUGS, SOCKET-OUTLETS, VEHICLE**
156 **CONNECTORS AND VEHICLE INLETS –**
157 **CONDUCTIVE CHARGING OF ELECTRIC VEHICLES –**
158

159 **Part 3: Dimensional compatibility requirements**
160 **for DC and AC/DC pin and contact-tube vehicle couplers**
161

162
163
164 **1 Scope**

165 This document is applicable to vehicle couplers with pins and contact-tubes of standardized
166 configuration, herein also referred to as “accessories”, intended for use in electric vehicle
167 conductive charging systems which incorporate control means, with rated operating voltage
168 and current according to IEC 62196-1:2020¹.

169 This document applies to high power DC interfaces and combined AC/DC interfaces of vehicle
170 couplers that are intended for use in conductive charging systems for circuits specified in
171 IEC 61851-1:2017, and IEC 61851-23: 201X².

172 The DC vehicle connectors and inlets covered by this part of the standard are used only in
173 charging mode 4, according to Clause 6.2.4, and case C, as shown in Figure 3, of IEC 61851-
174 1:2017.

175 These vehicle couplers are intended to be used for circuits similar to those specified in
176 IEC 61851-23 which operate at different voltages and which may include ELV and
177 communication signals.

178 This document applies to the vehicle couplers to be used in an ambient temperature of
179 between –30 °C and +40 °C.

180 NOTE 1 In some countries, other requirements may apply.

181 NOTE 2 In the following country, –35 °C applies: SE. IEC 62196-3:2023

182 These vehicle couplers are intended to be connected only to cables with copper or copper-
183 alloy conductors.

184 **2 Normative references**

185 Clause 2 of IEC 62196-1:2020 applies, except as follows.

186 *Additional normative reference:*

187 IEC 62196-2:2020³, *Plugs, socket-outlets, vehicle connectors and vehicle inlets – Conductive*
188 *charging of electric vehicles – Part 2: Dimensional compatibility and interchangeability*
189 *requirements for AC pin and contact-tube accessories*

¹ IEC 62196-1:2020 at CDV stage

² IEC 61851-23:201X under development

³ IEC 62196-2:2020 at CDV stage

190 *ISO 17409:2015, Electrically propelled road vehicles – Connection to an external electric*
191 *power supply – Safety specifications*

192 **3 Terms and definitions**

193 Clause 3 of IEC 62196-1:2020 applies.

194 **4 General**

195 Clause 4 of IEC 62196-1:2020 applies.

196 **5 Ratings**

197 Clause 5 of IEC 62196-1:2020 applies.

198 For configuration AA, control pilot contacts are rated 30 V, 10 A

199 For configuration BB, auxiliary power supply contacts are rated 30 V, 20 A. The auxiliary
200 power supply may consist of a safety extra low voltage system circuit.

201 **6 Connection between the power supply and the electric vehicle**

202 Clause 6 of IEC 62196-1:2020 applies, except as follows:

203 **6.2 Basic interface**

204 *Not applicable.*

205 **6.3 DC interface**

206 The DC interface may contain up to 12 power or signal contacts, with only one physical
207 configuration of contact positions. The electrical ratings and contact functions are described in

208 <https://standards.iteh.ai/catalog/standards/sist/b9c032ed-1280-41dc-91a3-98da585c79e7/sist-en-iec-62196-3-2023>

209

Table 301 – Overview of the DC vehicle interface

Position number ^a	Configuration				Symbol	Function
	AA		BB			
	U_{max} V	I_{max} A	U_{max} V	I_{max} A		
1	1 000	400	950	250	DC +	DC +
2	1 000	400	950	250	DC –	DC –
3	30	10	30	2	CP	Control Pilot 1
4	30	10	30	2	CP2	Control Pilot 2
5	30	10	-	-	CP3	Control Pilot 3
6	30	2	30	2	COM1	Communication 1 (+)
7	30	2	30	2	COM2	Communication 1 (–)
8	30	2	-	-	IM	Isolation Monitor
9	-	-	950	Rated for fault ^b	PE	Protective earth
10	30	2	-	-	PP or CS	Proximity detection or connection switch
11	-	-	30	20	AUX1	Auxiliary Power Supply 1 (+)
12	-	-	30	20	AUX2	Auxiliary Power Supply 1 (–)

^a Position number does not refer to the location and/or identification of the contact in the accessory.

^b “Rated for fault” means “rated for the highest fault current”.

210

211 They shall be used in a system according to IEC 61851-23:201X, Annex AA “DC EV supply
212 equipment of System A” or Annex BB “DC EV supply equipment of System B” respectively.
213 See the corresponding standard sheets for additional interface details.

214 For use with non-isolated DC EV supply equipment, the interface shall be provided with a
215 contact for protective earthing conductors.

216 For use with isolated DC EV supply equipment, the interface may be provided with a contact
217 for protective earthing conductors.

218 *Additional subclause:*

219 6.6 Combined interface

220 A combined interface extends the use of a basic interface for AC and DC charging.

221 The combined interface permits the electric vehicle to receive/conduct AC or DC energy using
222 separate power contacts. The electrical ratings and their function are described in Table 302.

223 **Table 302 – Overview of the combined AC/DC vehicle interface,**

Position number ^a	Configuration EE				Configuration FF			
	U_{max}	I_{max}	Symbol	Function	U_{max}	I_{max}	Symbol	Function
	V	A			V	A		
1	250 ^b	32 ^b	L1	L1	480 ^c	63 ^{c,e}	L1	L1

2	250 ^b	32 ^b	L2	L2/N	480 ^c	63 ^c	L2	L2
3	—	—	—	—	480 ^c	63 ^c	L3	L3
4	—	—	—	—	480 ^c	63 ^{c,e}	N	Neutral
5	1000	-- ^f	PE	Protective earth	1000	-- ^f	PE	Protective earth
6	30 ^d	2 ^d	CP	Control Pilot	30 ^d	2 ^d	CP	Control Pilot
7	30 ^d	2 ^d	PP or CS	Proximity detection or connection switch	30 ^d	2 ^d	PP or CS	Proximity detection or connection switch
8	1000	400	DC+	DC+	1000	400	DC+	DC+
9	1000	400	DC-	DC-	1000	400	DC-	DC-

^a Position number does not refer to the location and/or identification of the contact in the accessory.

^b These contacts are only available in Configuration EE single phase vehicle inlet. They may be used as portion of basic interface, see IEC 62196-2: Ed.3.0, Standard Sheets 2-I.

^c These contacts are optional in Configuration FF. They may be used as portion of basic interface, see IEC 62196-2: Ed.3.0, Standard Sheets 2-II.

^d These contacts may be used as basic interface. For requirements for basic interface see IEC 62196-2: Ed.3.0, Standard Sheets 2-I and 2-II.

^e Contacts 1 and 4 for single phase rated $I_{max} = 70$ A.

^f Conductor size dependent upon system requirements.

224 The basic portion of the combined vehicle inlet can be used with a basic connector for either
225 AC or with a combined vehicle connector for DC charging.

226 Combined couplers shall only be used for DC charging with the “DC EV supply equipment of
227 System C” described in IEC 61851-23:201X, Annex CC.

228 NOTE 1: Implementation of all aspects (i.e. topology and communication) according to Annex CC ensures that:

229 This system allows DC charging but prevents AC and DC charging at the same time.

230 – AC chargeable EVs with a basic vehicle inlet do not need any means to protect themselves against DC voltage
231 at the inlet. This protection is provided by the DC charging system.

232 – Vehicle protection against mischarging in case of fault is provided in accordance with ISO 17409:2015. [iec-62196-3-2023](#)

233 NOTE 2: If the AC or DC ratings of a mating connector and inlet differ, the coupler (mating pair) is used at the
234 lower rating of either the vehicle connector or vehicle inlet of the mating accessory.

235 Accessories of the combined AC/DC type intended for use with AC shall comply with the
236 ratings and requirements of IEC 62196-2: 201X.

237 7 Classification of accessories

238 Clause 7 of IEC 62196-1:2020 applies, except as follows:

239 7.1.1 Replacement:

240 – Vehicle connectors,

241 – Vehicle inlets.

242 7.1.5 Replacement:

243 As specified in Clause 6 and in IEC 61851-1:2017:

244 – Combined interface

245 – DC interface

246 *Additional subclause:*

247 **7.301** According to the standard sheets used:

- 248 – Configuration AA
- 249 – Configuration BB
- 250 – Configuration EE and AC corresponding to Type 1 in IEC 62196-2: Ed.3.0
- 251 – Configuration FF and AC corresponding to Type 2 in IEC 62196-2: Ed.3.0.

252 **8 Marking**

253 Clause 8 of IEC 62196-1:2020 applies.

254 **9 Dimensions**

255 Clause 9 of IEC 62196-1:2020 applies, except as follows:

256 **9.1 Replacement:**

257 The vehicle connector and vehicle inlet shall comply with the relevant configuration shown in
258 Table 303:

259 **Table 303 – Interface Overview**

Configuration	Dimensions described in	Max. Rated Voltage V DC	Max. Rated Current A DC	Shall only be used with DC charging station according to
AA	Standard Sheets 3-I	1 000	400	IEC 61851-23: Ed.2.0, Annex AA
BB	Standard Sheets 3-II	950	250	IEC 61851-23: Ed.2.0, Annex BB
EE ^a	Standard Sheets 3-III	1 000	400	IEC 61851-23: Ed.2.0, Annex CC
FF ^b	Standard Sheets 3-IV	1 000	400	IEC 61851-23: Ed.2.0, Annex CC

^a AC ratings are in accordance with 62196-2:2016, clause 6.5, type 1

^b AC ratings are in accordance with 62196-2:2016, clause 6.5, type 2

260 **10 Protection against electric shock**

261 Clause 10 of IEC 62196-1:2020 applies, except as follows:

262 **10.3 Contact sequencing**

263 *Replacement:*

264 For all DC interfaces, the contact sequence during the connection process shall be:

- 265 – Protective Earth (if any)
- 266 – DC power contacts
- 267 – Isolation monitor contacts:

268 NOTE 1 if provided, isolation monitor contacts shall mate before or simultaneously with the control pilot contact.

- 269 – Proximity detection or connection switch contact

270 NOTE 2 if provided, proximity detection or connection switch contacts shall mate before or simultaneously with
271 the control pilot contact.

- 272 – Control pilot contact

273 During disconnection the order shall be reversed.

274 Accessories shall be so designed that

275 a) when inserting the vehicle connector,

276 1) the protective earth connection is made before the DC power contacts, if any, are
277 made;

278 2) the control pilot connection, if any, is made after the DC power contacts are made;

279 3) the proximity contact or connection switch contact, if any, is made after the protective
280 earth contact and before or simultaneously the control pilot are made.

281 b) when withdrawing the vehicle connector,

282 4) the DC power contacts are broken before the protective earth connection is broken;

283 5) the control pilot connection, if any, is broken before the DC power contacts are broken;

284 6) the proximity contact or connection switch contact, if any, is broken before the
285 protective earth contact and after or simultaneously the control pilot are opened.

286 *Compliance is checked by inspection and manual test, if required.*

287 **11 Size and colour of earthing conductors**

288 Clause 11 of IEC 62196-1:2020 applies.

289 *Additional subclauses:*

290 *11.301 The earthing conductor may be sized smaller than defined if the conductor can fulfil*
291 *the requirements of 12.3 of IEC 62196-1:201X.*

292 **12 Provision for earthing**

293 Clause 12 of IEC 62196-1:2020 applies, except as follows:

294 **12.1 Replacement:**

[SIST EN IEC 62196-3:2023](https://standards.iteh.ai/catalog/standards/sist/b9c032ed-1280-41dc-91a3-98da585c79e7/sist-en-iec-62196-3-2023)

295 Accessories shall be provided with a protective earthing contact and earthing terminal.
296 Protective earthing contacts shall be directly and reliably connected to the protective earthing
297 terminals.

298 **13 Terminals**

299 Clause 13 of IEC 62196-1:2020 applies.

300 **14 Interlocks**

301 Clause 14 of IEC 62196-1:201X applies, except as follows:

302 *Additional subclause:*

303 **14.301 Latching function**

304 Accessories shall be provided with a latching device to prevent the connection to be
305 separated unintentionally or by unauthorized persons.

306 The interlock function shall be performed by the proper functioning of the latching device.