INTERNATIONAL STANDARD

ISO 43

Second edition 2016-11-01

Aircraft — Jacking pads

Aéronefs — Points d'appui du vérin de levage

iTeh STANDARD PREVIEW (standards.iteh.ai)



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 43:2016 https://standards.iteh.ai/catalog/standards/sist/6f65de33-793e-4962-bf99-b3ed67507513/iso-43-2016



COPYRIGHT PROTECTED DOCUMENT

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Con	itents	Page
Forew	word	iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4.	Required characteristics	1

iTeh STANDARD PREVIEW (standards.iteh.ai)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

ISO 43 was prepared by Technical Committee ISO/TC 20, Aircraft and space vehicles, Subcommittee SC 9, Air cargo and ground equipment.

ISO 43 2016

This second edition cancels and replaces the first edition (ISO 43:1976), of which clause 4 and Figure 1 to Figure 6 has been technically revised to add a seventh size for heavier aircraft.

Aircraft — Jacking pads

1 Scope

This document specifies the profiles and dimensions of aircraft jacking pads and the minimum clearance to be provided around them. Aircraft jacking pads, also called adapters, can be attached to primary flight structure (PFS) or to axles.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

(standards.iteh.ai)


4 Required characteristics

ISO 43:2016

Aircraft jacking pads are to be limited to the seven/types specified below, which specify the shape, size and clearances to be provided around the pads 13/iso-43-2016

They shall meet the shape specified in <u>Figure 1</u> and the dimensions and clearances specified in <u>Table 1</u> and <u>Table 2</u> for the type corresponding to their intended load capacity.

Conversion factors: 1 pound force (lbf) = 4,45 Newtons. 1 inch = 25,4 mm



Key

1 optional taper

Figure 1 — Jacking pads adapters categorization

Table 1 — Jacking pads adapters categorization (pounds - inches)

				Øa	b	С	r_1
Туре	Load	Load	Adapter for	Minimum clearance space	Minimum clearance space	Wheel, brake, tire minimum clearance	Spherical radius
	min.	max.					± 0.010
	pound force	pound force		inch	inch	inch	inch
I	0	10000	PFS	3	1.125	N/A	0.5
II	10000	112000	PFS	3 to 12	1.187	N/A	0.75
III	0	10000	Axle	3	0.750	2.25	0.5
IV	10000	150000	Axle	3 to 9	0.875	3.5	0.75
V	150000	281100	Axle	9	1.187	4.5	1.25
VI	112000	250000	PFS	12 to 13.7	1.375	N/A	1.25
VII	250000	359700	PFS	13.7	1.500	N/A	1.75

 $Table\ 2- Jacking\ pads\ adapters\ categorization\ (kilonewtons-mm)$

				Øa	b	С	r_1
Туре	Load	Loa d T (Adapter 1 for	Minimum clearance space	space	Wheel, brake, tire minimum clearance	Spherical radius
	min.	max.	(St	andards.i	teh.aı)		± 0,25
	kN	kN		mm 43:2016	mm	mm	mm
I	0	44t5s://sta	ndarRF.Seh.a	ıi/catalog <mark>/6a2</mark> dards/si	st/6f6 <i>5</i> 28 <i>5</i> 58793e-	4962-b \/ / A	12,70
II	44,5	500	PFS	b376,2 to 304,80-4	13-20 B 0,15	N/A	19,05
III	0	44,5	Axle	76,2	19,05	57,15	12,70
IV	44,5	667	Axle	76,2 to 228,6	22,23	88,9	19,05
V	667	1250	Axle	228,6	30,15	114,3	31,75
VI	500	1112	PFS	304,8 to 347,98	34,93	N/A	31,75
VII	1112	1600	PFS	347,98	38,10	N/A	44,45

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 43:2016(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)