

ETSI TS 148 018 V17.0.0 (2022-05)



Digital cellular telecommunications system (Phase 2+) (GSM);
General Packet Radio Service (GPRS);
Base Station System (BSS)
- Serving GPRS Support Node (SGSN);
BSS GPRS protocol (BSSGP)

(3GPP TS 48.018 version 17.0.0 Release 17)

ETSI TS 148 018 V17.0.0 (2022-05)
<https://standards.etsi.org/standard/etsi-ts-148-018-v17-0-0-2022-05>
ac0e-4a03-989d-56dee7d39203/etsi-ts-148-018-v17-0-0-2022-05



Reference

RTS/TSGR-0048018vh00

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:
<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

(standards.iteh.ai)

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

[ETSI TS 148 018 V17.0.0 \(2022-05\)](https://www.etsi.org/deliverable/3gpp-ts-148-018-v17.0.0-2022-05)

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	14
1 Scope	15
2 References	15
3 Abbreviations	17
3.1 Vocabulary	17
4 Logical configuration of the Gb-interface.....	18
4.1 High-level characteristics of the Gb-interface	18
4.2 Position of BSSGP within the protocol stack on the Gb-interface	18
5 Elements for layer-to-layer communication.....	19
5.1 Definition of service model	19
5.2 Service primitives provided by the BSSGP at a BSS	21
5.2.1 RL-DL-UNITDATA.ind.....	24
5.2.2 RL-UL-UNITDATA.req.....	24
5.2.3 (void)	24
5.2.3a RL-DL-MBMS-UNITDATA.ind	24
5.2.3b RL-UL-MBMS-UNITDATA.req	25
5.2.4 GMM-PAGING.ind.....	25
5.2.5 GMM-RA-CAPABILITY.ind	25
5.2.6 GMM-RA-CAPABILITY-UPDATE.req	25
5.2.7 GMM-RA-CAPABILITY-Y-UPDATE.cnf	25
5.2.8 GMM-RADIO-STATUS.req.....	25
5.2.9 GMM-SUSPEND.req	25
5.2.10 GMM-SUSPEND.cnf	25
5.2.11 GMM-RESUME.req	25
5.2.12 GMM-RESUME.cnf	25
5.2.12a GMM-MS-REGISTRATION-ENQUIRY.req	25
5.2.12b GMM-MS-REGISTRATION-ENQUIRY.res	25
5.2.13 NM-FLUSH-LL.ind.....	26
5.2.14 NM-FLUSH-LL.res	26
5.2.15 NM-LCC-DISCARDED.req	26
5.2.16 NM-FLOW-CONTROL-BVC.req	26
5.2.17 NM-FLOW-CONTROL-BVC.cnf	26
5.2.18 NM-FLOW-CONTROL-MS.req	26
5.2.19 NM-FLOW-CONTROL-MS.cnf	26
5.2.19a NM-FLOW-CONTROL-PFC.req	26
5.2.19b NM-FLOW-CONTROL-PFC.cnf	26
5.2.20 NM-STATUS.req	26
5.2.21 NM-STATUS.ind	26
5.2.22 NM-BVC-BLOCK.req	26
5.2.23 NM-BVC-BLOCK.cnf	27
5.2.24 NM-BVC-UNBLOCK.req	27
5.2.25 NM-BVC-UNBLOCK.cnf	27
5.2.26 NM-BVC-RESET.req	27
5.2.27 NM-BVC-RESET.res	27
5.2.28 NM-BVC-RESET.ind	27
5.2.29 NM-BVC-RESET.cnf	27
5.2.30 NM-TRACE.ind	27
5.2.30a NW-OVERLOAD.ind	27
5.2.31 PFM-DOWNLOAD-BSS-PFC.req	27
5.2.32 PFM-CREATE-BSS-PFC.ind	27

5.2.33	PFM-CREATE-BSS-PFC.res	27
5.2.34	PFM-MODIFY-BSS-PFC.req	28
5.2.35	(void)	28
5.2.36	(void)	28
5.2.37	PFM-MODIFY-BSS-PFC.cnf	28
5.2.38	PFM-DELETE-BSS-PFC.ind	28
5.2.39	PFM-DELETE-BSS-PFC.res	28
5.2.39a	PFM-DELETE-BSS-PFC.req	28
5.2.39b	PFM-PS-HANDOVER-REQUIRED.req	28
5.2.39c	PFM-PS-HANDOVER-REQUIRED.cnf	28
5.2.39d	PFM-PS-HANDOVER-REQUEST.ind	28
5.2.39e	PFM-PS-HANDOVER-REQUEST.res	28
5.2.39f	PFM-PS-HANDOVER-COMPLETE.req	28
5.2.39g	PFM-PS-HANDOVER-CANCEL.req	29
5.2.40	LCS-LOCATE.ind	29
5.2.41	LCS-LOCATE.res	29
5.2.42	LCS-ABORT.ind	29
5.2.43	LCS-INFORMATION-TRANSFER.req	29
5.2.44	LCS-INFORMATION-TRANSFER.cnf	29
5.2.45	RIM-PDU-TRANSFER.req	29
5.2.46	RIM-PDU-TRANSFER.ind	29
5.2.47	(void)	30
5.2.48	(void)	30
5.2.49	(void)	30
5.2.50	(void)	30
5.2.51	(void)	30
5.2.52	(void)	30
5.2.53	MBMS-SESSION-START-REQUEST.ind	30
5.2.54	MBMS-SESSION-START-RESPONSE.res	30
5.2.55	MBMS-SESSION-STOP-REQUEST.ind	30
5.2.56	MBMS-SESSION-STOP-RESPONSE.res	30
5.2.57	MBMS-SESSION-UPDATE-REQUEST.ind	30
5.2.58	MBMS-SESSION-UPDATE-RESPONSE.res	30
5.3	Service primitives provided by the BSSGP at an SGSN	30
5.3.1	BSSGP-DL-UNITDATA.req	33
5.3.2	BSSGP-UL-UNITDATA.ind	33
5.3.3	(void)	33
5.3.3a	BSSGP-DL-MBMS-UNITDATA.req	34
5.3.3b	BSSGP-UL-MBMS-UNITDATA.ind	34
5.3.4	GMM-PAGING.req	34
5.3.5	GMM-RA-CAPABILITY.req	34
5.3.6	GMM-RA-CAPABILITY-UPDATE.ind	34
5.3.7	GMM-RA-CAPABILITY-UPDATE.res	34
5.3.8	GMM-RADIO-STATUS.ind	34
5.3.9	GMM-SUSPEND.ind	34
5.3.10	GMM-RESUME.ind	34
5.3.10a	GMM-MS-REGISTRATION-ENQUIRY.ind	34
5.3.10b	GMM-MS-REGISTRATION-ENQUIRY.res	34
5.3.11	NM-FLUSH-LL.req	34
5.3.12	NM-FLUSH-LL.cnf	35
5.3.13	NM-LLC-DISCARDED.ind	35
5.3.14	NM-FLOW-CONTROL-BVC.ind	35
5.3.15	NM-FLOW-CONTROL-MS.ind	35
5.3.15a	NM-FLOW-CONTROL-PFC.ind	35
5.3.16	NM-STATUS.req	35
5.3.17	NM-STATUS.ind	35
5.3.18	NM-BVC-BLOCK.ind	35
5.3.19	NM-BVC-UNBLOCK.ind	35
5.3.20	NM-BVC-RESET.req	35
5.3.21	NM-BVC-RESET.res	35
5.3.22	NM-BVC-RESET.ind	35
5.3.23	NM-BVC-RESET.cnf	36

5.3.24	NM-TRACE.req	36
5.3.24a	NM-OVERLOAD-START.req.....	36
5.3.25	PFM-DOWNLOAD-BSS-PFC.ind.....	36
5.3.26	PFM-CREATE-BSS-PFC.req.....	36
5.3.27	PFM-CREATE-BSS-PFC.cnf.....	36
5.3.28	PFM-MODIFY-BSS-PFC.ind	36
5.3.29	PFM-MODIFY-BSS-PFC.res.....	36
5.3.30	PFM-DELETE-BSS-PFC.req	36
5.3.31	PFM-DELETE-BSS-PFC.cnf	36
5.3.31a	PFM-DELETE-BSS-PFC.ind	36
5.3.31b	PFM-PS-HANDOVER-REQUIRED.ind	36
5.3.31c	PFM-PS-HANDOVER-REQUIRED.res.....	37
5.3.31d	PFM-PS-HANDOVER-REQUEST.req.....	37
5.3.31e	PFM-PS-HANDOVER-REQUEST.cnf.....	37
5.3.31f	PFM-PS-HANDOVER-COMPLETE.ind.....	37
5.3.31g	PFM-PS-HANDOVER-CANCEL.ind.....	37
5.3.32	LCS-LOCATE.req.....	37
5.3.33	LCS-LOCATE.cnf.....	37
5.3.34	LCS-ABORT.req	37
5.3.35	LCS-INFORMATION-TRANSFER.ind	37
5.3.36	LCS-INFORMATION-TRANSFER.res.....	37
5.3.37	RIM-PDU-TRANSFER.req.....	37
5.3.38	RIM-PDU-TRANSFER.ind.....	38
5.3.39	(void)	38
5.3.40	(void)	38
5.3.41	(void)	38
5.3.42	(void)	38
5.3.43	(void)	38
5.3.44	(void)	38
5.3.45	MBMS-SESSION-START-REQUEST.req	38
5.3.46	MBMS-SESSION-START-RESPONSE.cnf.....	38
5.3.47	MBMS-SESSION-STOP-REQUEST.req.....	38
5.3.48	MBMS-SESSION-STOP-RESPONSE.cnf.....	38
5.3.49	MBMS-SESSION-UPDATE-REQUEST.req	38
5.3.50	MBMS-SESSION-UPDATE-RESPONSE.cnf.....	38
5.4	Primitive parameters.....	38
5.4.1	BSSGP Virtual Connection Identifier (BVCI).....	38
5.4.2	Link Selector Parameter (LSP)	40
5.4.3	[functional-name] PDU.....	40
5.4.4	Network Service Entity Identifier (NSEI)	41
5.4.5	BSS Context.....	41
5.4.6	MBMS Service Context.....	41
5.4.7	TLLI.....	41
6	User data and signalling procedures between RL and BSSGP SAPs.....	41
6.1	Downlink UNITDATA procedure	41
6.1.1	Abnormal conditions.....	44
6.2	Uplink UNITDATA procedure	44
6.2.1	Abnormal conditions.....	45
6.3	RA-CAPABILITY procedure	45
6.3.1	Abnormal conditions.....	45
6.4	Downlink MBMS-UNITDATA procedure	45
6.5	Uplink MBMS-UNITDATA procedure	46
6.6	Rerouting procedure in case of MOCN configuration for network sharing, Dedicated Core Networks or MS assisted Dedicated Core Network selection	46
6.6.1	General.....	46
6.6.2	Reroute Indication	47
6.6.3	Reroute complete	49
6.6.4	Abnormal Conditions.....	49
6.7	Rerouting procedure in case of GWCN configuration for network sharing	49
6.7.1	General.....	49
6.7.2	Reroute indication.....	50

6.7.3	Reroute complete	51
6.7.4	Abnormal Conditions.....	51
7	Signalling procedures between GMM SAPs.....	51
7.1	Paging procedure.....	51
7.1a	Paging procedure for Extended Coverage and eDRX	53
7.1a.1	Coverage Class and eDRX information available	53
7.1a.2	Coverage Class information not available, eDRX information available	53
7.1a.3	Coverage Class information available, eDRX information not available	54
7.1b	Paging Procedure for Extended Coverage with Paging Indication.....	54
7.2	Radio Access Capability Update procedure	54
7.2.1	Abnormal conditions.....	54
7.3	Radio Status procedure.....	55
7.4	SUSPEND procedure	55
7.4.1	Abnormal conditions.....	56
7.5	RESUME procedure.....	56
7.5.1	Abnormal conditions.....	56
7.6	MS Registration Enquiry.....	57
7.6.1	General.....	57
7.6.2	Registration enquiry.....	57
7.6.3	Registration response.....	57
8	Signalling procedures between NM SAPs	57
8.1	FLUSH-LL (logical link) procedure.....	57
8.1.1	Abnormal Conditions.....	59
8.2	Flow Control procedure.....	59
8.2.1	General model of operation	59
8.2.2	Mode of operation.....	59
8.2.3	Flow Control of Traffic from an SGSN to BSS	60
8.2.3.1	Control of the downlink throughput by the SGSN.....	60
8.2.3.2	Flow Control Conformance Definition	61
8.2.3.3	Response time within the SGSN to flow control messages.....	63
8.2.3.4	Frequency of sending BVC or MS or PFC Flow Control PDUs.....	63
8.2.3.5	FLOW-CONTROL PDUs.....	63
8.2.3.6	Condition of Bmax for MS after Initial Flow-Control-BVC.....	64
8.2.4	Flow Control of Uplink Traffic from a BSS to an SGSN.....	64
8.3	BVC blocking and unblocking procedure	64
8.3.1	PTP BVC	64
8.3.2	Signalling BVC.....	65
8.3.3	Abnormal Conditions.....	65
8.4	BVC-RESET procedure	66
8.4.1	Signalling BVC.....	67
8.4.2	PTP BVC	67
8.4.3	Abnormal Conditions.....	67
8.5	Trace procedure	67
8.6	Overload Control procedure	68
8.6.1	General.....	68
8.6.2	Overload Operation.....	68
8a	Signalling procedures between PFM SAPs.....	68
8a.1	Create BSS PFC procedure	68
8a.1.0	General.....	68
8a.1.0a	Allocation/Retention Priority handling.....	69
8a.1.1	Abnormal conditions.....	71
8a.2	Modify BSS PFC procedure	71
8a.2.1	Abnormal conditions.....	71
8a.3	Delete BSS PFC procedure	72
8a.4	PS Handover Required procedure	72
8a.4.1	Abnormal conditions.....	74
8a.5	PS Handover Request procedure	74
8a.5.1	Abnormal conditions.....	75
8a.6	PS Handover Complete procedure	76
8a.6.1	Abnormal conditions.....	76

8a.7	PS Handover Cancel procedure.....	76
8a.7.1	Abnormal conditions.....	77
8b	Signalling Procedures between LCS SAPs	78
8b.1	Location Procedure.....	78
8b.1.1	Unsuccessful Operation	79
8b.1.2	Abnormal Conditions.....	79
8b.1.3	Overload	79
8b.2	Position Command Procedure	80
8b.2.1	Position Command.....	80
8b.2.2	Position Response	80
8b.2.3	Unsuccessful Operation	80
8c	Signalling procedures between RIM SAPs	81
8c.1	General	81
8c.1.1	Introduction.....	81
8c.1.2	Definitions	81
8c.1.2.1	Controlling, serving, originating and receiving nodes	81
8c.1.2.2	RIM association	81
8c.1.2.3	RIM variables.....	82
8c.1.3	RIM PDUs description.....	82
8c.1.3.1	RAN-INFORMATION-REQUEST PDU	82
8c.1.3.2	RAN-INFORMATION PDU	82
8c.1.3.3	RAN-INFORMATION-ACK PDU	83
8c.1.3.4	RAN-INFORMATION-ERROR PDU.....	83
8c.1.3.5	RAN-INFORMATION-APPLICATION-ERROR PDU	83
8c.1.4	RIM addressing and routing principles	83
8c.1.4.1	RIM routing address.....	83
8c.1.4.1.1	GERAN BSS identification	83
8c.1.4.1.2	UTRAN RNS identification	83
8c.1.4.1.3	E-UTRAN eNodeB identification	83
8c.1.4.1.4	eHRPD eAN identification	83
8c.1.4.2	Routing via the core network	83
8c.1.4.3	Address mirroring	84
8c.1.5	In-order delivery and reliable transfer - RSN	84
8c.1.5.1	General.....	84
8c.1.5.2	Allocating RSN values at the sending BSS	85
8c.1.5.3	Comparing RSN values at the receiving BSS	85
8c.1.6	RIM Protocol Version Number.....	85
8c.2	RIM procedures.....	86
8c.2.1	General.....	86
8c.2.2	RAN Information Request procedure	86
8c.2.2.1	RAN Information Request/Single Report procedure	86
8c.2.2.1.1	Initiation by the controlling BSS	86
8c.2.2.1.2	Reception of a valid RAN-INFORMATION-REQUEST/Single Report PDU by the serving BSS	87
8c.2.2.1.3	Reception of a valid RAN-INFORMATION/Single Report PDU by the controlling BSS	87
8c.2.2.1.4	Expiration of T(RIR) in the controlling BSS	87
8c.2.2.2	RAN Information Request/Multiple Report procedure	87
8c.2.2.2.1	Initiation by the controlling BSS	88
8c.2.2.2.2	Reception of a valid RAN-INFORMATION-REQUEST/Multiple Report PDU by the serving BSS	88
8c.2.2.2.3	Reception of a valid RAN-INFORMATION PDU/Initial Multiple Report PDU by the controlling BSS	89
8c.2.2.2.4	Expiration of T(RIR) in the controlling BSS	89
8c.2.2.3	RAN Information Request/Stop procedure	89
8c.2.2.3.1	Initiation by the controlling BSS	89
8c.2.2.3.2	Reception of a valid RAN-INFORMATION-REQUEST/Stop PDU by the serving BSS	89
8c.2.2.3.3	Reception of a valid RAN-INFORMATION/Stop PDU by the controlling BSS	90
8c.2.2.3.4	Expiration of T(RIR) in the controlling BSS	90
8c.2.3	RAN Information Send procedure	91
8c.2.3a	Autonomous RAN Information Send procedure.....	91

8c.2.3a.1	Initiation by the originating BSS	91
8c.2.3a.2	Reception of a valid RAN-INFORMATION PDU by the receiving BSS	92
8c.2.3a.3	Reception of a valid RAN-INFORMATION-ACK PDU in the originating BSS	92
8c.2.3a.4	Expiration of T(RI) in the originating BSS	92
8c.2.3.1	Initiation by the serving BSS	92
8c.2.3.2	Reception of a valid RAN-INFORMATION PDU by the controlling BSS	93
8c.2.3.3	Reception of a valid RAN-INFORMATION-ACK PDU in the serving BSS	94
8c.2.3.4	Expiration of T(RI) in the serving BSS	94
8c.2.4	RAN Information Application Error procedure	94
8c.2.4.1	Initiation by the controlling or receiving BSS	94
8c.2.4.2	Reception of a valid RAN-INFORMATION-APPLICATION-ERROR PDU by the serving BSS	95
8c.2.4.3	Reception of a valid RAN-INFORMATION-ACK PDU by the controlling or receiving BSS	95
8c.2.4.4	Expiration of T(RIAE) in the controlling or receiving BSS	95
8c.2.5	RAN Information Error procedure	96
8c.3	Abnormal conditions	96
8c.3.0	General	96
8c.3.1	Abnormal conditions at the BSSGP level	96
8c.3.1.1	General	96
8c.3.1.2	RIM addressing error in BSS	96
8c.3.1.3	RIM addressing error in the CN	97
8c.3.1.4	RIM PDU addressed to a BSS not supporting RIM	97
8c.3.2	Abnormal conditions encountered in the RIM container	97
8c.3.2.1	Unknown RIM Application Identity	97
8c.3.2.2	Erroneous PDU Type Extension field	97
8c.3.2.3	Missing conditional IE	97
8c.3.2.4	Missing mandatory IE	97
8c.3.2.5	Syntactical error in an expected conditional IE	98
8c.3.2.6	Syntactical error in a mandatory IE	98
8c.3.2.7	Unexpected conditional IE	98
8c.3.2.8	Containers with out-of-sequence information elements	98
8c.3.2.9	Container with semantically incorrect content	98
8c.3.3	Unexpected RIM PDU	99
8c.3.4	RIM error reporting	99
8c.3.4.1	General	99
8c.3.4.2	Sending of a RAN-INFORMATION-ERROR PDU	99
8c.3.4.3	Reception of a RAN-INFORMATION-ERROR PDU in the BSS	99
8c.4	RIM timers	99
8c.5	Action upon deletion of a cell in a BSS	100
8c.5.0	General	100
8c.5.1	Actions due to the deletion of the cell	100
8c.5.2	Additional actions in the case the deleted cell is used as a source cell by RIM	100
8c.6	Specific requirements related to RIM applications	101
8c.6.0	General requirements	101
8c.6.1	Requirements related to the NACC RIM application	101
8c.6.2	SI3 application	101
8c.6.3	MBMS data channel application	102
8c.6.4	Requirements related to the SON Transfer RIM application	102
8c.6.5	Requirements related to the UTRA SI RIM application	103
8c.6.6	Multilateration Timing Advance application	103
8d	Signalling procedures between MBMS SAPs	104
8d.1	General	104
8d.2	MBMS Session Start	104
8d.2.1	Abnormal Conditions	106
8d.3	MBMS Session Stop	106
8d.3.1	Abnormal Conditions	106
8d.4	MBMS Session Update	106
8d.4.1	Abnormal Conditions	108
9	General Protocol Error Handling	108
10	PDU functional definitions and contents	108
10.1	General Structure Of A PDU	108

10.2	PDU functional definitions and contents at RL and BSSGP SAPs	109
10.2.1	DL-UNITDATA	109
10.2.2	UL-UNITDATA	111
10.2.3	RA-CAPABILITY.....	113
10.2.4	(void)	113
10.2.5	DL-MBMS-UNITDATA.....	114
10.2.6	UL-MBMS-UNITDATA.....	114
10.3	PDU functional definitions and contents at GMM SAP.....	114
10.3.1	PAGING PS.....	114
10.3.2	PAGING CS	116
10.3.3	RA-CAPABILITY-UPDATE.....	116
10.3.4	RA-CAPABILITY-UPDATE-ACK	117
10.3.5	RADIO-STATUS	117
10.3.6	SUSPEND	117
10.3.7	SUSPEND-ACK.....	118
10.3.8	SUSPEND-NACK.....	118
10.3.9	RESUME	118
10.3.10	RESUME-ACK	119
10.3.11	RESUME-NACK	119
10.3.12	DUMMY PAGING PS	119
10.3.13	DUMMY PAGING PS RESPONSE	120
10.3.14	PAGING PS REJECT.....	120
10.3.15	MS REGISTRATION ENQUIRY	120
10.3.16	MS REGISTRATION ENQUIRY RESPONSE.....	120
10.4	PDU functional definitions and contents at NM SAP.....	121
10.4.1	FLUSH-LL	121
10.4.2	FLUSH-LL-ACK.....	121
10.4.3	LLC-DISCARDED.....	122
10.4.4	FLOW-CONTROL-BVC	122
10.4.5	FLOW-CONTROL-BVC ACK	122
10.4.6	FLOW-CONTROL-MS.....	123
10.4.7	FLOW-CONTROL-MS-ACK	123
10.4.8	BVC-BLOCK	123
10.4.9	BVC-BLOCK-ACK	124
10.4.10	BVC-UNBLOCK	124
10.4.11	BVC-UNBLOCK-ACK	124
10.4.12	BVC-RESET	125
10.4.13	BVC-RESET-ACK	125
10.4.14	STATUS	126
10.4.14.1	Static conditions for BVCI.....	126
10.4.15	SGSN-INVOKE-TRACE	126
10.4.16	DOWNLOAD-BSS-PFC	127
10.4.17	CREATE-BSS-PFC	127
10.4.18	CREATE-BSS-PFC-ACK	127
10.4.19	CREATE-BSS-PFC-NACK	128
10.4.20	MODIFY-BSS-PFC	128
10.4.21	MODIFY-BSS-PFC-ACK	128
10.4.22	DELETE-BSS-PFC	129
10.4.23	DELETE-BSS-PFC-ACK	129
10.4.24	FLOW-CONTROL-PFC	129
10.4.25	FLOW-CONTROL-PFC-ACK	130
10.4.26	DELETE-BSS-PFC-REQ	130
10.4.27	PS-HANDOVER-REQUIRED	130
10.4.28	PS-HANDOVER-REQUIRED-ACK	131
10.4.29	PS-HANDOVER-REQUIRED-NACK	131
10.4.30	PS-HANDOVER-REQUEST	132
10.4.31	PS-HANDOVER-REQUEST-ACK	132
10.4.32	PS-HANDOVER-REQUEST-NACK	133
10.4.33	PS-HANDOVER-COMPLETE.....	133
10.4.34	PS-HANDOVER-CANCEL	133
10.4.35	PS-HANDOVER-COMPLETE-ACK	134
10.5	PDU functional definitions and contents at LCS SAP	134

10.5.1	PERFORM-LOCATION-REQUEST	134
10.5.2	PERFORM-LOCATION-RESPONSE.....	136
10.5.3	PERFORM-LOCATION-ABORT	136
10.5.4	POSITION-COMMAND.....	137
10.5.5	POSITION-RESPONSE.....	137
10.6	PDU functional definitions and contents at RIM SAP	137
10.6.1	RAN-INFORMATION-REQUEST	137
10.6.2	RAN-INFORMATION.....	138
10.6.3	RAN-INFORMATION-ACK	138
10.6.4	RAN-INFORMATION-ERROR	138
10.6.5	RAN-INFORMATION-APPLICATION-ERROR.....	139
10.7	PDU functional definitions and contents at MBMS SAP	139
10.7.1	MBMS-SESSION-START-REQUEST.....	139
10.7.2	MBMS-SESSION-START-RESPONSE.....	140
10.7.3	MBMS-SESSION-STOP-REQUEST.....	140
10.7.4	MBMS-SESSION-STOP-RESPONSE.....	140
10.7.5	MBMS-SESSION-UPDATE-REQUEST.....	140
10.7.6	MBMS-SESSION-UPDATE-RESPONSE.....	141
11	General information elements coding	141
11.1	General structure of the information elements	141
11.2	Information element description.....	141
11.3	Information Element Identifier (IEI)	142
11.3.1	Alignment octets	145
11.3.2	Bmax default MS	145
11.3.3	BSS Area Indication	145
11.3.4	Bucket Leak Rate (R)	146
11.3.5	BVC Bucket Size	146
11.3.6	BVCI (BSSGP Virtual Connection Identifier).....	146
11.3.7	BVC Measurement	146
11.3.8	Cause	147
11.3.9	Cell Identifier.....	150
11.3.10	Channel needed.....	150
11.3.11	DRX Parameters	150
11.3.12	eMLPP-Priority.....	150
11.3.13	Flush Action.....	151
11.3.14	IMSI.....	151
11.3.15	LLC-PDU	151
11.3.16	LLC Frames Discarded.....	151
11.3.17	Location Area	152
11.3.18	LSA Identifier List.....	152
11.3.19	LSA Information.....	152
11.3.20	Mobile Id	152
11.3.21	MS Bucket Size	153
11.3.22	MS Radio Access Capability	153
11.3.23	OMC Id.....	153
11.3.24	PDU In Error.....	153
11.3.25	PDU Lifetime.....	153
11.3.26	PDU Type	155
11.3.27	Priority	157
11.3.28	QoS Profile	157
11.3.29	Radio Cause	159
11.3.30	RA-Cap-UPD-Cause.....	159
11.3.31	Routeing Area.....	159
11.3.32	R_default_MS	160
11.3.33	Suspend Reference Number.....	160
11.3.34	Tag	160
11.3.35	Temporary logical link Identity (TLLI)	160
11.3.36	Temporary Mobile Subscriber Identity (TMSI).....	161
11.3.37	Trace Reference	161
11.3.38	Trace Type	161
11.3.39	Transaction Id	161

11.3.40	Trigger Id.....	161
11.3.41	Number of octets affected.....	162
11.3.42	Packet Flow Identifier (PFI)	162
11.3.42a	(void)	162
11.3.43	Aggregate BSS QoS Profile.....	162
11.3.44	GPRS Timer.....	163
11.3.45	Feature Bitmap.....	163
11.3.46	Bucket Full Ratio.....	164
11.3.47	Service UTRAN CCO	164
11.3.48	NSEI (Network Service Entity Identifier)	165
11.3.49	RRLP APDU	165
11.3.50	LCS QoS	166
11.3.51	LCS Client Type	166
11.3.52	Requested GPS Assistance Data.....	166
11.3.53	Location Type	166
11.3.54	Location Estimate	166
11.3.55	Positioning Data.....	167
11.3.56	Deciphering Keys	167
11.3.57	LCS Priority.....	167
11.3.58	LCS Cause	167
11.3.59	LCS Capability	168
11.3.60	RRLP Flags.....	168
11.3.61	RIM Application Identity.....	168
11.3.62	RIM Sequence Number	169
11.3.62a	RIM Container	169
11.3.62a.0	General	169
11.3.62a.1	RAN-INFORMATION-REQUEST RIM Container	169
11.3.62a.2	RAN-INFORMATION RIM Container.....	170
11.3.62a.3	RAN-INFORMATION-ACK RIM Container	170
11.3.62a.4	RAN-INFORMATION ERROR RIM Container	171
11.3.62a.5	RAN-INFORMATION-APPLICATION-ERROR RIM Container.....	171
11.3.63	Application Container	172
11.3.63.1	RAN-INFORMATION-REQUEST Application Container	172
11.3.63.1.0	General	172
11.3.63.1.1	RAN-INFORMATION-REQUEST Application Container for the NACC Application.....	172
11.3.63.1.2	RAN-INFORMATION-REQUEST Application Container for the SI3 Application	172
11.3.63.1.3	RAN-INFORMATION-REQUEST Application Container for the MBMS data channel Application	173
11.3.63.1.4	RAN-INFORMATION-REQUEST Application Container for the SON Transfer Application ...	173
11.3.63.1.5	RAN-INFORMATION-REQUEST Application Container for the UTRA SI Application	173
11.3.63.2	RAN-INFORMATION Application Container Unit.....	174
11.3.63.2.0	General	174
11.3.63.2.1	RAN-INFORMATION Application Container for the NACC Application.....	174
11.3.63.2.2	RAN-INFORMATION Application Container for the SI3 Application	175
11.3.63.2.3	RAN-INFORMATION Application Container for the MBMS data channel Application	175
11.3.63.2.4	RAN-INFORMATION Application Container for the SON Transfer Application	177
11.3.63.2.5	RAN-INFORMATION Application Container for the UTRA SI Application.....	177
11.3.63.2.6	RAN-INFORMATION Application Container for the Multilateration Timing Advance Application	178
11.3.64	Application Error Container	178
11.3.64.1	Application Error Container layout for the NACC application.....	178
11.3.64.2	Application Error Container for the SI3 application	179
11.3.64.3	Application Error Container for the MBMS data channel application.....	180
11.3.64.4	Application Error Container for the SON Transfer Application	181
11.3.64.5	Application Error Container for the UTRA SI Application	181
11.3.64.6	Application Error Container for the Multilateration Timing Advance Application	182
11.3.65	RIM PDU Indications	182
11.3.65.0	General.....	182
11.3.65.1	RAN-INFORMATION-REQUEST RIM PDU Indications.....	182
11.3.65.2	RAN-INFORMATION RIM PDU Indications	183
11.3.65.3	RAN-INFORMATION-APPLICATION-ERROR RIM PDU Indications	183
11.3.66	(void)	183

11.3.67	RIM Protocol Version Number.....	183
11.3.68	PFC Flow Control parameters	184
11.3.69	Global CN-Id	185
11.3.70	RIM Routing Information.....	185
11.3.71	MBMS Session Identity.....	186
11.3.72	MBMS Session Duration	186
11.3.73	MBMS Service Area Identity List.....	187
11.3.74	MBMS Response	187
11.3.75	MBMS Routing Area List.....	188
11.3.76	MBMS Session Information	188
11.3.77	TMGI (Temporary Mobile Group Identity).....	189
11.3.78	MBMS Stop Cause	189
11.3.79	Source BSS to Target BSS Transparent Container	190
11.3.80	Target BSS to Source BSS Transparent Container	190
11.3.81	NAS container for PS Handover.....	191
11.3.82	PFCs to be set-up list	191
11.3.83	List of set-up PFCs	192
11.3.84	Extended Feature Bitmap.....	193
11.3.85	Source to Target Transparent Container	194
11.3.86	Target to Source Transparent Container	194
11.3.87	RNC Identifier	195
11.3.88	Page Mode	196
11.3.89	Container ID	196
11.3.90	Global TFI	196
11.3.91	IMEI.....	197
11.3.92	Time to MBMS Data Transfer.....	197
11.3.93	MBMS Session Repetition Number.....	197
11.3.94	Inter RAT Handover Info	198
11.3.95	PS Handover Command.....	198
11.3.95a	PS Handover Indications.....	198
11.3.95b	SI/PSI Container	198
11.3.95c	Active PFCs List.....	200
11.3.96	Velocity Data	200
11.3.97	DTM Handover Command	200
11.3.98	CS Indication.....	201
11.3.99	Requested GANSS Assistance Data	201
11.3.100	GANSS Location Type	201
11.3.101	GANSS Positioning Data.....	201
11.3.102	Flow Control Granularity.....	202
11.3.103	eNB Identifier	202
11.3.104	E-UTRAN Inter RAT Handover Info	203
11.3.105	Subscriber Profile ID for RAT/Frequency priority	203
11.3.106	Request for Inter-RAT Handover Info.....	203
11.3.107	Reliable Inter-RAT Handover Info	204
11.3.108	SON Transfer Application Identity.....	204
11.3.109	CSG Identifier.....	204
11.3.110	Tracking Area Code.....	205
11.3.111	Redirect Attempt Flag.....	205
11.3.112	Redirection Indication.....	206
11.3.113	Redirection Completed	206
11.3.114	Unconfirmed send state variable.....	207
11.3.115	IRAT Measurement Configuration	207
11.3.116	SCI.....	208
11.3.117	GGSN/P-GW location	208
11.3.118	Selected PLMN ID.....	209
11.3.119	Priority Class Indicator	209
11.3.120	Source Cell ID IE.....	209
11.3.121	IRAT Measurement Configuration (extended E-ARFCNs).....	210
11.3.122	eDRX Parameters	212
11.3.123	Time Until Next Paging Occasion	212
11.3.124	Coverage Class	213
11.3.125	Paging Attempt Information	213

11.3.126	Exception Report Flag	214
11.3.127	Old Routing Area Identification	214
11.3.128	Attach Indicator	215
11.3.129	PLMN Identity.....	215
11.3.130	MME Query.....	215
11.3.131	SGSN Group Identity.....	215
11.3.132	Additional P-TMSI	216
11.3.133	UE Usage Type.....	216
11.3.134	DCN-ID	216
11.3.135	Void	217
11.3.136	Multilateration Timer.....	217
11.3.137	Multilateration Timing Advance.....	217
11.3.138	MS Sync Accuracy	217
11.3.139	BTS Reception Accuracy Level.....	218
11.3.140	Timing Advance Request (TAR)	218
11.3.141	Enhanced Coverage Additional Information	218
11.3.142	MTA Access Security Required(MTASR)	219
11.3.143	MTA Sequence	219
11.3.144	MTA Signature	219
12	List of system variables	220
12.1	General Variables	220
12.2	Flow control variables	220
Annex A (informative):	Change history.....	222
History	iTeh STANDARD	223

PREVIEW (standards.iteh.ai)

ETSI TS 148 018 V17.0.0 (2022-05)

<https://standards.iteh.ai/catalog/standards/sist/e82e19de-ac0e-4a03-989d-56dee7d39203/etsi-ts-148-018-v17-0-0-2022-05>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The present document specifies or references procedures used on the Base Station System (BSS) to Serving GPRS Support Node (SGSN) interface for control of GSM packet data services within the digital cellular telecommunications system (Phase 2+).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

**iTeh STANDARD
PREVIEW**

(standards.iteh.ai)

[ETSI TS 148 018 V17.0.0 \(2022-05\)](#)

<https://standards.iteh.ai/catalog/standards/sist/e82e19de-ac0e-4a03-989d-56dee7d39203/etsi-ts-148-018-v17-0-0-2022-05>