DRAFT INTERNATIONAL STANDARD ISO/DIS 4034

ISO/TC 2/SC 12 Secretariat: DIN

Voting begins on: Voting terminates on:

2016-03-31 2016-06-29

Hexagon regular nuts (style 1) — Product grade C

Écrous hexagonaux normaux (style 1) — Grade C

ICS: 21.060.20

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/DIS 4034

https://standards.iteh.ai/catalog/standards/sist/94b1d01f-62c6-4ab6-bc99-d1b30c3f97b8/iso-dis-4034

ISO/CEN PARALLEL PROCESSING

This draft has been developed within the International Organization for Standardization (ISO), and processed under the **ISO lead** mode of collaboration as defined in the Vienna Agreement.

This draft is hereby submitted to the ISO member bodies and to the CEN member bodies for a parallel three month enquiry.

To expedite distribution, this document is circulated as received from the committee secretariat. ISO Central Secretariat work of editing and text composition will be undertaken at publication stage.

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.



Reference number ISO/DIS 4034:2016(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/DIS 4034 https://standards.iteh.ai/catalog/standards/sist/94b1d01f-62c6-4ab6-bc99-d1b30c3f97b8/iso-dis-4034



COPYRIGHT PROTECTED DOCUMENT

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document \$150/TC 2, Fasteners, Subcommittee SC 12, Fasteners with metric internal thread. sixth ai/catalog/standards/sist/94b1d01f-62c6-4ab6-bc99-d1b30c3f97b8/iso-dis-4034

This fifth edition cancels and replaces the fourth edition (ISO 4034:2012).

This standard differs from ISO 4034:2012 as follows:

- the Scope has been updated;
- the thread M7 has been added;
- errors for m_{min} have been corrected for M27 (22,5 instead of 22,6) and M64 (49,1 instead of 49,4);
- errors in calculation of $m_{\rm w, \, min}$ values have been corrected for M6 (3,9 instead of 3,7), M27 (18,0 instead of 18,1), M36 (23,5 instead of 23,2) and M64 (39,3 instead of 39,5);
- the property class 6 has been added;
- the reference to ISO/TR 16224 for nut design has been added.

Hexagon regular nuts (style 1) — Product grade C

1 Scope

This International Standard specifies the characteristics of hexagon regular nuts (style 1) with coarse pitch thread from nominal diameters M5 through M64, with product grade C.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 225, Fasteners — Bolts, screws, studs and nuts — Symbols and descriptions of dimensions

ISO 262, ISO general purpose metric screw threads — Selected sizes for screws, bolts and nuts

ISO 724, ISO general-purpose metric screw threads — Basic dimensions

ISO 898-2, Mechanical properties of fasteners made of carbon steel and alloy steel — Part 2: Nuts with specified property classes — Coarse thread and fine pitch thread

ISO 965-2, ISO general purpose metric screw threads—Tolerances—Part 2: Limits of sizes for general purpose external and internal screw threads—Medium quality

(standards.iteh.ai)

ISO 965-5, ISO general-purpose metric screw threads — Tolerances — Part 5: Limits of sizes for internal screw threads to mate with hot-dip galvanized external screw threads with maximum size of tolerance position h before galvanizing standards itch ai/catalog/standards/sist/94b1d01f-62c6-4ab6-bc99-

d1b30c3f97b8/iso-dis-4034

ISO 3269, Fasteners — Acceptance inspection

ISO 4042, Fasteners — Electroplated coatings

ISO 4759-1, Tolerances for fasteners — Part 1: Bolts, screws, studs and nuts — Product grades A, B and C

ISO 6157-2, Fasteners — Surface discontinuities — Part 2: Nuts

ISO 8992, Fasteners — General requirements for bolts, screws, studs and nuts


ISO 10683, Fasteners — Non-electrolytically applied zinc flake coatings

ISO 10684, Fasteners — Hot dip galvanized coatings

3 **Dimensions**

See Figure 1 and Tables 1 and 2.

Symbols and descriptions of dimensions are specified in ISO 225.



- β = 15° to 30°
- θ = 90° to 120°

Figure 1 - Dimensions

iTeh STANDARD PREV Table 1—Preferred threads (standards.iteh.ai)

Dimensions in millimetres

Thread, D		М5	M6	O/DIS 4034	M10	M12	M16	M20
P ^a	htt	ps://s0;8dards.	iteh.ai/catalog/s	standar, 25 /sist/9	4b1d 0, \$f-62c6	-4ab 1,75 99-	2	2,5
dw	min.	6,7	8,7 ^{30c3}	19768/iso-dis- 11,5	4034 14,5	16,5	22,0	27,7
е	min.	8,63	10,89	14,20	17,59	19,85	26,17	32,95
	max.	5,6	6,4	7,9	9,5	12,2	15,9	19,0
m	min.	4,4	4,9	6,4	8,0	10,4	14,1	16,9
$m_{ m w}$	min.	3,5	3 ,9	5,1	6,4	8,3	11,3	13,5
	nom. = max.	8,00	10,00	13,00	16,00	18,00	24,00	30,00
S	min.	7,64	9,64	12,57	15,57	17,57	23,16	29,16
Thread, D		M24	M30	M36	M42	M48	M56	M64
P ^a		3	3,5	4	4,5	5	5,5	6
dw	min.	33,3	42,8	51,1	60,0	69,5	78,7	88,2
е	min.	39,55	50,85	60,79	71,30	82,60	93,56	104,86
m	max.	22,3	26,4	31,9	34,9	38,9	45,9	52,4
m	min.	20,2	24,3	29,4	32,4	36,4	43,4	49, 1
$m_{ m W}$	min.	16,2	19,4	23 ,5	25,9	29,1	34,7	39, 3
S	nom. = max.	36,00	46,00	55,00	65,00	75,00	85,00	95,00
3	min.	35,00	45,00	53,80	63,10	73,10	82,80	92,80
a P is th	^a <i>P</i> is the pitch of the thread.							

Table 2 — Non-preferred threads

Dimensions in millimetres

	Thread, D	М7	M14	M18	M22	M27	M33	М39	M45	M52	M60
Pa		1	2	2,5	2,5	3	3,5	4	4,5	5	5,5
dw	min.	9,5	19,2	24,9	31,4	38,0	46,6	55,9	64,7	74,2	83,4
e	min.	11,94	22,78	29,56	37,29	45,20	55,37	66,44	76,95	88,25	99,21
т	max.	8,30	13,9	16,9	20,2	24,7	29,5	34,3	36,9	42,9	48,9
	min.	6,10	12,1	15,1	18,1	22,5	27,4	31,8	34,4	40,4	46,4
m _w	min.	5,50	9,7	12,1	14,5	18,0	21,9	25,4	27,5	32,3	37,1
s	nom. = max.	11,00	21,00	27,00	34,00	41,00	50,00	60,00	70,00	80,00	90,00
	min.	10,57	20,16	26,16	33,00	40,00	49,00	58,80	68,10	78,10	87,80
a P is the pitch of the thread.											

4 Requirements and reference International Standards

See Table 3.

Table 3 — Requirements and reference International Standards

Mat	erial (stand	dards.iteh.ai) Steel				
General requirements	International Standard	ISO 8992				
Thread	Tolerance class https://standards.iteh.ai/catalo	ISO/DIS 4034 9/standards/sist/94b1d01f-62c6-4ab6-bc99-				
	International Standards 3	c3f97b8/iso-dis- ISO 2 62, ISO 724, ISO 965-2, ISO 965-5				
	Property class	$M5 \le D \le M39 \qquad 5, 6$				
Mechanical properties		D < M5 and $D > M39$ Mechanical properties as agreed ^b				
	International Standard	ISO 898-2				
Tolerance	Product grade	С				
Tolerance	International Standard	ISO 4759-1				
		As processed				
		Requirements for electroplating are specified in ISO 4042.				
Finish — Coating		Requirements for non-electrolytically applied zinc flake coatings are specified in ISO 10683.				
rinisii — Coating		Requirements for hot dip galvanized coatings are specified in ISO 10684.				
		Additional requirements or other finishes or coatings shall be agreed between the supplier and the purchaser.				
Surface integrity		Limits for surface discontinuities are specified in ISO 6157-2.				
Acceptability		Acceptance inspection is specified in ISO 3269.				

^a Other tolerance classes may be specified prior to coating, depending on the type of coating to be applied. For coated nuts, see relevant coating standards, e.g. ISO 4042, ISO 10683 and ISO 10684.

b See ISO/TR 16224 for information.

5 Designation

EXAMPLE A hexagon regular nut (style 1) with nominal diameter M12 and property class 5 is designated as follows:

Hexagon regular nut ISO 4034 - M12 - 5

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/DIS 4034 https://standards.iteh.ai/catalog/standards/sist/94b1d01f-62c6-4ab6-bc99-d1b30c3f97b8/iso-dis-4034

Bibliography

ISO/TR 16224, Technical aspects of nut design

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/DIS 4034 https://standards.iteh.ai/catalog/standards/sist/94b1d01f-62c6-4ab6-bc99-d1b30c3f97b8/iso-dis-4034