



**Fixed Radio Systems;
Characteristics and requirements for
point-to-point equipment and antennas;
Part 1: Overview, common characteristics and
requirements not related to access to radio spectrum**

ETSI EN 302 217-1 V3.4.0 (2025-04)

<https://standards.iteh.ai/catalog/standards/etsi/bfb1049f-f6a6-4c7b-b708-4e5d1042e7aa/etsi-en-302-217-1-v3-4-0-2025-04>

Reference

REN/ATTM-0457

Keywords

antenna, DFRS, digital, DRRS, FWS,
point-to-point, radio, regulation, transmission

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Contents

Intellectual Property Rights	6
Foreword.....	6
Modal verbs terminology.....	7
Introduction	7
1 Scope	8
2 References	8
2.1 Normative references	8
2.2 Informative references.....	10
3 Definition of terms, symbols and abbreviations.....	13
3.1 Terms.....	13
3.2 Symbols.....	19
3.3 Abbreviations	20
4 Structure and applicability of the ETSI EN 302 217 series.....	22
4.1 Generality	22
4.2 Summary of system options provided	23
4.3 User's guide	27
5 General characteristics	29
5.1 Frequency bands and channel arrangements	29
5.2 Special compatibility requirements between systems	29
5.3 Transmission capacity and spectral efficiency	29
5.4 Performance and availability requirements	29
5.5 Environmental profiles	30
5.5.0 Introduction.....	30
5.5.1 Environmental profile under Directive 2014/53/EU.....	30
5.5.2 ETSI standardized environmental profiles.....	30
5.5.2.0 Generality.....	30
5.5.2.1 Equipment intended for telecommunications applications installed in weather-protected locations (indoor locations)	31
5.5.2.2 Equipment intended for telecommunications applications installed in not-weather-protected locations (outdoor locations)	31
5.5.3 Test environment profiles	31
5.6 Power supply	31
5.6.0 Introduction.....	31
5.6.1 Power supply profile under Directive 2014/53/EU.....	31
5.6.2 ETSI power supply profile.....	31
5.7 System block diagram	31
6 Baseband interfaces and parameters.....	32
6.0 Introduction	32
6.1 Ethernet interfaces.....	32
6.2 Plesiochronous interfaces	32
6.3 Synchronous digital hierarchy interfaces	33
6.4 Other baseband data interfaces.....	33
7 Main requirements.....	33
7.0 Introduction	33
7.1 General requirements	33
7.1.1 System identification	33
7.1.2 System nominal loading.....	34
7.1.3 Environmental profile	34
7.2 Transmitter characteristics.....	34
7.2.1 Transmitter power and power tolerance.....	34
7.2.1.1 Transmitter maximum power and EIRP.....	34
7.2.1.2 Transmitter combined output power and EIRP limits	34
7.2.1.3 Transmitter output power environmental variation	34
7.2.2 Transmitter power and frequency control.....	35

7.2.2.1	Transmitter Power and Frequency Control (ATPC, RTPC and RFC)	35
7.2.2.1.1	Automatic Transmit Power Control (ATPC).....	35
7.2.2.1.2	Remote Transmit Power Control (RTPC)	36
7.2.2.1.3	Transmitter Remote Frequency Control (RFC)	36
7.2.3	Transmitter Radio Frequency spectrum mask.....	36
7.2.4	Transmitter discrete CW components exceeding the spectrum mask limit	36
7.2.4.1	Transmitter discrete CW components at the symbol rate	36
7.2.4.2	Transmitter other discrete CW components exceeding the spectrum mask limit.....	36
7.2.5	Transmitter unwanted emissions in the spurious domain	36
7.2.6	Transmitter dynamic change of modulation order	36
7.2.7	Transmitter radio frequency tolerance	36
7.2.8	Transmitter emission limitations outside the allocated band	37
7.3	Receiver characteristics	37
7.3.1	Unwanted emissions in the spurious domain	37
7.3.2	Receiver BER as a function of Receiver Signal Level (RSL).....	37
7.3.3	Receiver selectivity.....	37
7.3.3.1	Introduction	37
7.3.3.2	Receiver co-channel, first and second adjacent channel interference sensitivity	37
7.3.3.3	Blocking (CW spurious interference sensitivity)	37
7.4	Antenna directional characteristics.....	37
8	Complementary requirements	38
8.0	Introduction	38
8.1	Branching/feeder requirements	38
8.1.1	Waveguide flanges (or other connectors)	38
8.1.2	Return loss of feeder/antenna systems at equipment antenna port (C/C' reference point)	39
8.2	Intermodulation products	40
8.3	Transmitter characteristics.....	40
8.3.1	Unwanted emissions - internal.....	40
8.3.2	Transmitter Radio Frequency (RF) spectrum mask when mixed manufacturer compatibility under same antenna is required	40
8.4	Receiver characteristics	41
8.4.1	Receiver maximum input level and input level range.....	41
8.4.2	Unwanted emissions - internal.....	42
8.4.3	Image rejection	42
8.4.4	Innermost channel selectivity	43
8.5	System performance without diversity	43
8.5.1	Equipment Residual BER (RBER)	43
8.5.2	Multipath distortion sensitivity	45
8.5.2.1	Introduction	45
8.5.2.2	Requirement	45
8.5.2.3	Assessment.....	47
8.5.3	Interference sensitivity for CCDP with XPIC operation.....	47
8.5.3.1	General	47
8.5.3.2	Co-channel "internal" interference sensitivity in flat fading conditions.....	47
8.6	System characteristics with diversity	48
8.6.0	Introduction.....	48
8.6.1	Differential delay compensation	48
8.6.2	BER performance	48

Annex A (normative): Transmitter Radio Frequency spectrum masks and receiver selectivity when mixed manufacturer compatibility is required49

A.0	Introduction	49
A.1	Transmitter Radio Frequency masks assessment	50
A.2	Normal channels - Emission mask floor for local TX to RX compatibility.....	50
A.2.1	Spectrum mask	50
A.2.2	Receiver selectivity	50
A.3	Innermost channels for channel arrangements from about 4 GHz to about 8,5 GHz with channel separation of 28 MHz to 30 MHz.....	51
A.3.0	Introduction	51

A.3.1	Innermost channels spectrum masks	51
A.3.2	Receiver innermost channel selectivity	53
A.4	Innermost channels for channel arrangements from about 4 GHz to 11 GHz with channel separation of 40 MHz	54
A.4.0	Introduction	54
A.4.1	Innermost channels spectrum masks	54
A.4.2	Receiver innermost channels selectivity.....	55
A.5	Innermost channels for 18 GHz channel arrangements with channel separation of 55 MHz	56
A.5.0	Introduction	56
A.5.1	Innermost channels spectrum masks	56
A.5.2	Receiver innermost channels selectivity.....	57
Annex B (normative):	Definition of equivalent data rates for packet data, PDH/SDH and other signals on the traffic interface.....	59
Annex C (informative):	Information on <i>Multi-channel</i> and <i>Channels-aggregation</i> differences and operation	60
C.1	Multi-channel and Channels-aggregation (two channel case).....	60
C.2	Channels-aggregation (more than two channels case)	61
Annex D (informative):	Additional information on relevant characteristics and operation	64
D.1	Residual Bit Error Ratio (RBER) and Residual Frame Error Ratio (RFER)	64
D.2	Measurement test set for XPI characteristics	65
D.3	Differential delay compensation range.....	66
D.4	FER/BER equivalence and FER performance measurement equipment settings (example).....	67
D.4.1	FER/BER equivalence.....	67
D.4.2	FER equipment settings and measurement techniques (example).....	68
D.5	Impact of power control (ATPC and/or RTPC), mixed-mode and bandwidth adaptive operation on spectrum mask and link design requirements.....	68
D.5.0	Introduction	68
D.5.1	ATPC and RTPC.....	68
D.5.1.1	ATPC.....	68
D.5.1.2	ATPC and RTPC implementation background.....	69
D.5.2	Mixed-mode and bandwidth adaptive operation impact.....	71
D.5.2.1	Mixed-mode basic concepts.....	71
D.5.2.2	Bandwidth adaptive	72
D.5.2.2.1	Basic concepts.....	72
D.5.2.2.2	Bandwidth (channel) occupancy	72
D.5.3	Impact on frequency co ordination.....	72
D.5.4	Impact of operating conditions on the access to radio spectrum through European Harmonised Standard	72
D.6	Typical interference sensitivity behaviour for frequency planning purpose	73
D.7	Band and Carrier Aggregation (BCA) operation.....	74
Annex E (informative):	Mechanical characteristics.....	75
Annex F (informative):	Mitigation techniques referred in CEPT/ERC/DEC(00)07 (18 GHz band).....	76
Annex G (informative):	Bibliography.....	77
Annex H (informative):	Change history	78
History		79

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This draft European Standard (EN) has been produced by ETSI Technical Committee Access, Terminals, Transmission and Multiplexing (ATTM), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI EN Approval Procedure (ENAP).

The present document is part 1 of a multi-part deliverable covering the Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas, as identified below (see note):

Part 1: "Overview, common characteristics and requirements not related to access to radio spectrum";

Part 2: "Digital systems operating in frequency bands from 1 GHz to 174,8 GHz; Harmonised Standard for access to radio spectrum";

Part 4: "Antennas".

NOTE: In previous regulatory regime under Directive 1999/5/EC more parts (harmonised and non-harmonised standards) were published. Since Directive 2014/53/EU [i.1] repealed Directive 1999/5/EC the following parts have been replaced while the content has been moved to other parts of the series.

Those parts are:

Part 2-1: Technical content moved to present document (Part 1);

Part 2-2: Technical content reproduced in Part 2 (*);

(*) Part 2-2- was also published in the OJEU under Directive 2014/53/EU [i.1], presumption of conformity ceased on 31-12-2018;

Part 3: Technical content moved to Part 2 (including a complete new set of receiver parameters);

Part 4-1: Technical content reproduced in Part 4;

Part 4-2: Technical content reproduced in Part 4.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The ETSI EN 302 217 series replaced and superseded a number of older standards (frequency and/or capacity oriented), which remained, only as "historical" documents, in the ETSI data base. Provided that they may still be referenced in some documentation, the version 2.1.1 of the present document [i.41] provides their list.


 (https://standards.iteh.ai)
 Document Preview

[ETSI EN 302 217-1 V3.4.0 \(2025-04\)](#)

<https://standards.iteh.ai/catalog/standards/etsi/bfb1049f-f6a6-4c7b-b708-4e5d1042e7aa/etsi-en-302-217-1-v3-4-0-2025-04>