
**Information technology — Scalable
compression and coding of
continuous-tone still images —**

**Part 2:
Coding of high dynamic range images**

*Technologies de l'information — Compression échelonnable et codage
d'images plates en ton continu —*

Partie 2: Codage d'images à gamme dynamique élevée

PROOF/ÉPREUVE

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/03623de2-cb28-4f21-aae4-5e5d2e1a3f3a/iso-iec-18477-2-2016>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Abbreviated terms and symbols	4
4.1 Abbreviated terms	4
4.2 Symbols	4
5 Conventions	4
5.1 Conformance language	4
5.2 Operators	4
5.2.1 Arithmetic operators	5
5.2.2 Logical operators	5
5.2.3 Relational operators	5
5.2.4 Precedence order of operators	5
5.2.5 Mathematical functions	5
6 General	6
6.1 Elements specified	6
6.2 High level overview of this document	6
6.3 High level functional overview of decoding process	7
6.4 Encoder requirements	7
6.5 Decoder requirements	8
7 Decoder definition	8
7.1 Decoder functionality overview	8
7.2 Legacy Inverse Decorrelation Block B3	9
7.3 Base Mapping and Colour space conversion Block B4	9
7.4 Residual decode Blocks B5, B6	11
7.5 Residual Mapping and Inverse Decorrelation Blocks B7, B8	11
7.6 HDR Reconstruction Blocks B9, B10	12
8 Codestream syntax for Main Profile	13
8.1 Main Profile Header Structure	13
8.2 Parameter ASCII segment	13
8.3 Parameter binary segment	15
8.4 Residual codestream segment	15
Annex A (normative) Checksum computation	16
Bibliography	17

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/IEC JTC 1, *Information technology, SC 29, Coding of audio, picture, multimedia and hypermedia information*.

Introduction

This document is an extension of ISO/IEC 18477-1, a compression system for continuous tone digital still images which is backward compatible with Rec. ITU-T T.81 | ISO/IEC 10918-1. That is, legacy applications conforming to Rec. ITU-T T.81 | ISO/IEC 10918-1 will be able to reconstruct streams generated by an encoder conforming to this document, but will possibly not be able to reconstruct such streams in full dynamic range, full quality or other features defined in this document.

The aim of this document is to provide a migration path for legacy applications to support coding of high-dynamic range images. Existing tools depending on the existing standards will continue to work, but will only be able to reconstruct a lossy and/or a low-dynamic range version of the image contained in the codestream. This document specifies a codestream, referred to as JPEG XT, which is designed primarily for storage and interchange of continuous-tone photographic content.

This document specifies a coded codestream format for storage of continuous-tone high and low dynamic range photographic content. JPEG XT Part 2 is a scalable image coding system supporting multiple component images in floating point. It is by itself an extension of the coding tools defined in ISO/IEC 18477-1; the codestream is composed in such a way that legacy applications conforming to Rec. ITU-T T.81 | ISO/IEC 10918-1 are able to reconstruct a lower quality, low dynamic range, eight bits per sample version of the image.

Today, the most widely used digital photography format, a minimal implementation of JPEG (specified in Rec. ITU-T T.81 | ISO/IEC 10918-1), uses a bit depth of 8; each of the three channels that together compose an image pixel is represented by 8 bits, providing 256 representable values per channel. For more demanding applications, it is not uncommon to use a bit depth of 16 or higher, providing greater than 65 536 representable values to describe each channel within a pixel, resulting on over 2.8×10^{14} representable colour values. In some less common scenarios, even greater bit depths are used.

The most common photo and image formats use an 8-bit or 16-bit unsigned integer value to represent some function of the intensity of each colour channel. While it might be theoretically possible to agree on one method for assigning specific numerical values to real world colours, doing so is not practical. Since any specific device has its own limited range for colour reproduction, the device's range may be a small portion of the agreed-upon universal colour range. As a result, such an approach is an extremely inefficient use of the available numerical values, especially when using only 8 bits (or 256 unique values) per channel. To represent pixel values as efficiently as possible, devices use a numeric encoding optimized for their own range of possible colours or gamut.

JPEG XT is primarily designed to provide coded data containing high dynamic range and wide colour gamut content while simultaneously providing 8 bits per pixel low dynamic range images using tools defined in ISO/IEC 18477-1. The goal is to provide a backward compatible coding specification that allows legacy applications and existing toolchains to continue to operate on codestreams conforming to this this document.

JPEG XT has been designed to be backward compatible to legacy applications while at the same time having a small coding complexity; JPEG XT uses, whenever possible, functional blocks of Rec. ITU-T T.81 | ISO/IEC 10918-1 to extend the functionality of the legacy JPEG Coding System. It is optimized for storage and transmission of high dynamic range and wide colour gamut 32 bit float images while also enabling low-complexity encoder and decoder implementations.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/03623de2-cb28-4f21-aae4-5e5d2e1a3f3a/iso-iec-18477-2-2016>

Information technology — Scalable compression and coding of continuous-tone still images —

Part 2: Coding of high dynamic range images

1 Scope

This document specifies a coding format, referred to as JPEG XT, which is designed primarily for continuous-tone photographic content.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 10918-1, *Information technology — Digital compression and coding of continuous-tone still images: Requirements and guidelines — Part 1*

ISO/IEC 18477-1, *Information technology — Scalable Compression and Coding of Continuous-Tone Still Images, Core Coding System Specification*

IEC 61966-2-1, *sRGB Colour management — Default RGB colour space — sRGB*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

ASCII encoding

character encoding scheme defined by ANSI X3.4-1986

3.2

codestream

partially encoded or decoded sequence of bits comprising an entropy-coded segment

3.3

byte

group of 8 bits

3.4

coder

embodiment of a coding process

3.5

coding

encoding or decoding

3.6
(coding) process

general term for referring to an encoding process, a decoding process, or both

3.7
compression

reduction in the number of bits used to represent source image data

3.8
component

two-dimensional array of samples having the same designation in the output or display device

Note 1 to entry: An image typically consists of several components, e.g. red, green and blue.

3.9
continuous-tone image

image whose components have more than one bit per sample

3.10
discrete cosine transform
DCT

sum of cosine transforms at different frequencies

3.11
decoder

embodiment of a decoding process

3.12
decoding process

process which takes as its input compressed image data and outputs a continuous-tone image

3.13
downsampling

procedure by which the spatial resolution of a component is reduced

3.14
encoder

embodiment of an encoding process

3.15
encoding process

process which takes as its input a continuous-tone image and outputs compressed image data

3.16
grayscale image

continuous-tone image that has only one component

3.17
high dynamic range

image or image data comprised of more than eight bits per sample

3.18
Joint Photographic Experts Group
JPEG

informal name of the working group which created this part of ISO/IEC 18477

Note 1 to entry: The term “joint” comes from the ITU-T and ISO/IEC collaboration.

3.19**legacy decoder**

embodiment of a decoding process conforming to Rec. ITU-T T.81 | ISO/IEC 10918-1, confined to the lossy discrete cosine transformation (DCT) process and the baseline, sequential or progressive modes, decoding at most four components to eight bits per component

3.20**lossless**

descriptive term for encoding and decoding processes and procedures in which the output of the decoding procedure(s) is identical to the input of the encoding procedure(s)

3.21**lossless coding**

mode of operation which refers to any one of the coding processes defined in this part of ISO/IEC 18477 in which all of the procedures are lossless

3.22**lossy**

descriptive term for encoding and decoding processes which are not lossless

3.23**low-dynamic range**

image or image data comprised of data with no more than 8 bits per sample

3.24**marker**

two-byte code in which the first byte is hexadecimal FF and the second byte is a value between 1 and hexadecimal FE

3.25**marker segment**

marker together with its associated set of parameters

3.26**minimum coded unit****MCU**

smallest group of data units that is coded

3.27**pixel**

collection of sample values in the spatial image domain having all the same sample coordinates

Note 1 to entry: A pixel may consist of three samples describing its red, green and blue value.

3.28**precision**

number of bits allocated to a particular sample or discrete cosine transformation (DCT) coefficient

3.29**procedure**

set of steps which accomplishes one of the tasks which comprise an encoding or decoding process

3.30**residual codestream**

codestream that contains an encoded (according to Rec. ITU-T T.81 | ISO/IEC 10918-1) residual image

3.31**residual data**

data that contains luminance ratio and red, green, and blue (RGB) differential data

3.32

residual image

pseudo image that contains encoded luminance ratio as luminance and encoded chrominance data that is computed from red, green, and blue (RGB) differential data using Multiple Component Decorrelation Transformation defined in ISO/IEC 18477-1

3.33

red, green, and blue

RGB

additive colour model

3.34

luminance ratio

array of per pixel ratio of HDR image luminance and LDR image luminance

3.35

quantization value

integer value used in the quantization procedure

3.36

quantize

act of performing the quantization procedure for a value

3.37

upsampling

procedure by which the spatial resolution of a component is increased

4 Abbreviated terms and symbols

4.1 Abbreviated terms

ASCII	American Standard Code for Information Interchange
HDR	High Dynamic Range
LDR	Low Dynamic Range

4.2 Symbols

Nc	Number of components in an image
----	----------------------------------

5 Conventions

5.1 Conformance language

The keyword “reserved” indicates a provision that is not specified at this time, shall not be used, and may be specified in the future. The keyword “forbidden” indicates “reserved” and in addition indicates that the provision will never be specified in the future.

5.2 Operators

NOTE Many of the operators used in this document are similar to those used in the C programming language.