



SLOVENSKI STANDARD

SIST EN 12569:2020

01-december-2020

Nadomešča:

SIST EN 12569:2000

SIST EN 12569:2000/AC:2000

SIST EN 12569:2000/AC:2001

Industrijski ventili - Ventili za kemično in petrokemično procesno industrijo - Zahteve in preskusi

Industrial valves - Valves for chemical and petrochemical process industry -
Requirements and tests

Industriearmaturen - Armaturen für die chemische und petrochemische
Verfahrensindustrie - Anforderungen und Prüfungen

Robinetterie industrielle - Appareils de robinetterie destinés aux procédés de l'industrie
chimique et pétrochimique - Prescriptions et essais

Ta slovenski standard je istoveten z: EN 12569:2020

ICS:

23.060.01 Ventili na splošno Valves in general

SIST EN 12569:2020 en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 12569:2020

<https://standards.iteh.ai/catalog/standards/sist/86d0aa16-a8ac-4764-8fdd-18dbbf73b0c/sist-en-12569-2020>

EUROPEAN STANDARD

EN 12569

NORME EUROPÉENNE

EUROPÄISCHE NORM

October 2020

ICS 23.060.01

Supersedes EN 12569:1999

English Version

Industrial valves - Valves for chemical and petrochemical process industry - Requirements and tests

Robinetterie industrielle - Appareils de robinetterie destinés aux procédés de l'industrie chimique et pétrochimique - Prescriptions et essais

Industriearmaturen - Armaturen für die chemische und petrochemische Verfahrensindustrie - Anforderungen und Prüfungen

This European Standard was approved by CEN on 14 September 2020.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword.....	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms, definitions and symbols	6
3.1 Terms and definitions	6
3.2 Symbols	7
4 Category of valves	7
5 Requirements	7
5.1 Design	7
5.1.1 General	7
5.1.2 Shell design strength	9
5.1.3 Protection against exceeding the allowable limits	9
5.1.4 Connection to the drive	9
5.1.5 Additional requirements for butterfly valves, ball and plug valves	10
5.1.6 Strength of valve stem and shaft	10
5.1.7 Anti-blow out design	10
5.2 Materials	11
5.2.1 General	11
5.2.2 Spheroidal graphite cast iron to EN 1563	11
5.2.3 Spheroidal graphite cast iron to EN 1563, 5.3103 and 5.3104	12
5.2.4 Cast steel	12
5.3 Manufacturing	12
5.3.1 Welding	12
5.3.2 Supply chain	12
5.4 Non-destructive testing (NDT)	12
5.5 Final assessment	12
5.6 Marking	13
5.7 Surface and coating	14
5.7.1 Surface finish	14
5.7.2 Flange facing surfaces	15
5.8 Condition as delivered	15
5.9 Documentation	15
Annex A (normative) Supplementary possible steel grades for fasteners	16
Annex B (normative) Threaded holes for pneumatic connections	18
Annex C (informative) Basic configuration of the valve interface from part-turn actuator to the valve with a bracket	20
Bibliography	23

European foreword

This document (EN 12569:2020) has been prepared by Technical Committee CEN/TC 69 “Industrial valves”, the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2021, and conflicting national standards shall be withdrawn at the latest by April 2021.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 12569:1999 and EN 12569:1999/AC:2000.

The main technical changes compared to the previous edition are the following:

- Clause 2 on normative references has been updated;
- Clause 3 for terms, definitions and symbols has been added;
- Clause 5 on the applicable requirements has been completely re-written;
- normative Annex A on supplementary possible steel grades for fasteners and normative Annex B for threaded holes for pneumatic connections have been added;
- informative Annex C giving basic configuration of the valve interface from actuator to the valve with a bracket has been added.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

EN 12569:2020 (E)**Introduction**

This document is based on the experience of the chemical and petrochemical industry and provides additional requirements to those given in EN 16668 and valve product standards.

It is assumed that the essential safety requirements of the European legislation for pressure equipment (satisfied by European product standards) and safety requirements from EN 16668 and other standards are satisfied.

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 12569:2020](https://standards.iteh.ai/catalog/standards/sist/86d0aa16-a8ac-4764-8fdd-18dbbf73b0c/sist-en-12569-2020)

<https://standards.iteh.ai/catalog/standards/sist/86d0aa16-a8ac-4764-8fdd-18dbbf73b0c/sist-en-12569-2020>

1 Scope

This document applies to valves of DN 15 and larger, made of metallic materials for chemical and petrochemical plants. It contains additional requirements to those contained in the relevant European product standards (e.g. EN 593, EN 1349) and EN 16668.

The use of design codes or technical rules other than described by European product standards is subject to agreement with the purchaser.

Process control devices and safety accessories are not subject of this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 558, *Industrial valves — Face to-face and centre-to-face dimensions of metal valves for use in flanged pipe systems — PN and Class designated valves*

EN 736-2:2016, *Valves — Terminology — Part 2: Definition of components of valves*

EN 736-3:2008, *Valves — Terminology — Part 3: Definition of terms*

EN 1092-1, *Flanges and their joints — Circular flanges for pipes, valves, fittings and accessories, PN designated — Part 1: Steel flanges*

EN 1267, *Industrial valves — Test of flow resistance using water as test fluid*

EN 1349, *Industrial process control valves*

EN 1515-4, *Flanges and their joints — Bolting — Part 4: Selection of bolting for equipment subject to the Pressure Equipment Directive 97/23/EC*

EN 1563, *Founding — Spheroidal graphite cast irons*

EN 1759 (all parts), *Flanges and their joint — Circular flanges for pipes, valves, fittings and accessories, Class designated*

EN 10204, *Metallic products — Types of inspection documents*

EN 10269, *Steels and nickel alloys for fasteners with specified elevated and/or low temperature properties*

EN 12266-1:2012, *Industrial valves — Testing of metallic valves — Part 1: Pressure tests, test procedures and acceptance criteria — Mandatory requirements*

EN 12266-2:2012, *Industrial valves — Testing of metallic valves — Part 2: Tests, test procedures and acceptance criteria – Supplementary requirements*

EN 12351, *Industrial valves — Protective caps for valves with flanged connections*

EN 12570, *Industrial valves — Method for sizing the operating element*

EN 15081, *Industrial valves — Mounting kits for part-turn valve actuator attachment*

EN 12569:2020 (E)

EN 16668:2016+A1:2018, *Industrial valves — Requirements and testing for metallic valves as pressure accessories*

EN 60534-4:2006, *Industrial-process control valves — Part 4: Inspection and routine testing*

EN ISO 1179-1, *Connections for general use and fluid power — Ports and stud ends with ISO 228-1 threads with elastomeric or metal-to-metal sealing — Part 1: Threaded ports (ISO 1179-1)*

EN ISO 5210, *Industrial valves — Multi-turn valve actuator attachments (ISO 5210)*

EN ISO 5211:2017, *Industrial valves — Part-turn actuator attachments (ISO 5211:2017)*

EN ISO 15848-1:2015,¹ *Industrial valves — Measurement, test and qualification procedures for fugitive emissions – Part 1: Classification system and qualification procedures for type testing of valves (ISO 15848-1:2015)*

3 Terms, definitions and symbols**3.1 Terms and definitions**

For the purposes of this document, the terms and definitions given in EN 736-2, EN 736-3, EN 1267, EN 16668 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1.1**shell tapping**

threaded hole in the wall of the shell

[SOURCE: EN 736-2:2016, 3.1.1.23]

3.1.2**fugitive emission**

chemical or mixture of chemicals, in any physical form, which represents an unanticipated or spurious leak from equipment on an industrial site

[SOURCE: EN ISO 15848-1:2015, 3.5]

3.1.3**sound engineering practice****SEP**

design taking into account all relevant factors influencing safety

¹ As impacted by amendment EN ISO 15848-1:2015/A1:2017.

3.1.4

anti-blow out design

valve design which ensures that, when the valve is under pressure, the shaft or stem cannot be fully blown out of the shell by disassembly of any external part or by failure of the connection between obturator and shaft or stem even when external parts (which are not included in the bare shaft valve, e.g. bracket, lever, actuator) are removed

[SOURCE: EN 736-3:2008, 3.3.7, modified – Note and indents have been incorporated into the sentence]

3.2 Symbols

Symbols and units are given in Table 1.

Table 1 — Symbols and units

Symbol	Denomination	Unit
ρ	Liner density	g/cm ³

4 Category of valves

Classification of valves shall be carried out as stated in EN 16668. Unless otherwise agreed, valves shall always be classified for gaseous fluids of Fluid Group 1 (to ensure universal use of the components).

Valves like condensate traps and pressure controllers that are used exclusively for steam and steam condensate service shall be classified in Fluid Group 2.

If the result of the categorization is not category I, II or III, SEP applies.

5 Requirements

[SIST EN 12569:2020](https://standards.iteh.ai/catalog/standards/sist/86d0aa16-a8ac-4764-8fdd-18dbbf73b0c/sist-en-12569-2020)

<https://standards.iteh.ai/catalog/standards/sist/86d0aa16-a8ac-4764-8fdd-18dbbf73b0c/sist-en-12569-2020>

5.1 Design

5.1.1 General

5.1.1.1 For threaded holes for pneumatic connections, all threads shall be G-threads, see Annex B.

5.1.1.2 The individual parts of the components shall be manufactured in such a way as to ensure their interchangeability for components of the same make, same type, same design status and the same nominal size.

5.1.1.3 The fatigue life depending on the maximum stress range to which a bellow is exposed during the entire service life shall be specified in the bellow documentation being considered as integrated part of the valve manufacturer documentation.

Flooded bellows in manually operated valves up to PN 40 for process application shall be designed for 20 000 full strokes (10 000 cycles, i.e. motions of the valve obturator moving from fully closed position to fully opened position, and returning to fully closed position) at least. As an option, at least 5 000 full strokes are subject to agreement.

Flooded bellows in manually operated valves higher than PN 40 for process application shall be designed for 2 500 full strokes at least.

As subject to agreement, the performance of the bellows may be qualified by a type test in accordance with EN ISO 15848-1 with its numbers of mechanical cycles for a defined level of the valve (to which the

EN 12569:2020 (E)

bellow is fitted). All other stem (or shaft) seal systems may be considered equivalent if they meet the requirements in accordance with EN ISO 15848-1.

5.1.1.4 Spindle seals (e.g. bellows and diaphragms) which are designed for increased tightness requirements (e.g. to avoid fugitive emissions into the atmosphere) and are considered as primary seals shall, unless otherwise agreed, be provided with a secondary seal in the event of unforeseen damage to the primary seal.

5.1.1.5 Concerning the sizing of the operating element, the following shall apply in the absence of requirements.

For any manual operation of valves, the minimum size of the operating element shall be in accordance with EN 12570. The size of the operating element shall be selected such that the valve can be operated:

- a) when the allowable differential pressure is equal to the maximum allowable pressure, and
- b) taking into account the effect of hydrodynamic torque due to flow velocity.

When specified by the customer, it is allowed to size an actuator based on a reduced differential pressure taking into account the effect of the hydraulic torque.

The actual differential pressure shall be marked on the valve.

5.1.1.6 Concerning flow characteristics Table 2 shall apply.

NOTE 1 Flow velocity is a design parameter to be considered for valves.

NOTE 2 The flow velocity is the quotient of the volumetric flow rate (expressed in m³/s) and the area calculated using the diameter (expressed in m) having a value equal to the number of the DN divided by 1 000.

SIST EN 12569:2020
<https://standards.iteh.ai/catalog/standards/sist/80c10aa16-a8ac-4764-8ffd-18dbbfa73b0c/sist-en-12569-2020>
Table 2 — Flow velocity

PS bar	Maximum flow velocity m/s	
	Liquids with a density of 1 000 kg/m ³ ^a	Gas (at density 1,293 kg/m ³ at 273 °K and 1 bar) ^a
Up to 6	2,5	25
6 < PS ≤ 10	3	30
10 < PS ≤ 16	4	35
PS > 16	5	40

^a In case of other physical properties of fluids, the values are adapted to the specific weight of the fluid.

5.1.1.7 The face-to-face lengths of valves shall conform to EN 558, unless agreed otherwise.

5.1.1.8 On all components where an electrically conductive connection to the piping line cannot be ensured for installation-specific reasons (e.g. wafer-style valves), suitable engineering measures (e.g. a pocket hole with internal threading in the shell) shall be provided to ensure proper discharge of any developing electrostatic charges to the piping line.

Durable protection against electrostatic charging shall be ensured.

The discharge resistance between any part of the component (including attachments) and the piping line shall be affirmed $< 10 \Omega$ for metallic components and $< 10^6 \Omega$ for plastic-lined metallic components.

In oil and grease-free design, special cleanliness requirements shall be a separate subject to agreement.

5.1.1.9 For valves classified in SEP, the relevant requirements of this document shall be considered in addition.

5.1.1.10 All screwed connections, e.g. body/cover connections or screwed in parts of valves, shall be properly secured (e.g. by mechanical / contact friction or locking) against accidental loosening.

Screwed body/cover connections that rely on the thread to seal are not acceptable.

5.1.1.11 The valve shall be designed so that the risk of media induced crevice corrosion is avoided.

5.1.1.12 Gaskets of the shell shall be radially retained against the pressure. In case of body bonnet joints up to and including PN 25 (or Class 150) valves, it is not mandatory.

Spiral wound gaskets sealing the body/cover connection shall be fully retained or provided with outer and inner guide rings.

The sealing face of spiral wound gaskets and metallic ring-joint gaskets shall not be interrupted by bolts, rings, etc.

5.1.1.13 Flange bolting shall not be used to compensate pipe stresses.

5.1.1.14 The design of the valve shall allow, with or without an intermediate part, mounting of a pneumatic, hydraulic or electric actuator complying with EN ISO 5210 (multi-turn valve actuators) or EN ISO 5211 (part-turn actuators).

5.1.1.15 Manually operated valves shall normally be closed by turning the handwheel or lever in a clockwise direction when facing the handwheel or lever.

If anti-clockwise closing is ordered, this shall be specified and marked on the operating element.

5.1.2 Shell design strength

The requirements in accordance with EN 16668 and existing product standards shall be fulfilled.

Isolating valves and control valves shall have no shell tapping, unless otherwise specified.

5.1.3 Protection against exceeding the allowable limits

The requirements in accordance with EN 16668:2016+A1:2018, 5.1.3 and existing product standards shall be fulfilled.

5.1.4 Connection to the drive

Where a connecting flange is specified for actuators as per EN ISO 5210 or EN ISO 5211, the design and type of execution shall be agreed between the manufacturer and the purchaser.

The connection between the valve body and the gearbox or actuator shall be vented such that any product leakage from the stem or shaft cannot penetrate into the gearbox or actuator housing.

Mounting of pneumatic part-turn actuators on valves shall be done in accordance with EN 15081. The preferred design is mentioned in Annex C.