

ETSI TS 138 141-1 V16.11.0 (2022-04)



iTeh STANDARD
5G;
NR;
PREVIEW

Base Station (BS) conformance testing Part 1: Conducted
conformance testing

(3GPP TS 38.141-1 version 16.11.0 Release 16)

<https://standards.iteh.ai/catalog/standards/sist/7cfla256-8db2-43f0-801b-e115357c058a/etsi-ts-138-141-1-v16-11-0-2022-04>



Reference

RTS/TSGR-0438141-1vgb0

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.

All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

(standards.iteh.ai)

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	15
1 Scope	17
2 References	17
3 Definitions, symbols and abbreviations	19
3.1 Definitions	19
3.2 Symbols.....	21
3.3 Abbreviations	23
4 General conducted test conditions and declarations.....	24
4.1 Measurement uncertainties and test requirements	24
4.1.1 General.....	24
4.1.2 Acceptable uncertainty of Test System.....	24
4.1.2.1 General	24
4.1.2.2 Measurement of transmitter	25
4.1.2.3 Measurement of receiver.....	27
4.1.2.4 Measurement of performance requirements.....	31
4.1.3 Interpretation of measurement results.....	31
4.2 Conducted requirement reference points.....	31
4.2.1 BS type 1-C	31
4.2.2 BS type 1-H.....	32
4.3 Base station classes	33
4.4 Regional requirements.....	33
4.5 BS configurations	34
4.5.1 BS type 1-C	34
4.5.1.1 Transmit configurations.....	34
4.5.1.1.1 General	34
4.5.1.1.2 Transmission with multiple transmitter antenna connectors.....	35
4.5.1.2 Receive configurations.....	35
4.5.1.2.1 General	35
4.5.1.2.2 Reception with multiple receiver antenna connectors, receiver diversity.....	35
4.5.1.3 Duplexers	36
4.5.1.4 Power supply options	36
4.5.1.5 Ancillary RF amplifiers.....	36
4.5.2 BS type 1-H.....	37
4.5.2.1 Transmit configurations	37
4.5.2.2 Receive configurations.....	38
4.5.2.3 Power supply options	38
4.5.3 BS with integrated Luant BS modem	38
4.6 Manufacturer declarations.....	38
4.7 Test configurations	44
4.7.1 General.....	44
4.7.2 Test signal used to build Test Configurations.....	44
4.7.3 NRTC1: Contiguous spectrum operation.....	44
4.7.3.1 NRTC1 generation	44
4.7.3.2 NRTC1 power allocation	45
4.7.4 NRTC2: Contiguous CA occupied bandwidth.....	45
4.7.4.1 NRTC2 generation	45
4.7.4.2 NRTC2 power allocation	46
4.7.5 NRTC3: Non-contiguous spectrum operation	46
4.7.5.1 NRTC3 generation	46
4.7.5.2 NRTC3 power allocation	46
4.7.6 NRTC4: Multi-band test configuration for full carrier allocation.....	46

4.7.6.1	NRTC4 generation	46
4.7.6.2	NRTC4 power allocation	47
4.7.7	NRTC5: Multi-band test configuration with high PSD per carrier	47
4.7.7.1	NRTC5 generation	47
4.7.7.2	NRTC5 power allocation	48
4.7.8	NRTC6: Non-contiguous spectrum operation in band n46 and n96	48
4.7.8.1	NRTC6 generation	48
4.7.8.2	NRTC6 power allocation	48
4.8	Applicability of requirements	48
4.8.1	General	48
4.8.2	Requirement set applicability	48
4.8.3	Applicability of test configurations for single-band operation	49
4.8.4	Applicability of test configurations for multi-band operation	50
4.9	RF channels and test models	51
4.9.1	RF channels	51
4.9.2	Test models	52
4.9.2.1	General	52
4.9.2.2	FR1 test models	52
4.9.2.2.1	FR1 test model 1.1 (NR-FR1-TM1.1)	54
4.9.2.2.2	FR1 test model 1.2 (NR-FR1-TM1.2)	55
4.9.2.2.3	FR1 test model 2 (NR-FR1-TM2)	55
4.9.2.2.4	FR1 test model 2a (NR-FR1-TM2a)	56
4.9.2.2.5	FR1 test model 3.1 (NR-FR1-TM3.1)	56
4.9.2.2.6	FR1 test model 3.1a (NR-FR1-TM3.1a)	56
4.9.2.2.7	FR1 test model 3.2 (NR-FR1-TM3.2)	57
4.9.2.2.8	FR1 test model 3.3 (NR-FR1-TM3.3)	57
4.9.2.2.9	NB-IoT operation in NR in-band test model (NR-N-TM)	58
4.9.2.3	Data content of Physical channels and Signals for NR-FR1-TM	58
4.9.2.3.1	PDCCH	59
4.9.2.3.2	PDSCH	59
4.9.2.4	Data content of Physical channels and Signals for NR-N-TM	60
4.9.3	NB-IoT testing	61
4.10	Requirements for contiguous and non-contiguous spectrum	61
4.11	Requirements for BS capable of multi-band operation	61
4.12	Format and interpretation of tests	62
5	Operating bands and channel arrangement	64
6	Conducted transmitter characteristics	65
6.1	General	65
6.1.1	BS type 1-C	65
6.1.2	BS type 1-H	65
6.2	Base station output power	65
6.2.1	Definition and applicability	65
6.2.2	Minimum requirement	66
6.2.3	Test purpose	66
6.2.4	Method of test	66
6.2.4.1	Initial conditions	66
6.2.4.2	Procedure	67
6.2.5	Test requirement	67
6.3	Output power dynamics	67
6.3.1	General	67
6.3.2	RE power control dynamic range	68
6.3.2.1	Definition and applicability	68
6.3.2.2	Minimum requirement	68
6.3.2.3	Test purpose	68
6.3.3	Total power dynamic range	68
6.3.3.1	Definition and applicability	68
6.3.3.2	Minimum requirement	68
6.3.3.3	Test purpose	68
6.3.3.4	Method of test	68
6.3.3.4.1	Initial conditions	68

6.3.3.4.2	Procedure.....	68
6.3.3.5	Test requirements.....	69
6.3.4	NB-IoT RB power dynamic range.....	69
6.3.4.1	Definition and applicability.....	69
6.3.4.2	Minimum requirement	70
6.3.4.3	Test purpose	70
6.3.4.4	Method of test	70
6.3.4.5	Test requirements.....	70
6.4	Transmit ON/OFF power	70
6.4.1	Transmitter OFF power	70
6.4.1.1	Definition and applicability.....	70
6.4.1.2	Minimum requirement	71
6.4.1.3	Test purpose	71
6.4.1.4	Method of test	71
6.4.1.5	Test requirements.....	71
6.4.2	Transmitter transient period.....	71
6.4.2.1	Definition and applicability.....	71
6.4.2.2	Minimum requirement	71
6.4.2.3	Test purpose	72
6.4.2.4	Method of test	72
6.4.2.4.1	Initial conditions.....	72
6.4.2.4.2	Procedure.....	72
6.4.2.5	Test requirements.....	73
6.5	Transmitted signal quality.....	73
6.5.1	General.....	73
6.5.2	Frequency error.....	73
6.5.2.1	Definition and applicability.....	73
6.5.2.2	Minimum Requirement	73
6.5.2.3	Test purpose	73
6.5.2.4	Method of test	73
6.5.2.5	Test Requirements.....	73
6.5.3	Modulation quality.....	74
6.5.3.1	Definition and applicability.....	74
6.5.3.2	Minimum Requirement	74
6.5.3.3	Test purpose	74
6.5.3.4	Method of test	74
6.5.3.4.1	Initial conditions.....	74
6.5.3.4.2	Procedure.....	74
6.5.3.5	Test requirements.....	75
6.5.4	Time alignment error	76
6.5.4.1	Definition and applicability.....	76
6.5.4.2	Minimum requirement	77
6.5.4.3	Test purpose	77
6.5.4.4	Method of test	77
6.5.4.4.1	Initial conditions.....	77
6.5.4.4.2	Procedure.....	77
6.5.4.5	Test requirement	78
6.6	Unwanted emissions.....	78
6.6.1	General.....	78
6.6.2	Occupied bandwidth	79
6.6.2.1	Definition and applicability.....	79
6.6.2.2	Minimum Requirements.....	79
6.6.2.3	Test purpose	79
6.6.2.4	Method of test	79
6.6.2.4.1	Initial conditions.....	79
6.6.2.4.2	Procedure.....	79
6.6.2.5	Test requirements.....	80
6.6.3	Adjacent Channel Leakage Power Ratio (ACLR)	80
6.6.3.1	Definition and applicability.....	80
6.6.3.2	Minimum requirement	81
6.6.3.3	Test purpose	81
6.6.3.4	Method of test	81

**ITeH STANDARD
PREVIEW
(standards.iteh.ai)**

ETSI TS 138 141-1 V16.11.0 (2022-04)
<https://standards.iteh.ai/catalog/standards/sist/7c11a256-812-43f0-801b-e115357c058a/etsi-ts-138-141-1-v16-11-0-2022-04>

6.6.3.4.1	Initial conditions	81
6.6.3.4.2	Procedure	81
6.6.3.5	Test requirements	82
6.6.3.5.1	General requirements	82
6.6.3.5.2	Limits and <i>basic limits</i>	82
6.6.3.5.3	<i>BS type 1-C</i>	86
6.6.3.5.4	<i>BS type 1-H</i>	86
6.6.4	Operating band unwanted emissions	87
6.6.4.1	Definition and applicability	87
6.6.4.2	Minimum requirement	88
6.6.4.3	Test purpose	88
6.6.4.4	Method of test	88
6.6.4.4.1	Initial conditions	88
6.6.4.4.2	Procedure	88
6.6.4.5	Test requirements	90
6.6.4.5.1	General requirements	90
6.6.4.5.2	Basic limits for Wide Area BS (Category A)	90
6.6.4.5.3	Basic limits for Wide Area BS (Category B)	91
6.6.4.5.3.1	Category B requirements (Option 1)	91
6.6.4.5.3.2	Category B requirements (Option 2)	92
6.6.4.5.4	Basic limits for Medium Range BS (Category A and B)	93
6.6.4.5.5	Basic limits for Local Area BS (Category A and B)	95
6.6.4.5.5A	Basic limits for Local Area and Medium Range BS for band n46 and n96 (Category A and B)	96
6.6.4.5.6	Basic limits for additional requirements	99
6.6.4.5.6.1	Limits in FCC Title 47	99
6.6.4.5.6.2	Protection of DTT	99
6.6.4.5.6.3	Additional operating band unwanted emissions limits for Band n48	99
6.6.4.5.6.4	Additional operating band unwanted emissions limits for Band n53	99
6.6.4.5.7	<i>BS type 1-C</i>	100
6.6.4.5.8	<i>BS type 1-H</i>	100
6.6.5	Transmitter spurious emissions	100
6.6.5.1	Definition and applicability	100
6.6.5.2	Minimum requirement	101
6.6.5.3	Test purpose	101
6.6.5.4	Method of test	101
6.6.5.4.1	Initial conditions	101
6.6.5.4.2	Procedure	101
6.6.5.5	Test requirements	102
6.6.5.5.1	Basic limits	102
6.6.5.5.1.1	Tx spurious emissions	102
6.6.5.5.1.2	Protection of the BS receiver of own or different BS	103
6.6.5.5.1.3	Additional spurious emissions requirements	103
6.6.5.5.1.4	Co-location with other base stations	112
6.6.5.5.2	(void)	118
6.6.5.5.3	<i>BS type 1-C</i>	118
6.6.5.5.4	<i>BS type 1-H</i>	118
6.7	Transmitter intermodulation	119
6.7.1	Definition and applicability	119
6.7.2	Minimum requirement	119
6.7.3	Test purpose	119
6.7.4	Method of test	119
6.7.4.1	Initial conditions	119
6.7.4.2	Procedure	120
6.7.5	Test requirements	121
6.7.5.1	<i>BS type 1-C</i>	121
6.7.5.1.1	Co-location minimum requirements	121
6.7.5.1.2	Additional requirements	121
6.7.5.2	<i>BS type 1-H</i>	122
6.7.5.2.1	Co-location minimum requirements	122
6.7.5.2.2	Intra-system minimum requirements	122
6.7.5.2.3	Additional requirements	123

7	Conducted receiver characteristics	124
7.1	General	124
7.2	Reference sensitivity level.....	124
7.2.1	Definition and applicability	124
7.2.2	Minimum requirement	124
7.2.3	Test purpose.....	124
7.2.4	Method of test	125
7.2.4.1	Initial conditions	125
7.2.4.2	Procedure	125
7.2.5	Test requirements.....	125
7.3	Dynamic range	131
7.3.1	Definition and applicability	131
7.3.2	Minimum requirement	131
7.3.3	Test purpose.....	131
7.3.4	Method of test	132
7.3.4.1	Initial conditions	132
7.3.4.2	Procedure	132
7.3.5	Test requirements.....	132
7.4	In-band selectivity and blocking	142
7.4.1	Adjacent Channel Selectivity (ACS)	142
7.4.1.1	Definition and applicability.....	142
7.4.1.2	Minimum requirement	142
7.4.1.3	Test purpose	142
7.4.1.4	Method of test	143
7.4.1.4.1	Initial conditions.....	143
7.4.1.4.2	Procedure.....	143
7.4.1.5	Test requirements.....	143
7.4.2	In-band blocking.....	145
7.4.2.1	Definition and applicability.....	145
7.4.2.2	Minimum requirement.....	145
7.4.2.3	Test purpose	145
7.4.2.4	Method of test	145
7.4.2.4.1	Initial conditions.....	145
7.4.2.4.2	Procedure for general blocking.....	146
7.4.2.4.3	Procedure for narrowband blocking.....	146
7.4.2.5	Test requirements.....	147
7.5	Out-of-band blocking.....	150
7.5.1	Definition and applicability	150
7.5.2	Minimum requirement	150
7.5.3	Test purpose.....	150
7.5.4	Method of test	151
7.5.4.1	Initial conditions	151
7.5.4.2	Procedure	151
7.5.5	Test requirements.....	151
7.5.5.1	General requirements	151
7.5.5.2	Co-location requirements	152
7.6	Receiver spurious emissions.....	153
7.6.1	Definition and applicability	153
7.6.2	Minimum requirement	154
7.6.3	Test purpose.....	154
7.6.4	Method of test	154
7.6.4.1	Initial conditions	154
7.6.4.2	Procedure	154
7.6.5	Test requirements.....	155
7.6.5.1	Basic limits.....	155
7.6.5.2	BS type 1-C	155
7.6.5.3	BS type 1-H.....	155
7.7	Receiver intermodulation	156
7.7.1	Definition and applicability	156
7.7.2	Minimum requirement	156
7.7.3	Test purpose.....	156
7.7.4	Method of test	156

7.7.4.1	Initial conditions	156
7.7.4.2	Procedure	156
7.7.5	Test requirements.....	157
7.8	In-channel selectivity	162
7.8.1	Definition and applicability	162
7.8.2	Minimum requirement	162
7.8.3	Test purpose.....	162
7.8.4	Method of test	162
7.8.4.1	Initial conditions	162
7.8.4.2	Procedure	162
7.8.5	Test requirements.....	162
8	Conducted performance characteristics.....	170
8.1	General	170
8.1.1	Scope and definitions.....	170
8.1.2	Applicability rule	171
8.1.2.0	General	171
8.1.2.1	Applicability of PUSCH performance requirements.....	171
8.1.2.1.1	Applicability of requirements for different subcarrier spacings	171
8.1.2.1.2	Applicability of requirements for different channel bandwidths	171
8.1.2.1.3	Applicability of requirements for different configurations.....	171
8.1.2.1.7	Applicability of 2-step RA type requirements for different subcarrier spacings	172
8.1.2.2	Applicability of PUCCH performance requirements	172
8.1.2.2.1	Applicability of requirements for different formats.....	172
8.1.2.2.2	Applicability of requirements for different subcarrier spacings	172
8.1.2.2.3	Applicability of requirements for different channel bandwidths	172
8.1.2.2.4	Applicability of requirements for different configurations.....	172
8.1.2.2.5	Applicability of requirements for multi-slot PUCCH	172
8.1.2.3	Applicability of PRACH performance requirements	173
8.1.2.3.1	Applicability of requirements for different formats.....	173
8.1.2.3.2	Applicability of requirements for different subcarrier spacings	173
8.1.2.3.3	Applicability of requirements for different channel bandwidths	173
8.1.2.3.4	Applicability of requirements for different restricted set types of long PRACH format 0	173
8.1.2.4	Applicability of PUSCH for high speed train performance requirements.....	173
8.1.2.4.1	Applicability of requirements for different speeds	173
8.1.2.4.2	Applicability of requirements for 1T1R	173
8.1.2.5	Applicability of interlaced PUSCH performance requirements	173
8.1.2.5.1	General applicability of interlaced PUSCH performance requirements	173
8.1.2.5.2	Applicability of requirements for different subcarrier spacings	173
8.1.2.5.3	Applicability of requirements for different channel bandwidths	174
8.1.2.5.4	Applicability of requirements for different configurations.....	174
8.1.2.5.5	Applicability of CG-UCI multiplexed on PUSCH requirements.....	174
8.1.2.6	Applicability of interlaced PUCCH performance requirements.....	174
8.1.2.6.1	General applicability of interlaced PUCCH performance requirements.....	174
8.1.2.6.2	Applicability of requirements for different formats.....	174
8.1.2.6.3	Applicability of requirements for different subcarrier spacings	174
8.1.2.6.4	Applicability of requirements for different channel bandwidths	174
8.1.2.7	Applicability of performance requirements for PRACH with $L_{RA} = 1151$ and $L_{RA} = 571$	175
8.1.2.7.1	Applicability of requirements for different formats.....	175
8.1.2.7.2	Applicability of requirements for different subcarrier spacings	175
8.1.2.7.3	Applicability of requirements for different channel bandwidths	175
8.2	Performance requirements for PUSCH	175
8.2.1	Performance requirements for PUSCH with transform precoding disabled	175
8.2.1.1	Definition and applicability.....	175
8.2.1.2	Minimum Requirement	175
8.2.1.3	Test Purpose	175
8.2.1.4	Method of test	175
8.2.1.4.1	Initial Conditions	175
8.2.1.4.2	Procedure.....	175
8.2.1.5	Test Requirement	176
8.2.2	Performance requirements for PUSCH with transform precoding enabled	184
8.2.2.1	Definition and applicability.....	184

8.2.2.2	Minimum Requirement	184
8.2.2.3	Test Purpose	184
8.2.2.4	Method of test	184
8.2.2.4.1	Initial Conditions	184
8.2.2.4.2	Procedure	185
8.2.2.5	Test Requirement	186
8.2.3	Performance requirements for UCI multiplexed on PUSCH	186
8.2.3.1	Definition and applicability	186
8.2.3.2	Minimum Requirements	187
8.2.3.3	Test purpose	187
8.2.3.4	Method of test	187
8.2.3.4.1	Initial conditions	187
8.2.3.4.2	Procedure	187
8.2.3.5	Test Requirement	188
8.2.4	Performance requirements for PUSCH for high speed train	189
8.2.4.1	Definition and applicability	189
8.2.4.2	Minimum Requirement	190
8.2.4.3	Test Purpose	190
8.2.4.4	Method of test	190
8.2.4.4.1	Initial Conditions	190
8.2.4.4.2	Procedure	190
8.2.4.5	Test Requirement	191
8.2.5	Performance requirements for UL timing adjustment	194
8.2.5.1	Definition and applicability	194
8.2.5.2	Minimum Requirement	194
8.2.5.3	Test Purpose	194
8.2.5.4	Method of test	194
8.2.5.4.1	Initial Conditions	194
8.2.5.4.2	Procedure	194
8.2.5.5	Test Requirement for High Speed Train	197
8.2.6	Performance requirements for PUSCH with 0.001% BLER	198
8.2.6.1	Definition and applicability	198
8.2.6.2	Minimum Requirement	198
8.2.6.3	Test Purpose	198
8.2.6.4	Method of test	198
8.2.6.4.1	Initial Conditions	198
8.2.6.4.2	Procedure	198
8.2.6.5	Test Requirement	199
8.2.7	Performance requirements for PUSCH repetition Type A	200
8.2.7.1	Definition and applicability	200
8.2.7.2	Minimum Requirement	201
8.2.7.3	Test Purpose	201
8.2.7.4	Method of test	201
8.2.7.4.1	Initial Conditions	201
8.2.7.4.2	Procedure	201
8.2.7.5	Test Requirement	202
8.2.8	Performance requirements for PUSCH Mapping Type B with non-slot transmission	204
8.2.8.1	Definition and applicability	204
8.2.8.2	Minimum Requirement	204
8.2.8.3	Test Purpose	204
8.2.8.4	Method of test	204
8.2.8.4.1	Initial Conditions	204
8.2.8.4.2	Procedure	204
8.2.8.5	Test Requirement	205
8.2.9	Performance requirements for PUSCH msgA for 2-step RA type	206
8.2.9.1	Definition and applicability	206
8.2.9.2	Minimum Requirement	206
8.2.9.3	Test Purpose	206
8.2.9.4	Method of test	206
8.2.9.4.1	Initial Conditions	206
8.2.9.4.2	Procedure	206
8.2.9.5	Test Requirement	208

8.2.10	Requirements for interlaced PUSCH	209
8.2.10.1	Definition and applicability	209
8.2.10.2	Minimum Requirement	209
8.2.10.3	Test Purpose	209
8.2.10.4	Method of test	209
8.2.10.4.1	Initial Conditions	209
8.2.10.4.2	Procedure	210
8.2.10.5	Test Requirement	211
8.2.11	Performance requirements for CG-UCI multiplexed on interlaced PUSCH	211
8.2.11.1	Definition and applicability	211
8.2.11.2	Minimum Requirements	212
8.2.11.3	Test purpose	212
8.2.11.4	Method of test	212
8.2.11.4.1	Initial conditions	212
8.2.11.4.2	Procedure	212
8.2.11.5	Test Requirement	213
8.3	Performance requirements for PUCCH	214
8.3.1	Performance requirements for PUCCH format 0	214
8.3.1.1	Definition and applicability	214
8.3.1.2	Minimum Requirement	214
8.3.1.3	Test purpose	215
8.3.1.4	Method of test	215
8.3.1.4.1	Initial conditions	215
8.3.1.4.2	Procedure	215
8.3.1.5	Test Requirement	216
8.3.2	Performance requirements for PUCCH format 1	217
8.3.2.1	NACK to ACK detection	217
8.3.2.1.1	Definition and applicability	217
8.3.2.1.2	Minimum Requirement	217
8.3.2.1.3	Test purpose	217
8.3.2.1.4	Method of test	217
8.3.2.1.4.1	Initial Conditions	217
8.3.2.1.4.2	Procedure	217
8.3.2.1.5	Test Requirement	218
8.3.2.2	ACK missed detection	219
8.3.2.2.1	Definition and applicability	219
8.3.2.2.2	Minimum Requirement	219
8.3.2.2.3	Test purpose	219
8.3.2.2.4	Method of test	220
8.3.2.2.4.1	Initial Conditions	220
8.3.2.2.4.2	Procedure	220
8.3.2.2.5	Test Requirement	221
8.3.3	Performance requirements for PUCCH format 2	221
8.3.3.1	ACK missed detection	221
8.3.3.1.1	Definition and applicability	221
8.3.3.1.2	Minimum requirements	222
8.3.3.1.3	Test purpose	222
8.3.3.1.4	Method of test	222
8.3.3.1.4.1	Initial Condition	222
8.3.3.1.4.2	Procedure	222
8.3.3.1.5	Test requirements	223
8.3.3.2	UCI BLER performance requirements	223
8.3.3.2.1	Definition and applicability	223
8.3.3.2.2	Minimum Requirement	223
8.3.3.2.3	Test purpose	224
8.3.3.2.4	Method of test	224
8.3.3.2.4.1	Initial Condition	224
8.3.3.2.4.2	Procedure	224
8.3.3.2.5	Test requirements	225
8.3.4	Performance requirements for PUCCH format 3	225
8.3.4.1	Definition and applicability	225
8.3.4.2	Minimum requirement	225

8.3.4.3	Test purpose	225
8.3.4.4	Method of test	226
8.3.4.4.1	Initial conditions	226
8.3.4.4.2	Procedure	226
8.3.4.5	Test requirement	227
8.3.5	Performance requirements for PUCCH format 4	228
8.3.5.1	Definition and applicability	228
8.3.5.2	Minimum requirement	228
8.3.5.3	Test purpose	228
8.3.5.4	Method of test	228
8.3.5.4.1	Initial conditions	228
8.3.5.4.2	Procedure	228
8.3.5.5	Test requirement	229
8.3.6	Performance requirements for multi-slot PUCCH	230
8.3.6.1	Performance requirements for multi-slot PUCCH format 1	230
8.3.6.1.1	NACK to ACK detection	230
8.3.6.1.1.1	Definition and applicability	230
8.3.6.1.1.2	Minimum Requirement	230
8.3.6.1.1.3	Test purpose	230
8.3.6.1.1.4	Method of test	230
8.3.6.1.1.4.1	Initial conditions	230
8.3.6.1.1.4.2	Procedure	231
8.3.6.1.1.5	Test Requirement	231
8.3.6.1.2	ACK missed detection	232
8.3.6.1.2.1	Definition and applicability	232
8.3.6.1.2.2	Minimum Requirement	232
8.3.6.1.2.3	Test purpose	232
8.3.6.1.2.4	Method of test	232
8.3.6.1.2.4.1	Initial conditions	232
8.3.6.1.2.4.2	Procedure	232
8.3.6.1.2.5	Test Requirement	233
8.3.7	Performance requirements for interlaced PUCCH format 0	234
8.3.7.1	Definition and applicability	234
8.3.7.2	Minimum Requirement	234
8.3.7.3	Test purpose	234
8.3.7.4	Method of test	234
8.3.7.4.1	Initial conditions	234
8.3.7.4.2	Procedure	234
8.3.7.5	Test Requirement	235
8.3.8	Performance requirements for interlaced PUCCH format 1	236
8.3.8.1	NACK to ACK detection	236
8.3.8.1.1	Definition and applicability	236
8.3.8.1.2	Minimum Requirement	236
8.3.8.1.3	Test purpose	236
8.3.8.1.4	Method of test	236
8.3.8.1.4.1	Initial Conditions	236
8.3.8.1.4.2	Procedure	236
8.3.8.1.5	Test Requirement	237
8.3.8.2	ACK missed detection	238
8.3.8.2.1	Definition and applicability	238
8.3.8.2.2	Minimum Requirement	238
8.3.8.2.3	Test purpose	238
8.3.8.2.4	Method of test	238
8.3.8.2.4.1	Initial Conditions	238
8.3.8.2.4.2	Procedure	238
8.3.8.2.5	Test Requirement	239
8.3.9	Performance requirements for interlaced PUCCH format 2	239
8.3.9.1	Definition and applicability	239
8.3.9.2	Minimum requirement	240
8.3.9.3	Test purpose	240
8.3.9.4	Method of test	240
8.3.9.4.1	Initial conditions	240

8.3.9.4.2	Procedure.....	240
8.3.9.5	Test requirement	241
8.3.10	Performance requirements for interlaced PUCCH format 3	241
8.3.10.1	Definition and applicability.....	241
8.3.10.2	Minimum requirement	242
8.3.10.3	Test purpose	242
8.3.10.4	Method of test	242
8.3.10.4.1	Initial conditions.....	242
8.3.10.4.2	Procedure.....	242
8.3.10.5	Test requirement	243
8.4	Performance requirements for PRACH.....	243
8.4.1	PRACH false alarm probability and missed detection.....	243
8.4.1.1	Definition and applicability.....	243
8.4.1.2	Minimum requirement	244
8.4.1.3	Test purpose	244
8.4.1.4	Method of test	244
8.4.1.4.1	Initial conditions.....	244
8.4.1.4.2	Procedure.....	244
8.4.1.5	Test requirement for Normal Mode.....	246
8.4.1.6	Test requirement for high speed train.....	247
8.4.1.7	Test requirement for PRACH with $L_{RA}=1151$ and $L_{RA}=571$	248
Annex A (normative): Reference measurement channels.....		249
A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, $R=1/3$).....	249
A.2	Fixed Reference Channels for dynamic range (16QAM, $R=2/3$).....	250
A.3	Fixed Reference Channels for performance requirements (QPSK, $R=193/1024$)	252
A.3A	Fixed Reference Channels for performance requirements (QPSK, $R=99/1024$)	254
A.3B	Fixed Reference Channels for performance requirements (QPSK, $R=308/1024$)	255
A.4	Fixed Reference Channels for performance requirements (16QAM, $R=658/1024$)	256
A.5	Fixed Reference Channels for performance requirements (64QAM, $R=567/1024$)	258
A.6	PRACH test preambles.....	260
A.7	Fixed Reference Channels for performance requirements (QPSK, $R=157/1024$)	260
Annex B (normative): Environmental requirements for the BS equipment.....		262
B.1	General	262
B.2	Normal test environment	262
B.3	Extreme test environment.....	262
B.3.1	Extreme temperature	262
B.4	Vibration.....	263
B.5	Power supply	263
B.6	Measurement of test environments.....	263
Annex C (informative): Test tolerances and derivation of test requirements.....		264
C.1	Measurement of transmitter.....	264
C.2	Measurement of receiver	266
C.3	Measurement of performance requirements	267
Annex D (informative): Measurement system set-up.....		270
D.1	BS type 1-C transmitter.....	270

D.1.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for BS type 1-C	270
D.1.2	Transmitter intermodulation for BS type 1-C.....	270
D.1.3	Time alignment error for <i>BS type 1-C</i>	271
D.2	<i>BS type 1-C</i> receiver	271
D.2.1	Reference sensitivity level for BS type 1-C	271
D.2.2	Dynamic range for BS type 1-C	272
D.2.3	In-channel selectivity for BS type 1-C	272
D.2.4	Adjacent Channel Selectivity (ACS) and narrowband blocking for BS type 1-C	273
D.2.5	Blocking characteristics for BS type 1-C	273
D.2.6	Receiver spurious emission for BS type 1-C.....	274
D.2.7	Intermodulation characteristics for BS type 1-C	274
D.3	<i>BS type 1-H</i> transmitter	275
D.3.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for BS type 1-H	275
D.3.2	Transmitter intermodulation for BS type 1-H	276
D.3.3	Transmitter spurious emissions for BS type 1-H.....	276
D.3.4	Time alignment error for <i>BS type 1-H</i>	278
D.4	<i>BS type 1-H</i> receiver	278
D.4.1	Reference sensitivity level for BS type 1-H	278
D.4.2	Receiver dynamic range for BS type 1-H.....	279
D.4.3	Receiver adjacent channel selectivity and narrowband blocking for BS type 1-H.....	279
D.4.4	Receiver spurious emissions.....	279
D.4.5	Receiver In-channel selectivity for BS type 1-H	281
D.4.6	Receiver intermodulation for BS type 1-H.....	282
D.5	<i>BS type 1-C</i> performance requirements.....	282
D.5.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions and for high speed condition	282
D.5.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	283
D.5.3	Performance requirements for PUSCH and PRACH in static conditions	283
D.5.4	Performance requirements for UL timing adjustment	284
D.6	<i>BS type 1-H</i> performance requirements.....	284
D.6.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions and for high speed condition	284
D.6.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	285
D.6.3	Performance requirements for PUSCH and PRACH in static conditions	285
D.6.4	Performance requirements for UL timing adjustment	286

Annex E (normative): Characteristics of interfering signals.....	287
---	------------

Annex F (normative): Void 288

Annex G (normative): Propagation conditions.....	289
---	------------

G.1	Static propagation condition.....	289
G.2	Multi-path fading propagation conditions.....	289
G.2.1	Delay profiles	289
G.2.1.1	Delay profiles for FR1	290
G.2.2	Combinations of channel model parameters	291
G.2.3	MIMO channel correlation matrices.....	292
G.2.3.1	MIMO correlation matrices using Uniform Linear Array	292
G.2.3.1.1	Definition of MIMO correlation matrices	292
G.2.3.1.2	MIMO correlation matrices at high, medium and low level	293
G.2.3.2	Multi-antenna channel models using cross polarized antennas.....	295
G.2.3.2.1	Definition of MIMO correlation matrices using cross polarized antennas.....	296
G.2.3.2.2	Spatial correlation matrices at UE and gNB sides.....	296
G.2.3.2.2.1	Spatial correlation matrices at UE side.....	296
G.2.3.2.2.2	Spatial correlation matrices at gNB side	296
G.2.3.2.3	MIMO correlation matrices using cross polarized antennas	297

G.3	High speed train condition	297
G.4	Moving propagation conditions.....	301
Annex H (normative): In-channel TX tests		303
H.1	General	303
H.2	Basic principles	303
H.2.1	Output signal of the TX under test	303
H.2.2	Ideal signal	303
H.2.3	Measurement results.....	304
H.2.4	Measurement points	304
H.3	Pre-FFT minimization process	305
H.4	Timing of the FFT window	305
H.5	Resource element TX power	306
H.6	Post-FFT equalisation.....	307
H.7	EVM.....	308
H.7.0	General.....	308
H.7.1	Averaged EVM (FDD).....	309
H.7.2	Averaged EVM (TDD).....	309
Annex I (normative): General rules for statistical testing		310
I.1	Testing methodology of PUSCH performance requirements with 0.001% BLER	310
I.1.1	General	310
I.1.2	Numerical definition of the pass-fail limits for testing PUSCH 0.001% BLER.....	311
I.1.3	Theory to derive the early pass/fail limits in I.1.2 (informative)	312
I.1.3.1	Numerical definition of the pass-fail limits for testing PUSCH 0.001% BLER	312
I.1.3.2	Simulation to derive the pass-fail limits for testing PUSCH 0.001% BLER	312
Annex J (informative): Change history.....		314
History	https://standards.iteh.ai/catalog/standards/sist/7cfla256-8db2-43f0-801b-e115357c058a/etsi-ts-138-141-1-v16-11-0-2022-04	323