

SLOVENSKI STANDARD SIST EN 300 019-2-0 V2.1.2:2006

01-februar-2006

Okoljski inženiring (EE) – Okoljski pogoji in preskusi vplivov okolja na telekomunikacijsko opremo – 2-0. del: Specifikacija preskusov vplivov okolja – Uvod

Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-0: Specification of environmental tests; Introduction **iTeh STANDARD PREVIEW**

(standards.iteh.ai)

<u>SIST EN 300 019-2-0 V2.1.2:2006</u> https://standards.iteh.ai/catalog/standards/sist/dc798200-6009-4060-b91c-77353552ccde/sist-en-300-019-2-0-v2-1-2-2006

Ta slovenski standard je istoveten z:

EN 300 019-2-0 Version 2.1.2

ICS:

19.040	Preskušanje v zvezi z okoljem	Environmental testing
33.050.01	Telekomunikacijska terminalska oprema na splošno	Telecommunication terminal equipment in general

SIST EN 300 019-2-0 V2.1.2:2006

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 300 019-2-0 V2.1.2:2006</u> https://standards.iteh.ai/catalog/standards/sist/dc798200-6009-4060-b91c-77353552ccde/sist-en-300-019-2-0-v2-1-2-2006

ETSI EN 300 019-2-0 V2.1.2 (2003-09)

European Standard (Telecommunications series)

Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-0: Specification of environmental tests; Introduction



Reference REN/EE-01027-2-0

Keywords

environment, testing

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

(standards.iteh.ai)

<u>SIST EN 300 019-2-0 V2.1.2:2006</u> https://standards.iteh.ai/catalog/standards/sist/dc798200-6009-4060-b91c-77353552ccd.msportanto-notice-0-v2-1-2-2006

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <u>http://portal.etsi.org/tb/status/status.asp</u>

> If you find errors in the present document, send your comment to: editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

> © European Telecommunications Standards Institute 2003. All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members. **TIPHON**TM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members. **3GPP**TM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intell	ectual Property Rights	4
Forev	vord	4
1	Scope	5
2	References	5
3	Definitions, symbols and abbreviations	5
4	General	6
5 5.1 5.1.1 5.1.2 5.2	Users guide Test specifications and the states of test item In-use tests Not in-use tests Selection of tests and test severities	7 7 7
6 6.1 6.2 6.3	Topics on making a test programme Environmental resistibility requirements Test programme Verification	8 8
Histo	ry	.10

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 019-2-0 V2.1.2:2006

https://standards.iteh.ai/catalog/standards/sist/dc798200-6009-4060-b91c-77353552ccde/sist-en-300-019-2-0-v2-1-2-2006

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Environmental Engineering (EE).

The present document is part 2, sub-part 0 of a multi-part deliverable covering environmental conditions and environmental tests for telecommunications equipment, as identified below:

Part 1: "Classification of environmental conditions";

Part 2: "Specification of environmental tes	sts"
---	------

Sub-part 0:	"Introduction STANDARD PREVIEW
Sub-part 1:	"Storage"; (standards.iteh.ai)
Sub-part 2:	"Transportation"; <u>SIST EN 300 019-2-0 V2.1.2:2006</u>
Sub-part 3:	"Stationary uses at weather protected locations ?? 8200-6009-4060-b91c- 77353552ccde/sist-en-300-019-2-0-v2-1-2-2006
Sub-part 4:	"Stationary use at non-weatherprotected locations";
Sub-part 5:	"Ground vehicle installations";
Sub-part 6:	"Ship environments";
Sub-part 7:	"Portable and non-stationary use";
Sub-part 8:	"Stationary use at underground locations".

Part 1 specifies different standardized environmental classes covering climatic and biological conditions, chemically and mechanically active substances and mechanical conditions during storage, transportation and in use.

Part 2 specifies the recommended test severities and test methods for the different environmental classes.

National transposition dates		
Date of adoption of this EN:	5 September 2003	
Date of latest announcement of this EN (doa):	31 December 2003	
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2004	
Date of withdrawal of any conflicting National Standard (dow):	30 June 2004	

1 Scope

The purpose of the present document is to specify the test severities and methods for verification of the required resistibility for equipment which is to be stored, transported and used in the environments stated in Part 1 of the present document.

The purpose of the present document is to form a general overview of Part 2.

TR 100 035 [1] should be used in conjunction with all parts of EN 300 019 series. It gives an introduction to the main concepts of environmental engineering, the purpose and use of environmental classes and the corresponding test philosophy.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <u>http://docbox.etsi.org/Reference</u>.

[1]	ETSI TR 100 035: "Environmental Engineering (EE); Environmental engineering; Guidance and terminology". SIST EN 300 019-2-0 V2.1.2:2006
[2]	ETSI EN 300 019-1 (all subparts). Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment, Classification of environmental conditions".
[3]	ETSI EN 300 019-2 (all subparts): "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Specification of environmental tests".
[4]	IEC 60721-2-4: "Classification of environmental conditions - Part 2-4: Environmental conditions appearing in nature - Solar radiation and temperature".
[5]	IEC 60068: "Environmental testing".

3 Definitions, symbols and abbreviations

Void

4 General

The purpose of environmental testing is to demonstrate that an equipment under defined environmental conditions can survive without irreversible failures and perform according to requirements.

These tests are not reliability tests or lifetime tests.

The severities of testing in EN 300 019-2-1 to 2-8 [3] are closely correlated with the characteristic severities of the environmental classes in EN 300 019-1-1 to 1-8 [2]. The transformation has been made taking into account failure consequences, performance requirements and the graded test severities in IEC 60068-2 [5] test methods. In EN 300 019-2-1 to 2-8 [3], "moderate failure consequences" and "normal performance requirements" shall be taken as standards, unless otherwise stated (see also TR 100 035 [1]).

In order to satisfy the environmental resistibility requirements, EN 300 019-2-1 to 2-8 [3] detail the severities and methods used. In many cases these conditions are different from those shown in EN 300 019-1-1 to 1-8 [2] and for some parameters no testing is recommended. Where conditions have been changed, this is done in order to:

- produce the effect of the environment rather than attempt to reproduce the actual physical environmental conditions; and/or
- enable standard testing to IEC 60068-2 [5]; and/or
- recognize that the given characteristic severity relates to a condition with a very low probability of occurrence.

Where no test is specified:

- other specified tests are considered to be more severe and cover that parameter; and/or
- the condition is benign and consequently does not require testing. However certain product specifications may require additional testing; and/or(standards.iteh.ai)
- the condition is a valid one, but no standard test method exists; and/or
 - SIST EN 300 019-2-0 V2.1.2:2006
- the condition is considered when choosing components and materials 009-4060-b91c-

The mechanical test severities given may deviate from the characteristic severities and may even be split into several test alternatives, taking into consideration equipment mass. The method given may also be different. This does not invalidate the verification because:

- depending on the equipment category, size, installation method and location inside the premises, the probable stresses are different within the class;
- usually only one combination of several existing complex mechanical stresses are given as a characteristic. Therefore, tests with different severities and methods can serve as verification and reveal the same failure mechanisms.

In meeting the test requirements shown in EN 300 019-2-1 to 2-8 [3], the equipment shall be deemed to comply with the resistibility requirements shown in EN 300 019-1-1 to 1-8 [2].

It is emphasized that performance requirements and the individual failure criteria which apply to a specific equipment shall be included in the relevant product specification. In particular, if relevant, the distinction between normal and reduced performance and between intermittent function and cessation of function should be precisely defined.

The classifications given in EN 300 019-1-1 to 1-8 [2] and the test severities given in EN 300 019-2-1 to 2-8 [3] do not cover any microenvironment caused by installing one equipment inside another, e.g. several sub-racks installed inside one miscellaneous rack. In such cases the applicable conditions shall be agreed between vendor and buyer.

In some cases test severities have been chosen which are not IEC preferred values, e.g. in order to stay within the prescribed limits of a climatogram.

5 Users guide

5.1 Test specifications and the states of test item

The relevant environmental test programme shall specify whether the test item is powered-up and whether it is in-use during each phase of the tests.

Two states of test item are usually required. These are the equipments "not in-use" and "in-use" states where:

- "not in-use" is normally the condition applicable to storage and transportation (for which the test programme shall specify if the equipment is to be in its packaging or not);
- "in-use" is normally the condition of the equipment in its working environment (for which the test programme shall specify the equipment's performance criteria, heat dissipation, failure consequences, etc.).

5.1.1 In-use tests

The required performance before, during and after the test shall be specified in the product specification. Input and load conditions of the equipment shall be chosen to obtain full utilization of the equipment under test. The dissipation shall be maximized by selection of supply power and load conditions, except for the steady-state-low-temperature test, where it shall be minimized.

The tests shall be conducted in accordance with IEC 60068-2 [5], unless otherwise stated in Part 2 of this EN 300 019-2-1 to 2-8 [3]. However, in all "in-use" tests, the equipment under test shall remain in its operational state with the exception of the cold test, in which the equipment will not be powered-up until temperature stabilization has been achieved.

The above operational conditions form a deviation from the conditioning requirements of IEC 60068-2-2 [5].

5.1.2 Not in-use tests SIST EN 300 019-2-0 V2.1.2:2006 https://standards.iteh.ai/catalog/standards/sist/dc798200-6009-4060-b91c-

The test specifications corresponding to storage and transportation may call for the same or different test severities. The relevant environmental test programme shall describe the final compilation, where states of test item, performance requirements and failure consequences have been taken into account.

5.2 Selection of tests and test severities

In EN 300 019-1-1 to 1-8 [2], alternative characteristic severities for certain parameters may be chosen as special requirements in the environmental class. These special requirements shall be described in the relevant product specification and noted also in the test specification.

Some special test requirements may also exist. Usually they are based on the simultaneous combined effect of parameters causing similar stresses to the equipment.

Information about the combined effect of air temperature and solar radiation and the cooling effect of heat radiation are given in IEC 60721-2-4 [4]. The effect of surface colour and roughness on reflection of light and emission of heat are given in IEC 60068-2-5 [5].

For each environmental parameter all test severities in the chosen classes for storage, transportation and in-use should be considered and the relevant severity or severities should be chosen for the test. Non-relevant tests should be deleted. Experience from earlier tests may justify deletion of some tests.