INTERNATIONAL STANDARD

ISO 8124-1

Fourth edition 2014-12-15

Safety of toys —

Part 1: Safety aspects related to mechanical and physical properties

Sécurité des jouets —

iTeh STPartie I: Aspects de sécurité rélatifs aux propriétés mécaniques et physiques (standards.iteh.ai)

ISO 8124-1:2014 https://standards.iteh.ai/catalog/standards/sist/38ec4490-a64b-42f2-8f20-f0a43eee6c89/iso-8124-1-2014



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 8124-1:2014 https://standards.iteh.ai/catalog/standards/sist/38ec4490-a64b-42f2-8f20-f0a43eee6c89/iso-8124-1-2014



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Co	Contents				
Fore	eword		vii		
Introduction					
1		2			
_	-				
2		native references			
3	Term	s and definitions	3		
4	Regu	irements	13		
	4.1	Normal use			
	4.2	Reasonably foreseeable abuse	13		
	4.3	Material	13		
		4.3.1 Material quality			
		4.3.2 Expanding materials			
	4.4	Small parts			
		4.4.1 For children under 36 months			
		4.4.2 For children 36 months and over but under 72 months			
	4.5	Shape, size and strength of certain toys			
		4.5.1 Squeeze toys, rattles, fasteners, and certain other toys and components of			
		4.5.2 Small balls			
		4.5.3 Pompoms			
		4.5.4 Pre-school play figures4.5.5 Toypacifiers ANDARD PREVIEW	18		
		4.5.5 Toypacifiers ANDARD PREVIEW	18		
		4.5.6 Balloons 4.5.7 Marbles (standards.iteh.ai)	19		
		4.5.7 Marbles (STANGARGS.ITEN.AL) 4.5.8 Hemispheric-shaped toys	19		
	4.6	4.5.8 Hemispheric-shaped toys			
	4.0	4.6.1 http://accessible.sharp.edges.of.glass.or.metal_a64b-4242-8420	22 22		
		4.6.2 Functional sharp edges / 150 8124 1 2014	22		
		4.6.3 Edges on metal toys			
		4.6.4 Edges on moulded toys			
		4.6.5 Edges on exposed bolts or threaded rods			
	4.7	Points			
		4.7.1 Accessible sharp points			
		4.7.2 Functional sharp points			
		4.7.3 Wooden toys			
	4.8	Projections			
		4.8.1 General requirements			
		4.8.2 Special considerations for bath toy projections	24		
	4.9	Metal wires and rods	24		
	4.10	Plastic film or plastic bags in packaging and in toys	25		
	4.11	Cords and elastics			
		4.11.1 Cords and elastics in toys intended for children under 18 months			
		4.11.2 Self-retracting pull cords in toys intended for children under 18 months			
		4.11.3 Cords for pull toys intended for children under 36 months			
		4.11.4 Cords on toy bags			
		4.11.5 Crib or playpen toys and mobiles			
		4.11.6 Crib gyms and similar toys			
	4.10	4.11.7 Cords, strings and lines for flying toys			
	4.12	Folding mechanisms			
		4.12.1 Toy pushchairs, perambulators and similar toys			
		4.12.2 Other toys with folding mechanisms	28 28		
		T. LA. A. LUNGETHIE LEALANCE	/.0		

ISO 8124-1:2014(E)

4.13	Holes, clearances and accessibility of mechanisms	Z8			
	4.13.1 Circular holes in rigid materials	28			
	4.13.2 Accessible clearances for movable segments				
	4.13.3 Chains or belts in ride-on toys				
	4.13.4 Other driving mechanisms				
	4.13.5 Winding keys				
4.14	Springs	30			
4.15	Stability and overload requirements	31			
	4.15.1 Stability of ride-on toys and seats				
	4.15.2 Overload requirements for ride-on toys and seats				
	4.15.3 Stability of stationary floor toys				
110					
4.16	Enclosures				
	4.16.1 Ventilation				
	4.16.2 Closures				
	4.16.3 Toys that enclose the head	33			
4.17	Simulated protective equipment, such as helmets, hats and goggles	33			
4.18					
1.10	4.18.1 General				
	4.18.2 Projectiles				
	4.18.3 Projectile toys with stored energy				
	4.18.4 Projectile toys without stored energy				
4.19	Rotors and propellers	39			
4.20	Aquatic toys	40			
4.21					
4.22	Braking Toy bicycles iTeh STANDARD PREVIEW	40			
1.22	4.22.1 Instructions for use	11			
	4.22.2 Determination of maximum 3addle height	41 11			
	4.22.2 Determination of maximum saddle neight 1.21.)	41			
	4.22.3 Braking requirements				
4.23	Speed limitation of electrically driven ride-on toys				
4.24	Toys containing a heat source i/catalog/standards/sist/38cc4490-a64b-42f2-8f20-	42			
4.25	Liquid-filled toys #0a43ccc6c89/iso-8124-1-2014	42			
4.26	Mouth-actuated toys	42			
4.27	Toy roller skates, toy inline skates and toy skateboards				
4.28	Percussion caps				
4.29	Acoustic requirements				
4.30	Toy scooters				
	4.30.1 General				
	4.30.2 Warnings and instructions for use	44			
	4.30.3 Strength				
	4.30.4 Stability				
	4.30.5 Adjustable and folding steering tubes and handlebars				
	4.30.6 Braking				
	8				
	4.30.7 Wheel size				
	4.30.8 Protruding parts				
4.31	Magnets and magnetic components				
	4.31.1 Magnetic/electrical experimental sets intended for children 8 years and over	45			
	4.31.2 All other toys with magnets and magnetic components				
_					
Test 1	methods	46			
5.1	General	46			
5.2	Small parts test	47			
5.3	Test for shape and size of certain toys				
5.4	Small balls test				
5.5	Test for pompoms				
	* *				
5.6	Test for pre-school play figures				
5.7	Accessibility of a part or component				
	5.7.1 Principle	50			
	5.7.2 Apparatus	51			
	5.7.3 Procedure				

5

5.8	Sharp-edge test			
	5.8.1	Principle	52	
	5.8.2	Apparatus	52	
	5.8.3	Procedure	53	
5.9	Sharp-point test			
	5.9.1	Principle	54	
	5.9.2	Apparatus		
	5.9.3	Procedure		
5.10	Determ	ination of thickness of plastic film and sheeting	55	
	5.10.1	General		
	5.10.2	Apparatus	55	
	5.10.3	Procedure		
5.11	Test for	cords		
	5.11.1	Determination of cord thickness		
	5.11.2	Self-retracting pull cords		
	5.11.3	Electric resistance of cords		
5.12	Stability	y and overload tests		
	5.12.1	General		
	5.12.2	Sideways stability test, feet available for stabilization		
	5.12.3	Sideways stability test, feet unavailable for stabilization		
	5.12.4	Fore and aft stability test	57	
	5.12.5	Overload test for ride-on toys and seats		
	5.12.6	Stability test of stationary floor toys		
5.13		closures and toy chest lids	58	
	5.13.1	closures and toy chest lids	58	
	5.13.2	Toy chest lids	58	
5.14		test for toys that cover the face ten.ai	59	
5.15	Kinetic	energy and wall impact test	59	
	5.15.1			
		Wall impact test for projectiles //38cc4490-a64b-4212-8120-		
5.16	Free-w	heeling facility and brake performance test	62	
0110	5.16.1			
	5.16.2	Brake performance for mechanically or electrically powered ride-on toys		
	011012	other than toy bicycles	63	
	5.16.3	Brake performance for toy bicycles		
5.17		ination of speed of electrically driven ride-on toys		
5.18		ination of temperature increases		
5.19		e of liquid-filled toys		
5.20		ity of mouth-actuated toys		
5.21		ing materials		
5.22	Folding	or sliding mechanisms	65	
0.22		Loads		
		Toy pushchairs and perambulators		
		Other toys with folding mechanisms		
5.23		ble toys		
5.24		ably foreseeable abuse tests		
0.21	5.24.1			
	5.24.2	Drop test		
	5.24.3	Tip-over test for large and bulky toys		
	5.24.4	Dynamic strength test for wheeled ride-on toys other than toy scooters		
	5.24.5	Torque test		
	5.24.6	Tension test		
	5.24.7			
	5.24.8	1		
5.25		ination of sound pressure levels		
3.23	5.25.1			
		Measurement procedure		
5.26		trength for toy scooters		
0.20	Julie	61 C115 611 101 60 9 DCUUGCI J	/ /	

ISO 8124-1:2014(E)

5.27	Dynamic strength for toy scooters				
	5.27.1 Principle				
	5.27.2 Load				
	5.27.3 Procedure				
5.28	Brake performance for toy scooters				
	5.28.1 Toy scooters with handbrake				
= 0 0	5.28.2 Toy scooters with foot brake				
5.29	Strength of toy scooter steering tubes				
	5.29.1 Resistance to downward forces				
F 20	5.29.2 Resistance to upward forces				
5.30	Resistance to separation of handlebar				
5.31	Tension test for magnets				
	5.31.1 Principle				
	5.31.2 Toys with magnets or magnetic components				
	5.31.3 Toys that contain one magnet only and a mating metal component				
5.32	5.31.4 Toys that contain one magnet only and no mating metal component				
3.32	5.32.1 General				
	5.32.2 Principle				
	5.32.3 Apparatus				
	5.32.4 Procedure				
	5.32.5 Calculation of magnetic flux index				
5.33	Impact test for magnets				
5.34					
5.35	Soaking test for magnets Determination of projectile range IDARD PREVIEW	86			
5.36	Tip assessment of rigid projectiles	87			
5.37	Tip assessment of rigid projectiles Length of suction cup projectiles dards.iteh.ai)	87			
Annex A (in	formative) Age-grading guidelines	89			
Annex B (in	formative) Safety-labelling guidelines and manufacturer's markings	92			
	formative) Design guidelines for toys attached to cribs or playpens				
_	formative) Toy gun marking				
Annex E (informative) Rationale					
-	Formative) Bath toy projection design guidelines				
	v				

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 8124-1 was prepared by Technical Committee ISO/TC 181, Safety of toys.

This fourth edition cancels and replaces the third edition (ISO 8124-1:2012), of which it constitutes a minor revision. It also incorporates the amendments ISO 8124-1:2012/Amd.1:2014 and ISO 8124-1:2012/Amd.2:2014. STANDARD PREVIEW

ISO 8124 consists of the following parts, under the general title Safety of toys:

- Part 1: Safety aspects related to mechanical and physical properties
- Part 2: Flammability/standards.iteh.ai/catalog/standards/sist/38ec4490-a64b-42f2-8f20-
- Part 3: Migration of certain elements ee6c89/iso-8124-1-2014
- Part 4: Swings, slides and similar activity toys for indoor and outdoor family domestic use
- Part 6: Certain phthalate esters in toys and children's products
- Part 8: Age determination guidelines (Technical Report)

The following parts are under preparation:

- Part 5: Determination of total concentration of certain elements in toys
- Part 7: Finger paints Requirements and test methods

Introduction

This part of ISO 8124 is largely based upon existing standards in the European Union (EN 71-1 and in the United States of America (ASTM F963).

However, it should not be construed that a toy manufactured in compliance with this part of ISO 8124 will be in full compliance with relevant national toy safety requirements in the market where the product is intended to be distributed. The user of this part of ISO 8124 is therefore advised to be aware of relevant national requirements.

Compliance with the requirements of this part of ISO 8124 will minimize potential hazards associated with toys resulting from their use in their intended play modes (normal use) as well as unintended play modes (reasonably foreseeable abuse).

This part of ISO 8124 will not, nor is it intended to, eliminate parental responsibility in the appropriate selection of toys. In addition, this part of ISO 8124 will not eliminate the need for parental supervision in situations where children of various ages may have access to the same toy(s).

Although <u>Annexes A</u>, <u>B</u>, <u>C</u>, <u>D</u>, <u>E</u> and <u>F</u> are for information purposes only, they are crucial for the correct interpretation of this part of ISO 8124.

The safety of electric toys is described in IEC 62115.

When age indications are required for safety labelling purposes, they may be given in either months or years.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 8124-1:2014 https://standards.iteh.ai/catalog/standards/sist/38ec4490-a64b-42f2-8f20-f0a43eee6c89/iso-8124-1-2014

Safety of toys —

Part 1:

Safety aspects related to mechanical and physical properties

1 Scope

The requirements in this part of ISO 8124 apply to all toys, i.e. any product or material designed or clearly intended for use in play by children under 14 years of age. They are applicable to a toy as it is initially received by the consumer and, in addition, they apply after a toy is subjected to reasonably foreseeable conditions of normal use and abuse unless specifically noted otherwise.

The requirements of this part of ISO 8124 specify acceptable criteria for structural characteristics of toys, such as shape, size, contour, spacing (e.g. rattles, small parts, sharp points and edges, and hingeline clearances) as well as acceptable criteria for properties peculiar to certain categories of toy (e.g. maximum kinetic energy values for non-resilient-tipped projectiles and minimum tip angles for certain ride-on toys).

This part of ISO 8124 specifies requirements and test methods for toys intended for use by children in various age groups from birth to 14 years. The requirements vary according to the age group for which a particular toy is intended. The requirements for a particular age group reflect the nature of the hazards and the expected mental and/or physical abilities of a child to cope with them.

This part of ISO 8124 also requires that appropriate warnings and/or instructions for use be given on certain toys or their packaging. Due to linguistic problems which may occur in different countries, the wording of these warnings and instructions is not specified but given as general information in Annex B. It should be noted that different legal requirements exist in many countries with regard to such marking.

This part of ISO 8124 does not purport to cover or include every conceivable potential hazard of a particular toy or toy category. Except for labelling requirements indicating the functional hazards and the age range for which the toy is intended, this part of ISO 8124 has no requirements for those characteristics of toys which represent an inherent and recognized hazard which is integral to the function of the toy.

EXAMPLE 1 An example of such a hazard is the sharp point necessary for the proper function of a needle. The needle is a hazard which is well understood by the purchaser of a toy sewing kit, and the functional sharp-point hazard is communicated to the user as part of the normal educational process of learning to sew as well as at the point of purchase by means of cautionary labelling on the product's packaging.

EXAMPLE 2 As a further example, a two-wheeled toy scooter has inherent and recognized hazards associated with its use (e.g. instability during use, especially while learning). The potential hazards associated with its structural characteristics (sharp edges, pinch hazards, etc.) will be minimized by compliance with the requirements of this part of ISO 8124.

Products not included within the scope of this part of ISO 8124 are:

- a) bicycles, except for those considered to be toys, i.e. those having a maximum saddle height of 435 mm (see <u>E.1</u>, general);
- b) slingshots;

NOTE "Slingshots" are also known as "catapults" and are usually held in the hand; examples are given in Figure 1. Toy versions of medieval catapults and trebuchets are not exempt from this part of ISO 8124; an example is given in Figure 2.



Figure 1 — Examples of slingshots (not within the scope of this part of ISO 8124)



Figure 2 — Medieval toy catabult (within the scope of this part of ISO 8124)

- c) darts with metal points; ISO 8124-1:2014 https://standards.iteh.ai/catalog/standards/sist/38ec4490-a64b-42f2-8f20-
- d) home and public playground equipment, 43eee6c89/iso-8124-1-2014
- e) compressed air- and gas-operated guns and pistols (see E.1);
- f) kites (except for the electric resistance of their strings, which is included);
- g) model kits, hobby and craft items, in which the finished item is not primarily of play value;
- h) sporting goods and equipment, camping goods, athletic equipment, musical instruments and furniture; however, toys which are their counterparts are included.
 - It is recognized that there is often a fine distinction between, for example a musical instrument or a sporting item and its toy counterpart. The intention of the manufacturer or distributor, as well as normal use and reasonably foreseeable abuse, determines whether the item is a toy counterpart or not;
- i) models of aircraft, rockets, boats and land vehicles powered by combustion engines; however, toys which are their counterparts are included (see <u>E.1</u>);
- j) collectible products not intended for children under 14 years of age;
- k) holiday decorations that are primarily intended for ornamental purposes;
- l) aquatic equipment intended to be used in deep water, swimming-learning devices and flotation aids for children such as swim-seats and swim-aids;
- m) toys installed in public places (e.g. arcades and shopping centres);
- n) puzzles having more than 500 pieces or without a picture, for specialists;
- o) fireworks including percussion caps, except percussion caps specifically designed for toys;

- p) products containing heating elements intended for use under the supervision of an adult in a teaching context;
- q) steam engines;
- r) video toys that can be connected to a video screen and operated at a nominal voltage greater than 24 V;
- s) babies' pacifiers (dummies);
- t) faithful reproduction of firearms;
- u) electric ovens, irons or other functional products operated at a nominal voltage greater than 24 V;
- v) bows for archery with an overall relaxed length exceeding 120 cm;
- w) fashion jewellery for children (see E.1).

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 868, Plastics and ebonite — Determination of indentation hardness by means of a durometer (Shore hardness)

ISO 3746:2010, Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Survey method using an enveloping measurement surface over a reflecting plane

ISO 4287, Geometrical Product Specifications (GPS) Surface texture: Profile method — Terms, definitions and surface texture parameters

ISO 6508-1, Metallic materials is ite Rockwell hardness test 440 Part 1:4 Test method (scales A, B, C, D, E, F, G, H, K, N, T) f0a43eee6c89/iso-8124-1-2014

ISO 11201, Acoustics — Noise emitted by machinery and equipment — Determination of emission sound pressure levels at a work station and at other specified positions in an essentially free field over a reflecting plane with negligible environmental corrections

ISO 11202, Acoustics — Noise emitted by machinery and equipment — Determination of emission sound pressure levels at a work station and at other specified positions applying approximate environmental corrections

ISO 11204, Acoustics — Noise emitted by machinery and equipment — Determination of emission sound pressure levels at a work station and at other specified positions applying accurate environmental corrections

IEC 61672-1, Electroacoustics — Sound level meters — Part 1: Specifications

IEC 61672-2, Electroacoustics — Sound level meters — Part 2: Pattern evaluation tests

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

NOTE The requirements in this part of ISO 8124 are applicable to certain age ranges. For interpretation of these age ranges, see $\underline{\text{E.43}}$ (age-break terminology).

3.1

accessible

(part or component) any area of the toy that can be contacted by any portion forward of the collar of the accessibility probe as described in <u>5.7</u> (accessibility of a part or component)

3.2

aquatic toy

article, whether inflatable or not, intended to bear the mass of a child and used as an instrument of play in shallow water

Note 1 to entry: Bathroom toys and beach balls are not considered aquatic toys.

3.3

arrow

projectile in the form of a shaft with a length of 150 mm or more, intended to be discharged from a bow held by the user

3.4

backing

material adhering to flexible plastic sheeting

3.5

ball

spherical, ovoid or ellipsoidal object, usually but not always designed or intended to be thrown, hit, kicked, rolled, dropped or bounced

Note 1 to entry: This definition includes balls attached to a toy or article by a string, elastic cord or similar tether and also any multi-sided object formed by connecting planes into, and any novelty item of, a generally spherical, ovoid or ellipsoidal shape designed or intended to be used as a ball.

Note 2 to entry: This definition does not include dice, or balls permanently enclosed inside pinball machines, mazes or similar outer containers. A ball is permanently enclosed if, when tested according to <u>5.24</u> (reasonably foreseeable abuse), it is not removed from the outer container. (Standards.iteh.ai)

3.6

battery-operated toy

ISO 8124-1:2014

toy having at least one function dependent on electricity and powered by batteries

f0a43eee6c89/iso-8124-1-2014

3.7 **burr**

roughness caused by not cleanly severing or finishing the material

3.8

close-to-the-ear toy

toy that is intended to be used close to the ear, i.e. the sound-emitting part of such a toy is normally put against the ear of a child

EXAMPLE Toy cellphones or toy telephones that emit sounds from the handpiece.

3.9

collapse

sudden or unexpected folding of a structure

3.10

continuous sound

any steady-state sound or group of variable sounds greater than one second in duration

3.11

cord

length of slender, flexible material

EXAMPLE Monofilaments, woven and twisted cord, rope, plastic textile tapes, ribbon and those fibrous materials known as string.

Note 1 to entry: Doll hair is not considered a cord.

3.12

crushing

injury to part of the body resulting from compression between surfaces

C-weighted peak sound pressure level

*Lp*_{Cneak}

peak sound pressure level obtained when using standardized C-weighting

3.14

dart

projectile in the form of a shaft less than 150 mm in length that is intended to be thrown or blown

discharge mechanism

component of the toy, separate from the projectile, which releases or propels the projectile into free flight

driving mechanism

assembly of linked parts or components (e.g. gears, belts and winding mechanisms), at least one of which moves, powered by a source (e.g. electrical or mechanical means) independent of a child

3.17

edge

line, formed at the junction of two surfaces, whose length exceeds 2,0 mm

iTeh STANDARD PREVIEW 3.17.1

curled edge

curled edge (standards iteh.ai) edge in which the portion of the sheet adjacent to the edge is bent into an arc and forms an angle of less than 90° with the base sheet

ISO 8124-1:2014

Note 1 to entry: See Figure's andards.iteh.ai/catalog/standards/sist/38ec4490-a64b-42f2-8f20-

f0a43eee6c89/iso-8124-1-2014

3.17.2

hemmed edge

edge in which the portion of the sheet adjacent to the edge is folded back on the sheet itself through an angle of approximately 180°, so that the portion of the sheet adjacent to the edge is approximately parallel to the main sheet

Note 1 to entry: See Figure 3.


3.17.3

rolled edge


edge in which the portion of the sheet adjacent to the edge is bent into an arc and forms an angle between 90° and 120° with the main sheet

Note 1 to entry: See Figure 3.


Dimensions in millimetres




a) Rolled edge



b) Hemmed (folded) edge



c) Curled edge



d) Typical lap joint

a No limit.

Figure 3 — Edges iTeh STANDARD PREVIEW

(standards.iteh.ai)

3.18

equivalent sound pressure level

 Lp_{Aeq}

level of a steady-state sound which, in a stated time period and at a stated location, has the same A-weighted sound energy as the time varying sound made so the sound energy as the time varying sound made so the sound energy as the time varying sound made so the sound energy as the so

3.19

expanding material

material whose volume expands when exposed to water

3.20

explosive action

sudden release of energy characterized by the rapid expansion or bursting of a material

3.21

fastener

mechanical device which attaches two or more elements together

EXAMPLE Screws, rivets and staples.

3.22

feathering

bevelling of an edge (or decrease in thickness moving toward the edge) caused during shearing or cutting of material

3.23

flash

excess material that escapes between the mating parts of a mould assembly

3.24

folding mechanism

hinged, pivoted, folding or sliding assembly which could crush, scissor, pinch or shear during operation

EXAMPLE Toy ironing boards, toy pushchairs.

3.25

free flight

unconstrained travel through the air

Note 1 to entry: This includes projectiles that are ultimately restrained by means of a non-rigid tether (e.g. a pop-gun).

3.26

functional magnet in electrical or electronic components of toys

any magnet necessary for the function of motors, relays, speakers and other electrical or electronic components in a toy where the magnetic properties are not part of the play pattern of the toy

3.27

functional toy

toy which performs and is used in the same way as, and is often a scale model of, a certain product, appliance or installation intended for adults

EXAMPLE Stove with heating properties.

3.28

fuzz

bits of fibrous-type material which can be readily removed from toys with a pile surface

3.29

glass

hard, brittle, amorphous substance produced by fusion, usually consisting of mutually dissolved silica and silicates which also contain soda and lime RD PREVIEW

3.30

hand-held toy

(standards.iteh.ai)

toy that is intended to be used or operated while being held in the hand

ISO 8124-1:2014

EXAMPLE Toy tools, small electronic games, stuffed animals, dolls, musical toys and cap-firing toys.

1043eee6c89/iso-8124-1-2014

3.31

harm

physical injury or damage to the health of people or damage to property or the environment

3.32

hazard

potential source of harm

Note 1 to entry: The term hazard can be qualified in order to define its origin or the nature of the expected harm (i.e. electric shock hazard, crushing hazard, cutting hazard, toxic hazard, fire hazard or drowning hazard).

3.33

hazardous projection

projection that, because of its material or configuration or both, may present a puncture hazard should a child step on or fall onto it

Note 1 to entry: Excluded from this definition are puncture hazards to the eyes and/or mouth, because of the impossibility of eliminating puncture hazards to those areas of the body by product design.

Note 2 to entry: If the projection is on a small toy which topples over when pressure is applied to the end of the projection, it is unlikely to present a hazard.

3.34

hazardous sharp edge

accessible edge of a toy which presents an unreasonable risk of injury during normal use and reasonably foreseeable abuse