

ETSI TS 124 501 V15.7.0 (2022-07)



**5G;
Non-Access-Stratum (NAS) protocol for 5G System (5GS);
Stage 3
(3GPP TS 24.501 version 15.7.0 Release 15)**

[ETSI TS 124 501 V15.7.0 \(2022-07\)](https://standards.iteh.ai/catalog/standards/sist/9321326d-95b2-4688-a8d5-60018faa1513/etsi-ts-124-501-v15-7-0-2022-07)

<https://standards.iteh.ai/catalog/standards/sist/9321326d-95b2-4688-a8d5-60018faa1513/etsi-ts-124-501-v15-7-0-2022-07>



Reference

RTS/TSGC-0124501vf70

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards-portal.etsi.org/People/CommitteeSupportStaff.aspx> 4688-a8d5-

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	18
1 Scope	20
2 References	20
3 Definitions and abbreviations.....	22
3.1 Definitions	22
3.2 Abbreviations	26
4 General	28
4.1 Overview	28
4.2 Coordination between the protocols for 5GS mobility management and 5GS session management	28
4.3 UE domain selection	29
4.3.1 UE's usage setting	29
4.3.2 Domain selection for UE originating sessions / calls.....	29
4.3.3 Change of UE's usage setting.....	31
4.3.4 Change or determination of IMS voice availability	31
4.4 NAS security	32
4.4.1 General.....	32
4.4.2 Handling of 5G NAS security contexts.....	32
4.4.2.1 General	32
4.4.2.2 Establishment of a mapped 5G NAS security context during inter-system change from S1 mode to N1 mode in 5GMM-CONNECTED mode.....	34
4.4.2.3 Establishment of a 5G NAS security context during N1 mode to N1 mode handover	35
4.4.2.4 Establishment of an EPS security context during inter-system change from N1 mode to S1 mode in 5GMM-CONNECTED mode	36
4.4.2.5 Establishment of secure exchange of NAS messages	36
4.4.2.6 Change of security keys	38
4.4.3 Handling of NAS COUNT and NAS sequence number	38
4.4.3.1 General	38
4.4.3.2 Replay protection	39
4.4.3.3 Integrity protection and verification.....	39
4.4.3.4 Cipherring and decipherring	39
4.4.3.5 NAS COUNT wrap around.....	40
4.4.4 Integrity protection of NAS signalling messages.....	40
4.4.4.1 General	40
4.4.4.2 Integrity checking of NAS signalling messages in the UE	41
4.4.4.3 Integrity checking of NAS signalling messages in the AMF	41
4.4.5 Cipherring of NAS signalling messages	43
4.4.6 Protection of initial NAS signalling messages.....	43
4.5 Unified access control	45
4.5.1 General.....	45
4.5.2 Determination of the access identities and access category associated with a request for access.....	46
4.5.3 Operator-defined access categories.....	50
4.5.4 Access control and checking.....	51
4.5.4.1 Access control and checking in 5GMM-IDLE mode.....	51
4.5.4.2 Access control and checking in 5GMM-CONNECTED mode and in 5GMM-CONNECTED mode with RRC inactive indication	52
4.5.5 Exception handling and avoiding double barring	54
4.5.6 Mapping between access categories/access identities and RRC establishment cause	57
4.6 Network slicing	58
4.6.1 General.....	58
4.6.2 Mobility management aspects.....	59
4.6.2.1 General	59

4.6.2.2	NSSAI storage.....	59
4.6.2.3	Provision of NSSAI to lower layers in 5GMM-IDLE mode.....	60
4.6.3	Session management aspects	62
4.7	NAS over non-3GPP access	62
4.7.1	General.....	62
4.7.2	5GS mobility management aspects.....	62
4.7.2.1	General	62
4.7.2.2	Establishment cause for non-3GPP access.....	63
4.7.3	5GS session management aspects.....	63
4.7.4	Limited service state over non-3GPP access	63
4.8	Interworking with E-UTRAN connected to EPC	64
4.8.1	General.....	64
4.8.2	Single-registration mode.....	64
4.8.2.1	General	64
4.8.2.2	Single-registration mode with N26 interface	64
4.8.2.3	Single-registration mode without N26 interface	64
4.8.2.3.1	Interworking between NG-RAN and E-UTRAN	64
4.8.2.3.2	Interworking between N3IWF connected to 5GCN and E-UTRAN	65
4.8.3	Dual-registration mode	66
4.8.4	Core Network selection	67
4.9	Disabling and re-enabling of UE's N1 mode capability	67
4.9.1	General.....	67
4.9.2	Disabling and re-enabling of UE's N1 mode capability for 3GPP access.....	68
4.9.3	Disabling and re-enabling of UE's N1 mode capability for non-3GPP access.....	68
4.10	Interworking with ePDG connected to EPC.....	69
4.11	UE configuration parameter updates	69
5	Elementary procedures for 5GS mobility management	69
5.1	Overview	69
5.1.1	General.....	69
5.1.2	Types of 5GMM procedures.....	69
5.1.3	5GMM sublayer states	71
5.1.3.1	General	71
5.1.3.2	5GMM sublayer states	71
5.1.3.2.1	5GMM sublayer states in the UE	71
5.1.3.2.1.1	General.....	71
5.1.3.2.1.2	Main states	71
5.1.3.2.1.2.1	5GMM-NULL.....	71
5.1.3.2.1.2.2	5GMM-DEREGISTERED.....	71
5.1.3.2.1.2.3	5GMM-REGISTERED-INITIATED	72
5.1.3.2.1.2.4	5GMM-REGISTERED	72
5.1.3.2.1.2.5	5GMM-DEREGISTERED-INITIATED.....	72
5.1.3.2.1.2.6	5GMM-SERVICE-REQUEST-INITIATED.....	72
5.1.3.2.1.3	Substates of state 5GMM-DEREGISTERED	72
5.1.3.2.1.3.1	General	72
5.1.3.2.1.3.2	5GMM-DEREGISTERED.NORMAL-SERVICE.....	72
5.1.3.2.1.3.3	5GMM-DEREGISTERED.LIMITED-SERVICE.....	72
5.1.3.2.1.3.4	5GMM-DEREGISTERED.ATTEMPTING-REGISTRATION	72
5.1.3.2.1.3.5	5GMM-DEREGISTERED.PLMN-SEARCH.....	72
5.1.3.2.1.3.6	5GMM-DEREGISTERED.NO-SUPI	73
5.1.3.2.1.3.7	5GMM-DEREGISTERED.NO-CELL-AVAILABLE.....	73
5.1.3.2.1.3.8	5GMM-DEREGISTERED.eCALL-INACTIVE.....	73
5.1.3.2.1.3.9	5GMM-DEREGISTERED.INITIAL-REGISTRATION-NEEDED	73
5.1.3.2.1.4	Substates of state 5GMM-REGISTERED	73
5.1.3.2.1.4.1	General	73
5.1.3.2.1.4.2	5GMM-REGISTERED.NORMAL-SERVICE	73
5.1.3.2.1.4.3	5GMM-REGISTERED.NON-ALLOWED-SERVICE.....	73
5.1.3.2.1.4.4	5GMM-REGISTERED.ATTEMPTING-REGISTRATION-UPDATE.....	74
5.1.3.2.1.4.5	5GMM-REGISTERED.LIMITED-SERVICE	74
5.1.3.2.1.4.6	5GMM-REGISTERED.PLMN-SEARCH	74
5.1.3.2.1.4.7	5GMM-REGISTERED.NO-CELL-AVAILABLE	74
5.1.3.2.1.4.8	5GMM-REGISTERED.UPDATE-NEEDED	74

5.1.3.2.2	5GS update status in the UE	74
5.1.3.2.3	5GMM sublayer states in the network side	75
5.1.3.2.3.1	General	75
5.1.3.2.3.2	5GMM-DEREGISTERED	75
5.1.3.2.3.3	5GMM-COMMON-PROCEDURE-INITIATED	75
5.1.3.2.3.4	5GMM-REGISTERED	75
5.1.3.2.3.5	5GMM-DEREGISTERED-INITIATED	75
5.1.4	Coordination between 5GMM and EMM	76
5.1.4.1	General	76
5.1.4.2	Coordination between 5GMM and EMM with N26 interface	76
5.1.4.3	Coordination between 5GMM and EMM without N26 interface	76
5.2	Behaviour of the UE in state 5GMM-DEREGISTERED and state 5GMM-REGISTERED	77
5.2.1	General	77
5.2.2	UE behaviour in state 5GMM-DEREGISTERED	77
5.2.2.1	General	77
5.2.2.2	Primary substate selection	77
5.2.2.2.1	Selection of the substate after power on	77
5.2.2.3	Detailed description of UE behaviour in state 5GMM-DEREGISTERED	77
5.2.2.3.1	NORMAL-SERVICE	77
5.2.2.3.2	LIMITED-SERVICE	78
5.2.2.3.3	ATTEMPTING-REGISTRATION	78
5.2.2.3.4	PLMN-SEARCH	78
5.2.2.3.5	NO-SUPI	78
5.2.2.3.6	NO-CELL-AVAILABLE	78
5.2.2.3.7	eCALL-INACTIVE	78
5.2.2.4	Substate when back to state 5GMM-DEREGISTERED from another 5GMM state	79
5.2.3	UE behaviour in state 5GMM-REGISTERED	79
5.2.3.1	General	79
5.2.3.2	Detailed description of UE behaviour in state 5GMM-REGISTERED	79
5.2.3.2.1	NORMAL-SERVICE	79
5.2.3.2.2	NON-ALLOWED-SERVICE	80
5.2.3.2.3	ATTEMPTING-REGISTRATION-UPDATE	80
5.2.3.2.4	LIMITED-SERVICE	81
5.2.3.2.5	PLMN-SEARCH	81
5.2.3.2.6	NO-CELL-AVAILABLE	81
5.3	General on elementary 5GMM procedures	81
5.3.1	5GMM modes and N1 NAS signalling connection	81
5.3.1.1	Establishment of the N1 NAS signalling connection	81
5.3.1.2	Re-establishment of the N1 NAS signalling connection	82
5.3.1.3	Release of the N1 NAS signalling connection	83
5.3.1.4	5GMM-CONNECTED mode with RRC inactive indication	86
5.3.2	Permanent identifiers	88
5.3.3	Temporary identities	88
5.3.4	Registration areas	89
5.3.5	Service area restrictions	90
5.3.6	Mobile initiated connection only mode	91
5.3.7	Handling of the periodic registration update timer and mobile reachable timer	92
5.3.8	Handling of timer T3502	94
5.3.9	Handling of NAS level mobility management congestion control	94
5.3.10	Handling of DNN based congestion control	95
5.3.11	Handling of S-NSSAI based congestion control	95
5.3.12	Handling of local emergency numbers	95
5.3.12A	Handling of local emergency numbers received via 3GPP access and non-3GPP access	96
5.3.12A.1	General	96
5.3.12A.2	Receiving a REGISTRATION ACCEPT message via non-3GPP access	97
5.3.13	Lists of 5GS forbidden tracking areas	97
5.3.14	List of equivalent PLMNs	98
5.3.15	Transmission failure abnormal case in the UE	98
5.4	5GMM common procedures	98
5.4.1	Primary authentication and key agreement procedure	98
5.4.1.1	General	98
5.4.1.2	EAP based primary authentication and key agreement procedure	98

5.4.1.2.1	General	98
5.4.1.2.2	EAP-AKA' related procedures.....	101
5.4.1.2.2.1	General.....	101
5.4.1.2.2.2	Initiation.....	101
5.4.1.2.2.3	UE successfully authenticates network	101
5.4.1.2.2.4	Errors when handling EAP-request/AKA'-challenge message	102
5.4.1.2.2.5	Network successfully authenticates UE	102
5.4.1.2.2.6	UE handling EAP-AKA' notification message	102
5.4.1.2.2.6A	EAP based Identification initiation by the network	102
5.4.1.2.2.6B	EAP based Identification response by the UE	102
5.4.1.2.2.7	Network sending EAP-success message	103
5.4.1.2.2.8	UE handling EAP-success message	103
5.4.1.2.2.9	Network not successfully authenticates UE	103
5.4.1.2.2.10	Network sending EAP-failure message	103
5.4.1.2.2.11	UE handling EAP-failure message	104
5.4.1.2.2.12	Abnormal cases in the UE.....	104
5.4.1.2.3	EAP-TLS related procedures.....	104
5.4.1.2.3.1	General.....	104
5.4.1.2.4	EAP message reliable transport procedure	106
5.4.1.2.4.1	General.....	106
5.4.1.2.4.2	EAP message reliable transport procedure initiation by the network	106
5.4.1.2.4.3	EAP message reliable transport procedure accepted by the UE.....	106
5.4.1.2.4.4	Abnormal cases on the network side.....	107
5.4.1.2.4.5	Abnormal cases in the UE.....	107
5.4.1.2.5	EAP result message transport procedure	109
5.4.1.2.5.1	General.....	109
5.4.1.2.5.2	EAP result message transport procedure initiation by the network	109
5.4.1.3	5G AKA based primary authentication and key agreement procedure	110
5.4.1.3.1	General	110
5.4.1.3.2	Authentication initiation by the network	110
5.4.1.3.3	Authentication response by the UE	111
5.4.1.3.4	Authentication completion by the network.....	111
5.4.1.3.5	Authentication not accepted by the network	112
5.4.1.3.6	Authentication not accepted by the UE	112
5.4.1.3.7	Abnormal cases	113
5.4.2	Security mode control procedure	117
5.4.2.1	General	117
5.4.2.2	NAS security mode control initiation by the network.....	117
5.4.2.3	NAS security mode command accepted by the UE.....	119
5.4.2.4	NAS security mode control completion by the network	121
5.4.2.5	NAS security mode command not accepted by the UE.....	121
5.4.2.6	Abnormal cases in the UE.....	122
5.4.2.7	Abnormal cases on the network side.....	122
5.4.3	Identification procedure	122
5.4.3.1	General	122
5.4.3.2	Identification initiation by the network	123
5.4.3.3	Identification response by the UE	123
5.4.3.4	Identification completion by the network	123
5.4.3.5	Abnormal cases in the UE.....	123
5.4.3.6	Abnormal cases on the network side.....	123
5.4.4	Generic UE configuration update procedure.....	124
5.4.4.1	General	124
5.4.4.2	Generic UE configuration update procedure initiated by the network	126
5.4.4.3	Generic UE configuration update accepted by the UE.....	127
5.4.4.4	Generic UE configuration update completion by the network	128
5.4.4.5	Abnormal cases in the UE.....	129
5.4.4.6	Abnormal cases on the network side.....	129
5.4.5	NAS transport procedure(s).....	130
5.4.5.1	General	130
5.4.5.2	UE-initiated NAS transport procedure	131
5.4.5.2.1	General	131
5.4.5.2.2	UE-initiated NAS transport procedure initiation	131

5.4.5.2.3	UE-initiated NAS transport of messages accepted by the network	133
5.4.5.2.4	UE-initiated NAS transport of messages not accepted by the network	136
5.4.5.2.5	Abnormal cases on the network side	136
5.4.5.2.6	Abnormal cases in the UE	139
5.4.5.3	Network-initiated NAS transport procedure	140
5.4.5.3.1	General	140
5.4.5.3.2	Network-initiated NAS transport procedure initiation	140
5.4.5.3.3	Network-initiated NAS transport of messages	143
5.4.6	5GMM status procedure	145
5.4.6.1	General	145
5.4.6.2	5GMM status received in the UE	145
5.4.6.3	5GMM status received in the network	146
5.5	5GMM specific procedures	146
5.5.1	Registration procedure	146
5.5.1.1	General	146
5.5.1.2	Registration procedure for initial registration	147
5.5.1.2.1	General	147
5.5.1.2.2	Initial registration initiation	147
5.5.1.2.3	5GMM common procedure initiation	150
5.5.1.2.4	Initial registration accepted by the network	150
5.5.1.2.5	Initial registration not accepted by the network	156
5.5.1.2.6	Initial registration for emergency services not accepted by the network	159
5.5.1.2.6A	Initial registration for initiating a PDU session for emergency services not accepted by the network	159
5.5.1.2.7	Abnormal cases in the UE	160
5.5.1.2.8	Abnormal cases on the network side	162
5.5.1.3	Registration procedure for mobility and periodic registration update	163
5.5.1.3.1	General	163
5.5.1.3.2	Mobility and periodic registration update initiation	163
5.5.1.3.3	5GMM common procedure initiation	168
5.5.1.3.4	Mobility and periodic registration update accepted by the network	169
5.5.1.3.5	Mobility and periodic registration update not accepted by the network	178
5.5.1.3.6	Mobility and periodic registration update for initiating an emergency PDU session not accepted by the network	181
5.5.1.3.7	Abnormal cases in the UE	181
5.5.1.3.8	Abnormal cases on the network side	184
5.5.2	De-registration procedure	185
5.5.2.1	General	185
5.5.2.2	UE-initiated de-registration procedure	186
5.5.2.2.1	UE-initiated de-registration procedure initiation	186
5.5.2.2.2	UE-initiated de-registration procedure completion	187
5.5.2.2.3	UE-initiated de-registration procedure completion for 5GS services over 3GPP access	187
5.5.2.2.4	UE-initiated de-registration procedure completion for 5GS services non-3GPP access	188
5.5.2.2.5	UE-initiated de-registration procedure completion for 5GS services over both 3GPP access and non-3GPP access	188
5.5.2.2.6	Abnormal cases in the UE	188
5.5.2.2.7	Abnormal cases in the network side	190
5.5.2.3	Network-initiated de-registration procedure	190
5.5.2.3.1	Network-initiated de-registration procedure initiation	190
5.5.2.3.2	Network-initiated de-registration procedure completion by the UE	190
5.5.2.3.3	Network-initiated de-registration procedure completion by the network	193
5.5.2.3.4	Abnormal cases in the UE	193
5.5.2.3.5	Abnormal cases in the network side	194
5.5.3	eCall inactivity procedure	194
5.6	5GMM connection management procedures	195
5.6.1	Service request procedure	195
5.6.1.1	General	195
5.6.1.2	Service request procedure initiation	197
5.6.1.3	Common procedure initiation	199
5.6.1.4	Service request procedure accepted by the network	199
5.6.1.5	Service request procedure not accepted by the network	201
5.6.1.6	Service request procedure for initiating an emergency PDU session not accepted by the network	204

5.6.1.7	Abnormal cases in the UE.....	205
5.6.1.8	Abnormal cases on the network side.....	207
5.6.2	Paging procedure	208
5.6.2.1	General.....	208
5.6.2.2	Paging for 5GS services.....	208
5.6.2.2.1	General.....	208
5.6.2.2.2	Abnormal cases on the network side.....	209
5.6.2.2.3	Abnormal cases in the UE.....	209
5.6.3	Notification procedure.....	209
5.6.3.1	General.....	209
5.6.3.2	Notification procedure initiation.....	209
5.6.3.3	Notification procedure completion.....	210
5.6.3.4	Abnormal cases on the network side.....	211
5.6.3.5	Abnormal cases on the UE side.....	211
6	Elementary procedures for 5GS session management	211
6.1	Overview.....	211
6.1.1	General.....	211
6.1.2	Types of 5GSM procedures	212
6.1.3	5GSM sublayer states	212
6.1.3.1	General.....	212
6.1.3.2	5GSM sublayer states in the UE	212
6.1.3.2.1	Overview.....	212
6.1.3.2.2	PDU SESSION INACTIVE.....	213
6.1.3.2.3	PDU SESSION ACTIVE PENDING.....	213
6.1.3.2.4	PDU SESSION ACTIVE.....	213
6.1.3.2.5	PDU SESSION INACTIVE PENDING.....	213
6.1.3.2.6	PDU SESSION MODIFICATION PENDING.....	213
6.1.3.2.7	PROCEDURE TRANSACTION INACTIVE.....	213
6.1.3.2.8	PROCEDURE TRANSACTION PENDING.....	213
6.1.3.3	5GSM sublayer states in the network side	214
6.1.3.3.1	Overview.....	214
6.1.3.3.2	PDU SESSION INACTIVE.....	214
6.1.3.3.3	PDU SESSION ACTIVE.....	214
6.1.3.3.4	PDU SESSION INACTIVE PENDING.....	214
6.1.3.3.5	PDU SESSION MODIFICATION PENDING.....	215
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE.....	215
6.1.3.3.7	PROCEDURE TRANSACTION PENDING.....	215
6.1.4	Coordination between 5GSM and ESM.....	215
6.1.4.1	Coordination between 5GSM and ESM with N26 interface	215
6.1.4.2	Coordination between 5GSM and ESM without N26 interface	222
6.2	General on elementary 5GSM procedures.....	224
6.2.1	Principles of PTI handling for 5GSM procedures.....	224
6.2.2	PDU session types	226
6.2.3	PDU session management	226
6.2.4	IP address allocation	226
6.2.4.1	General.....	226
6.2.4.2	IP address allocation via NAS signalling.....	227
6.2.5	Quality of service.....	228
6.2.5.1	General.....	228
6.2.5.1.1	QoS rules	228
6.2.5.1.1.1	General.....	228
6.2.5.1.1.2	Signalled QoS rules	228
6.2.5.1.1.3	Derived QoS rules.....	229
6.2.5.1.1.4	QoS flow descriptions.....	229
6.2.5.1.2	Session-AMBR.....	230
6.2.5.1.3	UL user data packet matching	230
6.2.5.1.4	Reflective QoS.....	230
6.2.5.1.4.1	General.....	230
6.2.5.1.4.2	Derivation of packet filter for UL direction from DL user data packet	230
6.2.5.1.4.3	Creating a derived QoS rule by reflective QoS in the UE.....	232
6.2.5.1.4.4	Updating a derived QoS rule by reflective QoS in the UE	233

6.2.5.1.4.5	Deleting a derived QoS rule in the UE	233
6.2.5.1.4.6	Ignoring RQI in the UE.....	233
6.2.6	Local area data network (LADN)	233
6.2.7	Handling of DNN based congestion control	234
6.2.8	Handling of S-NSSAI based congestion control.....	234
6.2.9	Interaction with upper layers	235
6.2.9.1	General	235
6.2.9.2	URSP.....	235
6.2.10	Handling of 3GPP PS data off	236
6.2.11	Multi-homed IPv6 PDU session	237
6.3	Network-requested 5GSM procedures	237
6.3.1	PDU session authentication and authorization procedure.....	237
6.3.1.1	General	237
6.3.1.2	PDU EAP message reliable transport procedure.....	239
6.3.1.2.1	PDU EAP message reliable transport procedure initiation.....	239
6.3.1.2.2	PDU EAP message reliable transport procedure accepted by the UE	240
6.3.1.2.3	Abnormal cases on the network side	240
6.3.1.2.4	Abnormal cases in the UE	240
6.3.1.3	PDU EAP result message transport procedure	240
6.3.1.3.1	PDU EAP result message transport procedure initiation	240
6.3.2	Network-requested PDU session modification procedure	241
6.3.2.1	General	241
6.3.2.2	Network-requested PDU session modification procedure initiation	241
6.3.2.3	Network-requested PDU session modification procedure accepted by the UE.....	243
6.3.2.4	Network-requested PDU session modification procedure not accepted by the UE.....	248
6.3.2.5	Abnormal cases on the network side	251
6.3.2.6	Abnormal cases in the UE.....	251
6.3.3	Network-requested PDU session release procedure	252
6.3.3.1	General	252
6.3.3.2	Network-requested PDU session release procedure initiation	252
6.3.3.3	Network-requested PDU session release procedure accepted by the UE.....	253
6.3.3.4	N1 SM delivery skipped.....	259
6.3.3.5	Abnormal cases on the network side	259
6.3.3.6	Abnormal cases in the UE	259
6.4	UE-requested 5GSM procedures.....	259
6.4.1	UE-requested PDU session establishment procedure	259
6.4.1.1	General	259
6.4.1.2	UE-requested PDU session establishment procedure initiation	260
6.4.1.3	UE-requested PDU session establishment procedure accepted by the network	263
6.4.1.4	UE requested PDU session establishment procedure not accepted by the network	270
6.4.1.5	Handling the maximum number of established PDU sessions.....	279
6.4.1.6	Abnormal cases in the UE.....	279
6.4.1.7	Abnormal cases on the network side.....	280
6.4.2	UE-requested PDU session modification procedure.....	280
6.4.2.1	General	280
6.4.2.2	UE-requested PDU session modification procedure initiation	281
6.4.2.3	UE-requested PDU session modification procedure accepted by the network	283
6.4.2.4	UE-requested PDU session modification procedure not accepted by the network	283
6.4.2.5	Abnormal cases in the UE.....	290
6.4.2.6	Abnormal cases on the network side.....	290
6.4.3	UE-requested PDU session release procedure	291
6.4.3.1	General	291
6.4.3.2	UE-requested PDU session release procedure initiation	291
6.4.3.3	UE-requested PDU session release procedure accepted by the network.....	292
6.4.3.4	UE-requested PDU session release procedure not accepted by the network.....	292
6.4.3.5	Abnormal cases in the UE.....	292
6.4.3.6	Abnormal cases on the network side.....	293
6.5	5GSM status procedure	293
6.5.1	General.....	293
6.5.2	5GSM status received in the UE.....	294
6.5.3	5GSM status received in the SMF	294
6.6	Miscellaneous procedures	294

6.6.1	Exchange of extended protocol configuration options.....	294
7	Handling of unknown, unforeseen, and erroneous protocol data.....	295
7.1	General.....	295
7.2	Message too short or too long.....	295
7.2.1	Message too short.....	295
7.2.2	Message too long.....	295
7.3	Unknown or unforeseen procedure transaction identity or PDU Session identity.....	295
7.3.1	Procedure transaction identity.....	295
7.3.2	PDU Session identity.....	296
7.4	Unknown or unforeseen message type.....	296
7.5	Non-semantic mandatory information element errors.....	297
7.5.1	Common procedures.....	297
7.5.2	5GS mobility management.....	297
7.5.3	5GS session management.....	297
7.6	Unknown and unforeseen IEs in the non-imperative message part.....	298
7.6.1	IEs unknown in the message.....	298
7.6.2	Out of sequence IEs.....	298
7.6.3	Repeated IEs.....	298
7.7	Non-imperative message part errors.....	298
7.7.1	Syntactically incorrect optional IEs.....	299
7.7.2	Conditional IE errors.....	299
7.8	Messages with semantically incorrect contents.....	299
8	Message functional definitions and contents.....	299
8.1	Overview.....	299
8.2	5GS mobility management messages.....	299
8.2.1	Authentication request.....	299
8.2.1.1	Message definition.....	299
8.2.1.2	Authentication parameter RAND.....	300
8.2.1.3	Authentication parameter AUTN.....	300
8.2.1.4	Void.....	300
8.2.1.5	EAP message.....	300
8.2.2	Authentication response.....	300
8.2.2.1	Message definition.....	300
8.2.2.2	Authentication response parameter.....	301
8.2.2.3	EAP message.....	301
8.2.3	Authentication result.....	301
8.2.3.1	Message definition.....	301
8.2.3.2	ABBA.....	301
8.2.4	Authentication failure.....	302
8.2.4.1	Message definition.....	302
8.2.4.2	Authentication failure parameter.....	302
8.2.5	Authentication reject.....	302
8.2.5.1	Message definition.....	302
8.2.5.2	EAP message.....	303
8.2.6	Registration request.....	303
8.2.6.1	Message definition.....	303
8.2.6.2	Non-current native NAS key set identifier.....	305
8.2.6.3	5GMM capability.....	305
8.2.6.4	UE security capability.....	305
8.2.6.5	Requested NSSAI.....	305
8.2.6.6	Last visited registered TAI.....	305
8.2.6.7	S1 UE network capability.....	305
8.2.6.8	Uplink data status.....	305
8.2.6.9	PDU session status.....	305
8.2.6.10	MICO indication.....	305
8.2.6.11	UE status.....	305
8.2.6.12	Additional GUTI.....	305
8.2.6.13	Allowed PDU session status.....	306
8.2.6.14	UE's usage setting.....	306
8.2.6.15	Requested DRX parameters.....	306

8.2.6.16	EPS NAS message container.....	306
8.2.6.17	LADN indication.....	306
8.2.6.17A	Payload container type	306
8.2.6.18	Payload container.....	306
8.2.6.19	Network slicing indication	306
8.2.6.20	5GS update type	306
8.2.6.21	NAS message container	306
8.2.6.22	EPS bearer context status	307
8.2.7	Registration accept.....	307
8.2.7.1	Message definition	307
8.2.7.2	5G-GUTI.....	310
8.2.7.3	Equivalent PLMNs.....	310
8.2.7.4	TAI list	310
8.2.7.5	Allowed NSSAI	310
8.2.7.6	Rejected NSSAI	310
8.2.7.7	Configured NSSAI.....	310
8.2.7.8	5GS network feature support.....	310
8.2.7.9	PDU session status	310
8.2.7.10	PDU session reactivation result.....	310
8.2.7.11	PDU session reactivation result error cause	310
8.2.7.12	LADN information.....	311
8.2.7.13	MICO indication	311
8.2.7.14	Network slicing indication	311
8.2.7.15	Service area list	311
8.2.7.16	T3512 value.....	311
8.2.7.17	Non-3GPP de-registration timer value	311
8.2.7.18	T3502 value.....	311
8.2.7.19	Emergency number list	311
8.2.7.20	Extended emergency number list	311
8.2.7.21	SOR transparent container	311
8.2.7.22	EAP message.....	311
8.2.7.23	NSSAI inclusion mode.....	312
8.2.7.24	Operator-defined access category definitions	312
8.2.7.25	Negotiated DRX parameters	312
8.2.7.26	Non-3GPP NW provided policies	312
8.2.7.27	EPS bearer context status	312
8.2.8	Registration complete	312
8.2.8.1	Message definition	312
8.2.8.2	SOR transparent container	312
8.2.9	Registration reject.....	313
8.2.9.1	Message definition	313
8.2.9.2	T3346 value.....	313
8.2.9.3	T3502 value.....	313
8.2.9.4	EAP message.....	313
8.2.10	UL NAS transport.....	313
8.2.10.1	Message definition	313
8.2.10.2	PDU session ID	314
8.2.10.3	Old PDU session ID	314
8.2.10.4	Request type	314
8.2.10.5	S-NSSAI	314
8.2.10.6	DNN.....	314
8.2.10.7	Additional information.....	314
8.2.11	DL NAS transport.....	315
8.2.11.1	Message definition	315
8.2.11.2	PDU session ID	315
8.2.11.3	Additional information.....	315
8.2.11.4	5GMM cause.....	315
8.2.11.5	Back-off timer value	315
8.2.12	De-registration request (UE originating de-registration)	316
8.2.12.1	Message definition	316
8.2.13	De-registration accept (UE originating de-registration).....	316
8.2.13.1	Message definition	316

8.2.14	De-registration request (UE terminated de-registration).....	316
8.2.14.1	Message definition	316
8.2.14.2	5GMM cause.....	317
8.2.14.3	T3346 value.....	317
8.2.15	De-registration accept (UE terminated de-registration).....	317
8.2.15.1	Message definition	317
8.2.16	Service request.....	318
8.2.16.1	Message definition	318
8.2.16.2	Uplink data status.....	318
8.2.16.3	PDU session status	318
8.2.16.4	Allowed PDU session status	318
8.2.16.5	NAS message container	318
8.2.17	Service accept.....	319
8.2.17.1	Message definition	319
8.2.17.2	PDU session status	319
8.2.17.3	PDU session reactivation result.....	319
8.2.17.4	PDU session reactivation result error cause	319
8.2.17.5	EAP message.....	319
8.2.18	Service reject	320
8.2.18.1	Message definition	320
8.2.18.2	PDU session status	320
8.2.18.3	T3346 value.....	320
8.2.18.4	EAP message.....	320
8.2.19	Configuration update command.....	320
8.2.19.1	Message definition	320
8.2.19.2	Configuration update indication.....	321
8.2.19.3	5G-GUTI.....	321
8.2.19.4	TAI list	321
8.2.19.5	Allowed NSSAI	321
8.2.19.6	Service area list	322
8.2.19.7	Full name for network.....	322
8.2.19.8	Short name for network.....	322
8.2.19.9	Local time zone	322
8.2.19.10	Universal time and local time zone	322
8.2.19.11	Network daylight saving time	322
8.2.19.12	LADN information.....	322
8.2.19.13	MICO indication	322
8.2.19.14	Network slicing indication	322
8.2.19.15	Configured NSSAI.....	322
8.2.19.16	Rejected NSSAI	322
8.2.19.17	Operator-defined access category definitions	322
8.2.19.18	SMS indication.....	322
8.2.20	Configuration update complete.....	323
8.2.20.1	Message definition	323
8.2.21	Identity request	323
8.2.21.1	Message definition	323
8.2.22	Identity response	323
8.2.22.1	Message definition	323
8.2.23	Notification	324
8.2.23.1	Message definition	324
8.2.24	Notification response	324
8.2.24.1	Message definition	324
8.2.24.2	PDU session status	325
8.2.25	Security mode command	325
8.2.25.1	Message definition	325
8.2.25.2	IMEISV request	326
8.2.25.3	Void.....	326
8.2.25.4	Selected EPS NAS security algorithms.....	326
8.2.25.5	Additional 5G security information	326
8.2.25.6	EAP message.....	326
8.2.25.7	ABBA	326
8.2.25.8	Replayed S1 UE security capabilities	327

8.2.26	Security mode complete.....	327
8.2.26.1	Message definition	327
8.2.26.2	IMEISV	327
8.2.26.3	NAS message container	327
8.2.27	Security mode reject	327
8.6.27.1	Message definition	327
8.2.28	Security protected 5GS NAS message.....	328
8.2.28.1	Message definition	328
8.2.29	5GMM status	328
8.2.29.1	Message definition	328
8.3	5GS session management messages.....	329
8.3.1	PDU session establishment request	329
8.3.1.1	Message definition	329
8.3.1.2	PDU session type	330
8.3.1.3	SSC mode.....	330
8.3.1.4	Maximum number of supported packet filters	330
8.3.1.5	5GSM capability	330
8.3.1.6	Void.....	330
8.3.1.7	Always-on PDU session requested	330
8.3.1.8	SM PDU DN request container.....	330
8.3.1.9	Extended protocol configuration options	330
8.3.2	PDU session establishment accept.....	330
8.3.2.1	Message definition	330
8.3.2.2	5GSM cause	331
8.3.2.3	PDU address.....	331
8.3.2.4	RQ timer value	331
8.3.2.5	S-NSSAI	331
8.3.2.6	Always-on PDU session indication.....	332
8.3.2.7	Mapped EPS bearer contexts.....	332
8.3.2.8	EAP message.....	332
8.3.2.9	Authorized QoS flow descriptions	332
8.3.2.10	Extended protocol configuration options	332
8.3.2.11	DNN.....	332
8.3.3	PDU session establishment reject	332
8.3.3.1	Message definition	332
8.3.3.2	Back-off timer value	333
8.3.3.3	Allowed SSC mode	333
8.3.3.4	EAP message.....	333
8.3.3.5	Extended protocol configuration options	333
8.3.3.6	5GSM congestion re-attempt indicator	333
8.3.4	PDU session authentication command.....	333
8.3.4.1	Message definition	333
8.3.4.2	Extended protocol configuration options	334
8.3.5	PDU session authentication complete	334
8.3.5.1	Message definition	334
8.3.5.2	Extended protocol configuration options	335
8.3.6	PDU session authentication result	335
8.3.6.1	Message definition	335
8.3.6.2	EAP message.....	335
8.3.6.3	Extended protocol configuration options	335
8.3.7	PDU session modification request	335
8.3.7.1	Message definition	335
8.3.7.2	5GSM capability	336
8.3.7.3	5GSM cause	336
8.3.7.4	Maximum number of supported packet filters	336
8.3.7.5	Always-on PDU session requested	337
8.3.7.6	Integrity protection maximum data rate	337
8.3.7.7	Requested QoS rules	337
8.3.7.8	Requested QoS flow descriptions	337
8.3.7.9	Extended protocol configuration options	337
8.3.7.10	Mapped EPS bearer contexts.....	337
8.3.8	PDU session modification reject.....	337

8.3.8.1	Message definition	337
8.3.8.2	Back-off timer value	338
8.3.8.3	Extended protocol configuration options	338
8.3.8.4	5GSM congestion re-attempt indicator	338
8.3.9	PDU session modification command	338
8.3.9.1	Message definition	338
8.3.9.2	5GSM cause	338
8.3.9.3	Session-AMBR	339
8.3.9.4	RQ timer value	339
8.3.9.5	Always-on PDU session indication	339
8.3.9.6	Authorized QoS rules	339
8.3.9.7	Mapped EPS bearer contexts	339
8.3.9.8	Authorized QoS flow descriptions	339
8.3.9.9	Extended protocol configuration options	339
8.3.10	PDU session modification complete	339
8.3.10.1	Message definition	339
8.3.10.2	Extended protocol configuration options	340
8.3.11	PDU session modification command reject	340
8.3.11.1	Message definition	340
8.3.11.2	Extended protocol configuration options	340
8.3.12	PDU session release request	341
8.3.12.1	Message definition	341
8.3.12.2	5GSM cause	341
8.3.12.3	Extended protocol configuration options	341
8.3.13	PDU session release reject	341
8.3.13.1	Message definition	341
8.3.13.2	Extended protocol configuration options	342
8.3.14	PDU session release command	342
8.3.14.1	Message definition	342
8.3.14.2	Back-off timer value	342
8.3.14.3	EAP message	343
8.3.14.4	Extended protocol configuration options	343
8.3.14.5	5GSM congestion re-attempt indicator	343
8.3.15	PDU session release complete	343
8.3.15.1	Message definition	343
8.3.15.2	5GSM cause	343
8.3.15.3	Extended protocol configuration options	343
8.3.16	5GSM status	344
8.3.16.1	Message definition	344
9	General message format and information elements coding	344
9.1	Overview	344
9.1.1	NAS message format	344
9.1.2	Field format and mapping	345
9.2	Extended protocol discriminator	345
9.3	Security header type	346
9.4	PDU session identity	346
9.5	Spare half octet	346
9.6	Procedure transaction identity	346
9.7	Message type	346
9.8	Message authentication code	348
9.9	Plain 5GS NAS message	348
9.10	Sequence number	348
9.11	Other information elements	348
9.11.1	General	348
9.11.2	Common information elements	349
9.11.2.1	Additional information	349
9.11.2.1A	DNN	349
9.11.2.2	EAP message	350
9.11.2.3	GPRS timer	350
9.11.2.4	GPRS timer 2	350
9.11.2.5	GPRS timer 3	350