

ETSI EN 319 522-3 V1.2.1 (2024-01)



Electronic Signatures and Infrastructures (ESI); Electronic Registered Delivery Services; Part 3: Formats

(<https://standards.iteh.ai>)
Document Preview

[ETSI EN 319 522-3 V1.2.1 \(2024-01\)](https://standards.iteh.ai/catalog/standards/etsi/81191b20-a851-45d1-8db3-9ef7f6dede5e/etsi-en-319-522-3-v1-2-1-2024-01)

<https://standards.iteh.ai/catalog/standards/etsi/81191b20-a851-45d1-8db3-9ef7f6dede5e/etsi-en-319-522-3-v1-2-1-2024-01>



Reference

REN/ESI-0019522-3v121

Keywordse-delivery services, registered e-delivery services,
registered electronic mail**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important noticeThe present document can be downloaded from:
<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our Coordinated Vulnerability Disclosure Program:
<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied. In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI. The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	6
3 Definition of terms, symbols and abbreviations.....	7
3.1 Terms.....	7
3.2 Symbols.....	7
3.3 Abbreviations	7
4 Metadata formats.....	7
4.1 Introduction	7
4.2 IETF RFC 5322 format	8
4.3 XML format for use in AS4 binding	8
4.3.1 Introduction.....	8
4.3.2 Namespaces used	8
4.3.3 Auxiliary elements	8
4.3.3.1 Introduction	8
4.3.3.2 URI related types	8
4.3.3.3 String related types.....	9
4.3.3.4 Container for extensibility.....	9
4.3.3.5 RelayMetadata root element.....	10
4.3.4 MessageIdentifier element	10
4.3.5 ERDMessageType element.....	11
4.3.6 InReplyTo element	11
4.3.7 RelayTime element	11
4.3.8 ExpirationTime element	11
4.3.9 ScheduledDeliveryTime element.....	11
4.3.10 SenderId element	11
4.3.11 ReplyTo element.....	12
4.3.12 RecipientId element	12
4.3.13 UserContentInfo element	12
4.3.14 RequiredAssuranceLevel element	13
4.3.15 ApplicablePolicy element	15
4.3.16 RequestedConsignmentMode element.....	15
4.3.17 Extensions element	15
4.3.18 ds:Signature element.....	16
5 Evidence and identification formats.....	16
5.1 Introduction	16
5.2 XML format	16
5.2.1 Namespaces used	16
5.2.2 Evidence format.....	16
5.2.2.1 Introduction.....	16
5.2.2.2 Auxiliary elements	17
5.2.2.2.1 Introduction	17
5.2.2.3 Evidence root element	17
5.2.2.4 EvidenceIdentifier element.....	17
5.2.2.5 ERDSEventId element.....	17
5.2.2.6 Components elements group	18
5.2.2.7 EventReasons element	18
5.2.2.8 EventTime element	19
5.2.2.9 EvidenceIssuerPolicyID element.....	19

5.2.2.10	EntityDetailsType type	19
5.2.2.11	Identity element	20
5.2.2.12	CertificateDetailsType type	20
5.2.2.13	EvidenceIssuerDetails element	22
5.2.2.14	AssuranceLevelsDetailsType type	22
5.2.2.15	UserDetailsType type	22
5.2.2.16	SenderDetails element	22
5.2.2.17	SenderDelegateDetails element	23
5.2.2.18	RecipientDetails element	23
5.2.2.19	RecipientsDelegateDetails element	23
5.2.2.20	SubmissionTime element	24
5.2.2.21	EvidenceRefersToRecipient element	24
5.2.2.22	MessageIdentifier element	24
5.2.2.23	UserContentInfo element	25
5.2.2.24	ForwardedToExternalSystem element	25
5.2.2.25	ExternalERDSDetails element	25
5.2.2.26	TransactionLogInformation element	25
5.2.2.27	Extensions element	25
5.2.2.28	ds:Signature element	26
6	Common Service Infrastructure (CSI) formats	26
6.1	Routing information	26
6.2	Trust information	26
6.3	Capability management	26
6.3.1	Recipient metadata (recipient capabilities)	26
6.3.2	ERDS metadata (ERDS capabilities)	26
Annex A (normative):	XML schema files	28
A.1	XML Schema file location for namespace http://uri.etsi.org/19522/v1#	28
Annex B (informative):	Change History	29
History		30

ETSI EN 319 522-3 V1.2.1 (2024-01)

<http://standards.etsi.org/standards/catalog/standards/etsi/81191a8b521508dd19b7e6fd5e/etsi-en-319522-3-v1-2-002>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This European Standard (EN) has been produced by ETSI Technical Committee Electronic Signatures and Infrastructures (ESI).

The present document is part 3 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.10].

National transposition dates

Date of adoption of this EN:	3 January 2024
Date of latest announcement of this EN (doa):	30 April 2024
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 October 2024
Date of withdrawal of any conflicting National Standard (dow):	31 October 2024

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document specifies the format for the semantic content (metadata, evidence, identification, and Common Service Infrastructure) that flows across the different interfaces of an Electronic Registered Delivery Service (ERDS) as defined in ETSI EN 319 522-2 [1].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI EN 319 522-2](#): "Electronic Signatures and Infrastructures (ESI); Electronic Registered Delivery Services; Part 2: Semantic contents".
- [2] W3C® Recommendation: "[XML Signature Syntax and Processing, Version 1.1, 11 April 2013](#)".
- [3] [IETF RFC 3061](#): "A URN Namespace of Object Identifiers".
- [4] CEF eIDAS Technical Sub-group: "[eIDAS SAML Attribute profile](#)". Version 1.1.2. October 2016.
- [5] OASIS: "[Assertions and Protocols for the OASIS Security Assertion Markup Language \(SAML\) V2.0](#)", March 2005.
- [6] [IETF RFC 5646](#): "Tags for Identifying Languages".
- [7] [IETF RFC 5035](#): "Enhanced Security Services (ESS) Update: Adding CertID Algorithm Agility".
- [8] OASIS: "[Service Metadata Publishing \(SMP\) Version 1.0](#)", OASIS standard, August 2017.
- [9] [ETSI EN 319 532-3](#): "Electronic Signatures and Infrastructures (ESI); Registered Electronic Mail (REM) Services; Part 3: Formats".
- [10] [ETSI EN 319 522-4-3](#): "Electronic Signatures and Infrastructures (ESI); Electronic Registered Delivery Services; Part 4: Bindings; Sub-part 3: Capability/requirements bindings".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] [Commission Implementing Regulation \(EU\) 2015/1502](#) of 8 September 2015 on setting out minimum technical specifications and procedures for assurance levels for electronic identification means pursuant to Article 8(3) of Regulation (EU) No 910/2014 of the European Parliament and of the Council on electronic identification and trust services for electronic transactions in the internal market.
- [i.2] NIST Special Publication 800-63: "Digital Identity Guidelines".
- [i.3] NIST Special Publication 800-63-A: "Digital Identity Guidelines. Enrolment and Identity Proofing Requirements".
- [i.4] NIST Special Publication 800-63-B: "Digital Identity Guidelines. Authentication and Lifecycle Management".
- [i.5] NIST Special Publication 800-63-C: "Digital Identity Guidelines. Federation and Assertions".
- [i.6] IETF RFC 5322: "Internet Message Format".
- [i.7] ETSI EN 319 132-1: "Electronic Signatures and Infrastructures (ESI); XAdES digital signatures; Part 1: Building blocks and XAdES baseline signatures".
- [i.8] IETF RFC 7522: "Security Assertion Markup Language (SAML) 2.0 Profile for OAuth 2.0 Client Authentication and Authorization Grants".
- [i.9] ETSI TS 119 612: "Electronic Signatures and Infrastructures (ESI); Trusted Lists".
- [i.10] ETSI EN 319 522-1: "Electronic Signatures and Infrastructures (ESI); Electronic Registered Delivery Services; Part 1: Framework and Architecture".
- [i.11] OASIS: "AS4 Profile of ebMS 3.0 Version 1.0, OASIS Standard", January 2013.
- [i.12] ETSI EN 319 522-4-1: "Electronic Signatures and Infrastructures (ESI); Electronic Registered Delivery Services; Part 4: Bindings; Sub-part 1: Message delivery bindings".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 319 522-1 [i.10] apply.

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI EN 319 522-1 [i.10] apply.

4 Metadata formats

4.1 Introduction

The following clause aims at providing specific formats for metadata components identified in ETSI EN 319 522-2 [1], clause 6. Clause 4.2 maps metadata components in IETF RFC 5322 format; clause 4.3 maps metadata components in AS4 format [i.6].

Other mappings can be provided by future versions of the present document or by other parties.

In clause 4.3, all XML elements are given for information only. In case of conflict with the XML Schema file whose location is detailed in clause A.1, the Schema file shall take precedence.

4.2 IETF RFC 5322 format

Specification for the **mapping of ERDS metadata** in an IETF RFC 5322 [i.6] format shall be as specified in ETSI EN 319 532-3 [9].

4.3 XML format for use in AS4 binding

4.3.1 Introduction

This clause defines an XML format for the ERDS relay metadata as defined in ETSI EN 319 522-2 [1], clause 6, which is to be included in the AS4 message that is exchanged between ERDSs. Although its primary use is in the AS4 bindings it may also be used in other bindings.

4.3.2 Namespaces used

Table 1 shows the URIs corresponding to the namespaces and the prefixes associated to them in the present document.

Table 1: Namespaces URIs and prefixes

Namespace's URI	Namespace's prefix
http://uri.etsi.org/19522/v1#	erds
http://www.w3.org/2001/XMLSchema	xs
http://www.w3.org/2000/09/xmldsig#	ds
urn:oasis:names:tc:SAML:2.0:assertion	saml

Below follows a copy of the `xs:schema` element of the XML Schema file whose location is detailed in clause A.1 and that defines the namespace whose URI is <http://uri.etsi.org/19522/v1#>:

```
<xs:schema targetNamespace="http://uri.etsi.org/19522/v1#"
xmlns:ds="http://www.w3.org/2000/09/xmldsig#" xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns="http://uri.etsi.org/19522/v1#" xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion">

  <xs:import namespace="http://www.w3.org/XML/1998/namespace"
schemaLocation="http://www.w3.org/2001/xml.xsd"/>

  <xs:import namespace="http://www.w3.org/2000/09/xmldsig#"
schemaLocation="http://www.w3.org/TR/2002/REC-xmldsig-core-20020212/xmldsig-core-schema.xsd"/>

  <xs:import namespace="urn:oasis:names:tc:SAML:2.0:assertion" schemaLocation="http://docs.oasis-
open.org/security/saml/v2.0/saml-schema-assertion-2.0.xsd"/>
```

4.3.3 Auxiliary elements

4.3.3.1 Introduction

The present clause provides details of a number of auxiliary types and elements used in throughout the XML Schema file whose location is detailed in clause A.1.

4.3.3.2 URI related types

The present clause defines a number of types whose instances' values are URIs.

These types shall be defined as in XML Schema file whose location is detailed in clause A.1 and is copied below for information:

```
<!-- targetNamespace="http://uri.etsi.org/19522/v1#" -->
```

```

<xs:simpleType name="NonEmptyURIType">
  <xs:restriction base="xs:anyURI">
    <xs:minLength value="1"/>
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="NonEmptyAttributedURIType">
  <xs:simpleContent>
    <xs:extension base="NonEmptyURIType">
      <xs:attribute ref="xml:lang" use="optional"/>
      <xs:attribute name="scheme" type="xs:string" use="optional"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

<xs:complexType name="NonEmptyMultiLangURIType">
  <xs:simpleContent>
    <xs:extension base="NonEmptyURIType">
      <xs:attribute ref="xml:lang" use="required"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

<xs:complexType name="NonEmptyMultiLangURIListType">
  <xs:sequence>
    <xs:element name="URI" type="NonEmptyMultiLangURIType maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

```

Instances of `NonEmptyURIType` type shall have a non-empty URI as value.

Instances of `NonEmptyAttributedURIType` shall have a non-empty URI as value. The `xml:lang` attribute shall identify a language using the language code as specified in IETF RFC 5646 [6]. The `scheme` attribute shall indicate the scheme for the URI value of the element.

Instances of `NonEmptyMultiLangURIType` shall have a non-empty URI as value. The `xml:lang` attribute shall identify a language using the language code as specified in IETF RFC 5646 [6].

4.3.3.3 String related types

The present clause defines a number of types whose instances' values are strings.

These types shall be defined as in XML Schema file whose location is detailed in clause A.1 and is copied below for information:

```

<!-- targetNamespace="http://uri.etsi.org/19522/v1#" -->

<xs:simpleType name="NonEmptyStringType">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
  </xs:restriction>
</xs:simpleType>

<xs:complexType name="AttributedNonEmptyStringType">
  <xs:simpleContent>
    <xs:extension base="NonEmptyStringType">
      <xs:attribute name="type" type="NonEmptyStringType" use="required"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>

```

Instances of `NonEmptyStringType` type shall have a non-empty string as value.

Instances of `NonEmptyAttributedStringType` type shall have a non-empty string as value. The `type` attribute shall indicate the type of the corresponding string value.

4.3.3.4 Container for extensibility

The present clause defines the `Any` element that may have any content.

The present clause also defines the `AnyType` type whose instances may have any content.

They are specified for serving as placeholders for contents that are not specified in the present document.

This `Any` element shall be defined as in XML Schema file whose location is detailed in clause A.1 and is copied below for information:

```
<!-- targetNamespace="http://uri.etsi.org/19522/v1#" -->
<xs:element name="Any" type="AnyType"/>
<xs:complexType name="AnyType" mixed="true">
  <xs:sequence minOccurs="0" maxOccurs="unbounded">
    <xs:any namespace="##any" processContents="lax"/>
  </xs:sequence>
  <xs:anyAttribute namespace="##any"/>
</xs:complexType>
```

4.3.3.5 RelayMetadata root element

The root element of the XML document containing the ERDS metadata shall be the `RelayMetadata` element.

This element shall be defined as in XML Schema file whose location is detailed in clause A.1 and is copied below for information:

```
<!-- targetNamespace="http://uri.etsi.org/19522/v1#" -->
<xs:element name="RelayMetadata" type="RelayMetadataType"/>
<xs:complexType name="RelayMetadataType">
  <xs:sequence>
    <xs:element ref="MessageIdentifier"/>
    <xs:element name="ERDMessageType" type="ERDSMessageTypeType"/>
    <xs:element minOccurs="0" name="InReplyTo" type="MessageIdentifierType"/>
    <xs:element minOccurs="0" name="RelayTime" type="xs:dateTime"/>
    <xs:element minOccurs="0" name="ExpirationTime" type="xs:dateTime"/>
    <xs:element minOccurs="0" name="ScheduledDeliveryTime" type="xs:dateTime"/>
    <xs:element name="SenderId" type="EntityIdentifierType"/>
    <xs:element minOccurs="0" name="ReplyTo" type="EntityIdentifierType"/>
    <xs:element name="RecipientId" type="EntityIdentifierType"/>
    <xs:element ref="UserContentInfo"/>
    <xs:element name="RequiredAssuranceLevel" type="AssuranceLevelDetailsType" minOccurs="0"/>
    <xs:element name="ApplicablePolicy" minOccurs="0" type="ERDSPolicyIDType"/>
    <xs:element name="RequestedConsignmentMode" minOccurs="0" type="ConsignmentModeType"/>
    <xs:element minOccurs="0" ref="Extensions"/>
    <xs:element minOccurs="0" ref="ds:Signature"/>
  </xs:sequence>
  <xs:attribute name="version" use="required">
    <xs:simpleType>
      <xs:restriction base="xs:string"/>
    </xs:simpleType>
  </xs:attribute>
</xs:complexType>
```

Metadata documents shall have "EN319522v1.1.1" as value for `version` attribute.

Attribute `version` shall implement the semantics specified in clause 6.2.1 of ETSI EN 319 522-2 [1].

Clauses from 4.3.4 to 4.3.18 provide XML Schema definitions and requirements on its components.

4.3.4 MessageIdentifier element

The `MessageIdentifier` element shall have the semantics of component MD11 as specified in clause 6.2.11 of ETSI EN 319 522-2 [1].

This element shall be defined as in XML Schema file whose location is detailed in clause A.1 and is copied below for information:

```
<!-- targetNamespace="http://uri.etsi.org/19522/v1#" -->
<xs:element name="MessageIdentifier" type="MessageIdentifierType"/>
<xs:simpleType name="MessageIdentifierType">
  <xs:restriction base="NonEmptyStringType"/>
</xs:simpleType>
```

```
</xs:simpleType>
```

4.3.5 ERDMessageType element

The ERDMessageType element shall have the semantics of component MD13 as specified in clause 6.2.13 of ETSI EN 319 522-2 [1].

The type of this element shall be defined as in XML Schema file whose location is detailed in clause A.1 and is copied below for information. It enumerates the ERD message types as defined in Table 1 in clause 4 of ETSI EN 319 522-2 [1]:

```
<!-- targetNamespace="http://uri.etsi.org/19522/v1#" -->

<xs:simpleType name="ERDSMessageTypeType">
  <xs:restriction base="xs:anyURI">
    <xs:enumeration value="http://uri.etsi.org/19522/v1#/ERDMessageType/dispatch"/>
    <xs:enumeration value="http://uri.etsi.org/19522/v1#/ERDMessageType/receipt"/>
    <xs:enumeration value="http://uri.etsi.org/19522/v1#/ERDMessageType/serviceInfo"/>
    <xs:enumeration value="http://uri.etsi.org/19522/v1#/ERDMessageType/payload"/>
  </xs:restriction>
</xs:simpleType>
```

4.3.6 InReplyTo element

The optional InReplyTo element shall have the semantics of component MD12 as specified in clause 6.2.12 of ETSI EN 319 522-2 [1].

The type of this element shall be a message identifier as defined by the MessageIdentifierType type definition in XML Schema file whose location is detailed in clause A.1 and is copied in clause 4.3.4 for information.

4.3.7 RelayTime element

The optional RelayTime element shall have the semantics of component MD02 as specified in clause 6.2.2 of ETSI EN 319 522-2 [1]. The 'Z' indicator for UTC may be used.

4.3.8 ExpirationTime element

The optional ExpirationTime element shall have the semantics of component MD03 as specified in clause 6.2.3 of ETSI EN 319 522-2 [1]. The 'Z' indicator for UTC may be used.

4.3.9 ScheduledDeliveryTime element

The optional ScheduledDeliveryTime element shall have the semantics of component MD07 as specified in clause 6.2.7 of ETSI EN 319 522-2 [1]. The 'Z' indicator for UTC may be used.

4.3.10 SenderId element

The SenderId element shall have the semantics of component MD08 as specified in clause 6.2.8 of ETSI EN 319 522-2 [1].

The type of this element shall be defined as in XML Schema file whose location is detailed in clause A.1 and is copied below for information:

```
<!-- targetNamespace="http://uri.etsi.org/19522/v1#" -->

<xs:complexType name="EntityIdentifierType">
  <xs:simpleContent>
    <xs:extension base="NonEmptyStringType">
      <xs:attribute name="IdentifierSchemeName" type="NonEmptyStringType" use="required"/>
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
```