

INTERNATIONAL STANDARD

NORME INTERNATIONALE

BASIC EMC PUBLICATION
PUBLICATION FONDAMENTALE EN CEM

**Electromagnetic compatibility (EMC) –
Part 4-17: Testing and measurement techniques – Ripple on d.c. input power
port immunity test**

**Compatibilité électromagnétique (CEM) –
Partie 4-17: Techniques d'essai et de mesure – Essai d'immunité à l'ondulation
résiduelle sur entrée de puissance à courant continu**

<https://standards.iteh.ai/catalog/standards/iec/5217dd61-3abd-47cf-aa2b-c4bea7cd2e05/iec-61000-4-17-1999>





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC online collection - oc.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 18 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC online collection - oc.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 000 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 16 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



IEC 61000-4-17

Edition 1.2 2009-10
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE

BASIC EMC PUBLICATION
PUBLICATION FONDAMENTALE EN CEM

**Electromagnetic compatibility (EMC) –
Part 4-17: Testing and measurement techniques – Ripple on d.c. input power
port immunity test**

**Compatibilité électromagnétique (CEM) –
Partie 4-17: Techniques d'essai et de mesure – Essai d'immunité à l'ondulation
résiduelle sur entrée de puissance à courant continu**

<https://standards.iteh.ai/catalog/standards/iec/5217dd61-3abd-47cf-aa2b-c4bea7cd2e05/iec-61000-4-17-1999>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.100.20

ISBN 978-2-8891-0385-0

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references.....	7
3 General.....	7
4 Definitions.....	7
5 Test levels and waveform.....	8
6 Test generator.....	9
6.1 Characteristics and performance of the generator.....	9
6.2 Verification of the characteristics of the generator.....	9
7 Test set-up.....	10
8 Test procedure.....	10
8.1 Laboratory reference conditions.....	10
8.1.1 Climatic conditions.....	10
8.1.2 Electromagnetic conditions.....	10
8.2 Execution of the test.....	10
9 Evaluation of test results.....	11
10 Test report.....	12
Annex A (informative) Information on the phenomenon.....	14
Figure 1 – Examples of ripple voltage waveforms.....	13
Figure A.1 – Example of generator based on a rectifier system.....	15
Figure A.2 – Example of generator based on programmable instrumentation.....	15
Table 1 – Test levels.....	8

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTROMAGNETIC COMPATIBILITY (EMC) –

Part 4-17: Testing and measurement techniques – Ripple on d.c. input power port immunity test

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendments has been prepared for user convenience.

IEC 61000-4-17 edition 1.2 contains the first edition (1999) [documents 77A/271/FDIS and 77A/280/RVD], its amendment 1 (2001) [documents 77B/291+293/FDIS and 77B/298+300/RVD] and its amendment 2 (2008) [documents 77A/632/CDV and 77A/652/RVC].

A vertical line in the margin shows where the base publication has been modified by amendments 1 and 2.

International Standard IEC 61000-4-17 has been prepared by subcommittee 77A: Low-frequency phenomena, of IEC technical committee 77: Electromagnetic compatibility.

It forms part 4-17 of IEC 61000. It has the status of a basic EMC publication in accordance with IEC Guide 107.

Annex A is for information only.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[IEC 61000-4-17:1999](#)

<https://standards.itih.ai/catalog/standards/iec/5217dd61-3abd-47cf-aa2b-c4bea7cd2e05/iec-61000-4-17-1999>

INTRODUCTION

This standard is part of the IEC 61000 series, according to the following structure:

Part 1: General

- General considerations (introduction, fundamental principles)
- Definitions, terminology

Part 2: Environment

- Description of the environment
- Classification of the environment
- Compatibility levels

Part 3: Limits

- Emission limits
- Immunity limits (in so far as they do not fall under the responsibility of the product committees)

Part 4: Testing and measurement techniques

- Measurement techniques
- Testing techniques

Part 5: Installation and mitigation guidelines

- Installation guidelines
- Mitigation methods and devices

Part 6: Generic standards

[IEC 61000-4-17:1999](https://standards.iteh.ai/catalog/standards/iec/5217dd61-3abd-47cf-aa2b-c4bea7cd2e05/iec-61000-4-17-1999)

<https://standards.iteh.ai/catalog/standards/iec/5217dd61-3abd-47cf-aa2b-c4bea7cd2e05/iec-61000-4-17-1999>

Part 9: Miscellaneous

Each part is further subdivided into several parts, published either as International Standards or technical reports, some of which have already been published as sections. Others will be published with the part number followed by a dash and a second number identifying the subdivision.

This part is an International Standard which gives test procedures related to ripple on d.c. input power port.

ELECTROMAGNETIC COMPATIBILITY (EMC) –

Part 4-17: Testing and measurement techniques – Ripple on d.c. input power port immunity test

1 Scope

This part of IEC 61000 defines test methods for immunity to ripple at the d.c. input power port of electrical or electronic equipment.

This standard is applicable to low-voltage d.c. power ports of equipment supplied by external rectifier systems, or batteries which are being charged.

The object of this standard is to establish a common and reproducible basis for testing, in a laboratory, electrical and electronic equipment when subjected to ripple voltages such as those generated by rectifier systems and/or auxiliary service battery chargers overlaying on d.c. power supply sources.

This standard defines

- test voltage waveform;
- range of test levels;
- test generator;
- test set-up;
- test procedure.

The test described hereafter applies to electrical or electronic equipment and systems. It also applies to modules or subsystems whenever the equipment under test (EUT) rated power is greater than the test generator capacity specified in clause 6.

This test does not apply to equipment connected to battery charger systems incorporating switch mode converters.

This standard does not specify the tests to be applied to particular apparatus or systems. Its main aim is to give a general basic reference to IEC product committees. These product committees (or users or manufacturers of equipment) remain responsible for the appropriate choice of the test and the severity level to be applied to their equipment.

Dedicated test procedures are in use for testing specific categories of electrical or electronic equipment, e.g. equipment connected to d.c. supply network of telephone switching centres; the related product committees should evaluate the relevance and applicability of the test procedure specified in this basic standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050(161), *International Electrotechnical Vocabulary (IEV) – Chapter 161: Electromagnetic compatibility*

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

3 General

Ripple may influence the reliable operation of equipment and systems, powered by d.c. supplies, installed in industrial plants as well in residential and commercial installations.

The ripple disturbance is represented by the voltage derived from a pulsating quantity from which the direct component has been removed.

The main sources of ripple disturbance are rectifier systems used in the external d.c. power networks and battery chargers.

Ripple is therefore a phenomenon continuously present in this type of d.c. power source, and may be accentuated when the battery is recharging after a recovery of the a.c. power line service.

Ripple components may also be produced by equipment absorbing a pulsating current; this is not covered in this standard.

4 Definitions

For the purpose of this part of IEC 61000 the following definitions apply, together with the definitions of IEC 60050(161) [IEV].

4.1

ripple content, alternating component

quantity derived by removing the direct component from a pulsating quantity (see figure 1), [IEV 161-02-25]

4.2

EUT

equipment under test

5 Test levels and waveform

The preferred range of test levels, applicable to the d.c. power supply port of the equipment, are given in table 1.

Table 1 – Test levels

Level	Percentage of the nominal d.c. voltage
1	2
2	5
3	10
4	15
x	x

NOTE "x" is an open level. This level can be given in the product specification. For the duration of the test, see 8.2.

The test levels are a peak-to-peak voltage expressed as a percentage of the nominal d.c. voltage $U_{d.c.}$.

The amplitude of the ripple voltage is represented in figure 1 by the difference $U_{max} - U_{min}$.

The frequency of the ripple is the power frequency or its multiple 2, 3 or 6, as specified by a product committee or according to the EUT manufacturer's specifications or according to the characteristics of the rectifier system (see also clause A.2).

The waveform of the ripple voltage, at the output of the test generator, has a sinusoid-linear character.

A sinusoidal-linear characteristic can be described as a part of a sine wave and a line, tangent to the decreasing side of the rectified wave, that intersects the rising edge of the following half-wave; the voltage difference between the peak value of the sine wave and the point of intersection to the following half-wave is the ripple voltage (see figure 1). The decreasing voltage can be assumed as a linear function in the presence of constant current loads. The voltage deviation, in the case of a constant resistor or constant power load, is very small and can be considered acceptable for the purpose of the test.

Deviations from the defined waveform, due to the impedance of the EUT, are allowed during the test. However, care should be taken in order to assess that the deviation from the original waveform is not caused by limitation of the generator. Furthermore, the peak-to-peak value and the frequency of ripple shall be maintained by adjustment in order to maintain the severity of the test.

The graphical representation of the waveform obtained from a single-phase bridge and a three-phase bridge rectifier is shown in figure 1; the difference $U_{max} - U_{min}$ is the percentage of the nominal d.c. voltage and corresponds to the selected test level.

NOTE Information on the phenomenon and on the selection of the test level is given in annex A, clauses A.1 and A.2.

6 Test generator

6.1 Characteristics and performance of the generator

The test generator shall be able to operate in continuous mode with the following main specifications:

- output voltage range: up to 360 V;
- output voltage change with load:
(0 to rated current) less than 5 %;
- output voltage waveform: alternating component at power frequency or its multiple, with a sinusoid-linear character, superimposed on the d.c. voltage
- output voltage tolerance: ± 10 %
- output current (steady state): up to 25 A;
- peak output current capability:
(maximum allowable duration 5 ms) +2,5/–0,5 times the steady-state current;
- ripple frequency tolerance: ± 1 %.

NOTE The 360 V output voltage value covers the test condition of a 300 V d.c. supply voltage plus a 15 % ripple corresponding to test level 4.

The use of a generator with higher or lower voltage/current capability is allowed provided that the other specifications (waveform, change with load, peak output current/steady-state current ratio, etc.) are preserved. The test generator output power/current capability shall be at least 20 % greater than the EUT power/current ratings.

The generator must be able to produce positive and negative peak current with positive voltage output.

Examples of generators can be found in clause A.3.7:1999

<https://standards.iteh.ai/catalog/standards/iec/5217dd61-3abd-47cf-aa2b-c4bea7cd2e05/iec-61000-4-17-1999>

Figure A.1 shows a schematic diagram of a generator based on a rectifier system; figure A.2 shows a schematic diagram of a generator based on a programmable power supply with controller.

6.2 Verification of the characteristics of the generator

In order to compare the test results the following characteristics of the generator shall be verified:

- the sinusoid-linear character of the ripple signal shall be maintained at maximum output voltage, with the output connected to a resistive load of 60 Ω ;
- the sinusoid-linear character of the ripple signal shall be maintained at maximum current (25 A), with the output connected to a resistive load (e.g. 2,4 Ω at output voltage of 60 V);
- the ripple frequency;
- the peak output current shall meet the requirements of 6.1, when switching the generator output from 0 V to 60 V and driving an uncharged capacitor whose value is at least 1 700 μF .

The verification of a generator with voltage/current capability less than specified in 6.1 shall be made with load conditions reflecting the rated voltage and current.

The measurement uncertainty of the instrumentation (e.g. low-frequency oscilloscope, d.c. voltmeter and a.c. peak-to-peak voltmeter) shall be less than or equal to 2 %.