

**SLOVENSKI STANDARD
SIST-TS CEN/TS 16614-1:2020****01-julij-2020****Nadomešča:
SIST-TS CEN/TS 16614-1:2014**

**Javni prevoz - Izmenjava omrežnih in voznorednih podatkov (NeTEx) - 1. del:
Izmenjavi format za topologijo omrežja javnega prevoza**

Public transport - Network and Timetable Exchange (NeTEx) - Part 1: Public transport network topology exchange format

Öffentlicher Verkehr - Netzwerk- und Fahrplan-Austausch (NeTEx) Teil 1:
Austauschformat für Netzwerk-Topologie im öffentlichen Verkehr
(standards.iteh.ai)

Transport Public - Échanges des informations planifiées (NeTEx) - Partie 1: Topologie du réseau
<https://standards.iteh.ai/catalog/standards/sist-a62fc36a-13ef-48f8-a079-6598801c4e30/sist-ts-cen-ts-16614-1-2020>

Ta slovenski standard je istoveten z: CEN/TS 16614-1:2020

ICS:

03.220.01	Transport na splošno	Transport in general
35.240.60	Uporabniške rešitve IT v prometu	IT applications in transport

SIST-TS CEN/TS 16614-1:2020 en,fr,de

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST-TS CEN/TS 16614-1:2020

<https://standards.iteh.ai/catalog/standards/sist/a62fc36a-13ef-48f8-a079-6598801c4e30/sist-ts-cen-ts-16614-1-2020>

TECHNICAL SPECIFICATION
SPÉCIFICATION TECHNIQUE
TECHNISCHE SPEZIFIKATION

CEN/TS 16614-1

April 2020

ICS 35.240.60

Supersedes CEN/TS 16614-1:2014

English Version

**Public transport - Network and Timetable Exchange
(NeTEx) - Part 1: Public transport network topology
exchange format**

Transport Public - Échanges des informations planifiées (NeTEx) - Partie 1: Topologie du réseau

Öffentlicher Verkehr - Netzwerk- und Fahrplan-Austausch (NeTEx) - Teil 1: Austauschformat für Netzwerk-Topologie im öffentlichen Verkehr

This Technical Specification (CEN/TS) was approved by CEN on 8 December 2019 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

<https://standards.iteh.ai/catalog/standards/sist-a62fc36a-13ef-48f8-a079-6598801c4e30/sist-ts-cen-ts-16614-1-2020>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

	Page
European foreword.....	6
1 Scope.....	8
1.1 General.....	8
1.2 Transport modes.....	8
1.3 Compatibility with existing standards and recommendations	8
2 Normative references.....	8
3 Terms and definitions	9
4 Symbols and abbreviations	63
5 Use Cases for Network Topology Exchange	65
5.1 Purpose.....	65
5.2 Actors and Use Case Types.....	65
5.2.1 Actors.....	65
5.2.2 Delivery Use Cases	66
5.2.3 Content Use Cases	67
5.2.4 Object Lifecycle Support Use Cases.....	69
5.2.5 Security Use Cases.....	69
5.2.6 Excluded Use Cases.....	69
5.3 Use Cases	70
5.3.1 Requirements Table.....	70
5.3.2 Collection of Use Cases	77
https://standards.iteh.ai/catalog/standards/sist/a62fc36a-13ef-48f8-a079-	
6 Generic Physical Model and XSD mapping rules.....	110
6.1 Introduction	110
6.2 Model Driven Design.....	110
6.3 Models – levels of abstraction.....	111
6.4 Open Implementation and technology use	112
6.5 Models versus Protocols.....	113
6.6 Modularisation.....	113
6.7 Summary of Modelling Approach.....	114
6.7.1 General.....	114
6.7.2 Use of packages in NeTEx models.....	115
6.8 Model transforms and Traceability.....	116
6.8.1 General.....	116
6.8.2 Conceptual Model UML Package	116
6.8.3 Physical Model UML Container Packages and Mapping from Conceptual model	116
6.8.4 XSD Model subschemas and Mapping from Physical model.....	117
6.8.5 Summary of Basic Mapping	117
6.9 Physical model to XSD schema mapping notes	118
6.10 Uniqueness of reference and Namespaces.....	119
6.11 Handling of inheritance	119
6.12 NeTEx Notation, presentation and naming conventions	119
6.12.1 General.....	119
6.12.2 Presentation of Element Names.....	120
6.12.3 Presentation of Data Type Names	120
6.12.4 Naming conventions.....	120

6.12.5	Presentation of UML Diagrams	121
6.12.6	Use of Stereotypes	122
6.12.7	Use of Colour.....	122
6.13	Mapping between models in NeTEx.....	122
6.13.1	Common Design Patterns in NeTEx.....	122
6.13.2	Mapping Example – Thing Model	123
6.13.3	Mapping Example – Handling Inheritance the SubThing Model.....	131
7	NeTEx Framework - Conceptual and Physical data model	136
7.1	Introduction.....	136
7.2	Implementing Transmodel framework features in NeTEx	137
7.3	Versions & Validity.....	138
7.3.1	Introduction.....	138
7.3.2	Version & Validity – Model Dependencies.....	138
7.3.3	Generic Entity.....	139
7.3.4	Generic Version	149
7.3.5	Implementing relationships in NeTEx	163
7.3.6	Generic Version Frame	169
7.3.7	Generic Validity	191
7.4	Responsibility	199
7.4.1	Introduction.....	199
7.4.2	Responsibility – Model Dependencies	200
7.4.3	Generic Responsibility.....	201
7.4.4	Responsibility Role	215
7.4.5	AlternativeText	223
7.4.6	Alternative Name	226
7.4.7	Generic Organisation	230
7.5	Generic Frames.....	247
7.5.1	Composite Frame	248
7.5.2	General Frame	249
7.6	Generic Framework Model.....	251
7.6.1	Generic Framework – Model Dependencies	252
7.6.2	Unit & Utility Base Types	253
7.6.3	Location.....	266
7.6.4	Generic Grouping.....	271
7.6.5	Generic Point & Link.....	280
7.6.6	Generic Section	291
7.6.7	Generic Point & Link Sequence.....	299
7.6.8	Generic Zone and Feature	305
7.6.9	Generic Projection	314
7.6.10	Generic Place	333
7.6.11	Generic Assignment	342
7.6.12	Generic Layer	345
7.6.13	Accessibility	348
7.7	Reusable Components.....	364
7.7.1	Reusable Components – Model Dependencies	364
7.7.2	Resource Frame.....	366
7.7.3	Transport Mode.....	370
7.7.4	Transport Submode	375
7.7.5	Service Calendar	380
7.7.6	Availability Condition	405
7.7.7	Topographic Place.....	409
7.7.8	Transport Organisation.....	423

7.7.9	Generic Equipment	435
7.7.10	Additional Organisations	450
7.7.11	Vehicle Type	456
7.7.12	Actual Vehicle Equipment	471
7.7.13	Vehicle Passenger Equipment	473
7.7.14	Facility	478
7.7.15	Service Restrictions	512
7.7.16	Train	520
7.7.17	Schematic Map	532
7.7.18	Notice	538
7.7.19	Security List	549
8	Part 1 – The Network Topology	555
8.1	Network Description – Model dependencies	556
8.2	Network Description – Version Frarmes	558
8.2.1	Infrastructure Frame	558
8.2.2	Service Frame	562
8.3	Network Description – Subsystem	565
8.3.1	Network Infrastructure	565
8.3.2	Activation	587
8.3.3	Vehicle & Crew Point	594
8.3.4	Lines and Routes	600
8.3.5	Line Network	637
8.3.6	Timing Pattern	646
8.3.7	Flexible Network	657
8.4	Fixed Objects – Subsystem	670
8.4.1	Fixed Objects – Model Dependencies	670
8.4.2	Site Frame	671
8.4.3	Site	675
8.4.4	Stop Place	698
8.4.5	Flexible Stop Place	735
8.4.6	Point Of Interest	741
8.4.7	Associating Equipment with Places	756
8.4.8	Equipment Description	757
8.4.9	Path Links	853
8.4.10	Navigation Paths	869
8.4.11	Check Constraint	893
8.4.12	Parking	903
8.4.13	Vehicle Stopping	924
8.4.14	Accessibility Coverage	932
8.4.15	Accessibility Coverage of Paths	933
8.5	Tactical Planning Components – Subsystem	935
8.5.1	Tactical Planning – Model Dependencies	935
8.5.2	Connections & Transfer times	936
8.5.3	Journey Pattern	950
8.5.4	Service Pattern	964
8.5.5	Common Section	989
8.5.6	Routing Constraints	993
8.5.7	Time Demand Type	999
8.5.8	Passenger Stop Assignment	1007
8.5.9	Train Stop Assignment	1015
8.5.10	Path Assignment	1021
8.5.11	Passenger Information Equipment	1025

9	NeTEx Service Interface	1032
9.1	Introduction.....	1032
9.2	Protocols versus payload.....	1033
9.3	NeTEx Publication XSD schema	1034
9.3.1	NeTEx Publication Delivery – Physical Model.....	1034
9.3.2	Publication Delivery – Attributes and XSD	1037
9.3.3	XML Examples of Publications	1044
9.4	NeTEx SIRI-NX services XSD schema	1045
9.4.1	Brief overview of SIRI communication layer.....	1047
9.4.2	SIRI ServiceRequest wrapper.....	1048
9.4.3	SIRI ServiceDelivery	1050
9.4.4	Data Object Service [SIRI-NX]	1053
9.5	Use of NeTEx with SOAP / WSDL	1059
9.5.1	Web Services	1059
9.5.2	SOAP (Simple Object Access Protocol)	1059
9.5.3	WSDL (Web Services Definition Language).....	1059
9.5.4	NeTEx WSDL	1060
Annex A (informative) Mapping with existing standards	1062	
A.1	Introduction.....	1062
A.2	VDV 452 Mapping	1066
A.3	NOPTIS Mapping	1066
A.4	NEPTUNE (Trident /Chouette profile)	1067
A.4.1	Foreword iTech STANDARD PREVIEW	1067
A.4.2	NEPTUNE.....	1067
A.4.3	NEPTUNE to NeTEx mapping information.....	1068
A.5	ERA mapping	1069
A.5.1	Foreword	1069
A.5.2	Explanation of the mapping.....	1070
A.5.3	Limitations	1071
A.6	TransXChange, NaPTAN & NPTG mappings	1072
A.6.1	Foreword	1072
A.6.2	TransXChange to NeTEx mapping information	1072
Annex B (informative) Summary of Changes	1073	
B.1.1	Introduction.....	1073
B.2	General Changes.....	1073
B.2.1	Part1 – Changes to Reusable Components.....	1074
B.2.2	Part1 – Changes to Network Description	1075
B.2.3	Part1 – Changes to Fixed Objects	1075
Bibliography	1078	

European foreword

This document (CEN/TS 16614-1:2020) has been prepared by Technical Committee CEN/TC 278 “Intelligent transport systems”, the secretariat of which is held by NEN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN/TS 16614-1:2014.

This document presents Part 1 of the Technical Specification known as “NeTEx”. NeTEx provides a framework for specifying communications and data exchange protocols for organisations wishing to exchange scheduled Information relating to public transport operations.

This Technical Specification is made up of three parts defining a single European Standard series, which provides a complete exchange format for public transport networks, timetable description and fare information.

Part 1 is the description of the public transport network topology exchange format. It also contains use cases shared with part 2, and modelling rules and the description of a framework shared by all parts.

Part 2 is the description of the scheduled timetables exchange format.

Part 3 is the description of the fare information exchange format.¹

Part 1 is fully standalone, and Parts 2 and 3 rely on Part 1.

The XML schema can be downloaded from <http://netex-cen.eu>, along with available guidance on its use, example XML files, and case studies of national and local deployments. 13ef-48f8-a079-6598801c4e30/sist-ts-cen-ts-16614-1-2020

NOTE This document is highly technical, and a special care has been taken on keeping the text readable. This has been done through a set of editorial rules enhancing usual CEN writing rules:

- To avoid confusion with usual wording, Transmodel terms are in capital letters (JOURNEY PATTERN for example).
- To avoid confusion with usual wording, attributes names are in bold/italic style and use camelcase style with no spaces (**JourneyPattern** for example).
- To avoid confusion with usual wording, attributes types are in italic style and use camelcase style with no spaces (*TypeOfEntity* for example).

This document describes the NeTEx 1.1 schema which includes corrections and enhancements to the original 1.0 schema.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

¹ Currently under development.

Introduction

Public transport services rely increasingly on information systems to ensure reliable, efficient operation and widely accessible, accurate passenger information. These systems are used for a range of specific purposes: setting schedules and timetables; managing vehicle fleets; issuing tickets and receipts; providing real-time information on service running, and so on.

This Technical Specification specifies a Network and Timetable Exchange (NeTEx) standard for Public Transport. It is intended to be used to exchange data relating to scheduled public transport between the systems of PT organisations. It can also be seen as complementary to the SIRI (Service Interface for Real-time Information) standard, as SIRI needs a prior exchange of reference data from NeTEx's scope to provide the necessary context for the subsequent exchange of real-time data.

Well-defined and open interfaces have a crucial role in improving the economic and technical viability of Public Transport Information Systems of all kinds. Using standardized interfaces, systems can be implemented as discrete pluggable modules that can be chosen from a wide variety of suppliers in a competitive market, rather than as monolithic proprietary systems from a single supplier. Interfaces also allow the systematic automated testing of each functional module, vital for managing the complexity of increasing large and dynamic systems. Furthermore, individual functional modules can be replaced or evolved, without unexpected breakages of obscurely dependent function.

This Technical Specification will improve a number of features of public transport information and service management: Interoperability – the Technical Specification will facilitate interoperability between information processing systems of the transport operators by: (i) introducing common architectures for message exchange; (ii) introducing a modular set of compatible information services for real-time vehicle information; (iii) using common data models and schemas for the messages exchanged for each service; and (iv) introducing a consistent approach to data management.

Technical advantages include the following: a modular reusing of a common communication layer shared with SIRI for all the various technical services enables cost-effective implementations, and makes the standard readily extensible in future.

1 Scope

1.1 General

NeTEx is dedicated to the exchange of scheduled data (network, timetable and fare information). It is based on Transmodel V6 (EN 12896 series) and SIRI (CEN/TS 15531-4/-5 and EN 15531-1/-2/-3) and supports the exchange of information of relevance for passenger information about public transport services and also for running Automated Vehicle Monitoring Systems (AVMS).

NOTE Many NeTEx concepts are taken directly from Transmodel; the definitions and explanation of these concepts are extracted directly from the respective standard and reused in NeTEx, sometimes with adaptions in order to fit the NeTEx context.

Although the data exchanges targeted by NeTEx are predominantly oriented towards provisioning passenger information systems and AVMS with data from transit scheduling systems, it is not restricted to this purpose and NeTEx can also provide an effective solution to many other use cases for transport data exchange.

1.2 Transport modes

All mass public transport modes are taken into account by NeTEx, including train, bus, coach, metro, tramway, ferry, and their submodes. It is possible to describe airports and air journeys, but there has not been any specific consideration of any additional requirements that apply specifically to air transport.

iTeh STANDARD PREVIEW

1.3 Compatibility with existing standards and recommendations (standards.iteh.ai)

Concepts covered in NeTEx that relate in particular to long-distance train travel include; rail operators and related organizations; stations and related equipment; journey coupling and journey parts; train composition and facilities; planned passing times; timetable versions and validity conditions.

In the case of long distance train the NeTEx takes into account the requirements formulated by the ERA (European Rail Agency) – TAP/TSI (Telematics Applications for Passenger/ Technical Specification for Interoperability, entered into force on 13 May 2011 as the Commission Regulation (EU) No 454/2011), based on UIC directives.

As regards the other exchange protocols, a formal compatibility is ensured with TransXChange (UK), VDV 452 (Germany), NEPTUNE (France), UIC Leaflet, BISON (The Netherlands) and NOPTIS (Nordic Public Transport Interface Standard).

The data exchange is possible either through dedicated web services, through data file exchanges, or using the SIRI exchange protocol as described in part 2 of the SIRI documentation.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12896 (all parts), *Public transport – Reference data model*

EN 15531-2, *Public transport - Service interface for real-time information relating to public transport operations - Part 2: Communications infrastructure*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

NOTE A lot of definitions are shared with Transmodel (EN 12896 series): special attention was paid to the consistency of definitions, keeping exactly the same wording. The italic bracket name at the beginning of the definition is a package name that will help the reader to find the related concept in the UML data model.

3.1

access

(Generic Place MODEL)

physical (spatial) possibility for a passenger to access or leave the public transport system

Note 1 to entry: This link may be used during a trip for the walking movement of a passenger from a PLACE (origin of the trip) to a STOP POINT (origin of the PT TRIP), or for the walking movement from a STOP POINT (destination of the PT TRIP) to a PLACE (destination of the trip).

3.2

access end

(Generic Place MODEL)

origin or destination end of an ACCESS link

Note 1 to entry: May indicate a MODE, POINT and PLACE

The STANDARD PREVIEW (standards.iteh.ai)

3.3

access mode

(Reusable Transport Mode MODEL) [SIST-TS CEN/TS 16614-1:2020](#)

characterisation of the passenger movement according to the means of transport different from public transport (e.g. walk, bicycle, etc.) [198801c4e30/sist-ts-cen-ts-16614-1-2020](#)

3.4

access space

(Stop Place MODEL)

passenger area within a STOP PLACE such as a concourse or booking hall, immigration hall or security area that is accessible by passengers, but without a direct access to vehicles

Note 1 to entry: Direct access to a VEHICLE is always from a QUAY and/or BOARDING POSITION.

Note 2 to entry: An ACCESS SPACE may be a Room, Hall, Concourse, Corridor, or bounded open space within a STOP PLACE.

3.5

access zone

(Site MODEL)

ZONE for which the duration to cover any ACCESS LINK to a particular STOP POINT is the same

3.6

accessibility assessment

(Accessibility MODEL)

accessibility characteristics of an entity used by passengers such as a STOP PLACE or a STOP PLACE COMPONENT

CEN/TS 16614-1:2020 (E)

Note 1 to entry: Described by ACCESSIBILITY LIMITATIONS, and/or a set of SUITABILITIES.

3.7**accessibility limitation**

(Accessibility MODEL)

categorisation of the accessibility characteristics of a SITE, e.g. a STOP PLACE or a STOP PLACE COMPONENT to indicate its usability by passengers with specific needs, for example, those needing wheelchair access, step-free access or wanting to avoid confined spaces such as lifts

Note 1 to entry: A small number of well-defined categories are used that are chosen to allow the consistent capture of data and the efficient computation of routes for different classes of user.

3.8**accommodation**

(Facility MODEL)

combination of accommodation characteristics available on a service, e.g. First Class Couchette with shower and 2 bunks

3.9**activated equipment**

(Activation MODEL)

equipment activated by the passage of a vehicle at an ACTIVATION POINT or on an ACTIVATION LINK

3.10**(standards.iteh.ai)****activation assignment**

(Activation MODEL)

SIST-TS CEN/TS 16614-1:2020

<https://standards.iteh.ai/catalog/standards/sist/a62fc36a-13ef-48f8-a079-6398801c4c50/sist-ts-cen-ts-16614-1:2020>

assignment of an ACTIVATION POINT/LINK to an ACTIVATED EQUIPMENT related on its turn to a TRAFFIC CONTROL POINT

Note 1 to entry: The considered ACTIVATION POINT/LINK will be used to influence the control process for that TRAFFIC CONTROL POINT (e.g. to fix priorities as regards the processing of competing requests from different ACTIVATION POINTs/LINKs).

3.11**activation link**

(Activation MODEL)

LINK where a control process is activated when a vehicle passes it

3.12**activation point**

(Activation MODEL)

POINT where a control process is activated when a vehicle passes it. Equipment may be needed for the activation

3.13**actual vehicle equipment**

(Actual Vehicle Equipment MODEL)

item of equipment of a particular type in an individual VEHICLE

3.14**address***(Topographic MODEL)*

address of a PLACE

3.15**administrative zone***(Generic Organisation MODEL)*

area of a district, a region, a city, a municipality, or other area with which an ORGANIZATION has a RESPONSIBILITY ROLE

3.16**allowed line direction***(Route MODEL)*

allowed DIRECTION that can be used on a given ROUTE. This can be used to validate the selection of allowed values

3.17**alternative name***(Site MODEL)*alternative name for the entity **iTeh STANDARD PREVIEW****3.18****(standards.iteh.ai)****assistance service***(Local Service Equipment MODEL)* [SIST-TS CEN/TS 16614-1:2020](#)<https://standards.iteh.ai/catalog/standards/sist/a62fc36a-13ef-48f8-a079-859880c4e50/sist-ts-16614-1-020>

specialisation of LOCAL SERVICE for ASSISTANCE providing information like language, accessibility trained staff, etc.

3.19**authority***(Transport Organisations MODEL)*

organisation under which the responsibility of organising the transport service in a certain area is placed

3.20**availability condition***(Reusable Availability MODEL)*

VALIDITY CONDITION expressed in terms of temporal parameters and referring to DAY TYPES

3.21**beacon point***(Activation MODEL)*

POINT where a beacon or similar device to support the automatic detection of vehicles passing by is located

CEN/TS 16614-1:2020 (E)**3.22****block***(Vehicle Service MODEL)*

work of a vehicle from the time it leaves a PARKING POINT after parking until its next return to park at a PARKING POINT

Note 1 to entry: Any subsequent departure from a PARKING POINT after parking marks the start of a new BLOCK. The period of a BLOCK has to be covered by DUTies

3.23**block part***(Vehicle Service MODEL)*

part of a BLOCK corresponding to the different JOURNEY PARTs of the VEHICLE JOURNEYs in a BLOCK

3.24**boarding position***(Stop Place MODEL)*

location within a QUAY from which passengers may directly board, or onto which passengers may directly alight from a VEHICLE

3.25**booking arrangements****iTeh STANDARD PREVIEW
(standards.iteh.ai)**

booking arrangements for FLEXIBLE LINE

[SIST-TS CEN/TS 16614-1:2020](#)

<https://standards.iteh.ai/catalog/standards/sist/a62fc36a-13ef-48f8-a079-6598801c4e30/sist-ts-cen-ts-16614-1-2020>

3.26**check constraint***(Check Constraint MODEL)*

characteristics of a process that takes place at a SITE COMPONENT, such as check-in, security screening, ticket control or immigration, that may potentially incur a time penalty that should be allowed for when journey planning

3.27**check constraint delay***(Check Constraint MODEL)*

time penalty associated with a CHECK CONSTRAINT

3.28**check constraint throughput***(Check Constraint MODEL)*

throughput of a CHECK CONSTRAINT: the number of passengers who can pass through it in a specified interval

3.29**class in frame***(Generic Version MODEL)*

different CLASSEs IN REPOSITORY which can be relevant for corresponding VERSION FRAMES

3.30**class in repository***(Generic Entity MODEL)*

ENTITY name belonging to the repository, e.g. DAY TYPE, PROPERTY OF DAY, TIME BAND, VEHICLE TYPE, DUTY, etc. are relevant instances of CLASS IN REPOSITORY in the context of Version Management

3.31**class of use***(Fare-Related Service Restriction MODEL)*

classification of fare and other service classes by category of user entitled to use them

3.32**common section***(Generic Point & Link MODEL)*

part of a public transport network where the ROUTEs of several JOURNEY PATTERNs are going in parallel and where the synchronisation of SERVICE JOURNEYs may be planned and controlled with respect to commonly used LINKs and STOP POINTs

Note 1 to entry: COMMON SECTIONS are defined arbitrarily and need not cover the total lengths of topologically bundled sections

3.33 iTeh STANDARD PREVIEW**communication service****(standards.iteh.ai)***(Local Commercial Service MODEL)*

specialisation of LOCAL SERVICE dedicated to communication services

<https://standards.iteh.ai/catalog/standards/sist/a62fc36a-13ef-48f8-a079-6598801c4e30/sist-ts-cen-ts-16614-1-2020>

3.34**complaints service***(Local Service Equipment MODEL)*

specialisation of CUSTOMER SERVICE for COMPLAINTs

3.35**complex feature***(Generic Zone and Feature MODEL)*

aggregate of SIMPLE FEATURES and/or other COMPLEX FEATURES; e.g. a STOP AREA: combination of STOP POINTs; a train station: combination of SIMPLE FEATURES (POINTs, LINKs) and COMPLEX FEATURES (STOP AREAs)

3.36**complex feature projection***(Generic Projection MODEL)*

oriented correspondence: from one COMPLEX FEATURE in the source layer, onto an entity in a target layer: e.g. POINT, COMPLEX FEATURE, within a defined TYPE OF PROJECTION

3.37**compound block***(Vehicle Service MODEL)*

work of a vehicle during the time it is coupled to another vehicle