



# SLOVENSKI STANDARD SIST EN IEC 62271-100:2021

01-november-2021

Nadomešča:

SIST EN 62271-100:2009

SIST EN 62271-100:2009/A1:2013

SIST EN 62271-100:2009/A2:2017

SIST EN 62271-100:2009/A2:2017/AC:2018

---

**Visokonapetostne stikalne in krmilne naprave - 100. del: Izmenični odklopniki (IEC 62271-100:2021)**

High-voltage switchgear and controlgear - Part 100: Alternating-current circuit-breakers (IEC 62271-100:2021)

Hochspannungs-Schaltgeräte und Schaltanlagen - Teil 100: Wechselstrom-Leistungsschalter (IEC 62271-100:2021)

Appareillage à haute tension - Partie 100: Disjoncteurs à courant alternatif (IEC 62271-100:2021)

**Ta slovenski standard je istoveten z: EN IEC 62271-100:2021**

---

**ICS:**

29.130.10	Visokonapetostne stikalne in krmilne naprave	High voltage switchgear and controlgear
-----------	--	---

**SIST EN IEC 62271-100:2021**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN IEC 62271-100:2021](https://standards.iteh.ai/catalog/standards/sist/0ae3eba1-3440-40ec-a282-e72458aca30e/sist-en-iec-62271-100-2021)

<https://standards.iteh.ai/catalog/standards/sist/0ae3eba1-3440-40ec-a282-e72458aca30e/sist-en-iec-62271-100-2021>

EUROPEAN STANDARD

**EN IEC 62271-100**

NORME EUROPÉENNE

EUROPÄISCHE NORM

August 2021

ICS 29.130.10

Supersedes EN 62271-100:2009 and all of its  
amendments and corrigenda (if any)

English Version

**High-voltage switchgear and controlgear - Part 100: Alternating  
current circuit-breakers  
(IEC 62271-100:2021)**Appareillage à haute tension - Partie 100: Disjoncteurs à  
courant alternatif  
(IEC 62271-100:2021)Hochspannungs-Schaltgeräte und -Schaltanlagen - Teil  
100: Wechselstrom-Leistungsschalter  
(IEC 62271-100:2021)

This European Standard was approved by CENELEC on 2021-08-11. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

[SIST EN IEC 62271-100:2021](#)

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels**

**EN IEC 62271-100:2021 (E)****European foreword**

The text of document 17A/1299/FDIS, future edition 3 of IEC 62271-100, prepared by SC 17A “Switching devices” of IEC/TC 17 “High-voltage switchgear and controlgear” was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 62271-100:2021.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2022-05-11 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2024-08-11 document have to be withdrawn

This document supersedes EN 62271-100:2009 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users’ national committee. A complete listing of these bodies can be found on the CENELEC website.

**Endorsement notice**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

The text of the International Standard IEC 62271-100:2021 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60137:2017 NOTE Harmonized as EN 60137:2017 (not modified)

IEC 62271-110 NOTE Harmonized as EN IEC 62271-110

IEC 60296 NOTE Harmonized as EN IEC 60296

IEC 60376 NOTE Harmonized as EN IEC 60376

IEC 60480 NOTE Harmonized as EN IEC 60480

## Annex ZA (normative)

### Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: [www.cenelec.eu](http://www.cenelec.eu).

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60050-151	2001	International Electrotechnical Vocabulary (IEV) - Part 151: Electrical and magnetic devices	-	-
+A1	2013			
+A2	2014			
+A3	2019			
+A4	2020			
IEC 60050-441	1984	International Electrotechnical Vocabulary (IEV) - Part 441: Switchgear, controlgear and fuses	-	-
+A1	2000			
IEC 60050-442	1998	International Electrotechnical Vocabulary (IEV) - Part 442: Electrical accessories	-	-
+A1	2015			
+A2	2015			
+A3	2019			
IEC 60050-461	2008	International Electrotechnical Vocabulary (IEV) - Part 461: Electric cables	-	-
IEC 60050-601	1985	International Electrotechnical Vocabulary (IEV) - Part 601: Generation, transmission and distribution of electricity - General	-	-
+A1	1998			
+A2	2020			
IEC 60050-614	2016	International Electrotechnical Vocabulary (IEV) - Part 614: Generation, transmission and distribution of electricity - Operation	-	-
IEC 60059	-	IEC standard current ratings	EN 60059	-
IEC 60060-1	-	High-voltage test techniques - Part 1: General definitions and test requirements	EN 60060-1	-

**EN IEC 62271-100:2021 (E)**

IEC 60255-151	2009	Measuring relays and protection equipment - Part 151: Functional requirements for over/under current protection	EN 60255-151	2009
IEC 60270	-	High-voltage test techniques - Partial discharge measurements	EN 60270	-
IEC 62271-1	2017	High-voltage switchgear and controlgear - Part 1: Common specifications for alternating current switchgear and controlgear	EN 62271-1	2017
IEC 62271-101	-	High-voltage switchgear and controlgear - Part 101: Synthetic testing	EN 62271-101	-
IEC 62271-102	2018	High-voltage switchgear and controlgear - Part 102: Alternating current disconnectors and earthing switches	EN IEC 62271-102	2018
IEC 62271-200	2021	High-voltage switchgear and controlgear - Part 200: AC metal-enclosed switchgear and controlgear for rated voltages above 1 kV and up to and including 52 kV	EN IEC 62271-200	2021
IEC 62271-203	-	High-voltage switchgear and controlgear - Part 203: Gas-insulated metal-enclosed switchgear for rated voltages above 52 kV	EN 62271-203	-

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN IEC 62271-100:2021](https://standards.iteh.ai/catalog/standards/sist/0ae3eba1-3440-40ec-a282-e72458aca30e/sist-en-iec-62271-100-2021)

<https://standards.iteh.ai/catalog/standards/sist/0ae3eba1-3440-40ec-a282-e72458aca30e/sist-en-iec-62271-100-2021>



IEC 62271-100

Edition 3.0 2021-07

# INTERNATIONAL STANDARD

# NORME INTERNATIONALE



High-voltage switchgear and controlgear –  
Part 100: Alternating-current circuit-breakers

Appareillage à haute tension –  
Partie 100: Disjoncteurs à courant alternatif

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

COMMISSION  
ELECTROTECHNIQUE  
INTERNATIONALE

ICS 29.130.10

ISBN 978-2-8322-9885-5

**Warning! Make sure that you obtained this publication from an authorized distributor.  
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

## CONTENTS

FOREWORD .....	11
1 Scope .....	13
2 Normative references .....	13
3 Terms and definitions .....	14
3.1 General terms and definitions .....	15
3.2 Assemblies .....	19
3.3 Parts of assemblies .....	19
3.4 Switching devices .....	19
3.5 Parts of circuit-breakers .....	21
3.6 Operational characteristics .....	25
3.7 Characteristic quantities .....	27
3.8 Index of definitions.....	43
4 Normal and special service conditions .....	47
5 Ratings.....	47
5.1 General.....	47
5.2 Rated voltage ( $U_r$ ) .....	48
5.3 Rated insulation level ( $U_d$ , $U_p$ , $U_s$ ) .....	48
5.4 Rated frequency ( $f_r$ ).....	48
5.5 Rated continuous current ( $I_r$ ).....	48
5.6 Rated short-time withstand current ( $I_k$ ) .....	48
5.7 Rated peak withstand current ( $I_p$ ).....	48
5.8 Rated duration of short-circuit ( $t_k$ ).....	48
5.9 Rated supply voltage of auxiliary and control circuits ( $U_a$ ) .....	48
5.10 Rated supply frequency of auxiliary and control circuits .....	48
5.11 Rated pressure of compressed gas supply for controlled pressure systems .....	48
5.101 Rated short-circuit breaking current ( $I_{SC}$ ) .....	49
5.102 Rated first-pole-to-clear factor ( $k_{pp}$ ) for terminal fault .....	52
5.103 Rated short-circuit making current .....	52
5.104 Rated operating sequence .....	52
5.105 Rated out-of-phase making and breaking current .....	52
5.106 Rated capacitive currents.....	53
6 Design and construction .....	55
6.1 Requirements for liquids .....	55
6.2 Requirements for gases .....	55
6.3 Earthing .....	55
6.4 Auxiliary and control equipment and circuits .....	56
6.5 Dependent power operation .....	56
6.6 Stored energy operation.....	56
6.7 Independent unlatched operation (independent manual or power operation) .....	56
6.8 Manually operated actuators .....	56
6.9 Operation of releases.....	56
6.10 Pressure/level indication .....	57
6.11 Nameplates.....	58



6.12	Locking devices .....	60
6.13	Position indication.....	60
6.14	Degrees of protection provided by enclosures.....	60
6.15	Creepage distances for outdoor insulators .....	60
6.16	Gas and vacuum tightness .....	60
6.17	Tightness for liquid systems.....	60
6.18	Fire hazard (flammability) .....	60
6.19	Electromagnetic compatibility (EMC).....	60
6.20	X-ray emission .....	60
6.21	Corrosion .....	60
6.22	Filling levels for insulation, switching and/or operation.....	61
6.101	Requirements for simultaneity of poles during single closing and single opening operations .....	61
6.102	General requirement for operation .....	61
6.103	Pressure limits of fluids for operation .....	61
6.104	Vent outlets .....	62
6.105	Time quantities .....	62
6.106	Mechanical loads .....	62
6.107	Circuit-breaker classification .....	63
7	Type tests .....	65
7.1	General.....	65
7.2	Dielectric tests .....	67
7.3	Radio interference voltage (RIV) test .....	72
7.4	Resistance measurement.....	72
7.5	Continuous current tests.....	73
7.6	Short-time withstand current and peak withstand current tests .....	74
7.7	Verification of the protection .....	74
7.8	Tightness tests .....	74
7.9	Electromagnetic compatibility tests (EMC) .....	74
7.10	Additional tests on auxiliary and control circuits .....	75
7.11	X-radiation test procedure for vacuum interrupters.....	75
7.101	Mechanical and environmental tests .....	75
7.102	Miscellaneous provisions for making and breaking tests .....	88
7.103	General considerations for making and breaking tests .....	106
7.104	Demonstration of arcing times.....	113
7.105	Short-circuit test quantities .....	132
7.106	Short-circuit test procedure .....	155
7.107	Terminal fault tests .....	157
7.108	Additional short-circuit tests .....	161
7.109	Short-line fault tests.....	164
7.110	Out-of-phase making and breaking tests .....	175
7.111	Capacitive current tests .....	177
7.112	Requirements for making and breaking tests on class E2 circuit-breakers having a rated voltage above 1 kV up to and including 52 kV .....	191
8	Routine tests .....	192
8.1	General.....	192
8.2	Dielectric test on the main circuit .....	193
8.3	Tests on auxiliary and control circuits .....	195

8.4	Measurement of the resistance of the main circuit.....	195
8.5	Tightness test .....	195
8.6	Design and visual checks.....	195
8.101	Mechanical operating tests .....	195
9	Guide to the selection of switchgear and controlgear (informative) .....	197
9.101	General.....	197
9.102	Selection of rated values for service conditions.....	199
9.103	Selection of rated values for fault conditions .....	201
9.104	Selection for electrical endurance in networks of rated voltage above 1 kV and up to and including 52 kV .....	205
9.105	Selection for switching of capacitive loads .....	205
10	Information to be given with enquiries, tenders and orders (informative).....	205
10.1	General.....	205
10.2	Information with enquiries and orders .....	205
10.3	Information to be given with tenders.....	206
11	Transport, storage, installation, operation instructions and maintenance.....	208
11.1	General.....	208
11.2	Conditions during transport, storage and installation.....	208
11.3	Installation .....	208
11.4	Operating instructions.....	214
11.5	Maintenance .....	214
11.101	Resistors and capacitors.....	215
12	Safety.....	215
13	Influence of the product on the environment.....	215
Annex A (normative)	Calculation of TRVs for short-line faults from rated characteristics .....	216
A.1	Basic approach .....	216
A.2	Transient voltage on line side .....	219
A.3	Transient voltage on source side .....	219
A.4	Examples of calculations.....	223
Annex B (normative)	Tolerances on test quantities during type tests.....	226
Annex C (normative)	Records and reports of type tests.....	235
C.1	Information and results to be recorded .....	235
C.2	Information to be included in type test reports.....	235
Annex D (normative)	Method of determination of the prospective TRV .....	239
D.1	General.....	239
D.2	Drawing the envelope .....	239
D.3	Determination of parameters .....	240
Annex E (normative)	Methods of determining prospective TRV waves .....	243
E.1	General.....	243
E.2	General summary of the recommended methods.....	245
E.3	Detailed consideration of the recommended methods .....	246
E.4	Comparison of methods .....	257
Annex F (informative)	Requirements for breaking of transformer-limited faults by circuit-breakers with rated voltage higher than 1 kV .....	261
F.1	General.....	261
F.2	Circuit-breakers with rated voltage less than 100 kV .....	262

F.3	Circuit-breakers with rated voltage from 100 kV to 800 kV .....	264
F.4	Circuit-breakers with rated voltage higher than 800 kV .....	264
Annex G (normative)	Use of mechanical characteristics and related requirements .....	265
Annex H (normative)	Requirements for making and breaking test procedures for metal-enclosed and dead tank circuit-breakers .....	266
H.1	General.....	266
H.2	Reduced number of making and breaking units for testing purposes .....	266
H.3	Tests for single pole in one enclosure .....	267
H.4	Tests for three poles in one enclosure .....	270
Annex I (normative)	Requirements for circuit-breakers with opening resistors .....	272
I.1	General.....	272
I.2	Switching performance to be verified .....	272
I.3	Insertion time of the resistor.....	285
I.4	Current carrying performance .....	285
I.5	Dielectric performance .....	285
I.6	Mechanical performance .....	285
I.7	Requirements for the specification of opening resistors.....	285
I.8	Examples of recovery voltage waveshapes .....	285
Annex J (normative)	Verification of capacitive current breaking in presence of single or two-phase earth faults .....	292
J.1	General.....	292
J.2	Test voltage .....	292
J.3	Test current .....	292
J.4	Test-duty .....	293
J.5	Criteria to pass the tests .....	293
Bibliography	.....	294
Figure 1	– Typical oscillogram of a three-phase short-circuit make-break cycle.....	29
Figure 2	– Circuit-breaker without switching resistors – Opening and closing operations.....	30
Figure 3	– Circuit breaker without switching resistors – Close-open cycle .....	31
Figure 4	– Circuit-breaker without switching resistors – Reclosing (auto-reclosing).....	32
Figure 5	– Circuit-breaker with switching resistors – Opening and closing operations .....	33
Figure 6	– Circuit-breaker with switching resistors – Close-open cycle.....	34
Figure 7	– Circuit-breaker with switching resistors – Reclosing (auto-reclosing).....	35
Figure 8	– Determination of short-circuit making and breaking currents, and of percentage DC component.....	50
Figure 9	– Percentage DC component in relation to the time interval from the initiation of the short-circuit for the different time constants.....	51
Figure 10	– Example of wind velocity measurement .....	82
Figure 11	– Test sequence for low temperature test.....	84
Figure 12	– Test sequence for high temperature test .....	85
Figure 13	– Humidity test.....	87
Figure 14	– Example of reference mechanical characteristics (idealised curve) .....	91
Figure 15	– Reference mechanical characteristics of Figure 14 with the envelopes centred over the reference curve (+5 %, –5 %) .....	92

Figure 16 – Reference mechanical characteristics of Figure 14 with the envelope fully displaced upward from the reference curve (+10 %, –0 %)	93
Figure 17 – Reference mechanical characteristics of Figure 14 with the envelope fully displaced downward from the reference curve (+0 %, –10 %)	93
Figure 18 – Equivalent testing set-up for unit testing of circuit-breakers with more than one separate making and breaking units	95
Figure 19 – Earthing of test circuits for single-phase short-circuit tests, $k_{pp} = 1,5$	96
Figure 20 – Earthing of test circuits for single-phase short-circuit tests, $k_{pp} = 1,3$	97
Figure 21 – Test circuit for single-phase out-of-phase tests	97
Figure 22 – Test circuit for out-of-phase tests using two voltages separated by 120 electrical degrees	98
Figure 23 – Test circuit for out-of-phase tests with one terminal of the circuit-breaker earthed (subject to agreement of the manufacturer)	98
Figure 24 – Example of prospective test TRV with four-parameter envelope which satisfies the conditions to be met during type test – Case of specified TRV with four-parameter reference line	99
Figure 25 – Example of prospective test TRV with two-parameter envelope which satisfies the conditions to be met during type test: case of specified TRV with two-parameter reference line	100
Figure 26 – Example of prospective test TRV-waves and their combined envelope in two-part test	101
Figure 27 – Earthing of test circuits for three-phase short-circuit tests, $k_{pp} = 1,5$	108
Figure 28 – Earthing of test circuits for three-phase short-circuit tests, $k_{pp} = 1,3$	109
Figure 29 – Determination of power frequency recovery voltage	111
Figure 30 – Graphical representation of the time parameters for the demonstration of arcing times in three-phase tests of test-duty T100a	114
Figure 31 – Graphical representation of an example of the three valid symmetrical breaking operations for $k_{pp} = 1,5$	115
Figure 32 – Graphical representation of the three valid symmetrical breaking operations for $k_{pp} = 1,2$ or $1,3$	116
Figure 33 – Graphical representation of an example of the three valid asymmetrical breaking operations for $k_{pp} = 1,5$	120
Figure 34 – Graphical representation of an example of the three valid asymmetrical breaking operations for $k_{pp} = 1,2$ or $1,3$	121
Figure 35 – Example of a graphical representation of the three valid symmetrical breaking operations for single-phase tests in substitution of three-phase conditions for $k_{pp} = 1,5$	125
Figure 36 – Example of a graphical representation of an example of the three valid symmetrical breaking operations for single-phase tests in substitution of three-phase conditions for $k_{pp} = 1,2$ or $1,3$	126
Figure 37 – Example of a graphical representation of an example of the three valid asymmetrical breaking operations for single-phase tests in substitution of three-phase conditions for $k_{pp} = 1,5$	128
Figure 38 – Example of a graphical representation of an example of the three valid asymmetrical breaking operations for single-phase tests in substitution of three-phase for $k_{pp} = 1,2$ and $1,3$	129

Figure 39 – Graphical representation of the arcing window and the pole factor $k_p$ , determining the TRV of the individual pole, for systems with a $k_{pp}$ of 1,2.....	131
Figure 40 – Graphical representation of the arcing window and the pole factor $k_p$ , determining the TRV of the individual pole, for systems with a $k_{pp}$ of 1,3.....	131
Figure 41 – Graphical representation of the arcing window and the pole factor $k_p$ , determining the TRV of the individual pole, for systems with a $k_{pp}$ of 1,5.....	132
Figure 42 – Representation of a specified TRV by a 4-parameter reference line and a delay line.....	135
Figure 43 – Representation of a specified TRV by a two-parameter reference line and a delay line.....	136
Figure 44 – Basic circuit for terminal fault with ITRV.....	136
Figure 45 – Representation of ITRV in relationship to TRV.....	137
Figure 46 – Example of line transient voltage with time delay with non-linear rate of rise....	151
Figure 47 – Necessity of additional single-phase tests and requirements for testing.....	162
Figure 48 – Basic circuit arrangement for short-line fault testing and prospective TRV-circuit-type a) according to 7.109.3: Source side and line side with time delay.....	166
Figure 49 – Basic circuit arrangement for short-line fault testing – circuit type b1) according to 7.109.3: Source side with ITRV and line side with time delay.....	167
Figure 50 – Basic circuit arrangement for short-line fault testing – circuit type b2) according to 7.109.3: Source side with time delay and line side without time delay.....	168
Figure 51 – Example of a line side transient voltage with time delay.....	169
Figure 52 – Flow chart for the choice of short-line fault test circuits.....	170
Figure 53 – Compensation of deficiency of the source side time delay by an increase of the excursion of the line side voltage.....	172
Figure 54 – Recovery voltage for capacitive current breaking tests.....	188
Figure 55 – Reclassification procedure for line and cable-charging current tests.....	190
Figure 56 – Reclassification procedure for capacitor bank current tests.....	191
Figure A.1 – Typical graph of line and source side TRV parameters – Line side and source side with time delay.....	218
Figure A.2 – Actual course of the source side TRV for short-line fault $L_{90}$ , $L_{75}$ and $L_{60}$ ....	221
Figure A.3 – Typical graph of line and source side TRV parameters – Line side and source side with time delay, source side with ITRV.....	222
Figure D.1 – Representation by four parameters of a prospective TRV of a circuit – Case D.2 c) 1).....	241
Figure D.2 – Representation by four parameters of a prospective TRV of a circuit – Case D.2 c) 2).....	241
Figure D.3 – Representation by four parameters of a prospective TRV of a circuit – Case D.2 c) 3) i).....	242
Figure D.4 – Representation by two parameters of a prospective TRV of a circuit – Case D.2 c) 3) ii).....	242
Figure E.1 – Effect of depression on the peak value of the TRV.....	244
Figure E.2 – Breaking with arc-voltage present.....	246
Figure E.3 – TRV in case of ideal breaking.....	247
Figure E.4 – Breaking with pronounced premature current-zero.....	247
Figure E.5 – Relationship between the values of current and TRV occurring in test and those prospective to the system.....	248

Figure E.6 – Breaking with post-arc current .....	249
Figure E.7 – Schematic diagram of power-frequency current injection apparatus .....	250
Figure E.8 – Sequence of operation of power-frequency current injection apparatus .....	251
Figure E.9 – Schematic diagram of capacitance injection apparatus .....	253
Figure E.10 – Sequence of operation of capacitor-injection apparatus .....	254
Figure F.1 – First example of transformer-limited fault (also called transformer-fed fault)....	261
Figure F.2 – Second example of transformer-limited fault (also called transformer-secondary fault) .....	262
Figure H.1 – Test configuration considered in Table H.1, Table H.2 and Table H.3 .....	268
Figure I.1 – Typical system configuration for breaking by a circuit-breaker with opening resistors .....	272
Figure I.2 – Test circuit for test-duties T60 and T100 .....	274
Figure I.3 – Test circuit for test-duties T10, T30 and OP2 .....	275
Figure I.4 – Example of an underdamped TRV for T100s(b), $U_r = 1\ 100\ \text{kV}$ , $I_{\text{SC}} = 50\ \text{kA}$ , $f_r = 50\ \text{Hz}$ .....	277
Figure I.5 – Example of an overdamped TRV for T10, $U_r = 1\ 100\ \text{kV}$ , $I_{\text{SC}} = 50\ \text{kA}$ , $f_r = 50\ \text{Hz}$ .....	278
Figure I.6 – Example of a test circuit for short-line fault test-duty $L_{90}$ .....	279
Figure I.7 – Example of real line simulation for short-line fault test-duty $L_{90}$ based on $U_r = 1\ 100\ \text{kV}$ , $I_{\text{SC}} = 50\ \text{kA}$ and $f_r = 50\ \text{Hz}$ .....	280
Figure I.8 – Typical recovery voltage waveshape of capacitive current breaking on a circuit-breaker equipped with opening resistors.....	282
Figure I.9 – Typical recovery voltage waveshape of T10 (based on $U_r = 1\ 100\ \text{kV}$ , $I_{\text{SC}} = 50\ \text{kA}$ and $f_r = 50\ \text{Hz}$ ) on the resistor switch of a circuit-breaker equipped with opening resistors.....	283
Figure I.10 – TRV waveshapes for high short-circuit current breaking operation .....	286
Figure I.11 – Currents in case of high short-circuit current breaking operation .....	287
Figure I.12 – TRV shapes for low short-circuit current breaking operation.....	288
Figure I.13 – Currents in case of low short-circuit current breaking operation.....	289
Figure I.14 – Voltage waveshapes for line-charging current breaking operation .....	290
Figure I.15 – Current waveshapes for line-charging current breaking operation .....	291
Table 1 – Preferred values of rated capacitive currents.....	54
Table 2 – Nameplate information .....	59
Table 3 – Examples of static horizontal and vertical forces for static terminal load .....	63
Table 4 – Number of mechanical operations .....	64
Table 5 – Type tests .....	66
Table 6 – Invalid tests.....	67
Table 7 – Test requirements for voltage tests as condition check for metal-enclosed circuit-breakers.....	70
Table 8 – Number of operating sequences.....	79
Table 9 – Standard values of ITRV – Rated voltages 100 kV and above .....	112

Table 10 – Last current loop parameters in three-phase tests and in single-phase tests in substitution for three-phase conditions in relation with short-circuit test-duty T100a – Tests for 50 Hz operation.....	117
Table 11 – Last current loop parameters in three-phase tests and in single-phase tests in substitution for three-phase conditions in relation with short-circuit test-duty T100a – Tests for 60 Hz operation.....	118
Table 12 – Prospective TRV parameters for single-phase tests in substitution for three-phase tests to demonstrate the breaking of the second-pole-to-clear for $k_{pp} = 1,3$ .....	122
Table 13 – Prospective TRV parameters for single-phase tests in substitution for three-phase tests to demonstrate the breaking of the third-pole-to-clear for $k_{pp} = 1,3$ .....	123
Table 14 – Standard multipliers for TRV values for second and third clearing poles .....	130
Table 15 – Arcing window for tests with symmetrical current.....	130
Table 16 – Values of prospective TRV for class S1 circuit-breakers rated for $k_{pp} = 1,5$ .....	138
Table 17 – Values of prospective TRV for class S1 circuit-breakers rated for $k_{pp} = 1,3$ .....	140
Table 18 – Values of prospective TRV for class S2 circuit-breakers rated for $k_{pp} = 1,5$ .....	142
Table 19 – Values of prospective TRV for class S2 circuit-breakers for rated for $k_{pp} = 1,3$ .	144
Table 20 – Values of prospective TRV for circuit-breakers rated for $k_{pp} = 1,2$ or $1,3$ – Rated voltages of 100 kV and above.....	147
Table 21 – Values of prospective TRV for circuit-breakers rated for $k_{pp} = 1,5$ – Rated voltages of 100 kV to 170 kV .....	149
Table 22 – Values of prospective TRV for out-of-phase tests on class S1 circuit-breakers for $k_{pp} = 2,5$ .....	152
Table 23 – Values of prospective TRV for out-of-phase tests on class S1 circuit-breakers for $k_{pp} = 2,0$ .....	153
Table 24 – Values of prospective TRV for out-of-phase tests on class S2 circuit-breakers for $k_{pp} = 2,5$ .....	153
Table 25 – Values of prospective TRV for out-of-phase tests on class S2 circuit-breakers for $k_{pp} = 2,0$ .....	154
Table 26 – Values of prospective TRV for out-of-phase tests on circuit-breakers rated for $k_{pp} = 2,5$ – Rated voltages of 100 kV to 170 kV .....	154
Table 27 – Values of prospective TRV for out-of-phase tests on circuit-breakers rated for $k_{pp} = 2,0$ – Rated voltages of 100 kV and above .....	155
Table 28 – Prospective TRV parameters for single-phase and double-earth fault tests.....	163
Table 29 – Values of line characteristics for short-line faults .....	165
Table 30 – Values of prospective TRV for the supply circuit of short-line fault tests .....	174
Table 31 – Test-duties to demonstrate the out-of-phase rating.....	176
Table 32 – Specified values of $u_1$ , $t_1$ , $u_c$ and $t_2$ .....	179
Table 33 – Common requirements for test-duties .....	181
Table 34 – Operating sequence for electrical endurance test on class E2 circuit-breakers for auto-reclosing duty.....	192
Table 35 – Application of voltage for dielectric test on the main circuit.....	193
Table 36 – Test voltage for partial discharge test.....	194
Table A.1 – Ratios of voltage-drop and source-side TRV .....	218
Table B.1 – Tolerances on test quantities for type tests .....	227