

## SLOVENSKI STANDARD SIST EN 16657:2016+A1:2018

**01-november-2018** 

Nadomešča:

SIST EN 16657:2016

Cisterne za prevoz nevarnega blaga - Oprema cistern za preprečitev prepolnitve nepremičnih rezervoarjev (vključno z dopolnilom A1)

Tanks for the transport of dangerous goods - Transport tank equipment for overfill prevention devices for static tanks

Tanks für die Beförderung gefährlicher Güter - Transporttankausrüstung für Überfüllsicherungen für ortsfeste Tanks (standards.iteh.ai)

Citernes destinées au transport de matières dangereuses - Dispositifs limiteurs de remplissage pour réservoirs statiques à bord de véhicules citernes da 12 d995560/sist-en-16657-2016a1-2018

Ta slovenski standard je istoveten z: EN 16657:2016+A1:2018

ICS:

13.300 Varstvo pred nevarnimi Protection against dangerous

delki goods

23.020.20 Posode in vsebniki, montirani Vessels and containers

na vozila mounted on vehicles

SIST EN 16657:2016+A1:2018 en,fr,de

SIST EN 16657:2016+A1:2018

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST EN 16657:2016+A1:2018</u> https://standards.iteh.ai/catalog/standards/sist/10f12628-6f52-4f2e-a2aa-da1f2d995560/sist-en-16657-2016a1-2018 EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM EN 16657:2016+A1

June 2018

ICS 13.300; 23.020.10; 23.020.20; 75.200

Supersedes EN 16657:2016

#### **English Version**

# Tanks for the transport of dangerous goods - Transport tank equipment for overfill prevention devices for static tanks

Citernes destinées au transport de matières dangereuses - Dispositifs limiteurs de remplissage pour réservoirs statiques à bord de véhicules-citernes Tanks für die Beförderung gefährlicher Güter -Transporttankausrüstung für Überfüllsicherungen für ortsfeste Tanks

This European Standard was approved by CEN on 6 June 2015 and includes Amendment 1 approved by CEN on 28 December 2017.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greede, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents		Page
Europ	European foreword3	
1	Scope	5
2	Normative references	5
3	Terms, definitions and abbreviated terms	5
3.1	Terms and definitions	
3.2	Abbreviated terms	6
4	Requirements	6
4.1	Effectiveness	6
4.2	Construction	6
5	Overfill prevention device	
5.1	Equipment on the tank	6
5.2	Equipment on the tank vehicle	
5.3	EMC requirements	
5.4 5.4.1	Working characteristics	
5.4.1 5.4.2	General Response time Teh STANDARD PREVIEW	
5.4.3	Current interface	7
5.4.4	Current interface (Standards.iteh.ai)	9
5.4.5	Current interface - Auxiliary contact	10
5.4.6	Binary/Digital InterfaceSIST.EN 16657:2016±A1:2018	11
6	Test https://standards.iteh.ai/catalog/standards/sist/10f12628-6f52-4f2e-a2aa- Tart da112d995560/sist-en-16657-2016a1-2018	11
6.1	Type test	11
6.1.1	General	11
6.1.2	Performance tests - controller	
6.1.3	Fail-safe test	
6.1.4	EMC test	
6.2	Manufacturers production test	
6.2.1	General	
6.2.2 6.2.3	Controller response	
6.2.3	Current interfaceBinary/Digital interface	
6.3.1	General	
6.3.2	Sensor and digital interface	
6.3.3	PRD	
7	Marking	
	A. TANK TATAN M. CO. CO. CO. CO. CO. CO. CO. CO. CO. CO	

### **European foreword**

This document (EN 16657:2016+A1:2018) has been prepared by Technical Committee CEN/TC 296 "Tanks for the transport of dangerous goods", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2018, and conflicting national standards shall be withdrawn at the latest by December 2018.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document includes Amendment 1 approved by CEN on 28 December 2017.

This document A supersedes EN 16657:2016 (A).

The start and finish of text introduced or altered by amendment is indicated in the text by tags  $\boxed{\mathbb{A}}$ 

My With reference to EN 13616:2004, the following significant changes were made in EN 16657:2016 when it superseded it: (41)

- splitting of EN 13616:2004; the new EN 13616, under the general title Overfill prevention devices for static tanks for liquid fuels Requirements and test/assessment methods, will consist of the following parts:
  - Part 1: Overfill prevention devices with closure device;
  - https://standards.iteh.ai/catalog/standards/sist/10f12628-6t52-4tz
     Part 2: Overfill prevention devices without closure device;
- reference to EN 14116;
- explosion-technical parameters updated;
- the requirements for the equipment of the overfill prevention devices without closure device on the static tank are fixed in EN 13616-2;
- the requirements for the equipment of the overfill prevention devices without closure device on the tank vehicle are fixed in EN 16657.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

A1) deleted text (A1

SIST EN 16657:2016+A1:2018 https://standards.iteh.ai/catalog/standards/sist/10f12628-6f52-4f2e-a2aa-da1f2d995560/sist-en-16657-2016a1-2018

#### 1 Scope

This European Standard specifies the minimum performance and construction requirements for overfill prevention controllers located on the tank vehicle.

This European Standard applies to overfill prevention controllers for liquid fuels, having a flash point up to but not exceeding  $100\,^{\circ}\text{C}$ .

The requirements apply to overfill prevention controllers suitable for use at ambient temperatures in the range from -25 °C to +60 °C, and subject to normal operational pressure variations.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13616-2:2016, Overfill prevention devices for static tanks for liquid fuels — Part 2: Overfill prevention devices without a closure device

EN 14116, Tanks for transport of dangerous goods — Digital interface for the product recognition devices for liquid fuels

EN 60079-0, Explosive atmospheres — Part 0: Equipment — General requirements (IEC 60079-0, modified) **Teh STANDARD PREVIEW** 

EN 60079-11, Explosive atmospheres Part 11: Equipment protection by intrinsic safety "i" (IEC 60079-11)

SIST EN 16657:2016+A1:2018
EN 61000-6-1, Electromagnetic compatibility (EMC) To Part 6-1: Generic standards — Immunity for residential, commercial and light-industrial environments (IEC 61000-6-1)

EN 61000-6-3, Electromagnetic compatibility (EMC) — Part 6-3: Generic standards — Emission standard for residential, commercial and light-industrial environments (IEC 61000-6-3)

EN ISO 13849-1, Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design (ISO 13849-1)

ISO 7637-2, Road vehicles — Electrical disturbances from conduction and coupling — Part 2: Electrical transient conduction along supply lines only

#### 3 Terms, definitions and abbreviated terms

For the purposes of this document, the terms, definitions and abbreviated terms given in EN 13616-2 and the following apply.

#### 3.1 Terms and definitions

#### 3.1.1

# overfill prevention controller controller

installed on the tank vehicle, connects to sensors mounted in or on the tank, and provides an output

#### 3.2 Abbreviated terms

**PRD Product Recognition Device** 

#### Requirements

#### 4.1 Effectiveness

The filling process shall not start or shall automatically stop in the event of failure of the power supply.

Detection of a sensor's signal "non-permissive" shall result in a shut-down of the product flow by the controller.

Stopping the product flow shall not generate pressure in excess of the designed criteria for the whole system.

#### 4.2 Construction

The design shall be compatible with the ambient temperature range of -25 °C to +60 °C. The manufacturer shall confirm the compatibility of materials, which may be in contact with the liquid and/or its vapour phase.

If the controller forms part of an earth continuity path, then the conductivity of the path shall be  $< 10^{6} \Omega$ .

The controller shall be of a durable construction. DARD PREVIEW

The selection of materials and manufacturing processes shall consider environmental aspects.

#### 5 Overfill prevention device

SIST EN 16657:2016+A1:2018

### **5.1 Equipment on the tank** that standards.iteh.ai/catalog/standards/sist/10f12628-6f52-4f2e-a2aada1f2d995560/sist-en-16657-2016a1-2018

A sensor with mechanical interface shall be according to EN 13616-2.

#### 5.2 Equipment on the tank vehicle

The following equipment shall be on the tank-vehicle:

one or more controllers:

The controller shall provide:

- interface up to the maximum specified number of sensors;
- permissive/non-permissive output states.
- product supply system;
- appropriate devices for stopping the product flow;
- a connection between the controller and the sensor fitted with a socket according to Figure 1.

#### **5.3 EMC requirements**

The controller shall comply with:

EN 61000-6-3 for emission:

EN 61000-6-1 for immunity.

Furthermore, the controller shall be suitable for safe operation at the power supply of the tank vehicle. Disturbances according to ISO 7637-2 (pulse 2a, 2b, 3a, 3b and 4) shall not lead to malfunction.

#### 5.4 Working characteristics

#### 5.4.1 General

Upon the detection of a sensor's signal "non-permissive", the controller shall provide a signal which causes the appropriate devices to stop the product flow, to prevent an overfill. A device shall be provided to indicate that the maximum filling level has been reached.

The overfill prevention device shall include an interface to ensure the safe working function and self-checking.

Power supply interruption or short circuit may be indicated.

#### 5.4.2 Response time

- Sensor detection of the liquid to controller output as summary of two reaction times from status permissive to status non-permissive: maximum 2,5 s;
  - reaction time of the sensor ( $\Delta t_R$ ) from status permissive to status non-permissive: maximum 1,5 s according to EN 13616-2;
  - controller reaction time from permissive to non-permissive: maximum 1 s;
- controller output to the ceasing of product flow: maximum 3 s.

The maximum time from the detection of the liquid to the ceasing of product flow shall be 5,5 s.

#### **5.4.3** Current interface

da1f2d995560/sist-en-16657-2016a1-2018

#### 5.4.3.1 Socket

The socket of the plug/socket connection between the controller and the sensor shall be according to Figure 1.

Both socket types can be connected to plug type 907, type AS 907, type 904 or type 905 according to EN 13616-2. However, the types AS of sockets and plugs provide listener and grounding connection.