



Designation: D5871 – 08

Standard Specification for Benzene for Cyclohexane Feedstock¹

This standard is issued under the fixed designation D5871; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers benzene for cyclohexane feedstock.

1.2 The following applies to all specified limits in this standard: for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.3 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.4 Consult current OSHA regulations supplier’s Material Safety Data Sheets for all materials used in this specification.

2. Referenced Documents

2.1 ASTM Standards:²

D848 Test Method for Acid Wash Color of Industrial Aromatic Hydrocarbons

D852 Test Method for Solidification Point of Benzene

D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)

D1685 Test Method for Traces of Thiophene in Benzene by Spectrophotometry

D3437 Practice for Sampling and Handling Liquid Cyclic Products

D4017 Test Method for Water in Paints and Paint Materials by Karl Fischer Method

D4492 Test Method for Analysis of Benzene by Gas Chromatography

D4735 Test Method for Determination of Trace Thiophene in Refined Benzene by Gas Chromatography

D5386 Test Method for Color of Liquids Using Tristimulus Colorimetry

D5713 Test Method for Analysis of High Purity Benzene for Cyclohexane Feedstock by Capillary Gas Chromatography

D6875 Test Method for Solidification Point of Industrial Organic Chemicals by Thermistor

D7011 Test Method for Determination of Trace Thiophene in Refined Benzene by Gas Chromatography and Sulfur Selective Detection

D7183 Test Method for Determination of Total Sulfur in Aromatic Hydrocarbons and Related Chemicals by Ultra-violet Fluorescence

D7375 Test Method for Trace Quantities of Water in Aromatic Hydrocarbons and Their Mixtures by Coulometric Karl Fischer Titration

E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

2.2 Other Document:

OSHA Regulations, 29 CFR paragraphs 1910.1000 and 1910.1200³

3. Properties

3.1 Benzene for Cyclohexane Feedstock shall conform to the following requirements:

Property	Specification	ASTM Test Method ⁴
Benzene, min, weight %	99.90	D5713 or D4492
Sulfur, max, mg/kg	1.0	D7183
Thiophene, max, mg/kg	0.6	D1685, D4735 or D7011
Toluene plus methylcyclohexane max, mg/kg	150	D5713
Methylcyclopentane, max mg/kg	100	D5713
N-hexane, max, mg/kg	80	D5713
Acid wash color, max	pass with 1	D848
Appearance	B	...
Color, max, Pt-Co scale	10	D1209 or D5386
Water	(if needed)	D4017 or D7375
Solidification point, anhydrous basis, min, ^o C	5.45	D852 or D6875

⁴ If more than one method is listed for a property the producer and user should agree on the referee method.

^B Clear liquid free of sediment and haze when observed at 18.3 to 25.6°C (65 to 78°F).

³ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, http://www.access.gpo.gov.

*A Summary of Changes section appears at the end of this standard.