INTERNATIONAL STANDARD

Second edition 2019-01

Geographic information — Metadata —

Part 2: Extensions for acquisition and processing

iTeh STInformation géographique — Métadoanées — Partie 2: Extensions pour l'acquisition et le traitement

ISO 19115-2:2019 https://standards.iteh.ai/catalog/standards/sist/5917e4fd-b266-40b5-965efb379eed60db/iso-19115-2-2019



Reference number ISO 19115-2:2019(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 19115-2:2019</u> https://standards.iteh.ai/catalog/standards/sist/5917e4fd-b266-40b5-965efb379eed60db/iso-19115-2-2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Fax: +41 22 749 09 47 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Page

Contents

| Foreword Introduction | | | iv |
|--|-----------------------------|---|---|
| | | | v |
| 1 | Scope | | |
| 2 | Norma | ative references | |
| 3 | Terms | and definitions | |
| 4 | Symbo 4.1 | ols and abbreviated terms Abbreviated terms | 4 4 |
| 5 | Confo 5.1 5.2 | r mance Conformance requirements Metadata profiles | |
| 6 | Acquis 6.1 6.2 6.3 | sition and processing metadataMetadata for acquisition and processing requirementsAcquisition and processing metadata packages and dependenciesAcquisition and processing metadata class diagrams by package6.3.1Introduction6.3.2Acquisition Information6.3.3Extended Lineage information6.3.4Extended spatial representation information — Geolocation information6.3.5Extended Content information — Imagery | 5 5 6 6 7 10 11 13 |
| Annex A (normative) Conformance and arcassing metadata data distingary | | | |
| Annex Biblio | C (info graphy | rmative) XML schema implementation 9 https://standards.iteh.ai/catalog/standards/sist/5917e4fd-b266-40b5-965e- fb379eed60db/iso=19115-2=2019 | |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html. (standards.iteh.ai)

This document was prepared by ISO/TC 211, *Geographic information/Geomatics*.

This second edition cancels and replaces the first edition (4SO/191715 22009)) which has been technically revised. fb379eed60db/iso-19115-2-2019

The following is a summary of major changes to this document during the revision process:

- The name and scope were changed to better describe the purpose of the document;
- QE_CoverageResult and QE_Useability were moved to ISO 19157;
- All extended classes now extend ISO 19115-1:2014;
- Whereas the XML Schema encoding for ISO 19115-2:2009 was provided in ISO/TS 19139-2; the link and information about the XML schema for this revision is provided in <u>Annex C</u> of this document;
- A specified class of MI_Instrument MI_Sensor was defined. A list of all the parts in the ISO 19115 series, can be found on the ISO website.

Introduction

This document replaces the previous edition (ISO 19115-2:2009) *Geographic information* — *Metadata* — *Extension for imagery and gridded data*, which focused on metadata for imagery and gridded data as they are important information sources and products used within a geospatial environment by geographic information systems. During the revision process it was noted that this metadata applied to the acquisition and processing of geographic information from all sources not just imagery and gridded data. Hence, the new title *Geographic information* — *Metadata* — *Extensions for acquisition and processing*. The production of all geographic information, including imagery and gridded data, follows one or more process chains that begins with remote sensing data, scanned maps, field data collection or other sensing methods and ends with the creation of the end data products. In addition, metadata about the geometry of the measuring process and the properties of the measuring equipment need to be retained with the raw data to support the production process.

The object of this document is to provide the additional structure needed to more extensively describe the acquisition and processing of geographic information from all sources. This structure is intended to augment ISO 19115-1. This document also provides an XML schema for implementing this document using ISO/TS 19115-3.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 19115-2:2019 https://standards.iteh.ai/catalog/standards/sist/5917e4fd-b266-40b5-965efb379eed60db/iso-19115-2-2019

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 19115-2:2019 https://standards.iteh.ai/catalog/standards/sist/5917e4fd-b266-40b5-965efb379eed60db/iso-19115-2-2019

Geographic information — Metadata —

Part 2: **Extensions for acquisition and processing**

1 Scope

This document extends ISO 19115-1:2014 by defining the schema required for an enhanced description of the acquisition and processing of geographic information, including imagery. Included are the properties of measuring systems and the numerical methods and computational procedures used to derive geographic information from the data acquired by them. This document also provides the XML encoding for acquisition and processing metadata thereby extending the XML schemas defined in ISO/ TS 19115-3.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19103:2015, Geographic information - Conceptual schema language

ISO 19115-1:2014, Geographic information — Metadata — Part 1: Fundamentals

<u>ISO 19115-2:2019</u>

ISO 19157:2013, Geographic information log/Data quality 917e4fd-b266-40b5-965efb379eed60db/iso-19115-2-2019

ISO/IEC 19501:2005, Information technology — Open Distributed Processing — Unified Modeling Language (UML) Version 1.4.2

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 19115-1:2014 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at <u>https://www.electropedia.org/</u>

— ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>

3.1

attribute named property of an entity

Note 1 to entry: Describes a geometrical, topological, thematic, or other characteristic of an entity.

[SOURCE: ISO/IEC 2382:2015, 2121440, modified — Note 1 to entry replaces Notes 1 and 2 to entry.]

3.2 band

range of wavelengths of electromagnetic radiation that produce a single response by a sensing device

[SOURCE: ISO/TS 19101-2:2008, 4.1]

3.3

class

description of a set of objects that share the same *attributes* (<u>3.1</u>), operations, methods, relationships, and semantics

[SOURCE: ISO 19103:2015, 4.7]

3.4

coverage

feature that acts as a function to return *values* (3.29) from its range for any direct position within its spatial, temporal or spatiotemporal *domain* (3.8)

EXAMPLE Raster *image* (3.18), polygon overlay, or digital elevation matrix.

[SOURCE: ISO 19123:2005, 4.1.7, modified — NOTE deleted.]

3.5

data type

specification of a value domain (3.30) with operations allowed on values (3.29) in this domain (3.8)

[SOURCE: ISO 19103:2015, 4.14, modified — EXAMPLE and Note 1 to entry deleted.]

3.6

3.7

dataset identifiable collection of data

[SOURCE: ISO 19115-1:2014, 4.3, modified - Note 1 to entry deleted:] V F.W

(standards.iteh.ai)

dataset series

collection of *datasets* (3.6) sharing common characteristics

[SOURCE: ISO 19115-1:2014;194:4]^{tandards.iteh.ai/catalog/standards/sist/5917e4fd-b266-40b5-965efb379eed60db/iso-19115-2-2019}

3.8

domain well-defined set

[SOURCE: ISO 19109:2015, 4.8, modified — Note 1 to entry deleted.]

3.9 event action which occurs at an instant

[SOURCE: ISO 19108:2002, 4.1.6]

3.10

geolocation information

information used to determine geographic location corresponding to *image* (3.18) location

3.11

georectified

corrected for positional displacement with respect to the surface of the Earth

3.12

georeferencing

geopositioning an object using a Correspondence Model derived from a set of points for which both ground and *image* (3.18) coordinates are known

[SOURCE: ISO/TS 19130:2010, 4.37]

3.13

grid

network composed of two or more sets of curves in which the members of each set intersect the members of the other sets in an algorithmic way

Note 1 to entry: The curves partition a space into grid cells.

[SOURCE: ISO 19123:2005, 4.1.23]

3.14

grid coordinate system

coordinate system in which a position is specified relative to the intersection of curves

3.15

grid coordinates

sequence of two or more numbers specifying a position with respect to its location on a grid (3.13)

3.16

gridded data

data whose *attribute* (3.1) *values* (3.29) are associated with positions on a *grid coordinate system* (3.14)

3.17

ground control point

point on the earth that has an accurately known geographic position

3.18 image

iTeh STANDARD PREVIEW

gridded *coverage* (3.4) whose *attribute* (3.1) *values* (3.29) are a numerical representation of a physical parameter

Note 1 to entry: The physical parameters an<u>e the nexult of m</u>easurement by a *sensor* (3.27) or a prediction from a model. https://standards.iteh.ai/catalog/standards/sist/5917e4fd-b266-40b5-965efb379eed60db/iso-19115-2-2019

3.19

imagery

representation of phenomena as *images* (3.18) produced by electronic and/or optical techniques

Note 1 to entry: In this document, it is assumed that the objects and phenomena have been sensed or detected by radar, cameras, photometers, and infrared and multispectral scanners, or similar devices.

[SOURCE: ISO 19101-2:2008, 4.14]

3.20 metadata information about a resource

[SOURCE: ISO 19115-1:2014, 4.10]

3.21

pass

single instance of a remote, mobile measuring system going by a target of interest

Note 1 to entry: In this document, the measuring system will usually be a *remote sensing* (3.25) *platform* (3.23). In a navigation context, the measuring system might be a GPS satellite.

3.22

pixel

smallest element of a digital *image* (3.18) to which *attributes* (3.1) are assigned

Note 1 to entry: It is the smallest unit of display for a visible image.

[SOURCE: ISO/TS 19101-2:2008, 4.28, modified — Note 1 to entry replaces NOTES 1 and 2.]

3.23

platform

structure which supports a *sensor* (3.27) or sensors

3.24

polarization

restricting radiation, especially light, vibrations to a single plane

3.25

remote sensing

collection and interpretation of information about an object without being in physical contact with the object

[SOURCE: ISO/TS 19101-2:2008, 4.33]

3.26

resolution (of a sensor)

smallest difference between indications of a sensor (3.27) that can be meaningfully distinguished

Note 1 to entry: For *imagery* (<u>3.19</u>), resolution refers to radiometric, spectral, spatial and temporal resolutions.

[SOURCE: ISO/TS 19101-2:2008, 4.34]

3.27

sensor

element of a measuring system that is directly affected by a phenomenon, body, or substance carrying a quantity to be measured

[SOURCE: ISO/IEC Guide 99:2007, 3.8, modified C EXAMPLES and NOTE deleted.]

3.28

spectral width https://standards.iteh.ai/catalog/standards/sist/5917e4fd-b266-40b5-965especific wavelength interval within the electromagnetic spectrum 19

EXAMPLE Band (3.2) 1 of Landsat TM lies between 0,45 µm and 0,52 µm in the visible part of the spectrum.

3.29

value element of a type *domain* (3.8)

[SOURCE: ISO/IEC 19501:2005, 0000_5]

3.30

value domain set of accepted *values* (3.29)

EXAMPLE The range 3-28, all integers, any ASCII character, enumeration of all accepted values (green, blue, white).

[SOURCE: ISO 19103:2015, 4.37]

4 Symbols and abbreviated terms

4.1 Abbreviated terms

- IDL Interface Definition Language
- OCL Object Constraint Language
- UML Unified Modelling Language

5 Conformance

5.1 Conformance requirements

Metadata shall be provided as specified in <u>Clause 6</u> and <u>Annex B</u> of this document and ISO 19115-1:2014, Clause 6 and Annex B.

User-defined metadata extensions to this document shall be defined and provided as specified in ISO 19115-1:2014, Annex C.

Any metadata claiming conformance with this document shall pass the requirements described in <u>Annex A</u> of this document and the abstract test suite presented in ISO 19115-1:2014, Annex A.

5.2 Metadata profiles

Any profile conforming to this document shall conform to the rules for creating a profile given in ISO 19115-1:2014, C.6.

6 Acquisition and processing metadata

6.1 Metadata for acquisition and processing requirements

ISO 19115-1 identifies the metadata required to describe digital geographic resources. This document extends the metadata identified in ISO 19115-1 and identifies additional metadata required to describe the acquisition and processing of geographic resources.

(standards.iteh.ai)

6.2 Acquisition and processing metadata packages and dependencies

<u>ISO 19115-2:2019</u>

The ISO geographic information series of standards are defined using one or more UML packages and are maintained in a single integrated UML model. This document utilizes and extends concepts defined in several of these other standards' packages. Figure 1 illustrates the UML packages upon which this document is dependent. Dependencies between packages not defined in this document are not displayed. Metadata for acquisition and processing are defined and provided by one or more packages; each package provides a separate component of metadata information. There are four packages that are used to define and provide the metadata that is defined in this document: Acquisition information, Extended lineage information, Extended spatial representation information, and Extended content information.



Figure 1 — Metadata packages

6.3 Acquisition and processing metadata class diagrams by package

6.3.1 Introduction

Metadata are composed of one or more metadata packages containing one or more metadata classes containing attributes. The relationships between metadata packages and between metadata classes are specified by composition and aggregation relationship symbols. Class attributes and relationships are referred to collectively as metadata elements. The diagrams in <u>6.3.2</u> through <u>6.3.5</u> provide "views", which are portions of the total abstract model for metadata. Each diagram defines a metadata UML package of related classes, elements, data types, and code lists. Related external classes are shown with attributes relevant for this document and the package where they are fully specified identified by the package name proceeding a double colon (::). In some cases, this package may be from another standard identified by a labelled boxed outline. Since the classes in ISO 19115-1 being extended cannot be modified the class being modified is redefined in this document using a similar name. To differentiate between ISO 19115-1 and entities of this document, this part uses different prefixes. The prefixes used are MI (to denote an extended MD class), LE (LI extended) and CE (CI_Extended).

The classes from ISO 19115-1, being extended, are contained in a box labelled as such. The metadata are fully specified by the UML model diagrams and an associated data dictionary for each package in <u>Annex B</u>. Abstract classes (which are classes that are defined for schematic organization purposes, i.e. only their subclasses are implemented) are identified with their names in italic. Codelists and their values provided in this document are normative. User extensions to codelists shall follow the rules as described in ISO 19115-1:2014, Annex C.

NOTE In some cases, optional classes can have mandatory elements; those elements become mandatory only if the optional element is used.

6.3.2 Acquisition Information

6.3.2.1 Acquisition overview

This package extends MD_Metadata in ISO 19115-1 and provides details specific to the acquisition of geospatial data using imagery, sensors, and other acquisition methods. MI_AcquisitionInformation is an aggregate of the following entities:

- MI_Instrument, designations of the measuring instruments used to acquire the data;
- MI_Sensor, a specific type of MI_Instrument;
- MI_Operation, designations of the overall data gathering program to which the data contribute;
- MI_Platform, designations of the platform from which the data were taken;
- MI_InstrumentEventList, which lists events affecting MI_Platform and MI_Instrument;
- MI_InstrumentEvent which identifies events affecting MI_Platform and MI_Instrument;
- MI_Revision which identifies the revision history of events;
 - https://standards.iteh.ai/catalog/standards/sist/5917e4fd-b266-40b5-965e-
- MI_Objective, the characteristics and geometry of the intended object to be observed;
- MI_Requirement, the user requirements used to derive the acquisition plan;
- MI_Plan, the acquisition plan that was implemented to acquire the data.

Two additional classes are required to provide information on the acquisition of the data. These are:

- MI_Event, describes a significant event that occurred during data acquisition. An event can be associated with an operation, objective, or platform pass, and
- MI_PlatformPass, identifies a particular pass made by the platform during data acquisition. A platform pass is used to provide supporting identifying information for an event and for data acquisition of a particular objective.

Figure 2 defines an overview of the metadata classes required to define the acquisition of data. The data dictionary for this diagram is provided in <u>B.2.1</u>.



6.3.2.2 Acquisition Details

Figure 3 defines, in additional detail, the metadata classes necessary to define the acquisition of data. The data dictionary for this diagram is provided in <u>B.2.1</u>.

ISO 19115-2:2019(E)



Figure 3 — Acquisition Details