



SLOVENSKI STANDARD
SIST EN 60456:2016/A11:2021

01-februar-2021

Gospodinjski pralni stroji - Metode za merjenje funkcionalnosti - Dopolnilo A11

Clothes washing machines for household use - Methods for measuring the performance

Waschmaschinen für den Hausgebrauch - Verfahren zur Messung der Gebrauchseigenschaften

Machines à laver le linge pour usage domestique - Méthodes de mesure de l'aptitude à la fonction

ITeH STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: EN 60456:2016/A11:2020

SIST EN 60456:2016/A11:2021
<https://standards.iteh.ai/catalog/standards/sist/92f8013b-1bc6-4973-b884-751d525350ff/sist-en-60456-2016-a11-2021>

ICS:

97.060

Aparati za nego perila

Laundry appliances

SIST EN 60456:2016/A11:2021

en,fr

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 60456:2016/A11:2021](https://standards.iteh.ai/catalog/standards/sist/92f8013b-1bc6-4973-b884-751d525350ff/sist-en-60456-2016-a11-2021)

<https://standards.iteh.ai/catalog/standards/sist/92f8013b-1bc6-4973-b884-751d525350ff/sist-en-60456-2016-a11-2021>

EUROPEAN STANDARD

EN 60456:2016/A11

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2020

ICS 97.060

English Version

Clothes washing machines for household use - Methods for measuring the performance

Machines à laver le linge pour usage domestique -
Méthodes de mesure de l'aptitude à la fonction

Waschmaschinen für den Hausgebrauch - Verfahren zur
Messung der Gebrauchseigenschaften

This amendment A11 modifies the European Standard EN 60456:2016; it was approved by CENELEC on 2020-10-21. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this amendment the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This amendment exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

(standards.iteh.ai)

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

<https://standards.iteh.ai/catalog/standards/sist/92180136-1bc6-4973-b884-751d525350ff/sist-en-60456-2016-a11-2021>



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN 60456:2016/A11:2020 (E)

Contents	Page
1 Modification to Clause 2, "Normative references"	5
2 Modification to Clause 3, "Terms, definitions and symbols"	5
3 Modification to Clause 5, "Test conditions, materials, equipment and instrumentation"	14
4 Modification to Clause 6, "Preparation for testing"	15
5 Modification to Clause 7, Performance measurements – general requirements	18
6 Modification to Clause 8, "Tests for performance"	19
7 Modification to Clause 9, "Assessment of performance"	20
8 Modification to Annex A, "Specification of stain test strips with standardized soiling"	21
9 Modification to Annex B, "Reference detergents"	21
10 Modification to Annex C, "Specifications for base loads"	21
11 Modification to Annex D, "Reference machine specification"	22
12 Modification to Annex H, "Folding and loading the test load"	22
13 Modification to Annex I, "Calculation of weighted average age of the cotton base load"	22
14 Modification to Annex O, "Additional evaluation of washing performance"	24
15 Modification to Annex S, Test report – data to be reported	24
16 Modification to Annex ZA, "Test procedure for a combined test sequence of eco 40-60 with full load, half load and quarter load"	25
17 Modification to Annex ZB, "Multi-Drum Washing Machines"	56
Annex ZC (normative) Normative references to international publications with their corresponding European publications	59
Annex ZD (normative) Low power modes for washing machines	60
Annex ZZA	65
Annex ZZB	67
18 Modification of Bibliography	69

European foreword

This document (EN 60456:2016/A11:2020) consists of the text IEC 60456:2010 prepared by SC 59D "Home laundry appliances", together with the common modifications prepared by CLC/TC 59X "Performance of household and similar electrical appliances".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2021-07-21
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2023-10-21

Significant technical differences are:

a) the **programme** to be tested for the **combined test series** is the new introduced **eco 40-60 programme**. This **programme** needs to be tested with default settings with the given temperature;

b) the **test loads** that have to be used for testing are full, half and quarter of the **rated capacity** of the **washing machine**. Therefore, a new **quarter load** is introduced and defined to be approximately a quarter of the **rated capacity** (see table ZA15). The **quarter load** is treated as a separate load and not created by dividing **full load** or **half load**;

c) the number of **test runs** per **treatment** for the **combined test series** changed to 3 tests with **full load**, 4 tests with **half load** and 3 tests with **quarter load**;

d) the time between two subsequent **test runs** within one day changed from 2 h to one hour;

e) the normalization run is included in the calculation of the load age. The maximum number of usages for the cotton base load per item is changed to 96 and the weighted average age of the base load is changed to be between 35 and 60 normalisation runs and test runs.

f) rinsing effectiveness is integrated. It is referred to CLC/TS 50677 (see ZA 4.10);

g) temperature inside the load is integrated. It is referred to CLC/TS 50707:2020 (under preparation) (see ZA4.11);

h) the procedure to measure low power modes is modified (see ZA4.9);

i) specific weighting factors are introduced for the calculation of the weighted average value of the **combined test series** and

j) Annex ZB Tolerances and control procedures is deleted. Annex ZB is replaced by a new Annex ZB which defines the testing procedure for multi-drum **washing machines**.

This document also specifies, as far as necessary, the test method for household **washing machines** in accordance with the COMMISSION DELEGATED REGULATION (EU) 2019/2014 of 11 March 2019 supplementing Regulation 2017/1369 of the European Parliament and of the Council with regard to energy labelling of household **washing machines** and household **washer-dryers** and repealing Commission Regulation (EU) No 1061/2010 and Commission Directive 96/60/EC and in accordance with the COMMISSION REGULATION (EU) 2019/2023 of 1 October 2019 laying down ecodesign requirements for household **washing machines** and household **washer-dryers** pursuant to Directive 2009/125/EC of the European Parliament and of the Council, amending Commission Regulation (EC) No 1275/2008 and repealing Commission regulation (EU) No 1015/2010.

EN 60456:2016/A11:2020 (E)

Clauses, subclauses, notes, tables, figures and annexes which are additional to those in IEC 60456:2010 are prefixed “Z”.

Annex ZA sets out the procedure to be applied for testing according to Commission Regulations with regard to energy labelling and ecodesign and provides all necessary links to all relevant clauses of this European Standard.

This document has been prepared in view of upcoming Standardization Request which will be given to CENELEC by the European Commission and the European Free Trade Association, and supports Commission Delegated Regulation (EU) 2019/2014 and Commission Regulation (EU) 2019/2023.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

For the relationship with Commission Delegated Regulation (EU) 2019/2014 and Commission Regulation (EU) 2019/2023 informative Annex ZZA and Annex ZZB will be published following the adoption of the Standardization Request.

Endorsement notice

The text of the International Standard IEC 60456:2010 was approved by CENELEC as a European Standard with agreed common modifications

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 60456:2016/A11:2021](https://standards.iteh.ai/catalog/standards/sist/92f8013b-1bc6-4973-b884-751d525350ff/sist-en-60456-2016-a11-2021)

<https://standards.iteh.ai/catalog/standards/sist/92f8013b-1bc6-4973-b884-751d525350ff/sist-en-60456-2016-a11-2021>

1 Modification to Clause 2, "Normative references"

Add the following references:

CLC/TS 50677, *Clothes washing machines and washer-dryers for household and similar use - Method for the determination of rinsing effectiveness by measurement of the surfactant content at textile materials*

CLC/TS 50707:2020, *Clothes washing machines and washer-dryers for household and similar use - Method for the determination of the maximum temperature inside the load*

2 Modification to Clause 3, "Terms, definitions and symbols"

3.1 Terms and definitions

Addition of table before 3.1.1

Table 3.1 – Reference table for terms and definition in alphabetical order

Terms and Definition	sub-clause
automatic machine	3.1.10
base load	3.1.18
combined cycle time	3.1.Z19
combined programme time	3.1.Z18
combined rated capacity	3.1.Z17
combined test series	3.1.Z10
cycle	3.1.15
cycle time	3.1.25
delay start	3.1.Z22
eco 40-60	3.1.Z24
end of programme	3.1.24
full load	3.1.Z1
half load	3.1.Z2
horizontal axis washing machine	3.1.8
left on mode	3.1.29
main wash duration	3.1.26
manual washing machine	3.1.9
multi-drum mode	3.1.Z14
multi-drum washing machine	3.1.Z13
network	3.1.Z21
nominal test load mass	3.1.21
off-mode	3.1.28
operation	3.1.13
part A	3.1.Z3
part B	3.1.Z4
programme	3.1.14
programme time	3.1.23
quarter load	3.1.Z5
rated capacity	3.1.22
rated voltage	3.1.30
reference machine	3.1.3
remaining moisture content	3.1.27

EN 60456:2016/A11:2020 (E)

Terms and Definition	sub-clause
simultaneous cycle	3.1.Z16
simultaneous programme	3.1.Z15
spin extraction	3.1.16
spin extractor	3.1.5
spin speed	3.1.17
standard extractor	3.1.6
standby mode	3.1.Z20
test load	3.1.19
test load mass	3.1.20
test run	3.1.11
test series	3.1.12
test washing machine	3.1.2.
treatment	3.1.Z6
treatment full	3.1.Z7
treatment half	3.1.Z8
treatment quarter	3.1.Z9
vertical axis washing machine	3.1.7
washer-dryer	3.1.4
washing machine	3.1.1
wrinkle guard function	3.1.Z23

(standards.iteh.ai)

Replace items 3.1.12 and 3.1.22 to 3.1.24 and 3.1.28 with the following:

[SIST EN 60456:2016/A11:2021](https://standards.iteh.ai/catalog/standards/sist/92f8013b-1bc6-4973-b884-751d525350ff/sist-en-60456-2016-a11-2021)

3.1.12

<https://standards.iteh.ai/catalog/standards/sist/92f8013b-1bc6-4973-b884-751d525350ff/sist-en-60456-2016-a11-2021>

test series

repetitions of **test runs** with the same **treatment** which, collectively, are used to assess the performance for one **treatment**.

3.1.22**rated capacity**

maximum mass of dry textiles of a particular type which the manufacturer declares can be treated in the **test washing machine** on the **programme** selected; for **multi-drum mode washing machines** the **rated capacities** are for each individual drum

Note Z1 to entry: For different textile types the **rated capacity** of a **multi-drum washing machine** is usually different.

3.1.23**programme time**

the time from the initiation of the **programme** (excluding any user programmed delay) until the end of the **programme** and if the **end of programme** is not indicated, the **programme time** is equal to the **cycle time**

3.1.24**end of programme**

the time when the **test washing machine** indicates the end of the **programme** and the load is accessible to the user; where there is no **end of programme** indicator and the door is locked during **operation**, the **programme** is complete when the load is accessible to the user; where there is no **end of programme** indicator and the door is not locked during **operation**, the **programme** is complete when the power consumption of the appliance drops to some steady state condition and is not performing any function

Note to entry Z1: An indication of the end of the **programme** may be in the form of a light (on or off), a sound, an indicator shown on a display or the release of a door or latch. In some **washing machines** there may be a short delay from an **end of programme** indicator until the load is accessible by the user.

3.1.28**off-mode**

condition in which the **test washing machine** is connected to the mains and is not providing any function; the following shall also be considered as **off mode**:

- (a) conditions providing only an indication of off-mode;
- (b) conditions providing only functionalities intended to ensure electromagnetic compatibility

Replace as follows:

3.1.Z1**full load**

test load to be used for a **combined test series** according to Annex ZA, having a nominal mass that is equal to the **rated capacity** of the **test washing machine**

3.1.Z2**half load**

test load, part A or **part B**, to be used for a **combined test series** according to Annex ZA, having a nominal mass that is approximately equal to a half of the **rated capacity** of the **test washing machine**.

3.1.Z3**part A**

one half of the **full load**.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3.1.Z4**part B**

remaining part of the **full load** excluding **part A**.

[SIST EN 60456:2016/A11:2021](https://standards.iteh.ai/catalog/standards/sist/92f8013b-1bc6-4973-b884-751d525350ff/sist-en-60456-2016-a11-2021)
<https://standards.iteh.ai/catalog/standards/sist/92f8013b-1bc6-4973-b884-751d525350ff/sist-en-60456-2016-a11-2021>

3.1.Z5**quarter load**

test load to be used for a **combined test series** according to Annex ZA, having a nominal mass that is approximately equal to a quarter of the **rated capacity** (see Table ZA.15) of the **test washing machine**

3.1.Z6**treatment**

combination of **test load** and **programme** to be used for a **test run** within a **test series**

3.1.Z7**treatment full**

eco 40-60 programme with **full load**

3.1.Z8**treatment half**

eco 40-60 programme with **half load**

3.1.Z9**treatment quarter**

eco 40-60 programme with **quarter load**

3.1.Z10**combined test series**

combination of **test series** with different **treatments** which, collectively, are used to assess the performance

EN 60456:2016/A11:2020 (E)

3.1.Z13

multi-drum washing machine

washing machine equipped with more than one drum whether in separate units or in the same casing

3.1.Z14

multi-drum mode

programme where some or all of the drums of a **multi-drum washing machine** are operated simultaneously

Note Z1 to entry: A **washing machine** with more than one drum for the **treatment** of the textiles, where drums cannot be operated simultaneously is not regarded as having a **multi-drum mode**. In this case each drum has to be tested separately.

Note Z1 to entry: This definition may apply only for specific **programmes**. In this case only these **programmes** can be tested in **multi-drum mode**.

Add the following:

3.1.Z15

simultaneous programme

series of **operations** which are pre-defined within the **multi-drum washing machine** and which are declared by the manufacturer as suitable for washing certain textile types in two or more drums at the same time

3.1.Z16

simultaneous cycle

complete washing process, started at the same time for two or more drums, as defined by the **simultaneous programme** selected, consisting of a series of **operations** (wash, rinse, spin, etc.) and including any **operations** that occur after the completion of the **simultaneous programme**

Note Z1 to entry: Examples of **operations** that may occur after the completion of the **programme** are pumping, monitoring and anti-creasing (where applicable).

3.1.Z17

combined rated capacity

sum of rated capacities of all drums suitable for running a **simultaneous programme**

3.1.Z18

combined programme time

the time from the simultaneous initiation of the **programme** for two or more drums (excluding any user programmed delay) until the end of the **simultaneous programme**; if the **end of programme** is not indicated, the **combined programme time** is equal to the **combined cycle time**

3.1.Z19

combined cycle time

time from the simultaneous initiation of the **programme** for two or more drums (excluding any user programmed delay) until all activity ceases; activity is considered to have ceased when the power consumption reverts to a steady state condition that persists indefinitely without user intervention; if there is no activity after the end of the **programme**, the **combined cycle time** is equal to the **combined programme time**

Note Z1 to entry: **Cycle time** includes any activity that may occur after the **programme** is completed. This could include any electronic activity or any additional mechanical activity that occurs for a limited period after any **end of programme** indicator. Any cyclic event that occurs indefinitely is considered to be steady state.

3.1.Z20**standby mode**

condition where the **test washing machine** is connected to the mains and provides only the following functions, which may persist for an indefinite time:

- (a) reactivation function, or reactivation function and a mere indication of enabled reactivation function; and/or
- (b) reactivation function through a connection to a **network**; and/or
- (c) information or status display; and/or
- (d) detection function for emergency measures.

3.1.Z21**network**

communication infrastructure with topology of links, an architecture, including the physical components, organizational principles, communication procedures and formats protocols.

3.1.Z22**delay start**

condition where the user has selected a specified delay to the beginning of the **cycle** of the selected **programme**.

3.1.Z23**wrinkle guard function**

operation of the **test washing machine** after completion of a **programme** to prevent excessive wrinkle building of the laundry.

3.1.Z24**eco 40-60**

name of the programme to be able to clean normally soiled cotton laundry declared to be washable at 40 °C or 60 °C, together in the same washing cycle.

<https://standards.iteh.ai/catalog/standards/sist/92180136-1bc6-4973-b884-751d525350ff/sist-en-60456-2016-a11-2021>

EN 60456:2016/A11:2020 (E)

3.2 Symbols

3.2.Z1 Symbols relating to Annex ZA and Annex ZD

Replace with the following:

Symbol in this document	Symbol in IEC 60456 :2010	Unit	Description	Clause (first appearance)
$\lceil \rceil$	-	-	rounding up to full integer values (no decimal places) as defined in EN ISO 80000-2:2013	ZA.2
$\lfloor \rfloor$	-	-	Rounding to nearest integer values (no decimal places) as defined in EN ISO 80000-2:2013	ZA.2
$I_{W,z}$	-	-	Washing Efficiency Index for treatment z ($z = full, \frac{1}{2}, \frac{1}{4}$)	ZA5.4
A	-	-	weighting factor for the full rated capacity	ZA5.3.2
B	-	-	weighting factor for half of the rated capacity	ZA5.3.2
C	-	-	weighting factor for a quarter of the rated capacity	ZA5.3.2
c	-	kg	rated capacity to calculate the Standard Annual Energy Consumption of the test washing machine	ZA5.3.2
$C_{z,i}$	-	-	sum of the average reflectance values (Y-values) for treatment z ($z = full, \frac{1}{2}, \frac{1}{4}$) for each test run i ($i = 1, 2, 3, 4$)	ZA5.4
C_{ref}	\bar{C}_{ref}	-	average sum of the reflectance values in each test run of the reference machine out of all 5 runs	ZA5.4
C_z	-	-	average value for the sum of the reflectance values for treatment full , treatment half and treatment quarter	ZA5.4.
D	-	%	average value for the remaining moisture content for the combined test series	ZA5.5
$D_{1/2,part}$	-	%	remaining moisture content of test run with half load part ($part = part A, part B$)	ZA5.5
DL_l	-	g/kg	ratio of mass of detergent per kg of load for the test run	ZA6.2
R_{max}	-	g/kg	rinsing effectiveness for the combined test series	ZA.6.2
$D_{z,i}$	-	%	remaining moisture content of test run i for the treatment z ($z = full, \frac{1}{2}, \frac{1}{4}$)	ZA5.5
EEI	-	-	Energy Efficiency Index of a test washing machine	ZA5.10

Symbol in this document	Symbol in IEC 60456 :2010	Unit	Description	Clause (first appearance)
M	M	g	mass of the conditioned base load	ZA.6.2
M_{det}	M_{det}	g	mass of detergent used	ZA.6.2
M_{dry}	M_{dry}	g	mass of base load before each test run (without test strips)	ZA.6.2
Mn_{part}	-	kg	nominal partial test load mass	ZA.2
M_{part}	-	g	mass of the conditioned half load (<i>part = part A, part B</i>)	ZA5.5
$M_{r, \frac{1}{2}, part, i}$	-	g	mass of the half load part (<i>part = part A, part B</i>) at the end of the test run i ($i = 1, 2, 3, 4$)	ZA5.5
$M_{r, z, i}$	-	g	mass of base load for treatment z ($z = full, \frac{1}{4}$) at the end of the test run i ($i = 1, 2, 3$)	ZA5.5
n_{PC}	-	-	number of pillowcases at rated test load mass	ZA.2
$n_{PC, A}$	-	-	number of pillowcases in part A	ZA.2
$n_{PC, B}$	-	-	number of pillowcases in part B	ZA.2
n_{SH}	-	-	number of sheets at rated test load mass	ZA.2
$n_{SH, A}$	-	-	number of sheets in part A	ZA.2
$n_{SH, B}$	-	-	number of sheets in part B	ZA.2
$n_{STS, A}$	-	-	number of stain test strips in part A	ZA.2
$n_{STS, B}$	-	-	number of stain test strips in part B	ZA.2
n_T	-	-	number of towels at rated test load mass	ZA.2
$n_{T, A}$	-	-	number of towels in part A	ZA.2
$n_{T, B}$	-	-	number of towels in part B	ZA.2
n_z	-	-	number of test runs for treatment z	ZA.5.3
<i>part</i>	-	-	half load identifier (<i>part = part A, part B</i>)	ZA.5.5
p_c	p_c	kPa	laboratory supply water pressure cold	ZA.6.2
P_{ds}	-	W	power consumption in delay start	ZD.1
p_h	p_h	kPa	laboratory supply water pressure hot (if connected)	ZA.6.2
P_{ns}	-	W	Power consumption in standby mode in condition of network standby	ZD.1

EN 60456:2016/A11:2020 (E)

Symbol in this document	Symbol in IEC 60456 :2010	Unit	Description	Clause (first appearance)
P_{om}	-	W	Power consumption in off mode	ZD.1
P_{sm}	-	W	Power consumption in standby mode	ZD.1
$R_{1/4}$		g/kg	is the average value for rinsing effectiveness for treatment quarter	ZA.5.11
$R_{1/2}$		g/kg	is the average value for rinsing effectiveness for treatment half	ZA.5.11
R_{full}		g/kg	average value for rinsing effectiveness for treatment full	ZA.5.11
$S_{1/4}$	-	min ⁻¹	maximum spin speed for treatment quarter	ZA.5.6
$S_{1/2}$	-	min ⁻¹	maximum spin speed for treatment half	ZA.5.6
SCE_c	-	kWh	Standard Cycle Energy Consumption	ZA.5.10
S_{full}	-	min ⁻¹	maximum spin speed for treatment full	ZA.5.6
S_z	-	-	standard deviation for treatment z	ZA.5.3
$S_{z,i}$	-	min ⁻¹	maximum spin speed of test run i for treatment z ($z = full, 1/2, 1/4$)	ZA.5.6
t_a	t_a	°C	ambient temperature (test room)	ZA.6.2
t_c	t_c	°C	measured average cold water inlet temperature	ZA.6.2
t_h	t_h	°C	measured average hot water inlet temperature	ZA.6.2
t_z	-	min	average value for the programme time for treatment z ($z = full, 1/2, 1/4$)	ZA.5.8
$t_{z,i}$	-	min	programme time for test run i for treatment z ($z = full, 1/2, 1/4$)	ZA.5.8
V	-	L	weighted average value for the total water consumption for the combined test series	ZA.5.7
$V_{1/4}$	-	L	water consumption for treatment with quarter load	ZA.5.7
$V_{1/2}$	-	L	water consumption for treatment with half load	ZA.5.7
V_{cm}	V_{cm}	L	volume of cold water used during the main wash	ZA.6.2
V_{ct}	V_{ct}	L	volume of cold water used in the test run	ZA.6.2
V_{full}	-	L	water consumption for treatment with full load	ZA.5.7

Symbol in this document	Symbol in IEC 60456 :2010	Unit	Description	Clause (first appearance)
V_{hm}	V_{hm}	L	volume of supply hot water used during the main wash	ZA.6.2
V_{ht}	V_{ht}	L	volume of supply hot water used in the test run	ZA.6.2
V_m	V_m	L	water consumption during the main wash	ZA.6.2
V_z	-	L	water consumption for treatment z ($z = full, \frac{1}{2}, \frac{1}{4}$)	ZA.5.7
$V_{z,i}$	-	L	water consumption for test run i for treatment z ($z = full, \frac{1}{2}, \frac{1}{4}$)	ZA.5.7
W	-	kWh	value for the total energy consumption for the combined test series	ZA.5.9
$W_{\frac{1}{4}}$	-	kWh	energy consumption for treatment quarter	ZA.5.9
$W_{\frac{1}{2}}$	-	kWh	energy consumption for treatment half	ZA.5.9
W_{et}	W_{total}	kWh	total electrical energy metered during the test	ZA.6.2
W_{full}	-	kWh	energy consumption for treatment full	ZA.5.9
$W_{total,cold}$	-	kWh	value for total energy consumption without hot water	ZA.6.2
W_z	-	kWh	average value for the total energy consumption for treatment z ($z = full, \frac{1}{2}, \frac{1}{4}$)	ZA.5.9
$W_{z,i}$	-	kWh	total energy consumption for test run i for treatment z ($z = full, \frac{1}{2}, \frac{1}{4}$)	ZA.5.9
x_i			value for each test run i	ZA.6.2
x_z	-	-	average value for treatment z ($z = full, \frac{1}{2}, \frac{1}{4}$)	ZA.5.3
$x_{z,i}$	-	-	value for each test run i of treatment z ($z = full, \frac{1}{2}, \frac{1}{4}$)	ZA.5.3
z	-	-	treatment	ZA.5.3