



**SLOVENSKI STANDARD**  
**SIST ETS 300 392-2:1999**

**01-november-1999**

---

**Prizemni snopovni radio (TETRA) - Govor in podatki (V+D) - 2. del: Radijski vmesnik (AI)**

Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

**Ta slovenski standard je istoveten z: ETS 300 392-2 Edition 1**

SIST ETS 300 392-2:1999  
<https://standards.iteh.ai/catalog/standards/sist/4a6392dc-1b9c-4f80-b409-a5a47383e8b6/sist-ets-300-392-2-1999>

**ICS:**

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------


**SIST ETS 300 392-2:1999**

**en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ETS 300 392-2:1999](#)

<https://standards.iteh.ai/catalog/standards/sist/4a6392dc-1b9c-4f80-b409-a5a47383e8b6/sist-ets-300-392-2-1999>



**E**UROPEAN  
**T**ELECOMMUNICATION  
**S**TANDARD

**ETS 300 392-2**

March 1996

Source: ETSI TC-RES

Reference: DE/RES-06001-2

ICS: 33.020, 30.060.50

**Key words:** TETRA, V+D

**Radio Equipment and Systems (RES);  
Trans-European Trunked Radio (TETRA);  
Voice plus Data (V+D);  
Part 2: Air Interface (AI)**

**ETSI**

European Telecommunications Standards Institute

**ETSI Secretariat**

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE

**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

**X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 392-2:1999](https://standards.iteh.ai/catalog/standards/sist/4a6392dc-1b9c-4f80-b409-a5a47383e8b6/sist-ets-300-392-2-1999)

<https://standards.iteh.ai/catalog/standards/sist/4a6392dc-1b9c-4f80-b409-a5a47383e8b6/sist-ets-300-392-2-1999>



	6.4.2.2.2	Measurement during the switching transients.....	46
	6.4.2.3	Unwanted emissions far from the carrier .....	47
	6.4.2.4	Unwanted emissions during the CLCH and BLCH .....	47
	6.4.2.5	Unwanted emissions in the non-transmit state .....	47
6.4.3		Unwanted radiated emissions.....	47
6.4.4		RF tolerance .....	47
6.4.5		RF Output power time mask.....	48
	6.4.5.1	BS (BS) .....	49
	6.4.5.2	MS (MS) .....	49
6.4.6		Intermodulation attenuation .....	49
	6.4.6.1	Definition .....	49
	6.4.6.2	BS .....	49
	6.4.6.3	MS.....	49
6.4.7		Intra-BS intermodulation requirements.....	50
6.5		Receiver characteristics .....	50
6.5.1		Blocking characteristics .....	50
	6.5.1.1	Definition .....	50
	6.5.1.2	Specification.....	50
6.5.2		Spurious response rejection .....	51
	6.5.2.1	Definition .....	51
	6.5.2.2	Specification.....	51
6.5.3		Intermodulation response rejection .....	51
	6.5.3.1	Definition .....	51
	6.5.3.2	Specification.....	51
6.5.4		Unwanted conducted emissions.....	52
	6.5.4.1	Definition .....	52
	6.5.4.2	Specification.....	52
6.5.5		Unwanted radiated emissions.....	52
6.6		Transmitter/receiver performance.....	52
6.6.1		Modulation accuracy.....	52
	6.6.1.1	Ideal case.....	52
	6.6.1.2	Vector error magnitude requirement at symbol time.....	53
6.6.2		Receiver performance.....	53
	6.6.2.1	Nominal error rates.....	54
	6.6.2.2	Dynamic reference sensitivity performance .....	54
	6.6.2.2.1	BS receiver performance .....	55
	6.6.2.2.2	MS receiver performance.....	55
	6.6.2.3	Reference interference performance .....	55
	6.6.2.3.1	BS receiver performance .....	56
	6.6.2.3.2	MS receiver performance.....	56
	6.6.2.4	Static reference sensitivity performance .....	56
	6.6.2.4.1	BS receiver performance .....	57
	6.6.2.4.2	MS receiver performance.....	57
	6.6.2.5	MS receiver performance for synchronisation burst acquisition .....	57
6.6.3		Propagation conditions .....	58
	6.6.3.1	Propagation conditions - introduction.....	58
	6.6.3.2	Tap-gain process types.....	58
	6.6.3.3	Propagation models .....	59
7		Radio sub-system synchronisation .....	59
7.1		Introduction.....	59
7.2		General description of synchronisation system.....	59
7.3		Timebase counters.....	60
	7.3.1	Timing counters .....	60
	7.3.2	Values of the counters .....	60
7.4		Timing of transmitted signals .....	60
7.5		BS requirements for synchronisation .....	61
7.6		MS requirements for synchronisation.....	61
8		Channel coding.....	61
8.1		Introduction.....	61

8.2	General .....	62
8.2.1	Interfaces in the error control structure .....	62
8.2.2	Notation .....	63
8.2.3	Definition of error control codes .....	63
8.2.3.1	16-state Rate-Compatible Punctured Convolutional (RCPC) codes .....	63
8.2.3.1.1	Encoding by the 16-state mother code of rate 1/4.....	63
8.2.3.1.2	Puncturing of the mother code.....	64
8.2.3.1.3	Puncturing scheme of the RCPC code of rate 2/3.....	64
8.2.3.1.4	Puncturing scheme of the RCPC code of rate 1/3.....	64
8.2.3.1.5	Puncturing scheme of the RCPC code of rate 292/432.....	64
8.2.3.1.6	Puncturing scheme of the RCPC code of rate 148/432.....	64
8.2.3.2	Shortened (30,14) Reed-Muller (RM) code .....	65
8.2.3.3	$(K_1+16, K_1)$ block code .....	65
8.2.4	Definition of interleaving schemes.....	66
8.2.4.1	Block interleaving.....	66
8.2.4.2	Interleaving over $N$ blocks .....	66
8.2.5	Definition of scrambling .....	66
8.2.5.1	Scrambling method.....	66
8.2.5.2	Scrambling sequence .....	66
8.3	Error control schemes.....	67
8.3.1	Access Assignment Channel (AACH) .....	68
8.3.2	Broadcast Synchronisation Channel (BSCH) .....	68
8.3.3	Traffic channels in circuit switched mode .....	69
8.3.3.1	Traffic CHannel, net rate = 4,8 kbit/s (TCH/4,8) .....	69
8.3.3.2	Traffic CHannel, net rate = 2,4 kbit/s (TCH/2,4) .....	69
8.3.3.3	Traffic CHannel, net rate = 7,2 kbit/s (TCH/7,2) .....	70
8.3.4	Signalling channels for signalling and packet mode data.....	70
8.3.4.1	Signalling CHannel for mapping onto Half-bursts on the Downlink (SCH/HD), Broadcast Network CHannel (BNCH), and STEaling CHannel (STCH).....	70
8.3.4.2	Signalling CHannel for mapping onto Half-bursts on the Uplink (SCH/HU) .....	71
8.3.4.3	Signalling CHannel for mapping onto Full bursts (SCH/F) ..	71
9	Channel multiplexing for V+D.....	72
9.1	Introduction .....	72
9.2	Logical channels .....	72
9.2.1	Logical channels hierarchy.....	72
9.2.2	Traffic channels.....	72
9.2.3	Control CHannels (CCH).....	73
9.2.3.1	General .....	73
9.2.3.2	BCCH.....	73
9.2.3.3	LCH.....	73
9.2.3.4	SCH .....	73
9.2.3.5	AACH.....	74
9.2.3.6	STCH.....	74
9.3	The physical resource.....	74
9.3.1	General.....	74
9.3.2	RF channels .....	74
9.3.3	Timeslots.....	75
9.3.4	TDMA frame .....	75
9.3.5	Timeslot numbering.....	75
9.3.6	Subslot .....	75
9.3.7	Multiframe.....	76
9.3.8	Hyperframe.....	76
9.3.9	Frame alignment .....	76
9.4	Physical channels .....	76

9.4.1	General .....	76
9.4.2	Types of physical channels.....	76
9.4.2.1	CP channel.....	76
9.4.2.2	TP channel.....	76
9.4.2.3	UP channel.....	76
9.4.3	Bursts.....	77
9.4.3.1	General .....	77
9.4.3.2	Modulation symbol numbering .....	77
9.4.3.3	Modulation bit numbering.....	77
9.4.3.4	Burst timing .....	77
9.4.4	Type of bursts .....	77
9.4.4.1	General .....	77
9.4.4.2	Modulation bits allocation.....	79
9.4.4.2.1	Control uplink Burst (CB) .....	79
9.4.4.2.2	Linearisation uplink Burst (LB) .....	79
9.4.4.2.3	Linearisation downlink burst.....	80
9.4.4.2.4	Normal Uplink Burst (NUB) .....	80
9.4.4.2.5	Normal continuous downlink burst .....	80
9.4.4.2.6	Synchronisation continuous downlink burst .....	81
9.4.4.2.7	Normal discontinuous downlink burst... ..	81
9.4.4.2.8	Synchronisation discontinuous downlink burst .....	82
9.4.4.3	Burst fields .....	82
9.4.4.3.1	Frequency correction field .....	82
9.4.4.3.2	Normal training sequence .....	82
9.4.4.3.3	Extended training sequence.....	83
9.4.4.3.4	Synchronisation training sequence .....	83
9.4.4.3.5	Tail bits.....	83
9.4.4.3.6	Phase adjustment bits.....	83
9.4.5	Transmission modes .....	84
9.4.5.1	BS continuous transmission.....	84
9.4.5.2	BS timesharing transmission .....	84
9.4.5.3	MS multiple slot transmission .....	85
9.5	Mapping of logical channels into physical channels .....	86
9.5.1	General mapping of logical channels.....	86
9.5.2	Mapping of BCCH and CLCH .....	87
9.5.3	Mapping of SCH .....	88
9.5.4	Mapping of TCH and STCH.....	88
9.5.5	Mapping of AACH.....	88
9.6	Monitoring pattern for transmitting MSs .....	88
9.7	BS timesharing transmission.....	89
9.7.1	Carrier sharing .....	89
9.7.2	MCCH sharing .....	89
9.8	Modes of control.....	89
9.8.1	NCM.....	89
9.8.2	MCM .....	90
10	Radio subsystem link control .....	90
10.1	Introduction.....	90
10.2	RF power control.....	91
10.3	Radio link measurements.....	91
10.3.1	Received signal strength .....	91
10.3.1.1	Sample duration for signal strength measurement .....	91
10.3.2	Signal quality.....	91
10.3.3	Round-trip MS-BS path delay .....	91
11	Call Control (CC) service description.....	91
11.1	Introduction.....	91
11.2	Services offered .....	92
11.3	CC service.....	92
11.3.1	CC primitives exchanged through the TNCC-SAP .....	92
11.3.2	Service primitives at the TNCC-SAP .....	93



11.3.3	Primitive description .....	93
11.3.3.1	TNCC-ALERT primitive .....	94
11.3.3.2	TNCC-COMplete primitive .....	94
11.3.3.3	TNCC-DTMF primitive .....	94
11.3.3.4	TNCC-MODIFY primitive .....	95
11.3.3.5	TNCC-NOTIFY primitive .....	95
11.3.3.6	TNCC-PROCEED primitive .....	95
11.3.3.7	TNCC-RELEASE primitive .....	96
11.3.3.8	TNCC-SETUP primitive .....	96
11.3.3.9	TNCC-TX primitive .....	97
11.3.4	Parameter description .....	98
11.4	States for CC SAP .....	103
12	Supplementary Services (SS) service description .....	103
12.1	Introduction .....	103
12.2	Services offered .....	104
12.3	SS service .....	104
12.3.1	Primitives exchanged through TNSS-SAP .....	104
12.3.2	Service primitives .....	104
12.3.3	Service primitives at the TNSS-SAP .....	105
12.3.3.1	TNSS-ERROR indication .....	105
12.3.3.2	TNSS-SERVICE indication .....	105
12.3.3.3	TNSS-SERVICE request .....	105
12.3.3.4	TNSS-SERVICE confirm .....	105
12.3.3.5	TNSS-SERVICE response .....	105
12.3.3.6	TNSS-INFO confirm .....	105
12.3.3.7	TNSS-INFO indication .....	105
12.3.3.8	TNSS-INFO request .....	105
12.3.3.9	TNSS-INFO response .....	105
12.3.4	Primitive description .....	105
12.3.4.1	TNSS-ERROR primitive .....	106
12.3.4.2	TNSS-INFO primitive .....	106
12.3.4.3	TNSS-SERVICE primitive .....	106
12.3.5	Parameter description .....	106
13	Short Data Service (SDS) service description .....	108
13.1	Introduction .....	108
13.2	Services offered .....	108
13.3	SDS .....	108
13.3.1	SDS primitives exchanged through the TNSDS-SAP .....	108
13.3.2	Service primitives at the TNSDS-SAP .....	109
13.3.2.1	TNSDS-STATUS primitive .....	109
13.3.2.2	TNSDS-REPORT primitive .....	109
13.3.2.3	TNSDS-UNITDATA primitive .....	109
13.3.3	Parameter description .....	110
13.3.4	State description .....	112
13.3.4.1	NULL state .....	112
13.3.4.2	SHORT DATA INITIATED state .....	112
13.3.5	Service state diagram for the TNSDS-SAP .....	112
14	CMCE protocol .....	112
14.1	Introduction .....	112
14.2	Overview of CMCE .....	113
14.2.1	Communication routes of the CMCE model .....	113
14.2.2	Protocol structure and protocol stack .....	114
14.2.3	Addressing rules .....	115
14.2.4	CC, SS and SDS sub-entities .....	115
14.2.4.1	CC sub-entity .....	116
14.2.4.2	SS sub-entity .....	116
14.2.4.3	SDS sub-entity .....	116
14.2.5	PC sub-entity .....	116
14.2.6	Internal routes .....	117
14.2.7	Intra-CMCE primitive summary .....	118

	14.2.7.1	Down link CC PDU parameters .....	118
	14.2.7.2	Uplink CC PDU parameters .....	118
	14.2.7.3	Downlink SS PDU parameters .....	119
	14.2.7.4	Uplink SS PDU parameters .....	119
	14.2.7.5	Down link SDS PDU parameters .....	119
	14.2.7.6	Uplink SDS PDU parameters .....	119
	14.2.7.7	CMCE management primitives .....	119
	14.2.7.7.1	BREAK indication .....	119
	14.2.7.7.2	CANCEL request .....	119
	14.2.7.7.3	CLOSE indication .....	119
	14.2.7.7.4	CONFIGURE request .....	120
	14.2.7.7.5	IDENTITIES request .....	120
	14.2.7.7.6	OPEN indication .....	120
	14.2.7.7.7	REOPEN indication .....	120
	14.2.7.7.8	REPORT indication .....	120
	14.2.7.7.9	RESUME indication .....	120
14.3		Overview of services required by the CMCE .....	120
14.4		CMCE protocol states .....	120
	14.4.1	States for PC .....	121
	14.4.1.1	CLOSED .....	121
	14.4.1.2	OPEN .....	121
	14.4.2	States for CC .....	122
	14.4.2.1	IDLE .....	124
	14.4.2.2	MO-CALL-SETUP .....	124
	14.4.2.3	MT-CALL-SETUP .....	124
	14.4.2.4	CALL ACTIVE .....	124
	14.4.2.5	CALL DISCONNECT .....	124
	14.4.2.6	WAIT .....	125
	14.4.3	States for SS .....	125
	14.4.4	States for SDS .....	125
14.5		Procedures .....	126
	14.5.1	Individual CC procedures .....	126
	14.5.1.1	Call set-up procedures .....	126
	14.5.1.1.1	Incoming call .....	127
	14.5.1.1.2	Outgoing call .....	128
	14.5.1.1.3	Colliding calls .....	130
	14.5.1.1.4	Unsuccessful call set-up .....	130
	14.5.1.1.5	Call rejection .....	130
	14.5.1.2	Call maintenance procedures .....	131
	14.5.1.2.1	Transmission control procedures .....	131
	14.5.1.2.2	Call status information procedures .....	134
	14.5.1.2.3	Call modification procedures .....	134
	14.5.1.2.4	Call restoration procedures .....	135
	14.5.1.2.5	DTMF procedures .....	136
	14.5.1.2.6	Calls to and from external subscribers .....	137
	14.5.1.3	Call disconnection procedures .....	137
	14.5.1.3.1	User initiated disconnection .....	138
	14.5.1.3.2	Network initiated disconnection .....	138
	14.5.1.3.3	Reception of disconnection request .....	138
	14.5.1.3.4	Expiry of timers .....	138
	14.5.1.3.5	Colliding disconnection .....	139
	14.5.1.4	U-Plane switching .....	139
	14.5.1.4.1	End of call set-up phase .....	140
	14.5.1.4.2	During call maintenance phase .....	140
	14.5.1.4.3	Call disconnection phase .....	141
	14.5.2	Group CC procedures .....	141
	14.5.2.1	Call set-up procedures .....	141
	14.5.2.1.1	Incoming call .....	143
	14.5.2.1.2	Outgoing call .....	143
	14.5.2.1.3	Colliding calls .....	144
	14.5.2.1.4	Unsuccessful call set-up .....	144
	14.5.2.1.5	Call rejection .....	144
	14.5.2.2	Call maintenance procedures .....	145

	14.5.2.2.1	Transmission control procedures .....	145
	14.5.2.2.2	Call status information procedures .....	149
	14.5.2.2.3	Call modification procedures .....	149
	14.5.2.2.4	Call restoration procedures.....	150
	14.5.2.2.5	DTMF procedures.....	151
	14.5.2.2.6	Temporary address handling procedures.....	151
	14.5.2.2.7	Calls to and from external subscribers	152
14.5.2.3		Call disconnection procedures .....	152
	14.5.2.3.1	User initiated disconnection.....	153
	14.5.2.3.2	Network initiated disconnection .....	153
	14.5.2.3.3	Reception of disconnection request....	153
	14.5.2.3.4	Colliding disconnection .....	154
	14.5.2.3.5	Expiry of timers .....	154
14.5.2.4		U-Plane switching .....	154
	14.5.2.4.1	End of call set-up phase .....	155
	14.5.2.4.2	During call maintenance phase .....	155
	14.5.2.4.3	Call disconnection phase.....	156
	14.5.2.5	Acceptance of group-addressed channel allocation.....	156
	14.5.2.6	Acknowledged group call procedures.....	157
14.5.3		Traffic channel assignment procedures .....	158
14.5.4		SS procedures.....	159
14.5.5		SDS procedures .....	160
	14.5.5.1	Incoming short data message .....	160
	14.5.5.2	Outgoing short data messages.....	160
14.5.6		PC procedures .....	160
	14.5.6.1	Access to the communication resources.....	160
	14.5.6.2	Access priority handling .....	160
	14.5.6.2.1	Cancel .....	161
	14.5.6.3	CMCE PDU exchange .....	162
	14.5.6.3.1	Choice of layer 2 service.....	162
	14.5.6.4	Control information exchange.....	162
	14.5.6.5	PC protocol error conditions .....	163
	14.5.6.5.1	PDU Type error.....	163
	14.5.6.5.2	Invalid call identifier.....	163
	14.5.6.5.3	MS busy .....	163
14.6		Protocol timers.....	163
14.7		PDU descriptions .....	164
	14.7.1	PDU description tables - downlink.....	166
	14.7.1.1	D-ALERT .....	166
	14.7.1.2	D-CALL PROCEEDING.....	167
	14.7.1.3	D-CALL-RESTORE .....	167
	14.7.1.4	D-CONNECT .....	168
	14.7.1.5	D-CONNECT ACKNOWLEDGE .....	168
	14.7.1.6	D-DISCONNECT .....	169
	14.7.1.7	D-FACILITY .....	169
	14.7.1.8	D-INFO .....	170
	14.7.1.9	D-RELEASE .....	170
	14.7.1.10	D-SDS-DATA.....	171
	14.7.1.11	D-STATUS.....	171
	14.7.1.12	D-SETUP.....	172
	14.7.1.13	D-TX CEASED .....	172
	14.7.1.14	D-TX CONTINUE .....	173
	14.7.1.15	D-TX GRANTED.....	173
	14.7.1.16	D-TX INTERRUPT.....	174
	14.7.1.17	D-TX WAIT .....	174
	14.7.2	PDU description tables - uplink .....	175
	14.7.2.1	U-ALERT .....	175
	14.7.2.2	U-CALL-RESTORE .....	175
	14.7.2.3	U-CONNECT .....	176
	14.7.2.4	U-DISCONNECT .....	176
	14.7.2.5	U-FACILITY .....	176
	14.7.2.6	U-INFO .....	177

	14.7.2.7	U-STATUS .....	177
	14.7.2.8	U-SDS-DATA .....	178
	14.7.2.9	U-RELEASE .....	178
	14.7.2.10	U-SETUP .....	179
	14.7.2.11	U-TX CEASED .....	179
	14.7.2.12	U-TX DEMAND .....	180
14.8		Information elements coding .....	180
	14.8.1	Area Selection (AS) .....	180
	14.8.2	Basic service information .....	181
	14.8.3	Call identifier .....	181
	14.8.4	Call ownership .....	181
	14.8.5	Called party type identifier .....	182
	14.8.6	Called party SNA .....	182
	14.8.7	Called party extension .....	182
	14.8.8	Called party SSI .....	182
	14.8.9	Calling party type identifier .....	182
	14.8.10	Calling party extension .....	183
	14.8.11	Calling party SSI .....	183
	14.8.12	Call priority .....	183
	14.8.13	Call status .....	183
	14.8.14	Call queued .....	184
	14.8.15	Continue .....	184
	14.8.16	Call time-out .....	184
	14.8.17	Call time-out, set-up phase .....	185
	14.8.18	Disconnect cause .....	185
	14.8.19	DTMF .....	186
	14.8.20	External Subscriber Number (ESN) .....	186
	14.8.21	Encryption control .....	187
	14.8.22	Facility .....	187
	14.8.23	Hook method selection .....	187
	14.8.24	Length indicator .....	187
	14.8.25	New call identifier .....	187
	14.8.26	Modify .....	188
	14.8.27	Notification indicator .....	188
	14.8.28	PDU type .....	188
	14.8.29	Poll request .....	189
	14.8.30	Poll response .....	189
	14.8.31	Poll response addresses .....	189
	14.8.32	Poll response number .....	189
	14.8.33	Poll response percentage .....	190
	14.8.34	Pre-coded status .....	190
	14.8.35	Proprietary .....	190
	14.8.36	Request to transmit/send data .....	190
	14.8.37	Reset call time-out timer (T310) .....	191
	14.8.38	Short data type identifier .....	191
	14.8.39	Simplex/duplex selection .....	191
	14.8.40	Speech service .....	191
	14.8.41	Temporary address .....	191
	14.8.42	Transmission grant .....	192
	14.8.43	Transmission request permission .....	192
	14.8.44	Transmitting party type identifier .....	192
	14.8.45	Transmitting party extension .....	192
	14.8.46	Transmitting party SSI .....	192
	14.8.47	TX demand priority .....	193
	14.8.48	Type 3 element identifier .....	193
	14.8.49	User defined data-1 .....	193
	14.8.50	User defined data-2 .....	193
	14.8.51	User defined data-3 .....	194
	14.8.52	User defined data-4 .....	194
15		Mobility Management (MM) service description .....	194
	15.1	Introduction .....	194
	15.2	Services offered .....	194

15.3	Primitive description.....	195
15.3.1	Service state model for the MS .....	195
15.3.2	Service primitives at the TNMM-SAP, MS/LS side.....	195
15.3.3	Primitive description .....	196
15.3.3.1	TNMM-ATTACH DETACH GROUP IDENTITY primitive ..	196
15.3.3.2	TNMM-DEREGISTRATION primitive .....	196
15.3.3.3	TNMM-DISABLING primitive .....	196
15.3.3.4	TNMM-ENABLING primitive .....	197
15.3.3.5	TNMM-ENERGY SAVING primitive .....	197
15.3.3.6	TNMM-REPORT primitive .....	197
15.3.3.7	TNMM-REGISTRATION primitive .....	197
15.3.3.8	TNMM-SERVICE primitive .....	198
15.3.4	Parameters description .....	198
15.3.5	State description for the MS .....	201
15.3.5.1	Not updated .....	201
15.3.5.2	Wait updating.....	201
15.3.5.3	Updated .....	201
15.3.5.4	Temporary disabled.....	201
15.3.5.5	Permanently disabled .....	201
15.3.6	Service state diagram for the TNMM-SAP .....	202
16	MM protocol.....	205
16.1	Introduction .....	205
16.2	MM procedures .....	206
16.2.1	General.....	206
16.2.2	Services provided by the protocol .....	206
16.2.3	Underlying services assumed by the protocol.....	206
16.2.4	Services assumed from the local environment .....	206
16.3	Protocol functions .....	206
16.3.1	Activation and control of underlying MLE Service .....	208
16.3.1.1	Activation procedure .....	208
16.3.1.2	Deactivation procedure.....	209
16.3.1.3	Maintenance procedures .....	209
16.3.1.3.1	Report and cancel handling .....	209
16.3.1.3.2	Stealing permission and stealing repeats flag handling.....	209
16.3.1.3.3	Busy handling .....	209
16.4	Registration procedure.....	209
16.4.1	MLE initiated registration procedure.....	210
16.4.1.1	Normal registration .....	210
16.4.1.2	Forward registration.....	212
16.4.2	User application initiated registration procedure .....	213
16.4.3	Infrastructure initiated registration procedure.....	216
16.4.4	Colliding registrations .....	217
16.4.5	Expiry of timer T351 .....	217
16.5	Enable and disable procedures .....	217
16.6	De-registration procedure .....	218
16.7	Energy economy mode procedure.....	219
16.8	Attachment/detachment of group identities procedures .....	219
16.8.1	Infrastructure initiated attachment/detachment of group identities procedure .....	220
16.8.2	MS initiated attachment/detachment of group identities procedure .....	221
16.9	MM PDU structures and contents.....	221
16.9.1	MM PDU general description .....	221
16.9.2	MM PDU description tables - downlink.....	223
16.9.2.1	D-ATTACH/DETACH GROUP IDENTITY .....	223
16.9.2.2	D-ATTACH/DETACH GROUP IDENTITY ACKNOWLEDGEMENT .....	223
16.9.2.3	D-DISABLE .....	224
16.9.2.4	D-ENABLE.....	224
16.9.2.5	D-ENERGY SAVING .....	224
16.9.2.6	D-STATUS.....	225
16.9.2.7	D-LOCATION UPDATE ACCEPT .....	225

	16.9.2.8	D-LOCATION UPDATE COMMAND .....	226
	16.9.2.9	D-LOCATION UPDATE REJECT .....	226
	16.9.2.10	D-LOCATION UPDATE PROCEEDING .....	227
16.9.3		MM PDU descriptions - uplink .....	227
	16.9.3.1	U-ATTACH/DETACH GROUP IDENTITY .....	227
	16.9.3.2	U-ATTACH/DETACH GROUP IDENTITY ACKNOWLEDGEMENT .....	227
	16.9.3.3	U-ITSI DETACH .....	228
	16.9.3.4	U-LOCATION UPDATE DEMAND .....	228
	16.9.3.5	U-STATUS .....	229
16.10		MM information elements coding .....	229
	16.10.1	Address extension .....	229
	16.10.2	Cipher control .....	229
	16.10.3	Cipher parameters .....	229
	16.10.4	Cipher key type .....	230
	16.10.5	Class of MS .....	230
	16.10.6	Class of usage .....	231
	16.10.7	Disabling type .....	231
	16.10.8	Distribution on 18th frame .....	231
	16.10.9	Energy saving mode .....	231
	16.10.10	Energy saving information .....	232
	16.10.11	Frame Number (FN) .....	232
	16.10.12	Group identity accept/reject .....	232
	16.10.13	Group identity acknowledgement request .....	232
	16.10.14	Group identity acknowledgement type .....	233
	16.10.15	Group identity address type .....	233
	16.10.16	Group identity attachment lifetime .....	233
	16.10.17	Group identity attach/detach mode .....	233
	16.10.18	Group identity attach/detach type identifier .....	234
	16.10.19	Group identity attachment .....	234
	16.10.20	Group identity detachment downlink .....	234
	16.10.21	Group identity detachment uplink .....	234
	16.10.22	Group identity downlink .....	235
	16.10.23	Group identity location accept .....	235
	16.10.24	Group identity location demand .....	235
	16.10.25	Group identity location demand ack .....	235
	16.10.26	Group identity report .....	236
	16.10.27	Group identity uplink .....	236
	16.10.28	Group Short Subscriber Identity (GSSI) .....	236
	16.10.29	KSG number .....	236
	16.10.30	LA .....	237
	16.10.31	LACC .....	237
	16.10.32	LANC .....	237
	16.10.33	LA timer .....	237
	16.10.34	LA information .....	237
	16.10.35	Location update type .....	238
	16.10.36	MCC .....	238
	16.10.37	MNC .....	238
	16.10.38	Multiframe Number (MN) .....	238
	16.10.39	PDU type .....	239
	16.10.40	New registered area .....	239
	16.10.41	Proprietary .....	239
	16.10.42	Reject cause .....	240
	16.10.43	Request to append LA .....	240
	16.10.44	SSI .....	240
	16.10.45	SCCH information .....	241
	16.10.46	SCCH information and distribution on 18th frame .....	241
	16.10.47	SCK number .....	241
	16.10.48	Status .....	241
	16.10.49	Subscriber class .....	242
	16.10.50	TEI .....	242
	16.10.51	Type 3 element identifier .....	242
	16.10.52	(V)GSSI .....	242

16.11	Parameters .....	243
16.11.1	Timers .....	243
16.11.1.1	Timer T351: Registration response time .....	243
17	MLE service description .....	243
17.1	Introduction .....	243
17.2	Summary of services offered by MLE protocol .....	243
17.3	Service descriptions .....	246
17.3.1	Service state diagram for the LMM-SAP .....	246
17.3.2	Service primitives for the LMM-SAP .....	247
17.3.3	Service state diagram for the LCMC-SAP .....	249
17.3.4	Service primitives for LCMC-SAP .....	250
17.3.5	Service state diagram for the LSCL-SAP .....	251
17.3.6	Service primitives for LSCL-SAP .....	251
17.3.7	Service state diagram for the LCO-SAP .....	252
17.3.8	Service primitives for LCO-SAP .....	253
17.3.9	Parameter summary .....	254
18	MLE protocol .....	256
18.1	Introduction .....	256
18.2	Overview of the sub-layer .....	257
18.2.1	Protocol environment .....	257
18.2.2	Services and primitives offered by the MLE to the MM entity .....	258
18.2.3	Services and primitives offered by the MLE to the CMCE entities .....	259
18.2.4	Services and primitives offered by the MLE to the SCLNP entity .....	260
18.2.5	Services and primitives offered by the MLE to the CONP entity .....	260
18.2.6	Services and primitives offered by layer 2 to MLE .....	261
18.2.7	Services and primitives between the MLE and the LLME .....	261
18.2.8	Protocol sequences .....	262
18.3	MLE functions .....	265
18.3.1	Overview .....	265
18.3.2	Access to the communication resources and activation of the MLE .....	266
18.3.3	Deactivation of the MLE .....	267
18.3.4	Attachment management sub-entity .....	267
18.3.4.1	Scanning of cells .....	267
18.3.4.2	Monitoring of neighbour cells .....	268
18.3.4.3	Surveillance of the serving cell .....	268
18.3.4.4	Ranking of neighbour cells .....	268
18.3.4.4.1	Ranking of monitored cells .....	269
18.3.4.4.2	Ranking of scanned cells .....	269
18.3.4.5	Criteria used during cell re-selection .....	269
18.3.4.5.1	Criterion for starting the monitoring process .....	269
18.3.4.5.2	Criterion for starting scanning .....	270
18.3.4.5.3	Criterion for radio link failure .....	270
18.3.4.5.4	Criterion for radio relinquishable cell .....	270
18.3.4.5.5	Criterion for radio improvable cell .....	270
18.3.4.5.6	Criterion for radio usable cell .....	271
18.3.4.5.7	Criteria for initiating the cell re-selection procedures .....	271
18.3.4.6	Initial cell selection .....	273
18.3.4.7	Cell re-selection .....	273
18.3.4.7.1	Determination of which type of re-selection to apply .....	275
18.3.4.7.2	Undeclared cell re-selection .....	276
18.3.4.7.3	Unannounced cell re-selection .....	277
18.3.4.7.4	Announced cell re-selection - type 3 .....	279
18.3.4.7.5	Announced cell re-selection - type 2 .....	281
18.3.4.7.6	Announced cell re-selection - type 1 .....	284
18.3.5	Data transfer sub-entity .....	287
18.3.5.1	Address handling .....	287
18.3.5.1.1	Link addressing .....	287
18.3.5.1.2	Link addresses to be placed in layer 2 .....	288