

SLOVENSKI STANDARD
SIST ETS 300 393-2 E1:2003

01-december-2003

Radijska oprema in sistemi (RES) - Vseevropski prizemni snopovni radio (TETRA) - Optimirani paketirani podatki (PDO) - 2. del: Radijski vmesnik (AI)

Terrestrial Trunked Radio (TETRA); Packet Data Optimized (PDO); Part 2: Air Interface (AI)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: SIST ETS 300 393-2 E1:2003
<https://standards.iteh.ai/catalog/standards/sist/1247/la-a87b-40c3-ae95-e3854443bb9e/sist-ets-300-393-2-e1-2003>

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	------------------------------------	--------------------------------------

SIST ETS 300 393-2 E1:2003 **en**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

SIST ETS 300 393-2 E1:2003
<https://standards.iteh.ai/catalog/standards/sist/a12477fa-a87b-40c3-ae95-e3854443bb9e/sist-ets-300-393-2-e1-2003>



EUROPEAN TELECOMMUNICATION STANDARD

ETS 300 393-2

May 1996

Source: ETSI TC-RES

Reference: DE/RES-06004-2

ICS: 33.020, 33.060.50

Key words: TETRA, PDO

iTeh STANDARD PREVIEW
Radio Equipment and Systems (RES);
(standards.iteh.ai)
Trans-European Trunked Radio (TETRA);
Packet Data Optimized (PDO);
<https://standards.iteh.ai/catalog/standards/sist/a12477fa-a87b-40c3-ae95-e3844769/sist-300-393-2>
Part 2: Air Interface (AI)

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

*

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 393-2 E1:2003](https://standards.iteh.ai/catalog/standards/sist/a12477fa-a87b-40c3-ae95-e3854443bb9e/sist-ets-300-393-2-e1-2003)
<https://standards.iteh.ai/catalog/standards/sist/a12477fa-a87b-40c3-ae95-e3854443bb9e/sist-ets-300-393-2-e1-2003>

Contents

Foreword	19
1 Scope	21
2 Normative references.....	21
3 Definitions, symbols and abbreviations	22
3.1 Definitions	22
3.2 Symbols	23
3.3 Abbreviations	23
4 Radio aspects.....	24
4.1 Introduction	24
4.2 Set of logical channels	24
4.3 Reference configuration.....	24
4.4 Error control schemes.....	25
4.5 Multiple access and time slot structure.....	25
4.5.1 Sub-bursts	25
4.5.1.1 Downlink sub-bursts	25
4.5.1.2 Uplink sub-bursts.....	25
4.5.2 Bursts	26
4.5.2.1 Downlink bursts	26
4.5.2.2 Uplink bursts.....	26
4.6 Coding, interleaving and scrambling.....	27
4.7 Modulation	27
4.8 Transmission and reception.....	27
4.9 Other radio-related functions	27
4.10 Performance	28
https://standards.iteh.ai/catalog/standards/sist/a12477fa-a87b-40c3-ae95-e3854443bb9e/sist-ets-300-393-2-e1-2003	
5 Modulation.....	28
5.1 Introduction	28
5.2 Modulation type.....	28
5.3 Modulation rate	28
5.4 Modulation symbol definition.....	28
5.5 Modulated signal definition	29
5.6 Modulation filter definition	30
5.7 Modulation block diagram.....	30
6 Radio transmission and reception.....	30
6.1 Introduction	30
6.2 Frequency bands and channel arrangement	30
6.3 Reference test planes.....	31
6.4 Transmitter characteristics	31
6.4.1 Output power.....	31
6.4.1.1 BS	32
6.4.1.2 MS	32
6.4.2 Unwanted conducted emissions.....	32
6.4.2.1 Definitions	32
6.4.2.2 Unwanted emissions close to the carrier.....	33
6.4.2.2.1 Measurement over the useful part of the burst.....	33
6.4.2.2.2 Measurement during the switching transients	33
6.4.2.3 Unwanted emissions far from the carrier.....	33
6.4.2.4 Unwanted emissions during the CLCH and BLCH	34
6.4.2.5 Unwanted emissions in the non-transmit state.....	34
6.4.3 Unwanted radiated emissions	34

6.4.4	Radio frequency tolerance	34
6.4.5	RF Output power time mask.....	34
6.4.5.1	BS	36
6.4.5.2	MS.....	36
6.4.6	Intermodulation attenuation	36
6.4.6.1	Definition	36
6.4.6.2	BS	36
6.4.6.3	MS.....	36
6.4.7	Intra-BS intermodulation requirements	37
6.5	Receiver characteristics	37
6.5.1	Blocking characteristics	37
6.5.1.1	Definition	37
6.5.1.2	Specification.....	37
6.5.2	Spurious response rejection	38
6.5.2.1	Definition	38
6.5.2.2	Specification.....	38
6.5.3	Intermodulation response rejection	38
6.5.3.1	Definition	38
6.5.3.2	Specification.....	38
6.5.4	Unwanted conducted emissions	39
6.5.4.1	Definition	39
6.5.4.2	Specification.....	39
6.5.5	Unwanted radiated emissions.....	39
6.6	Transmitter/receiver performance.....	39
6.6.1	Modulation accuracy	39
6.6.1.1	Ideal case.....	39
6.6.1.2	Vector error magnitude requirement at symbol time.....	40
6.6.2	Receiver performance	40
6.6.2.1	Nominal error rates	41
6.6.2.2	Dynamic reference sensitivity performance	41
6.6.2.2.1	BS receiver performance	41
6.6.2.2.2	MS receiver performance	42
6.6.2.3	Reference interference performance	42
6.6.2.3.1	BS receiver performance	42
6.6.2.3.2	MS receiver performance	42
6.6.2.4	Static reference sensitivity performance	42
6.6.2.4.1	BS receiver performance	43
6.6.2.4.2	MS receiver performance.....	43
6.6.2.5	MS receiver performance for synchronisation burst acquisition	43
6.6.3	Propagation conditions	43
6.6.3.1	Propagation conditions - introduction.....	43
6.6.3.2	Tap-gain process types.....	44
6.6.3.3	Propagation models	45
7	Radio sub-system synchronisation	45
7.1	General description of synchronisation system.....	45
7.2	Timebase counters.....	45
7.2.1	Downlink	45
7.2.1.1	Timing counters	45
7.2.1.2	Values of counters	46
7.2.2	Uplink.....	46
7.2.2.1	Timing counters	46
7.2.2.2	Values of counters	46
7.3	Timing of transmitted signals	46
7.4	BS requirements for synchronisation	47
7.5	MS requirements for synchronisation.....	47
8	Channel coding	47
8.1	Introduction.....	47
8.2	General.....	47
8.2.1	Interfaces in the error control structure.....	47
8.2.2	Notation	49

8.2.3	Definition of error control codes	49
8.2.3.1	16-state Rate-Compatible Punctured Convolutional (RCPC) codes	49
8.2.3.1.1	Encoding by the 16-state mother code of rate 1/4.....	49
8.2.3.1.2	Puncturing of the mother code.....	50
8.2.3.1.3	Puncturing scheme of the RCPC code of rate 2/3.....	50
8.2.3.2	(K_1+16, K_1) block code	50
8.2.4	Definition of interleaving schemes.....	51
8.2.4.1	Block interleaving.....	51
8.2.5	Definition of scrambling	51
8.2.5.1	Scrambling method.....	51
8.2.5.2	Scrambling sequence	51
8.3	Error control schemes.....	52
8.3.1	Master Block CHannel (MBCH).....	52
8.3.2	Normal Block CHannel (NBCH)	52
9	Channel multiplexing	53
9.1	Logical channels for passing MAC blocks to the channel coding	53
9.2	The physical resource.....	54
9.2.1	General.....	54
9.2.2	Radio frequency channels	54
9.3	Physical channel	54
9.3.1	Sub-burst.....	54
9.3.2	Bursts	54
	9.3.2.1 General	54
	9.3.2.2 Modulation symbols numbering	55
	9.3.2.3 Modulation bit numbering	55
	9.3.2.4 Burst timing	55
9.3.3	Type of burst and burst timing	55
	9.3.3.1 General	55
	9.3.3.2 Modulation bits allocation	56
	9.3.3.2.1 Uplink start sub-burst	56
	9.3.3.2.2 Uplink even sub-burst	56
	9.3.3.2.3 Uplink odd sub-burst	56
	9.3.3.2.4 Uplink end sub-burst	56
	9.3.3.2.5 Downlink normal sub-burst	56
	9.3.3.2.6 Downlink synchronisation sub-burst	57
	9.3.3.2.7 Linearisation up-link burst	57
	9.3.3.3 Sub-burst fields	57
	9.3.3.3.1 Frequency correction field	57
	9.3.3.3.2 Normal training sequence	57
	9.3.3.3.3 Extended training sequence	58
	9.3.3.3.4 Synchronisation training sequence	58
	9.3.3.3.5 Tail bits	58
	9.3.3.3.6 Phase adjustment bits	58
9.4	Mapping of multiplexed blocks into sub-bursts	58
9.4.1	Mapping of multiplexed blocks into sub-bursts on the downlink	58
9.4.2	Mapping of multiplexed blocks into sub-bursts on the uplink	59
9.4.3	Timing of transmission	59
10	Radio subsystem link control.....	61
10.1	Scope	61
10.2	General	61
10.3	RF power control.....	62
	10.3.1 Overall process	62
	10.3.2 MS power control implementation	62
	10.3.3 MS power control range	62
10.4	Definition of path loss formulae	63
	10.4.1 Path loss parameter C1	63
	10.4.2 Path loss parameter C2	63
	10.4.3 Path loss parameter C3	64

10.4.4	Path loss parameter C4	64
10.5	Monitoring measurements.....	65
10.5.1	Signal strength measurement.....	65
10.6	Scanning measurement	65
10.6.1	Foreground scanning.....	65
10.6.2	Background scanning (optional)	66
10.6.2.1	Signal strength measurements	66
10.6.2.2	Cell selection parameters measurement	66
10.6.3	Interrupting scanning	66
10.6.3.1	Signal strength measurements	66
10.6.3.2	Cell selection parameters measurement	66
10.7	Selection formulae	67
10.7.1	Initial cell selection.....	67
10.7.2	Cell re-selection	67
10.7.2.1	Criterion for relinquishable link.....	68
10.7.2.2	Criterion for improvable link	68
10.8	Measuring quality of serving cell	69
10.8.1	Downlink measurements	69
10.8.1.1	Cell (re-)selection parameters decoding	69
10.8.1.2	Signal strength	69
10.8.1.3	Radio downlink counter	69
10.9	Radio link measurements of signal quality.....	70
10.9.1	Received signal strength	70
10.9.2	RDC counter	70
10.9.3	BER	70
10.9.4	MER	70
10.10	Control parameters	70
10.10.1	Parameters	70
11	Connection Oriented Network Service description (CONS) (ISO/IEC 8348 and ISO/IEC 8878 delta).....	73
11.1	Introduction.....	73
11.2	Organisation of this document.....	73
11.3	Service description.....	73
11.4	ISO/IEC 8878 delta	74
11.4.1	Scope and field of application.....	74
11.4.2	References	74
11.4.3	Definitions	74
11.4.4	Abbreviations	74
11.4.5	Overview	74
	11.4.5.1 Elements of the X.25/PLP 1984 used to support the OSI CONS.....	74
	11.4.5.2 General operation of the X 25 PLP 1984 for supporting the OSI CONS.....	78
11.4.6	Network connection establishment phase	78
	11.4.6.1 Primitive/parameter and packet field relationships	78
	11.4.6.2 Procedures	78
	11.4.6.2.1 Primitive and packet mapping	78
	11.4.6.2.2 NSAP addresses	78
	11.4.6.2.3 Receipt confirmation selection	78
	11.4.6.2.4 Expedited data selection	78
	11.4.6.2.5 QoS parameter set	78
	11.4.6.2.6 NS user data	79
11.4.7	Network connection release phase	79
	11.4.7.1 Primitive/Parameter and packet/field relationships	79
	11.4.7.2 Procedures	79
11.4.8	Data transfer phase: data transfer service	79
	11.4.8.1 Primitive/Parameter and packet/field relationship	79
	11.4.8.2 Procedures	79
11.4.9	Data transfer phase: receipt confirmation service	79
11.4.10	Data transfer phase: expedited data transfer service	79
11.4.11	Data transfer phase: reset service	79
11.4.12	Response to protocol violation.....	79

11.4.13	Conformance.....	80
11.5	Annex A: X.25 1980 sub-network dependant convergence protocol (normative)	80
11.6	Annex B: Classification (normative)	80
11.7	Annex C: Sub-network convergence protocol for use with X.25 permanent virtual circuits (normative)	80
11.8	Annex D: Protocol implementation conformance statement proforma (normative).....	80
11.9	Annex E: Additional considerations of CONS primitives (informative).....	80
11.10	Annex F: Use of X.25/PLP NPAI (informative)	80
11.11	Annex G: Transit delay calculations (informative)	80
11.12	Annex H: Example of priority negotiation (informative).....	80
11.13	Annex I: Differences between CCITT Recommendation X.223 and ISO/IEC 8878 [9] (informative).....	80
12	CONP protocol (ISO/IEC 8208 delta).....	80
12.1	Introduction	80
12.2	Organisation of this clause	81
12.3	Overview of the protocol	81
12.3.1	Position of the protocol in the network layer.....	81
12.3.2	Services provided by the protocol	81
12.3.3	Underlying services assumed by the protocol.....	81
12.3.4	Services assumed from the local environment	81
12.4	ISO/IEC 8208 delta	81
12.4.1	Scope	81
12.4.2	Normative references	82
12.4.3	General considerations	82
12.4.4	Procedures for restart	83
12.4.5	Procedures for virtual call set-up and clearing	84
12.4.6	Procedures for data and interrupt transfer.....	85
12.4.7	Procedures for flow control.....	85
12.4.8	Procedures for reset.....	85
12.4.9	Effects of clear, reset, restart procedures on the transfer of packets	85
12.4.10	Effects of layer 1 and 2 on the packet layer	86
12.4.11	Error handling.....	86
12.4.12	Packet format.....	86
12.4.13	Procedures for optional user facilities.....	86
12.4.14	Procedures for optional CCITT specified DTE facilities	86
12.4.15	Format for facility field in call set-up clearing packets	86
12.4.16	Format for registration field in registration packets	86
12.4.17	Diagnostic codes	86
12.4.18	Timers and re-transmission counts.....	86
12.4.19	State diagrams	86
12.4.20	State tables	86
12.4.21	Annex A: Private networks	86
12.4.22	Annex B: Differences between the first and the second editions of ISO/IEC 8208	86
12.4.23	Amendment 1: Alternative logical channel identifier assignment.....	87
12.5	Protocol functions	87
12.6	Provision of the underlying protocol	87
12.6.1	Mapping of the primitives	87
12.6.2	Mapping of QoS	88
13	Specific-ConnectionLess Network Service description (S-CLNS)	88
13.1	Introduction	88
13.1.1	Specific connectionless service.....	89
13.1.2	ISO principles of connectionless-mode transmission	89
13.1.3	General principles	90
13.1.4	Sub-addresses	90
13.2	S-CLNS service description.....	90
13.2.1	SAP	90
13.2.2	Services available at the TN-SCLNS SAP	90
13.2.3	Full and slim services	91
13.2.3.1	Data transfer service	91
13.2.3.2	Facilities provided by the service	91

13.3	Primitive definitions	92
13.3.1	Primitives types.....	92
13.3.2	Data transfer primitives.....	92
13.3.3	Sequence of data transfer primitives	93
13.3.4	Contents of primitives	93
13.3.4.1	Parameter definitions	93
13.3.4.2	TN-UNITDATA primitives.....	94
13.3.4.3	TN-DELIVERY primitives	95
13.3.5	State description	95
14	Protocol for providing the Specific Connectionless network service (S-CLNP).....	96
14.1	Introduction.....	96
14.2	Overview of the protocol.....	96
14.2.1	Position of the protocol in the NWK layer	96
14.2.2	Slim subset of the protocol	97
14.2.3	Addresses.....	97
14.2.4	Services provided by the protocol.....	97
14.2.4.1	Data transfer service	97
14.2.4.2	Facilities	98
14.2.5	Underlying services assumed by the protocol	98
14.2.6	One instance of protocol.....	98
14.2.7	Service assumed from the local environment.....	99
14.3	Overview of the PDU structures.....	99
14.4	PDU descriptions.....	100
14.4.1	General format.....	100
14.4.2	<S1-DT>and <S2-DT> PDU headers with short address	101
14.4.3	<S1-DT>and <S2-DT> PDU headers with long address	102
14.4.4	<S3-DT> PDU header	102
14.4.5	<S2-DEL> PDU header with short address	103
14.4.6	<S2-DEL> PDU header with long address	103
14.4.7	<S3-DEL> PDU header	104
14.5	Formats of fields.....	104
14.5.1	General principles.....	104
14.5.2	Fixed part fields	105
	https://standards.ieee.org/standard/sist-112477fa-a87b-40c3-ac95-e3854413bb9e/sist-ets-300-393-2-e1-2003	
	14.5.2.1 Version (4 bits)	105
	14.5.2.2 Type (4 bits)	105
	14.5.2.3 Flags (4 bits)	105
	14.5.2.4 Packet length (12 bits)	105
14.5.3	Address part fields	106
14.5.4	Facility part fields	106
14.5.4.1	Sub-address.....	106
14.5.4.2	Priority	106
14.5.4.3	Delivery/Storage request.....	106
14.5.4.4	Report request	107
14.5.4.5	Disposition.....	107
14.5.4.6	Multicast area selection.....	108
14.5.4.7	Time stamp	108
14.5.4.8	Packet route	108
14.5.5	Header checksum.....	109
14.5.6	User data part	109
14.6	Primitive definitions and format.....	109
14.7	Protocol functions.....	109
14.7.1	Data PDU composition	110
14.7.1.1	<S1-DT> PDU composition.....	111
14.7.1.2	<S2-DT> PDU composition.....	111
14.7.1.3	<S3-DT> PDU composition.....	111
14.7.1.4	Composition of facility fields.....	112
14.7.2	Delivery PDU composition	112
14.7.2.1	<S1-DEL> PDU composition	112
14.7.2.2	<S2-DEL> PDU composition	112
14.7.2.3	<S3-DEL> PDU composition	113
14.7.2.4	Composition of facility fields.....	113
14.7.3	Data PDU decomposition	113

14.7.4	Delivery PDU decomposition.....	113
14.7.5	Route PDU	114
14.7.6	Forward PDU.....	114
14.7.7	Discard PDU.....	114
14.7.8	PDU header error detection	114
14.7.9	Facility functions.....	115
14.7.9.1	Sub-addressing.....	115
14.7.9.2	Priority.....	115
14.7.9.3	D/S (delivery/storage) request	116
14.7.9.3.1	Delivery facility	116
14.7.9.3.2	Storage facility	116
14.7.9.4	Report request.....	116
14.7.9.5	Multicast area selection	116
14.7.9.6	Time stamping	116
14.7.9.7	Disposition report.....	117
14.8	Provision of the underlying service	117
14.8.1	General.....	117
14.8.2	Operation over MLE	117
14.9	Conformance	118
14.10	Algorithms for PDU header error detection function	118
14.10.1	Symbols used in algorithms	118
14.10.2	Arithmetic conventions	118
14.10.3	Algorithm for generating checksum parameters	118
14.10.4	Algorithms for checking checksum parameters	119
14.10.5	Algorithm to adjust the checksum parameter when an octet is altered.....	119
15	Mobility Management (MM): service description	120
15.1	Introduction	120
15.2	Services offered	120
15.3	Primitive description.....	120
15.3.1	Service state model for the MS	121
15.3.2	Service primitives for the MS	121
15.3.2.1	Primitives for authentication of the network.....	121
15.3.2.2	Primitives for de-registration (detach).....	121
15.3.2.3	Primitives for indication of the state of a mobile	121
15.3.2.4	Primitives for registration	122
15.3.2.5	Primitives for the energy saving mode	122
15.3.3	Primitive summary.....	122
15.3.4	Parameters definition	122
15.3.5	State description for the MS	123
15.3.5.1	Not updated	123
15.3.5.2	Wait updating.....	123
15.3.5.3	Updated	123
15.3.5.4	Temporary disabled.....	123
15.3.5.5	Permanently disabled	123
15.3.6	Service state diagram for the TNMM-SAP	124
16	PDO MM protocol.....	127
16.1	Introduction	127
16.2	MM procedures	128
16.2.1	General.....	128
16.2.2	Services provided by the protocol	128
16.2.3	Underlying services assumed by the protocol.....	128
16.2.4	Services assumed from the local environment	128
16.3	Protocol functions	128
16.3.1	Activation and control of underlying MLE Service	130
16.3.1.1	Activation procedure	130
16.3.1.2	Deactivation procedure	130
16.3.1.3	Maintenance procedures	131
16.3.1.3.1	Report and cancel handling	131
16.4	Registration procedure.....	131
16.4.1	MLE initiated registration procedure.....	131
16.4.1.1	Normal registration	131

16.4.2	User application initiated registration procedure.....	133
16.4.3	Infrastructure initiated registration procedure	136
16.4.4	Colliding registrations	137
16.4.5	Expiry of timer T351.....	137
16.5	De-registration procedure	137
16.6	Energy economy procedure	138
16.7	Group identity network download	138
16.8	MM PDUs structures and contents	139
16.8.1	MM PDU general description.....	139
16.8.2	MM PDU description tables - downlink.....	140
16.8.2.1	D-GROUP IDENTITY COMMAND.....	141
16.8.2.2	D-DISABLE	141
16.8.2.3	D-ENABLE	141
16.8.2.4	D-ENERGY SAVING.....	141
16.8.2.5	D-LOCATION UPDATE ACCEPT.....	142
16.8.2.6	N UPDATE COMMAND	142
16.8.2.7	D-LOCATION UPDATE REJECT	142
16.8.2.8	D-LOCATION UPDATE PROCEEDING	143
16.8.2.9	D-STATUS	143
16.8.3	MM PDU descriptions - uplink	143
16.8.3.1	GROUP-IDENTITY-ACKNOWLEDGE	144
16.8.3.2	U-ITSI DETACH	144
16.8.3.3	U-LOCATION UPDATE DEMAND.....	144
16.8.3.4	U-STATUS	145
16.9	MM information elements coding	145
16.9.1	Address extension	145
16.9.2	Class of MS	145
16.9.3	Class of usage	146
16.9.4	Disabling type	147
16.9.5	Energy Saving Mode (ESM)	147
16.9.6	Energy saving information	147
16.9.7	Location Area (LA)	147
16.9.8	Location Area Country Code (LACC)	147
16.9.9	LA information	148
16.9.10	LANC	148
16.9.11	LA timer	148
16.9.12	Location update type	148
16.9.13	MCC	148
16.9.14	MNC	149
16.9.15	New Registered Area (NRA)	149
16.9.16	PDU type	150
16.9.17	Proprietary	150
16.9.18	Reject Cause (RC)	151
16.9.19	Request to append LA	151
16.9.20	SSI	151
16.9.21	Status	152
16.9.22	Subscriber class	152
16.9.23	TETRA Equipment Identity (TEI)	152
16.9.24	Type 3 element identifier	153
16.9.25	Visitor Group Short Subscriber Identity ((V)GSSI)	153
16.10	Primitives definition	153
16.11	Parameters.....	153
16.11.1	Timers.....	153
16.11.1.1	Timer T351 -Registration response time	153
17	MLE service description.....	153
17.1	Introduction.....	153
17.2	Summary of services offered by MLE protocol	154
17.3	Detailed service descriptions.....	155
17.3.1	Services and primitives at the LMM-SAPs.....	155
17.3.1.1	Service state diagram for the LMM-m-SAP (mobile side).	156
17.3.1.2	Service primitives for the LMM-SAPs	156
17.3.2	Services and primitives at the LSCL-SAP	158

17.3.2.1	MS attachment	158
17.3.2.2	Data transfer.....	158
17.3.2.3	Service state diagram for the LSCL SAP	159
17.3.2.4	Service primitives for LSCL SAP	159
17.3.3	Services and primitives at the LCO-SAP.....	160
17.3.3.1	Radio link establishment.....	160
17.3.3.2	Connection restoration.....	160
17.3.3.3	Data transfer	160
17.3.3.4	Service state diagram for the LCO SAP	161
17.3.3.5	Service primitives for LCO SAP	161
18	PDO MLE protocol	162
18.1	Introduction	162
18.2	Overview of the sub-layer	163
18.2.1	Protocol environment	163
18.2.2	Services and primitives offered by the MLE to the MM entity.....	164
18.2.3	Services and primitives offered by the MLE to the SCLNP entity.....	165
18.2.4	Services and primitives offered by the MLE to the CONP entity	165
18.2.5	Services and primitives offered by layer 2 to MLE	166
18.2.6	Services and primitives between the MLE and the LLME	167
18.2.7	Protocol sequences	167
18.3	MLE functions	171
18.3.1	Overview.....	171
18.3.2	Access to the communication resources and activation of the MLE	172
18.3.3	Deactivation of the MLE	172
18.3.4	Attachment management sub entity.....	172
18.3.4.1	Scanning of cells.....	173
18.3.4.2	Monitoring of neighbour cells.....	173
18.3.4.3	Surveillance of the serving cell	174
18.3.4.4	Ranking of neighbour cells	174
18.3.4.4.1	Ranking of monitored cells	175
18.3.4.4.2	Ranking of scanned cells.....	175
18.3.4.5	Criteria used during cell re-selection	175
18.3.4.5.1	SIST ETS 300 393-2 E1:2003 Criterion for starting the monitoring process	175
18.3.4.5.2	e3854443bb9e/sist-ets-300-393-2-e1-2013 Criterion for starting scanning.....	175
18.3.4.5.3	Criterion for radio link failure.....	175
18.3.4.5.4	Criterion for radio relinquishable cell... 176	176
18.3.4.5.5	Criterion for radio improvable cell	176
18.3.4.5.6	Criterion for radio usable cell	176
18.3.4.5.7	Criteria for initiating the cell re-selection procedures.....	176
18.3.4.6	Initial cell selection.....	178
18.3.4.7	Cell re-selection	179
18.3.4.7.1	18.3.4.7.1 Determination of which type of re-selection to apply	180
18.3.4.7.2	18.3.4.7.2 Undeclared cell re-selection	181
18.3.4.7.3	18.3.4.7.3 Unannounced cell re-selection	182
18.3.4.7.4	18.3.4.7.4 Announced cell re-selection - type 3 ... 184	184
18.3.4.7.5	18.3.4.7.5 Announced cell re-selection - type 2 ... 186	186
18.3.5	Data transfer sub entity	189
18.3.5.1	Address handling	189
18.3.5.1.1	Link addressing.....	189
18.3.5.1.2	Link addresses to be placed in layer 2 189	189
18.3.5.1.3	Layer 2 end point identifier.....	189
18.3.5.1.4	Subscriber class	190
18.3.5.2	MLE connection handling	190
18.3.5.3	Message routing and selection of LLC services	190
18.3.5.3.1	18.3.5.3.1 Selection of LLC services via TLA-SAP	190
18.3.5.3.2	18.3.5.3.2 Selection of LLC services via TLB-SAP	193

iTeh STANDARDS PREVIEW
(standards.iteh.ai)

https://standards.iteh.ai/catalog/standards/sistv12477fa-as/0-40c3-ac95-
e3854443bb9e/sist-ets-300-393-2-e1-2013

	18.3.5.3.3	Selection of LLC services via TLC-SAP	193
	18.3.5.4	Routing of local control information.....	194
18.3.6	Network broadcast sub entity	195	
	18.3.6.1	Summary.....	195
	18.3.6.2	System information	195
	18.3.6.3	Message formats for system information.....	196
	18.3.6.4	Network broadcast procedures.....	196
	18.3.6.5	Neighbour cell enquiry procedure	196
18.3.7	Management sub-entity	196	
18.4	PDU descriptions.....	197	
18.4.1	Data transfer PDUs at the TLA SAP.....	197	
	18.4.1.1	Protocol discriminator	197
	18.4.1.2	PDU type.....	197
	18.4.1.3	MLE service user PDUs.....	197
	18.4.1.4	MLE protocol PDUs.....	197
	18.4.1.4.1	D-NWRK-BROADCAST.....	199
	18.4.1.4.2	D-NEW-CELL.....	199
	18.4.1.4.3	D-PREPARE-FAIL.....	199
	18.4.1.4.4	D-RESTORE-ACK	199
	18.4.1.4.5	D-RESTORE-FAIL	200
	18.4.1.4.6	U-PREPARE	200
	18.4.1.4.7	U-RESTORE	201
	18.4.1.5	D-MLE-SYSINFO	201
18.5	Information elements coding	201	
	18.5.1	Announced cell re-selection types supported	201
	18.5.2	BS service details	202
	18.5.3	Cell identifier	202
	18.5.4	Cell re-select parameters	203
	18.5.5	Cell service level	203
	18.5.6	Channel command valid	203
	18.5.7	Fail cause	204
	18.5.8	Late entry information	204
	18.5.9	LA	204
	18.5.10	Main carrier number	204
	18.5.11	Main carrier number extension	205
	18.5.12	Maximum MS transmit power	205
	18.5.13	Minimum RX access level	205
	18.5.14	MCC	205
	18.5.15	MNC	206
	18.5.16	Neighbour cell broadcast	206
	18.5.17	Neighbour cell information	206
	18.5.18	Neighbour cell synchronised	207
	18.5.19	Number of neighbour cells	207
	18.5.20	PDU type	207
	18.5.21	Protocol discriminator	207
	18.5.22	Subscriber class	208
	18.5.23	TETRA network time	208
	18.5.24	Timeshare cell information	208
18.6	Timers	209	
	18.6.1	Timer T370 - Cell re-selection preparation response time	209
19	Service description for PDO layer 2.....	209	
19.1	Layer 2 service descriptions	209	
	19.1.1	SAPs	209
	19.1.2	Services available at the layer 2 SAPs	210
	19.1.2.1	Services at the TLA-SAP	210
	19.1.2.2	Services at the TLB-SAP	211
	19.1.2.3	Services at the TLC-SAP	211
19.2	Primitive definitions	211	
	19.2.1	Primitives types	211
	19.2.2	Summary of primitives	211
	19.2.2.1	Primitives used at the TLA-SAP	211

	19.2.2.2	Primitives used at the TLB-SAP	212
	19.2.2.3	Primitives used at the TLC-SAP	212
19.2.3	Contents of primitives.....		213
	19.2.3.1	Parameter definitions.....	213
	19.2.3.2	TLA-SAP primitives	214
	19.2.3.2.1	TL-CONNECT primitives	214
	19.2.3.2.2	TL-DATA primitives.....	214
	19.2.3.2.3	TL-UNITDATA primitives	214
	19.2.3.3	TLB-SAP primitives	215
	19.2.3.3.1	TL-BROADCAST_1 primitives.....	215
	19.2.3.3.2	TL-BROADCAST_2 primitives.....	215
	19.2.3.4	TLC-SAP primitives	215
	19.2.3.4.1	TL-SCAN primitives	215
	19.2.3.4.2	TL-SERVING primitives	215
	19.2.3.4.3	TL-MONITOR primitives	215
	19.2.3.4.4	TL-SELECT primitives	216
	19.2.3.4.5	TL-ADDLIST primitives	216
20	Layer 2 PDUs and elements		216
20.1	Overview		216
20.2	Block structure		216
	20.2.1	Presiding block	216
	20.2.2	Following block.....	216
	20.2.3	Master block	217
	20.2.4	Block header	217
20.3	PDUs.....		217
	20.3.1	Uplink Response (UR).....	220
	20.3.2	Uplink Data, type 1 (UD1)	221
	20.3.3	Uplink Data, type 2 (UD2)	222
	20.3.4	Downlink Response, type 1 (DR1).....	223
	20.3.5	Downlink Response, type 2 (DR2)	224
	20.3.6	Downlink Response, type 3 (DR3)	225
	20.3.7	Access Announce (AA).....	227
	20.3.8	Downlink Data, type 1 (DD1).....	228
	20.3.9	Downlink Data, type 2 (DD2)	229
	20.3.10	Wake Up (WU).....	230
	20.3.11	Access Parameters (AP).....	231
	20.3.12	System INformation, type 2 (SIN2).....	232
	20.3.13	System INformation, type 1 (SIN1).....	233
20.4	Elements in the PDUs.....		233
	20.4.1	Access parameters element.....	234
	20.4.1.1	Access period length field.....	234
	20.4.1.2	Busy flag mode field	234
	20.4.1.3	Max access retries field	234
	20.4.1.4	Max data field	234
	20.4.2	Access window definition	235
	20.4.2.1	Direct priority field	235
	20.4.2.2	Max. random number for priority no x (MAXRNx)	235
	20.4.2.3	Min random number for priority no x (MINRNx).....	236
	20.4.2.4	Number of Access Periods field (NAP)	236
	20.4.2.5	Priority no x field.	236
	20.4.2.6	Retry Delay field (RD)	237
	20.4.3	Ack flag.....	237
	20.4.4	Assign element.....	238
	20.4.4.1	Address MASK field (AMASK).....	238
	20.4.4.2	Assigned event label field	238
	20.4.4.3	Low Duty FLAG (LOD FLAG)	238
	20.4.4.4	Random Access label FLAG (RA FLAG).....	239
	20.4.4.5	Subscriber CLass field (SCL)	239
	20.4.4.6	Specimen short subscriber identity field	239
	20.4.4.7	Very Low Duty FLAG (VLD FLAG)	239
	20.4.5	Auxiliary address	239
	20.4.5.1	Address type element.....	240