



SLOVENSKI STANDARD SIST EN 1474-2:2020

01-december-2020

Nadomešča:
SIST EN 1474-2:2009

Napeljave in oprema za utekočinjeni zemeljski plin - Načrtovanje in preskušanje obalnih pretakališč - 2. del: Načrtovanje in preskušanje cevi za pretakanje

Installation and equipment for liquefied natural gas - Design and testing of marine transfer systems - Part 2: Design and testing of transfer hoses

Anlagen und Ausrüstung für Flüssigerdgas - Auslegung und Prüfung von Schiffsübergabesystemen - Teil 2: Auslegung und Prüfung von Übergabeschläuchen
(standards.iteh.ai)

Installations et équipements de gaz naturel liquéfié - Conception et essais des systèmes de transfert marins - Partie 2: Conception et essais des tuyaux de transfert

<https://standards.iteh.ai/catalog/standards/sist/en-1474-2-2020/0a993335df4d/sist-en-1474-2-2020>

Ta slovenski standard je istoveten z: EN 1474-2:2020

ICS:

75.200	Oprema za skladiščenje nafte, naftnih proizvodov in zemeljskega plina	Petroleum products and natural gas handling equipment
--------	---	---

SIST EN 1474-2:2020

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 1474-2:2020

<https://standards.iteh.ai/catalog/standards/sist/eff67120-d399-4144-9c1e-0a993335df4d/sist-en-1474-2-2020>

EUROPEAN STANDARD

EN 1474-2

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2020

ICS 75.200

Supersedes EN 1474-2:2008

English Version

Installation and equipment for liquefied natural gas - Design and testing of marine transfer systems - Part 2: Design and testing of transfer hoses

Installations et équipements de gaz naturel liquéfié -
Conception et essais des systèmes de transfert marins -
Partie 2 : Conception et essais des flexibles de transfert

Anlagen und Ausrüstung für Flüssigerdgas - Auslegung
und Prüfung von Schiffsübergabesystemen - Teil 2:
Auslegung und Prüfung von Übergabeschläuchen

This European Standard was approved by CEN on 19 July 2020.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

iTeh STANDARD PREVIEW

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Page

European foreword.....	4
1 Scope.....	5
2 Normative references.....	5
3 Terms, definitions and abbreviations	5
3.1 Terms and Definitions.....	5
3.2 Abbreviations.....	10
4 Applications and Qualification Categories.....	10
4.1 Applications	10
4.2 Qualification Categories	10
5 Description of typical LNG transfer hose assembly designs and accessories	11
5.1 General.....	11
5.2 Mandatory components.....	11
5.3 Optional components.....	12
5.4 Typical construction of LNG transfer hose assemblies	12
5.4.1 Main hose categories	12
5.4.2 Corrugated metal hose assemblies.....	13
5.4.3 Thermoplastic multi-layer (non-vulcanized) hose assemblies (Composite hose assemblies).....	15
5.4.4 Hose-in-hose with annular space	16
6 Design features of the LNG transfer hoses assemblies.....	17
6.1 General.....	17
6.2 Transfer Hose Assembly technology design parameters	17
6.3 Project Specific Design Parameters.....	18
6.3.1 Selection of hose assembly length.....	18
6.3.2 Service life.....	18
6.3.3 Selection of buoyancy and submersion.....	18
6.3.4 Selection of insulation	18
6.3.5 Selection of external protection	19
6.3.6 Selection of leak detection.....	19
6.4 Component details – End fitting.....	19
6.4.1 General.....	19
6.4.2 Termination	20
6.4.3 Connector.....	20
6.4.4 Bending stiffener/restrictor (optional).....	20
6.5 Hose assembly handling / lifting device.....	20
6.6 Safety systems	20
6.6.1 Leak detection (optional).....	20
6.6.2 Fire safety requirements.....	21
6.6.3 Electrical safety requirements.....	21
6.7 Connection to the ship.....	21
6.8 Hydraulic and electric control systems.....	21
7 Qualification Requirements	21
7.1 Foreword.....	21
7.2 Qualification process	22
7.2.1 General Principle	22

7.2.2	Qualification Levels Specific Requirements.....	22
7.2.3	Certification range definition from a tested hose assembly	24
7.2.4	Certification extension and update.....	25
7.3	Hose Assembly tests	25
7.3.1	General	25
7.3.2	Hose assembly property characterization tests.....	26
7.3.3	Qualification tests with acceptance criteria	34
8	Quality assurance and control	44
8.1	General	44
8.2	Material selection	44
8.3	Manufacturing.....	45
8.3.1	Manufacturing basics	45
8.3.2	Traceability.....	45
8.3.3	Marking	45
8.3.4	Packing and Preservation.....	46
8.4	Factory acceptance tests	46
8.4.1	General	46
8.4.2	Tests to be performed on every hose assembly	46
9	Documentation	46
9.1	Purchasing Guidelines	46
9.2	Design, Qualification and Manufacturing Documentation	46
9.3	As-built documentation/Manufacturing Data Book	47
9.4	Operation manual.....	47
	Annex A (informative) Purchasing guidelines table.....	49
	Annex B (informative) Guidelines for additional testing program	52
	Annex C (Informative) Guidelines for Hose Qualification Categories (HQC) Selection	59
	Annex D (informative) Surge pressure considerations for LNG hose assemblies.....	61
	Annex E (Informative) Pressure Leak Tests - justification about maximum allowed permeability rate and leak detection value	62
	Bibliography	64

EN 1474-2:2020 (E)

European foreword

This document (EN 1474-2:2020) has been prepared by Technical Committee CEN/TC 282 "Installation and equipment for LNG", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2020, and conflicting national standards shall be withdrawn at the latest by March 2020.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 1474-2:2008.

In comparison with the previous edition, the following technical modifications have been made:

- Update of the scope
- Review of Application and introduction of Hose Qualification Categories
- Revision of hose assembly categories
- Review of design features
- Review of qualification requirements
- Review of Quality assurance and control
- Review of documentation
- Review of annexes

iTeH STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 1474-2:2020

<https://standards.iteh.ai/catalog/standards/sist/eff67120-d399-4144-9c1e-0a993335df4d/sist-en-1474-2-2020>

This series consists of 3 parts:

- EN 1474-1: *Installation and equipment for liquefied natural gas — Design and testing of marine transfer systems — Part 1: Design and testing of transfer arms*
(This standard has been superseded by EN ISO 16904 - Petroleum and natural gas industries - Design and testing of LNG marine transfer arms for conventional onshore terminals)
- EN 1474-2: *Installation and equipment for liquefied natural gas — Design and testing of marine transfer systems — Part 2: Design and testing of transfer hoses*
- EN 1474-3: *Installation and equipment for liquefied natural gas — Design and testing of marine transfer systems — Part 3: Offshore transfer systems*

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This document gives general guidelines for the design, material selection, qualification, certification, and testing details of hose assemblies for Liquefied Natural Gas (LNG) marine transfer applications.

The transfer hose assemblies are part of transfer systems (it means that they may be fitted with ERS, QCDC, handling systems, hydraulic and electric components etc.) To avoid unnecessary repetition, cross-references to EN ISO 16904 and EN 1474-3 are made for all compatible items, and for references, definitions and abbreviations. Where additional references, definitions and abbreviations are required specifically for LNG hose assemblies, they are listed in this European Standard.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1474-1:2008, *Installation and equipment for liquefied natural gas — Design and testing of marine transfer systems — Part 1: Design and testing of transfer arms*

EN 1474-3:2008, *Installation and equipment for liquefied natural gas - Design and testing of marine transfer systems - Part 3: Offshore transfer systems*

EN ISO 7369:2004, *Pipework - Metal hoses and hose assemblies - Vocabulary (ISO 7369:2004)*

EN ISO 8330:2014, *Rubber and plastics hoses and hose assemblies - Vocabulary (ISO 8330:2014)*

EN ISO 10012:2003, *Measurement management systems - Requirements for measurement processes and measuring equipment (ISO 10012:2003)*

EN ISO 10619-1:2018, *Rubber and plastics hoses and tubing - Measurement of flexibility and stiffness - Part 1: Bending tests at ambient temperature (ISO 10619-1:2017)*

EN ISO 16904:2016, *Petroleum and natural gas industries - Design and testing of LNG marine transfer arms for conventional onshore terminals (ISO 16904:2016)*

3 Terms, definitions and abbreviations

3.1 Terms and Definitions

For the purposes of this document, the terms and definitions given in EN ISO 7369:2004 and EN ISO 8330:2014 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1.1

annular space

space between the inner fluid carrying layer and a second layer which can be used for insulation and/or safety purposes

EN 1474-2:2020 (E)**3.1.2****armour layer**

either a braid made of wires (see braid) or strips of metal or plastic used to provide pressure strength and/or external protection

3.1.3**axial stiffness**

extent to which a hose assembly resists tensile deformation in response to an applied axial force

3.1.4**bend stiffness**

ability of a flexible pipe to resist deflection when subjected to bending loads at constant tension, pressure and temperature

3.1.5**bend restrictor**

device for limiting the bend radius by mechanical means

NOTE 1 to entry: A bend restrictor typically comprises a series of interlocking metallic or moulded rings, applied over the outer surface

3.1.6**bending stiffener**

ancillary conical shaped component, which locally supports the pipe to limit bending stresses and curvature of the pipe to acceptance levels

NOTE 1 to entry: Bend stiffeners may be either attached to an end fitting or a support structure where the flexible pipe passes through the bend stiffener

STANDARD PREVIEW
(standards.iteh.ai)
SIST EN 1474-2:2020
<https://standards.iteh.ai/catalog/standards/sist/eff67120-d399-4144-9c1e-0a993335df4d/sist-en-1474-2-2020>

3.1.7**boil-off gas****BOG**

natural evaporation from liquefied natural gas due to vaporization

3.1.8**burst test**

test conducted on a hose sample until it failed by internal pressurization

3.1.9**buoyancy**

degree, to which the hose assembly has buoyancy capabilities calculated according to 7.3.2.6

3.1.10**connector**

part of the end fitting used to provide a leak-tight structural connection between the end fitting and adjacent piping

3.1.11**crush test**

application of a vertical load through a beam placed laterally across the hose assembly

3.1.12**double-envelope**

layer or set of layers effecting the enclosure, and thus the isolation from the environment, of those structures, systems and components whose failure can lead to an unacceptable release of LNG

3.1.13**dynamic load**

loads to flexible hose assembly or hose assembly configuration which vary in time, or whose deflections or boundary conditions vary in time, while hose is connected

3.1.14**emergency release system****ERS**

system that provides a positive means of quick release of transfer system and safe isolation of LNG carrier and transfer system

NOTE 1 to entry: The ERS consists of an emergency release coupling (ERC) and interlocked isolating valves which automatically close on both sides, thereby containing the LNG or vapour in the lines (dry disconnect), and, if applicable, associated control system

3.1.15**end termination**

mechanical device which forms the transition between the flexible pipe body and the connector whose different pipe layers are terminated in the end fitting in such a way as to transfer the load between the flexible hose assembly and the connector

3.1.16**end fitting**

assembly of connector and end termination

3.1.17**emergency release coupler****ERC**

device to provide a means of quick release of the transfer system when such actions is required only as an emergency measure

3.1.18**fatigue life**

number of cycles of a specified character that a given specimen sustains before failure of a specified nature occurs

3.1.19**hose assembly**

hose and its fittings

3.1.20**impact test**

test for determining the impact strength of a material

3.1.21**leak detection system**

system able to detect a failure / leak from the fluid carrying part of the hose assembly

EN 1474-2:2020 (E)

3.1.22

liquefied natural gas**LNG**

natural gas that has been cooled and condensed into liquid form

3.1.23

maximum allowable impact energy**MAIE**

maximum impact energy which can be applied to the hose assembly without bringing permanent damage to the hose assembly structure and performances

3.1.24

maximum allowable crush load**MACL**

maximum allowable crush load which can be applied to the hose assembly without bringing permanent damage to the hose assembly structure and performances

3.1.25

maximum allowable working pressure**MAWP**

maximum pressure (gauge) across the entire specified temperature range to which the hose may be exposed and operated

Note 1 to entry: It is commonly used by terminals to define their cargo system pressure capabilities (i.e. pump shut-in plus any static head or cargo system safety valve relief setting).

Note 2 to entry: This pressure rating is not expected to account for dynamic surge pressures, but does include nominal pressure variations during cargo transfer operations).

<https://standards.iteh.ai/catalog/standards/sist/eff67120-d399-4144-9c1e-0a993335df4d/sist-en-1474-2-2020>

3.1.26

maximum working load**MWL**

maximum allowable tensile force of the hose assembly in axial direction, applied to the end-fittings

3.1.27

minimum Bend Radius**MBR**

minimum radius at which the hose assembly is designed to operate

3.1.28

non-destructive test**ND**

test that is not expected to cause permanent damage to the hose assembly, so that the hose assembly can be used in subsequent tests and for operation as well

3.1.29

owner

business entity who has the legal or rightful title to the asset intended for LNG transfer

3.1.30**proof pressure**

pressure to which the hose assembly is tested (i.e. during a Factory Acceptance Test) to demonstrate its structural integrity when subject to internal pressure

NOTE 1 to entry: According to the IMO IGC Code this pressure test at ambient temperature shall be not less than 1,5 x MAWP and not more than two-fifths of its burst pressure

3.1.31**pumping port**

connection to attach a vacuum pump for vacuum insulated hose assemblies

3.1.32**quick connect disconnect coupler****QCDC**

manual or hydraulic mechanical device used to connect a transfer arm or hose to the cargo manifold without employing bolts

3.1.33**service life**

period of time during which the hose assembly fulfils all performance requirements for the specified or less severe condition in the same Hose Qualification Category

3.1.34**static load**

flexible hose assemblies not exposed to significant cyclically varying loads or deflections during normal operations

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 1474-2:2020

<https://standards.iteh.ai/catalog/standards/sist/eff67120-d399-4144-9c1e-0a993335df4d/sist-en-1474-2-2020>

3.1.35**storage bend radius**

minimum radius at which the hose assembly is designed to be stored or handled. SBR may be lower than MBR

3.1.36**super-insulation**

several high reflecting foils to reduce heat transfer via radiation as part of a vacuum insulation system

3.1.37**type approval certificate**

certificate issued by an IVA confirming the suitability and appropriate limits on the manufacturer's design methodologies, manufacturing processes and materials

Note 1 to entry: The name of this certificate can differ according to the IVA

3.1.38**visual inspection**

examination of parts and equipment for visible defects in material and workmanship

3.2 Abbreviations

D	internal bore diameter of the hose assembly
FAT	factory acceptance test
FSRU	floating Storage Regasification Unit
HQC	hose qualification category
IVA	Independent verification agency
L	Length of flexible part of the hose assembly
LNGC	liquefied natural gas carrier
MAAT	Maximum allowable applied twist

4 Applications and Qualification Categories

4.1 Applications

This subclause describes the main application using LNG transfer hose assemblies.

As industry and technology is developing, other type of application may consider using LNG transfer hose assemblies and shall be covered in this standard.

List of applications (not exhaustive):

- Offshore tandem FLNG offloading / loading aerial or floating;
- Ship-To-Ship transfer such as LNGC to FSRU, LNG Bunkering;
- Shore-To-Ship such as LNG bunkering;
- Ship-To-Shore such as offloading / loading.

Based on the application and use of the hose assembly, there are different categories of hose assembly qualification required. Main difference are the dynamic loads on the hose assembly. The following subclause introduces Hose assembly Qualification Categories (HQC).

NOTE Guidelines for the owners regarding applications and relevant HQC are available in Annex C. Selection of HQC remains the owner's responsibility.

4.2 Qualification Categories

This subclause establishes criteria for definition of Hose Qualification Categories for the hose assemblies covered by this standard. The Hose Qualification Categories specified below define different design verification requirements as per subclause 7.2.2.

The test scope within all Qualification Categories define the basis for the hose assemblies qualification but are independent of each project specific data (metocean data, waves & current data,). During the design for a project the required HQC should be checked by the owner and / or IVA.

The owner / IVA can require executing additional tests in order to determine if the proposed hose assembly is "Fit for Purpose" (For fatigue test for example, specific attention should be paid on bending loads adjacent to end terminations)

- Hose Qualification Category A

This HQC is intended to be used for quasi-static applications (i.e. application only driven by handling and/or thermal and pressure fatigue).

This category is including the performance requirements applicable to all aerial transfer hose assembly, typically transfer hose assemblies used in protected environment for intermittent usage without contact with water and with negligible dynamic motions.

— Hose Qualification Category B

This HQC is intended to be used for dynamic applications driven by aerial transfer fatigue including significant tensile and bending fatigue loads (e.g. by vessel motions or wind loads).

This Category is including the performance requirements applicable to all aerial transfer hose assemblies and typically applicable for the hose assemblies used in combination of weather exposed environment and/or permanent usage and used in configurations with contact with floating structures.

— Hose Qualification Category C

This HQC is intended to be used for dynamic applications for submerged or floating hose assemblies.

Qualification tests for this category includes representative tests of contact with water such as insulation, water tightness properties and permanent connection potential issues.

The hose assemblies manufacturer shall propose a fatigue assessment methodology, to be applied at project phase, verifying that the hose assembly is fit for purpose for the intended application.

The methodology shall be validated by an IVA.

5 Description of typical LNG transfer hose assembly designs and accessories

5.1 General

This standard is addressing hose assemblies as a flange-to-flange component.

It means that all statements and requirements based on the hose assemblies shall be considered between conveyed fluid tightening surfaces at both ends.

5.2 Mandatory components

An LNG Transfer Hose assembly shall consist of the following:

- flexible part of the hose assembly
- associated end fittings

Hose extremity end fittings can permit the mounting of a QCDC or a spool piece or permit direct connection to LNGC or LNG terminal or another hose assembly.

NOTE A description of QCDC is given in EN ISO 16904:2016, for transfer system reference is made to EN 1474-3:2008.

Hose extremity end fittings can permit the mounting of an emergency release system with valves and ERC (Emergency Release Coupler).

(A description of emergency release system is given in EN ISO 16904:2016 and EN 1474-3:2008).

EN 1474-2:2020 (E)

- permanent identification marks
- hose handling device(s) (pad eye or lifting lugs, lifting collar, ...),

Hose assembly shall include necessary fittings for safe handling, coupling and uncoupling either from the LNGC or the onshore or offshore LNG terminal system as required by the system design according to EN 1474-3:2008.

5.3 Optional components

An LNG Transfer Hose assembly can consist of the following:

- leak detection system

If required by the owner, the hose assembly shall incorporate leak detection system e.

- insulation system (to minimize build-up of external ice)
- intermediate leak barrier(s)
- bending stiffeners or restrictors
- buoyancy
- weight elements
- specific supporting equipment

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Hose assembly can support (e.g. piggy back mounted) hydraulic or pneumatic hoses, electric cables for the powering of the ERS and QCDC systems according to EN ISO 16904:2016, Clause 6.

5.4 Typical construction of LNG transfer hose assemblies**5.4.1 Main hose categories**

At present LNG transfer hose assemblies are categorized in three types according to their method of construction:

- those based on a reinforced corrugated metal hose construction, hereafter called corrugated metal hose;
- those based on a construction in which polymeric films and fabrics are entrapped between a pair of close wound helical wires, hereafter called composite hose;
- those based on a hose-in-hose construction with annular space and which can derivate from one of the above technologies.
- as the technology develops, other types of hose assemblies can become available and are also to be considered covered by this European Standard.

5.4.2 Corrugated metal hose assemblies

A corrugated metal hose assembly consists of a core layer made of a stainless-steel corrugations, and several other layers, metallic or non-metallic, reinforcing mechanical strength of the flexible part of the hose assembly.

In sequence, starting from the bore, typical construction is as follow:

- a) Inner layer, made of stainless-steel corrugations (parallel or helical corrugated sometimes called bellows), parallel or helicoidal construction. Ensures the inner leakproofness of the structure, as well as sustaining the radial pressure.
- b) Armours layers, made of steel or textile, supporting the axial loads and reinforcing inner radial pressure resistance.
- c) Optionally, thermal insulation layers, ensuring that the inner temperature is conserved whilst preventing any build-up of ice on the exterior of the hose assembly.
- d) Optionally, Outer layers, protecting the hose assembly from external mechanical damages. These layers might be leak-proof, giving the hose assembly a double envelope (with an annulus between) thus permitting the detection of any leak of LNG as soon as it can occur. In case of a leak in the inner layer, the outer layer can be able to withstand some pressure at some temperature during certain amount of time.

The external layer, if leak-proof, prevents any ingress of water and air from the exterior.

The number, arrangement and sequence of the layers in steps b) to d) is specific to the hose assembly size and application and can vary based on metallic hose assembly technology.

The hose assembly construction shall ensure that all materials are used within their individual range of temperature.

[SIST EN 1474-2:2020](https://standards.iteh.ai/catalog/standards/sist/eff67120-d399-4144-9c1e-0a993335df4d/sist-en-1474-2-2020)

<https://standards.iteh.ai/catalog/standards/sist/eff67120-d399-4144-9c1e-0a993335df4d/sist-en-1474-2-2020>