

## SLOVENSKI STANDARD

SIST ETS 300 441:1999

01-julij-1999

FUX]g\_UcdfYa U]b'g]ghYa J'fF9GL!HY b] bY\_UfU\_hYf]gh]Y]b'a Yf]bYa YlcXY'nU  
dca cfg\_YfUX]chY'YZbg\_YglfYybYgdfYYa b]\_YnUbYj Ubcdgh]b\_`]WbUZY\_j YbW  
&% &\_<n

Radio Equipment and Systems (RES); Technical characteristics and methods of measurement for maritime radiotelephone watch receivers for the distress and calling frequency 2 182 kHz

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[SIST ETS 300 441:1999](#)

<https://standards.iteh.ai/catalog/standards/sist/31225c77-d9a8-438b-81ec-fa335d25c803/sist-ets-300-441-1999>

Ta slovenski standard je istoveten z: **ETS 300 441 Edition 1**

**ICS:**

33.060.99	Druga oprema za radijske komunikacije	Other equipment for radiocommunications
47.020.70	Navigacijska in krmilna oprema	Navigation and control equipment


**SIST ETS 300 441:1999**

**en**

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 441:1999](#)

<https://standards.iteh.ai/catalog/standards/sist/31225c77-d9a8-438b-81ec-fa335d25c803/sist-ets-300-441-1999>



# EUROPEAN TELECOMMUNICATION STANDARD

---

**ETS 300 441**

February 1996

Source: ETSI TC-RES

Reference: DE/RES-01-07

ICS: 33.060.20

**Key words:** Emergency, maritime, mobile, radio, receiver

**iTel STANDARD PREVIEW**  
**Radio Equipment and Systems (RES);**  
**Technical characteristics and methods of measurement for**  
**maritime radiotelephone watch receivers for the distress**  
<https://standards.iteh.ai/catalog/standards/sist/31225c77-d9a8-438b-81ec-fa2a3a0e09>  
**and calling frequency 2 182 kHz**

**ETSI**

European Telecommunications Standards Institute

**ETSI Secretariat**

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE

**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

**X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

\*

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.

Page 2

ETS 300 441: February 1996

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 441:1999](#)

<https://standards.iteh.ai/catalog/standards/sist/31225c77-d9a8-438b-81ec-fa335d25c803/sist-ets-300-441-1999>

## Contents

Foreword .....	7
1 Scope .....	9
2 Normative references.....	9
3 Abbreviations and symbols .....	9
3.1 Abbreviations .....	9
3.2 Symbols .....	9
4 General requirements .....	10
4.1 Construction.....	10
4.1.1 Equipment elements.....	10
4.1.2 Design .....	10
4.1.3 Inspection and maintenance .....	10
4.1.4 Illumination .....	10
4.1.5 Interfaces.....	10
4.2 Controls and indicators .....	10
4.2.1 General.....	10
4.2.2 Controls .....	10
4.2.3 Indicators.....	11
4.2.4 Misuse .....	11
4.3 Labels .....	11
4.3.1 Power supply .....	11
4.3.2 Identification .....	11
4.3.3 Compass safe distance .....	11
4.4 Safety precautions .....	11
4.4.1 Protection .....	11
4.4.2 Earthing .....	11
4.4.3 Antenna static protection .....	11
4.4.4 Access.....	11
4.5 Tuning .....	11
4.6 Classes of emission.....	12
4.7 Warming up period .....	12
4.8 Instructions.....	12
4.8.1 Repair instructions.....	12
4.8.2 Accessibility .....	12
5 Test conditions, power supplies and ambient temperatures .....	12
5.1 General .....	12
5.2 Test power source .....	12
5.3 Normal test conditions .....	12
5.3.1 Normal temperature and humidity .....	12
5.3.2 Normal test power source .....	13
5.3.2.1 Mains voltage and frequency .....	13
5.3.2.2 Secondary battery power sources .....	13
5.3.2.3 Other power sources .....	13
5.4 Extreme test conditions .....	13
5.4.1 Extreme temperatures.....	13
5.4.2 Extreme values of the test power source .....	13
5.4.2.1 Mains voltage and frequency .....	13
5.4.2.2 Secondary battery power sources .....	13
5.4.2.3 Other power sources .....	13
5.5 Procedures for tests at extreme temperatures .....	13
5.6 Artificial antenna .....	14
5.7 Test signals applied to the receiver input.....	14
5.8 Measurement uncertainty and interpretation of the measuring results.....	14

5.8.1	Measurement uncertainty .....	14
5.8.2	Interpretation of the measurement results.....	14
6	Environmental tests .....	15
6.1	Introduction.....	15
6.2	Procedure.....	15
6.3	Performance check .....	15
6.4	Vibration test .....	15
6.4.1	Method of measurement.....	15
6.4.2	Requirement .....	16
6.5	Damp heat test.....	16
6.5.1	General .....	16
6.5.2	Method of measurement.....	16
6.5.3	Requirement .....	16
7	Receiver.....	16
7.1	Audio frequency output power.....	16
7.1.1	Definition.....	16
7.1.2	Method of measurement.....	16
7.1.3	Limit .....	16
7.2	Maximum usable sensitivity.....	17
7.2.1	Definition.....	17
7.2.2	Method of measurement.....	17
7.2.3	Limit .....	17
7.3	Audio frequency pass band.....	17
7.3.1	Definition.....	17
7.3.2	Method of measurement.....	17
7.3.3	Limits .....	17
7.4	Adjacent signal selectivity.....	17
7.4.1	Definition.....	17
7.4.2	Method of measurement.....	17
7.4.3	Limits .....	18
7.5	Blocking.....	18
7.5.1	<a href="https://standards.iteh.ai/catalog/standards/sist/31225c77-d9a8-438b-81cc-1ab33d23c803/sist-ets-300-441-1999">https://standards.iteh.ai/catalog/standards/sist/31225c77-d9a8-438b-81cc-1ab33d23c803/sist-ets-300-441-1999</a>	18
7.5.2	Method of measurement.....	18
7.5.3	Limits .....	18
7.6	Cross modulation .....	18
7.6.1	Definition.....	18
7.6.2	Method of measurement.....	18
7.6.3	Limit .....	19
7.7	Intermodulation.....	19
7.7.1	Definition.....	19
7.7.2	Method of measurement.....	19
7.7.3	Limit .....	19
7.8	Spurious response rejection ratio.....	19
7.8.1	Definition.....	19
7.8.2	Method of measurement.....	19
7.8.3	Limit .....	20
7.9	Harmonic distortion .....	20
7.9.1	Definition.....	20
7.9.2	Method of measurement.....	20
7.9.3	Limit .....	20
7.10	Conducted spurious emissions .....	20
7.10.1	Definition.....	20
7.10.2	Method of measurement.....	20
7.10.3	Limits .....	20
7.11	Automatic gain control.....	20
7.11.1	Methods of measurement.....	21
7.11.2	Limits .....	21
7.12	Audio frequency gain controls .....	21
7.12.1	Definition.....	21
7.12.2	Method of measurement.....	21
7.12.3	Limit .....	21

7.13	Protection of input circuits.....	21
7.13.1	Definition .....	21
7.13.2	Method of measurement .....	21
7.13.3	Limit.....	21
8	Muting device .....	22
8.1	General .....	22
8.2	Mute response .....	22
8.2.1	Methods of measurement .....	22
8.2.2	Response to the radiotelephone alarm signal .....	22
8.2.3	Response to the navigational warning signal .....	22
8.2.4	Response to the 1 300 Hz EPIRB signal.....	23
8.2.5	Limit.....	23
8.3	Protection against unwanted signals .....	23
8.3.1	Method of measurement .....	23
8.3.1.1	Selective calling signals on 2 170,5 kHz.....	23
8.3.1.2	Speech modulation.....	23
8.3.1.3	Non-specific 2 200 Hz signals .....	23
8.3.2	Limits .....	24
8.4	Operation during radiotelephone silence periods .....	24
8.5	Provisions for testing.....	24
	History.....	25

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 441:1999](#)

<https://standards.iteh.ai/catalog/standards/sist/31225c77-d9a8-438b-81ec-fa335d25c803/sist-ets-300-441-1999>

Blank page

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 441:1999

<https://standards.iteh.ai/catalog/standards/sist/31225c77-d9a8-438b-81ec-fa335d25c803/sist-ets-300-441-1999>

## Foreword

This European Telecommunication Standard (ETS) has been produced by the Radio Equipment and Systems (RES) Technical Committee of the European Telecommunications Standards Institute (ETSI).

<b>Transposition dates</b>	
Date of adoption of this ETS:	23 February 1996
Date of latest announcement of this ETS (doa):	31 May 1996
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	30 November 1996
Date of withdrawal of any conflicting National Standard (dow):	30 November 1996

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 441:1999  
<https://standards.iteh.ai/catalog/standards/sist/31225c77-d9a8-438b-81ec-fa335d25c803/sist-ets-300-441-1999>

Blank page

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ETS 300 441:1999](#)

<https://standards.iteh.ai/catalog/standards/sist/31225c77-d9a8-438b-81ec-fa335d25c803/sist-ets-300-441-1999>

## 1 Scope

This ETS states the minimum requirements for maritime radiotelephone watch receivers, including power supply units or converters, intended for keeping watch on the international distress and calling frequency 2 182 kHz.

This ETS is intended to cover equipment installed below deck in accordance with the requirement of the International Maritime Organization (IMO) [2].

This ETS includes the relevant provisions of the Radio Regulations [1] and of the International Maritime Organization [2].

## 2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] ITU Radio Regulations.
- [2] International Convention for Safety of Life at Sea, as amended 1988.
- [3] ISO Recommendation 694 Method B.
- [4] ETR 028: "Radio Equipment and Systems (RES); Uncertainties in the measurement of mobile radio equipment characteristics".  
*iTeh STANDARD PREFERENCE (standards.iteh.ai)*
- [5] ITU-R Recommendation 332-4: "Selectivity of receivers".

## 3 Abbreviations and symbols

<https://standards.iteh.ai/catalog/standards/sist/31225c77-d9a8-438b-81ec-fa335d25c803/sist-ets-300-441-1999>

### 3.1 Abbreviations

AGC	Automatic Gain Control
emf	electromotive force
EPIRB	Emergency Position-Indicating Radio Beacon
rms	root mean square
IMO	International Maritime Organization
SND/N	Signal + Noise + Distortion/Noise

### 3.2 Symbols

For the purposes of this ETS, the following symbols apply:

A2A	Double sideband, single channel containing quantized or digital information with the use of a modulating sub-carrier, telephony.
H2A	Single sideband with full carrier single channel containing quantized or digital information with the use of a modulating sub-carrier, telephony.
A3E	Double sideband, single channel containing analogue information, telephony.
H3E	Single sideband, full carrier, single channel containing analogue information, telephony.