

## SLOVENSKI STANDARD SIST EN IEC 62209-3:2021

01-junij-2021

Merilni postopki za ocenjevanje stopnje specifične absorpcije pri izpostavljenosti ljudi elektromagnetnim sevanjem brezžičnih komunikacijskih naprav, ki se držijo v roki ali pritrdijo na telo - 3. del: Sistemi vektorskega merjenja (frekvenčno območje od 600 MHz do 6 GHz)

Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 3: Vector measurement-based systems (Frequency range of 600 MHz to 6 GHz) **iTeh STANDARD PREVIEW** 

### (standards.iteh.ai)

SIST EN IEC 62209-3:2021 https://standards.iteh.ai/catalog/standards/sist/1fec7cf4-bc26-4f06-bbf3f8f2f670db20/sist-en-iec-62209-3-2021

Ta slovenski standard je istoveten z: EN IEC 62209-3:2019

### ICS:

13.280	Varstvo pred sevanjem
33.050.10	Telefonska oprema

Radiation protection Telephone equipment

SIST EN IEC 62209-3:2021

en

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN IEC 62209-3:2021 https://standards.iteh.ai/catalog/standards/sist/1fec7cf4-bc26-4f06-bbf3f8f2f670db20/sist-en-iec-62209-3-2021

## EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

## EN IEC 62209-3

November 2019

ICS 33.060.20

**English Version** 

### Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices -Part 3: Vector measurement-based systems (Frequency range of 600 MHz to 6 GHz) (IEC 62209-3:2019)

Procédure de mesure pour l'évaluation du débit Messver d'absorption spécifique de l'exposition humaine aux champs radiofréquence produits par les dispositifs de gegenüber communications sans fil tenus à la main ou portes près du un corps - Partie 3: Systèmes basés sur la mesure vectorielle Kommunik (plage de fréquences comprise entre 600 MHz et 6 GHz) (IEC 62209-3:2019) AANDARD PREVIE

Messverfahren für die Beurteilung der spezifischen Absorptionsrate bei der Exposition von Personen gegenüber hochfrequenten Feldern von handgehaltenen und am Körper getragenen schnurlosen Kommunikationsgeräten - Teil 3: Auf Vektormessungen basierende Systeme (Frequenzbereich von 600 MHz bis 6 GHz) (IEC 62209-3:2019)

### (standards.iteh.ai)

This European Standard was approved by CENELEC on 2019-10-29. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. https://standards.iteh.ai/catalog/standards/sist/1fec7cf4-bc26-4f06-bbf3-

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2019 CENELEC All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

### European foreword

The text of document 106/494/FDIS, future edition 1 of IEC 62209-3, prepared by IEC/TC 106 "Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 62209-3:2019.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2020-07-29 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2022-10-29 document have to be withdrawn

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

## iTeh STANDARD PREVIEW (stendorsement holice1)

### SIST EN IEC 62209-3:2021

The text of the International Standard IEC 62209-3:2019 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

ISO/IEC 17025	NOTE	Harmonized as EN ISO/IEC 17025
ISO 3611:2010	NOTE	Harmonized as EN ISO 3611:2010 (not modified)
ISO/IEC 17043	NOTE	Harmonized as EN ISO/IEC 17043

### Annex ZA

### (normative)

## Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: <u>www.cenelec.eu</u>.

Publication	Year	<u>Title</u>	<u>EN/HD</u>	Year
IEC 62209-1	2016 iTe	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz) PREVER	EN 62209-1	2016
IEC 62209-2	2010 https://sta	Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption dirateist-(SAR) 22 (for 3-2 wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)	EN 62209-2 6-bbf3-	2010
IEC 62479	-	Assessment of the compliance of low- power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)	EN 62479	-
IEC TR 62630	2010	Guidance for evaluating exposure from multiple electromagnetic sources	-	-
ISO/IEC Guide 98-1	2009	Uncertainty of measurement – Part 1: Introduction to the expression of uncertainty in measurement	-	-
ISO/IEC Guide 98-3	3 -	Uncertainty of measurement - Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)	-	-
IEC/IEEE 62704-1	-	Determining the peak spatial-average specific absorption rate (SAR) in the human body from wireless communications devices, 30 MHz to 6 GHz - Part 1: General requirements for using the finite difference time-domain (FDTD) method for SAR calculations	-	-

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN IEC 62209-3:2021 https://standards.iteh.ai/catalog/standards/sist/1fec7cf4-bc26-4f06-bbf3f8f2f670db20/sist-en-iec-62209-3-2021



Edition 1.0 2019-09

# INTERNATIONAL STANDARD

## NORME INTERNATIONALE



HORIZONTAL STANDARD NORME HORIZONTALE

Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 3: Vector measurement-based systems (Frequency range of 600 MHz to 6 GHz) https://standards.iteh.ai/catalog/standards/sist/1fec7cf4-bc26-4f06-bbf3f8f2f670db20/sist-en-iec-62209-3-2021

Procédure de mesure pour l'évaluation du débit d'absorption spécifique de l'exposition humaine aux champs radiofréquence produits par les dispositifs de communications sans fil tenus à la main ou portes près du corps – Partie 3: Systèmes basés sur la mesure vectorielle (plage de fréquences comprise entre 600 MHz et 6 GHz)

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 33.060.20

ISBN 978-2-8322-7355-5

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

 Registered trademark of the International Electrotechnical Commission Marque déposée de la Commission Electrotechnique Internationale

### CONTENTS

FC	DREWO	RD	9
IN	TRODU	CTION	11
1	Scope	9	12
2	Norm	ative references	12
3	Terms	s and definitions	13
4	Symb	ols and abbreviated terms	14
5	Överv	view of the measurement procedure	14
6	Meas	urement system specifications	17
Ŭ	6 1	General requirements	17
	6.2	Phantom specifications	19
	621	Head phantom specifications – shell	19
	622	Body phantom specifications – shell	19
	6.2.3	Tissue-equivalent medium properties	19
	6.3	Measurement system requirements	19
	6.3.1	General	19
	6.3.2	Scanning measurement system specifications	19
	6.3.3	Array measurement system specifications	20
	6.4	Device holder specification N.D.A.D.D.D.D.T.V.I.T.V.	21
	6.5	Reconstruction algorithm and peak spatial-averaging specifications	22
7	Proto	col for SAR assessments and ards.iteh.ai)	22
	7.1	Measurement preparation	22
	7.1.1	General <u>SIST EN IEC 62209-3:2021</u>	22
	7.1.2	Preparation of tissue-equivalent medium	22
	7.1.3	System check	23
	7.1.4	Preparation of the device under test (DUT)	23
	7.1.5	Operating modes	23
	7.1.6	Position of the DUT in relation to the phantom	23
	7.1.7	Positions of the DUT in relation to the flat phantom for large DUT	23
	7.1.8	Test frequencies for DUT	24
	7.2	Tests to be performed	24
	7.3	General measurement procedure	25
	7.3.1	General	25
	7.3.2	Measurement procedure for scanning systems	25
	7.3.3	Measurement procedure for array systems	26
	7.4	SAR measurements for simultaneous transmission	26
	7.4.1	General	26
	7.4.2	SAR measurements for uncorrelated signals	27
	7.4.3	SAR measurements for correlated signals	31
8	Meas	urement uncertainty estimation	32
	8.1	General	32
	8.2	Requirements on the measurement uncertainty evaluation	32
	8.3	Description of measurement uncertainty models	33
	8.3.1	General	33
	8.3.2	Uncertainty models for array measurement system and scanning measurement systems	34
	8.3.3	Example uncertainty budget templates	35

### IEC 62209-3:2019 © IEC 2019

- 3 -	
-------	--

9	Meas	urement report	39
Ann	ex A (	normative) Phantom specifications	40
A	<b>\</b> .1	SAM phantom specifications	40
	A.1.1	Justification	40
	A.1.2	SAM phantom geometry	40
	A.1.3	Tissue-equivalent medium	40
Α	<b>.</b> .2	Flat phantom specifications	41
Α	<b>.</b> .3	Specific phantoms	42
A	.4	Tissue-equivalent medium	43
Ann	ex B (	normative) Calibration and characterization of dosimetric probes	44
В	8.1	General	44
В	3.2	Types of calibration	44
	B.2.1	Amplitude calibration with analytical fields	44
	B.2.2	Amplitude and phase calibration by transfer calibration	45
	B.2.3	Amplitude and phase calibration using numerical reference	47
Ann	ex C (	informative) Field reconstruction techniques	49
C	C.1	General	49
C	0.2	Objective of field reconstruction techniques	49
C	2.3	Background	49
C	2.4	Reconstruction techniques	51
	C.4.1	Expansion techniques.	51
	C.4.2	Source reconstruction techniquess.iteh.ai)	52
	C.4.3	Source base function decomposition	52
	C.4.4	Phase reconstruction	52
C	0.5	Source reconstruction and SAR estimation from fields measured outside the	
		phantom	53
C	0.6	Additional considerations for field reconstruction in scanning systems	53
Ann	ex D (	normative) SAR measurement system verification and system validation	54
D	D.1	Objectives and purpose	54
	D.1.1	General	54
	D.1.2	Objectives and purpose of <i>system check</i>	54
	D.1.3	Objectives of system validation	54
D	0.2	SAR measurement setup and procedure for <i>system check</i> and <i>system</i>	
		Validation	55
	D.Z.I		55
	D.Z.Z	Power measurement setups	55
	D.Z.3	Procedure to measure and normalize SAR	5/
Г	U.Z.4	System shock	59 61
L	י.ט 1 2 ח	System check antonnas and test conditions	01 61
	D.3.1	System check antennas and test conditions for scanning systems	01 61
	D.3.2	System check antennas and test conditions for array systems	01 61
	D.3.3	System check acceptance criteria	וט רא
Г	0.3.4 \/	System validation	20
L	ד.י 1 ⊿ ח	Validation of array systems and scanning systems	02 62
	D.4.1	Requirements for system validation antennas and test conditions	20 62
	D.4.2	Requirements for array systems and scanning systems	20 62
		Test positions for system validation	۲0 61
		System validation procedure based on peak spatial overage SAP	04 71
	D.4.0	Source and a second procedure based on peak spatial-average OAN	/ 1

540		70
D.4.6	On-site system validation after installation	
D.4.7	System validation acceptance criteria	80
Annex E (II	nformative) Interlaboratory comparisons	82
E.1 I	<sup>o</sup> urpose	82
E.2 I	Monitor laboratory	82
E.3 I	Phantom set-up	82
E.4 F	Reference devices	82
E.5 I	Power set-up	83
E.6 I	nterlaboratory comparison – Procedure	83
Annex F (n	ormative) System validation antennas	84
F.1 (	General requirements	84
F.2 I	Return loss requirements	84
F.3 S	Standard dipole antenna	85
F.4	/PIFA	88
F.5 2	2-PEAK CPIFA	90
F.6 /	Additional antennas	94
Annex G (r	normative) SAR calibration of reference antennas	95
G 1 1		95
G2 1	Darameters or quantities and ranges to be determined by calibration method	06
G.2 I	Parameters of quantities and ranges to be determined by calibration method.	90
G.3 I	Peterence antenna calibration setup PREVIEW	90
	Verification of refurt torned and a itale ai)	97
G.4.1	Collibration of references enternances atom by story proceedings	97
G.4.2	Calibration of reference antennas: step-by-step procedure	97
G.4.3	Uncertainty budget o <u>Breterence amennalca</u> libration	98
G.5 I	antennas of the same type using the array system 21	102
Annex H (i	nformative) General considerations on uncertainty estimation	105
H.1 (	Concept of uncertainty estimation	105
H.2	Type A and Type B evaluations	106
H.3 [	Degrees of freedom and coverage factor	106
H.4 (	Combined and expanded uncertainties	107
H.5 /	Analvtical reference functions	108
Annex I (no	ormative) Evaluation of measurement uncertainty of SAR results from	
scann	ing vector measurement-based systems with single probes	111
I.1 I	Measurement uncertainties to be evaluated by the system manufacturer MM	111
I.1.1	General	111
I.1.2	Calibration CF	111
I.1.3	Isotropy ISO	111
1.1.4	System linearity <i>LIN</i>	112
I.1.5	Sensitivity limit SL	112
I.1.6	Boundary effect <i>BE</i>	112
1.1.7	Readout electronics <i>RE</i>	
118	Response time RT	113
119	Probe positioning <i>PP</i>	113
1 10	Sampling error SE	113
1 11	Phantom shell <i>PS</i>	11 <u>/</u>
1 12	Tissue-equivalent medium parameters $MAT$	+ ۱۱،۰۰۰ ۱1 <i>۸</i>
1.1.12	Measurement system immunity/secondary recention MSI	116
1.1.13	Modeurement system minunity/secondary reception Mor	110

1.2	Uncertainty of reconstruction corrections and post-processing to be spec	ified
101		110
1.2.1	Evoluation of uncertainty due to reconstruction <i>BEC</i>	
1.2.2	Evaluation of uncertainty due to reconstruction $REC$	110
1.2.3		
1.2.4	SAR averaging SAV	
1.2.3	SAR scaling SARS	
1.2.0	SAR correction for deviations in permittivity and conductivity sc	
1.3		
1.3.1		
1.3.2	Probe coupling with the DUT PC	
1.3.3		
1.3.4		
1.3.5	Measured SAR drift SD	
1.4		
1.4.1		
1.4.2	Device holder DH	
1.4.3	Device positioning <i>DP</i>	
1.4.4	RF ambient conditions <i>AC</i>	
1.4.5	Measurement system drift and noise <i>DN</i>	121
1.5	Uncertainties of validation antennas MVR	122
I.5.1	General	122
1.5.2	Deviation of experimental antennas DEX 1.41,	122
1.5.3	Power measurement uncertainty <i>PMU</i>	122
1.5.4	Other uncertainty contributions when using validation antennas OVS https://standards.iteh.av/catalog/standards/sist/lfec/cf4-bc26-4f06-bbf3-	
Annex J ( or sc	normative) Evaluation of the measurement system uncertainty of fixed ar anning array vector measurement-based systems	ray 123
J.1	Measuring system uncertainties to be evaluated by the manufacturer MM	1
J.1.1	General	123
J.1.2	Calibration CF	123
J.1.3	lsotropy ISO	123
J.1.4	Mutual sensor coupling <i>MSC</i>	124
J.1.5	Scattering due to the presence of the array AS	
J.1.6	System linearity <i>LIN</i>	
J.1.7	Sensitivity limit <i>SL</i>	
J.1.8	Boundary effect <i>BE</i>	
J.1.9	Readout electronics <i>RE</i>	
J.1.1	0 Response time <i>RT</i>	
J.1.1	1 Probe position <i>PP</i>	
J.1.1	2 Sampling error <i>SE</i>	
J.1.1	3 Array boundaries <i>AB</i>	
J.1.1	4 Phantom shell <i>PS</i>	129
J.1.1		
	5 Tissue-equivalent medium parameters <i>MAT</i>	
J.1.1	<ul> <li>5 Tissue-equivalent medium parameters <i>MAT</i></li> <li>6 Phantom homogeneity <i>HOM</i></li> </ul>	
J.1.1 J.1.1	<ul> <li>Tissue-equivalent medium parameters <i>MAT</i></li> <li>Phantom homogeneity <i>HOM</i></li> <li>Measurement system immunity/secondary reception <i>MSI</i></li> </ul>	129 131 132
J.1.1 J.1.1 J.2	<ul> <li>Tissue-equivalent medium parameters <i>MAT</i></li> <li>Phantom homogeneity <i>HOM</i></li> <li>Measurement system immunity/secondary reception <i>MSI</i></li> <li>Uncertainty of reconstruction, corrections, and post-processing to be specified by the manufacturer <i>MN</i></li> </ul>	
J.1.1 J.1.1 J.2	<ul> <li>Tissue-equivalent medium parameters <i>MAT</i></li> <li>Phantom homogeneity <i>HOM</i></li> <li>Measurement system immunity/secondary reception <i>MSI</i></li> <li>Uncertainty of reconstruction, corrections, and post-processing to be specified by the manufacturer <i>MN</i></li></ul>	
J.1.1 J.1.1 J.2 J.2.1	<ul> <li>5 Tissue-equivalent medium parameters <i>MAT</i></li> <li>6 Phantom homogeneity <i>HOM</i></li> <li>7 Measurement system immunity/secondary reception <i>MSI</i></li> <li>9 Uncertainty of reconstruction, corrections, and post-processing to be specified by the manufacturer <i>MN</i></li></ul>	

J.2.3	Impact of noise on reconstruction POL	132
J.2.4	SAR averaging SAV	132
J.2.5	SAR scaling <i>SARS</i>	132
J.2.6	SAR correction for deviations in permittivity and conductivity SC	132
J.3	Measurement system uncertainties that are dependent on the DUT MD	132
J.3.1	General	132
J.3.2	Probe or probe-array coupling with the DUT <i>PC</i>	132
J.3.3	Modulation response <i>MOD</i>	133
J.3.4	Integration time IT	133
J.3.5	Measurement system drift and noise <i>DN</i>	133
J.4	Uncertainties related to the source or noise ME	133
J.4.1	General	133
J.4.2	Device holder DH	133
J.4.3	Device positioning DP	133
J.4.4	RF ambient conditions AC	134
J.4.5	Measurement system drift and noise <i>DN</i>	134
J.5	Uncertainties of validation antennas MV	134
J.5.1	General	134
J.5.2	Deviation of experimental antennas <i>DEX</i>	134
J.5.3	Power measurement uncertainty PMU	134
J.5.4	Other uncertainty contributions when using validation antennas OVS	134
Bibliograp	<sup>hy</sup> (standards.iteh.ai)	135
Figure 1 –	Evaluation plan checklist SIST.EN-IEC 62209+3:2021	15
Figure 2 – surface of	Illustration of the shape and orientation relative to a curved phantom the distorted cubic volume for computing psSAR2021	22
Figure 3 – measurem performed	Measurements performed by shifting a large device over the efficient ent area of the system including overlapping areas – in this case: six tests	24
Figure 4 – frequencie frequency	Flow chart for SAR measurements of uncorrelated signals at different s using a measurement system able to distinguish between different components (Method 2)	27
Figure 5 –	Illustration of the amplitude spectrum, as function of frequency, for	
simultane	busly transmitted signals of multiple frequency bands emitted by a DUT	28
Figure 6 – measurem	Illustration of a completely covered signal bandwidth $B_s$ by the nent system analysis bandwidth $B_a$ at single transmission mode	29
Figure 7 – the measu transmissi	Illustration of a completely covered signal bandwidths $B_{si}$ (for $i = 2$ to $N$ ) by rement system analysis bandwidth $B_a$ for simultaneous multiple-frequency on mode	29
Figure 8 – the measu transmissi	Illustration of a non-coverage of the signal bandwidths $B_{Si}$ (for $i = 2$ to $N$ ) by rement system analysis bandwidth $B_a$ for simultaneous multiple-frequency on mode.	29
Figure 9 – by the me frequency	Illustration of a partial-coverage of the signal bandwidths $B_{si}$ (for $i = 2$ to $N$ ) asurement system analysis bandwidth $B_a$ for simultaneous multiple-transmission mode	30
Figure 10 to cover o frequency	– Illustration of reduction of the measurement system analysis bandwidth $B_a$ nly one signal bandwidth $B_{Si}$ (for $i = 1$ to $N$ ) for simultaneous multiple-transmission mode	30
Figure 11 bandwidth simultaneo	– Illustration of increasing or moving the measurement system analysis $B_a$ to cover one or more signal bandwidth $B_{si}$ (for $i = 1$ to $N$ ) for bus multiple-frequency transmission mode	30

|--|

Figure A.1 – Sagittally-bisected phantom with extended perimeter, used for scanning measurement systems	41
Figure A.2 – Dimensions of the elliptical phantom	42
Figure C.1 – Coordinate system for 2D planar measurement-system	50
Figure C.2 – Generic configuration of SAR measurement system	50
Figure C.3 – Schematic representation of 2D planar measurement-based SAR system and its coordinate system	52
Figure C.4 – Source reconstruction from fields outside a phantom	53
Figure D.1 – Recommended power measurement setup for <i>system check</i> and <i>system validation</i>	56
Figure D.2 – Equipment setup for measurement of forward power $P_{f}$ and forward coupled power $P_{fC}$	57
Figure D.3 – Equipment setup for measuring the shorted reverse coupled power $P_{\text{rcs}}$	58
Figure D.4 – Equipment setup for measuring the power with the reference antenna connected	58
Figure D.5 – Port numbering for the <i>S</i> -parameter measurements of the directional coupler	60
Figure D.6 – SAM masks for positioning dipole antennas and VPIFAs on the head phantoms, including holes where the antenna spacer is inserted	65
Figure D.7 – Flat masks for positioning VPIFAs on the flat phantoms, including a hole in the centre where the VPIFA spacer is inserted	66
Figure D.8 – Dipole showing the distance of $s = 15 \text{ mm}$	67
Figure D.9 – 2-PEAK CPIFA showing the fixed distance of $s = 7 \text{ mm}$	67
Figure D.10 – VPIFA positioned showing the fixed distance of s = 2 mm	68
Figure D.11 – System check and the hidation locations to the the that phantom	69
Figure D.12 – System check and validation locations for the head phantom	70
Figure D.13 – Definition of rotation angles for dipoles	71
Figure F.1 – Mechanical details of the standard dipole	87
Figure F.2 – VPIFA validation antenna	89
Figure F.3 – 2-PEAK CPIFA at 2 450 MHz	92
Figure F.4 – Detail of the tuning structure and matching structure	93
Figure G.1 – Measurement setup for waveguide calibration of dosimetric probe, and similar setup (same tissue-equivalent liquid, dielectric spacer, power sensors and sequence) for entering calibration	05
Figure C.2. Setup for calibration of a reference antenna	95
Figure G.2 – Setup for calibration of a reference antenna Figure G.3 – Method for the transfer of calibration between two antennas of the same	102
Figure 1.1 Illustration of SAP measurement results during 8 h and the control maying	103
average	122
Table 1 – Evaluation plan checklist	16
Table 2 – Uncertainty budget template for the evaluation of the measurement system uncertainty of the 1 g or 10 g psSAR to be carried out by the system manufacturer	36
Table 3 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g SAR or 10 g SAR from a DUT	37
Table 4 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g SAR or 10 g SAR from a validation antenna	38

Table 5 – Uncertainty budget template for evaluating the uncertainty in the measuredvalue of 1 g SAR or 10 g SAR from the system check	39
Table A.1 – Dielectric properties of the tissue-equivalent medium	43
Table B.1 – Uncertainty analysis for single-probe calibration in waveguide	45
Table B.2 – Uncertainty analysis for transfer calibration of array systems	46
Table B.3 – Uncertainty analysis of transfer calibration of array systems	48
Table D.1 – Example of power measurement uncertainty in %	60
Table D.2 – Modulations and multiplexing modes used by radio systems	64
Table D.3 – Peak spatial-average SAR (psSAR) averaged over 1 g and 10 g values for the flat phantom filled with tissue-equivalent medium for the antennas specified in Annex F	72
Table D.4 – Peak spatial-average SAR (psSAR) averaged over 1 g and 10 g values for antenna generating two peaks on the flat phantom filled with tissue-equivalent medium for the antennas specified in Annex F	73
Table D.5 – Peak spatial-average SAR (psSAR) averaged over 1 g and 10 g values on the head left and right phantom for the antennas specified in Annex F	74
Table D.6 – Peak spatial-average SAR (psSAR) averaged over 1 g and 10 g values for antenna generating two peaks on the head left and right phantom for the antennas specified in Annex F. Modulations are as specified in Table D.2	79
Table D.7 – Set of randomised tests for on-site <i>system validation</i> using flat phantom 1 g and 10 g psSAR, normalized to 1 W forward power using the antennas specified in Annex F	79
Table D.8 – Set of tests for on-site system validation using left and right head phantoms for 1 g and 10 g psSAR for the antennas specified in Annex F	80
Table F.1 – Return loss values for antennas specified in Annex F and flat phantom filled with tissue-equivalent mediumai/catalog/standards/sist/1fec7cf4-bc26-4f06-bbf3	85
Table F.2 – Mechanical dimensions of the reference dipoles	86
Table F.3 – Dimensions for VPIFA antennas at different frequencies	90
Table F.4 – Dielectric properties of the dielectric layers for VPIFA antennas	90
Table F.5 – Thickness of substrates and planar metallization	93
Table F.6 – Dielectric properties of FR4	93
Table F.7 – Values for the antenna dimensions in Figures F.4 and F.5	94
Table G.1 – Example uncertainty budget for reference dipole antenna calibration for1 g and 10 g averaged SAR (750 MHz to 3 GHz)	99
Table G.2 – Example uncertainty budget for reference antenna calibration (PIFA) for 1 g and 10 g averaged SAR (750 MHz to 3 GHz)	100
Table G.3 – Example uncertainty budget for reference antenna (dipole) calibration for1 g and 10 g averaged SAR (3 GHz to 6 GHz)	101
Table G.4 – Example uncertainty budget for the calibration of an antenna using thetransfer method, as percentages	104
Table H.1 – Parameters of analytical reference functions and associated reference         peak 10 g SAR value	109

IEC 62209-3:2019 © IEC 2019

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

### MEASUREMENT PROCEDURE FOR THE ASSESSMENT OF SPECIFIC ABSORPTION RATE OF HUMAN EXPOSURE TO RADIO FREQUENCY FIELDS FROM HAND-HELD AND BODY-MOUNTED WIRELESS COMMUNICATION DEVICES –

#### Part 3: Vector measurement-based systems (Frequency range of 600 MHz to 6 GHz)

### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committee; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and nongovernmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate.//IEC.cannot.bec.heldgresponsible.for.the way in which they are used or for any misinterpretation by any end user.
  Rt2f670db20/sist-en-iec-62209-3-2021
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62209-3 has been prepared by IEC technical committee 106: Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
106/494/FDIS	106/497/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.