

SLOVENSKI STANDARD
oSIST prEN ISO 21484:2019
01-januar-2019

Jedrska energija - Tehnologija goriv - Ugotavljanje razmerja O/M v peletih MOX z gravimetrično metodo (ISO 21484:2017)

Nuclear Energy - Fuel technology - Determination of the O/M ratio in MOX pellets by the gravimetric method (ISO 21484:2017)

Kernenergie - Brennstofftechnologie - Bestimmung des O/M-Verhältnisses in MOX-Pellets mit dem gravimetrischen Verfahren (ISO 21484:2017)

Énergie nucléaire - Technologie du combustible - Détermination du rapport O/M dans les pastilles MOX par la méthode gravimétrique (ISO 21484:2017)

Ta slovenski standard je istoveten z: **prEN ISO 21484**

ICS:

17.240	Merjenje sevanja	Radiation measurements
27.120.30	Cepljivi materiali in jedrska gorivna tehnologija	Fissile materials and nuclear fuel technology

oSIST prEN ISO 21484:2019

en,fr,de

INTERNATIONAL STANDARD

ISO
21484

Second edition
2017-01

Nuclear Energy — Fuel technology — Determination of the O/M ratio in MOX pellets by the gravimetric method

*Énergie nucléaire — Technologie du combustible — Détermination
du rapport O/M dans les pastilles MOX par la méthode gravimétrique*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN ISO 21484:2019

<https://standards.iteh.ai/catalog/standards/sist/15acaf6b-4d28-40ca-a87d-9d1ff6bef0d/sist-en-iso-21484-2019>



Reference number
ISO 21484:2017(E)

ISO 21484:2017(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN ISO 21484:2019

<https://standards.iteh.ai/catalog/standards/sist/15acaf6b-4d28-40ca-a87d-9d1ff6bef0d/sist-en-iso-21484-2019>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	1
5 Reactions	1
6 Reagents and materials	1
7 Apparatus	2
8 Sampling	2
9 Procedure	2
9.1 Preliminary test	2
9.2 Preparing the crucibles	2
9.3 Weighing the sample	2
9.4 Heat treatment cycles	3
9.4.1 General	3
9.4.2 Example 1	3
9.4.3 Example 2	3
9.5 Final weighing	3
10 Calculation	4
10.1 Mean atomic mass of oxide after heat treatment	4
10.2 Calculation of O/M ratio	4
11 Precision	4
11.1 Accuracy	4
11.2 Precision	5
11.3 Sensitivity	5
12 Test report	5
Bibliography	6

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 85, *Nuclear energy, nuclear technologies, and radiological protection*, Subcommittee SC 5, *Nuclear installations, processes and technologies*.

This second edition cancels and replaces the first edition (ISO 21484:2008), which has been technically revised. <https://standards.iteh.ai/catalog/standards/sist/15acaf6b-4d28-40ca-a87d-9d1f6fbef0d/sist-en-iso-21484-2019>

Nuclear Energy — Fuel technology — Determination of the O/M ratio in MOX pellets by the gravimetric method

1 Scope

This document describes a method for determining the Oxygen-to-Metal (O/M) ratio in mixed uranium-plutonium oxide $(U,Pu)O_2 \pm x$ pellets. The parameters given in the following paragraphs are relevant for pellets within a range of O/M ratio corresponding to 1,98 to 2,01. The method described in the document is adapted, with regard to the parameters, if the expected values of O/M ratio are outside the range.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <http://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Principle

The $(U,Pu)O_2 \pm x$ sample is submitted to controlled oxidation-reduction under thermodynamic conditions designed to change the O/M ratio to a value of 2,000. The initial stoichiometric deviation, X , is determined from the sample mass difference before and after heat treatment.

5 Reactions

The main reactions are as follows:

- a) $(U,Pu)O_2 \pm x / 2 O_2 \rightarrow (U,Pu)O_{2,000}$;
- b) $(U,Pu)O_{2+x} + xH_2 \rightarrow (U,Pu)O_{2,000} + xH_2O$.

6 Reagents and materials

During the analysis, unless otherwise stated, use only reagents of recognized analytical grade and distilled or demineralized water or water of equivalent purity.

6.1 Nitric acid solution, 50 % per volume nitric acid aqueous solution.

6.2 Purge gas.

6.2.1 Air, a volume fraction of 99,99 % purity grade is recommended.

6.2.2 Inert gas, such as Argon or nitrogen can be used with a recommended volume fraction of 99,99 % purity grade [$O_2 < 0,000\ 5\%$ (5 ppm), $H_2O < 0,000\ 5\%$ (5 ppm), $N_2 < 0,000\ 5\%$ (5 ppm)].

ISO 21484:2017(E)

6.2.3 Hydrogen or mixture of hydrogen and inert gas, a volume fraction of 99,99 % purity grade to which water vapour may be added to obtain an oxygen potential (ΔG_0) near -420 kJ/mol (-100 kcal/mol).

7 Apparatus

7.1 Furnace, one of the following furnaces can be used.

7.1.1 Muffle furnace, controlled up to 950 °C, having a device for measuring the temperature and having sweeping possibility with various gases.

7.1.2 Other furnaces, other furnaces, with same performance can also be used such as Infrared gold image furnace (IR lamp heating).

7.2 Crucibles, use platinum or quartz crucibles.

7.3 Analytical balance, use an analytical balance with an accuracy of at least $\pm 0,1$ mg when muffle furnace is used or at least $\pm 0,01$ mg if samples are smaller.

8 Sampling

A representative sample shall be taken from the pellet batch for analysis. If necessary, crush pellets to make smaller samples according to the furnace type or the crucible size.

If necessary, care shall be taken to avoid sample oxidation during the sampling procedure and the sample preparation. Typical precautions include performing the sampling operation under argon atmosphere, placing the sample in an argon-filled bottle, etc. The laboratory performing the analyses shall establish the procedure.

SIST EN ISO 21484:2019

<https://standards.iteh.ai/catalog/standards/sist/15acaf6b-4d28-40ca-a87d-9d1ff6fbef0d/sist-en-iso-21484-2019>

9 Procedure

9.1 Preliminary test

The balance shall be checked at regular intervals using a standard mass.

9.2 Preparing the crucibles

The crucibles shall be clean and weighed before use. An example of a cleaning procedure that could be used is as follows.

- a) Clean the crucibles by heating them in nitric acid (6.1) near the boiling point.
- b) Rinse thoroughly with deionized water.
- c) Dry the crucibles in the furnace for 30 min at 150 °C under inert atmosphere.
- d) Allow the crucibles to cool to 35 °C in the furnace under inert atmosphere.
- e) Remove each crucible from the furnace and weigh it to within $\pm 0,1$ mg or better.
- f) Record the crucible mass, m_0 , in grams.

9.3 Weighing the sample

9.3.1 Place the sample, sampled as indicated in [Clause 8](#), in an empty crucible.

9.3.2 Weigh the crucible containing the pellets to within $\pm 0,1$ mg or better.

9.3.3 Record the mass, m_1 , in grams of the crucible containing the pellets.

9.4 Heat treatment cycles

9.4.1 General

The sample shall be heat treated in such a way that the O/M ratio is changed to exactly 2,000. The duration of the oxidation-reduction cycles and the gas flow rates in the furnace shall be optimized according to the nature of the furnace used, the number of sample pellets measured, the pellet composition, etc.

Load the furnace with the crucible containing the sample pellets. Apply the desired heat treatment cycle.

9.4.2 Example 1

9.4.2.1 Under argon sweeping, raise the temperature to $900\text{ }^{\circ}\text{C} \pm 30\text{ }^{\circ}\text{C}$ and hold for 5 min.

9.4.2.2 Under air sweeping, maintain the furnace temperature for 1 min to 7 min at $900\text{ }^{\circ}\text{C} \pm 30\text{ }^{\circ}\text{C}$.

9.4.2.3 Under argon sweeping, maintain the furnace temperature for 5 min at $900\text{ }^{\circ}\text{C} \pm 30\text{ }^{\circ}\text{C}$.

9.4.2.4 Under argon +5 % to 7 % H₂ sweeping, maintain the furnace temperature for 8 h to 13 h at $900\text{ }^{\circ}\text{C} \pm 30\text{ }^{\circ}\text{C}$.

9.4.2.5 Under argon +5 % to 7 % H₂ sweeping, shut off the furnace heating and allow the temperature to drop to 35 °C.

9.4.3 Example 2

9.4.3.1 Heat the samples for 16 h at 800 °C, in an atmosphere comprising a volume fraction of 4 % H₂ in argon saturated with water at room temperature.

9.4.3.2 Cool under dry argon containing a volume fraction of 4 % H₂.

9.5 Final weighing

9.5.1 Remove the crucible from the furnace.

9.5.2 Weigh the crucible to within 0,1 mg or better.

9.5.3 Record the mass, m_2 , in grams of the crucible after oxidation-reduction heat treatment.

ISO 21484:2017(E)

10 Calculation

10.1 Mean atomic mass of oxide after heat treatment

Calculate the mean atomic mass of the oxide after treatment, when O/M = 2,000 exactly, by using [Formula \(1\)](#):

$$m_a = \frac{m(\text{Pu}) \cdot x_{\text{Pu}} + m(\text{U}) \cdot x_{\text{U}} + m(\text{Am}) \cdot x_{\text{Am}}}{x_{\text{Pu}} + x_{\text{U}} + x_{\text{Am}}} + 2m(\text{O}) \quad (1)$$

where

m_a is the mean atomic mass of the oxide of heavy metals;

$m(\text{Pu})$ is the mean atomic mass of plutonium in the oxide;

$m(\text{U})$ is the mean atomic mass of uranium in the oxide;

$m(\text{Am})$ is the mean atomic mass of americium in the oxide;

x_{Pu} is the mole fraction in percent of plutonium in the oxide;

x_{U} is the mole fraction in percent of uranium in the oxide;

x_{Am} is the mole fraction in percent of americium in the oxide;

$m(\text{O})$ is the atomic mass of oxygen (15,999 4);

$x_{\text{Pu}} + x_{\text{U}} + x_{\text{Am}} = 100 \%$.

10.2 Calculation of O/M ratio

[SIST EN ISO 21484:2019](#)

<https://standards.iteh.ai/catalog/standards/sist/15acaf6b-4d28-40ca-a87d-9d1ff6bef0d/sist-en-iso-21484-2019>

Calculate the O/M ratio by using [Formula \(2\)](#):

$$\text{O/M} = 2,000 - \frac{m_a \times (m_2 - m_1)}{m(\text{O}) \times (m_2 - m_0)} \quad (2)$$

where

m_0 is the mass of empty crucible, in g;

m_1 is the mass of crucible with test sample before oxidation-reduction, in g;

m_2 is the mass of crucible with test sample after oxidation-reduction heat treatment, in g;

$m(\text{O})$ is the atomic mass of oxygen (15,999 4);

m_a is the mean atomic mass of the oxide of heavy metals.

11 Precision

11.1 Accuracy

30 determinations on stoichiometric mixed oxide pellets containing approximately 7 % plutonium gave a mean O/M ratio of 2,000.