

---

**Aeronavtika - Odklopniki, enopolni, temperaturno kompenzirani, za naznačene tokove od 1 A do 25 A - 006. del: Ploski spoji 6,3 mm in 2,8 mm s polariziranim signalnim kontaktom - Standard za proizvod**

Aerospace series - Circuit breakers, single-pole, temperature compensated, rated currents 1 A to 25 A - Part 006: 6,3 mm & 2,8 mm blade terminal with polarized signal contact - Product standard

Luft- und Raumfahrt - Schutzschalter, einpolig, temperaturkompensiert, Nennströme von 1 A bis 25 A - Teil 006: Flachsteckverbinder 6,3 mm & 2,8 mm mit polarisiertem signalkontakt - Produktnorm

Série aérospatiale - Disjoncteurs unipolaires compensés en température, intensités nominales 1 A à 25 A - Partie 006 : Borne à lames de 6,3 mm et 2,8 mm avec contact de signalisation polarisé - Norme de produit

<https://standards.iten.ai/catalog/standards/sist/878415ff-a797-401d-8adc-77673b961f11/sist-en-2995-006-2024>

**Ta slovenski standard je istoveten z: EN 2995-006:2023**

**ICS:**

29.120.50	Varovalke in druga nadtokovna zaščita	Fuses and other overcurrent protection devices
49.060	Letalska in vesoljska električna oprema in sistemi	Aerospace electric equipment and systems

**SIST EN 2995-006:2024****en,fr,de**



EUROPEAN STANDARD

EN 2995-006

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2023

ICS 49.060

English Version

**Aerospace series - Circuit breakers, single-pole,  
temperature compensated, rated currents 1 A to 25 A -  
Part 006: 6,3 mm & 2,8 mm blade terminal with polarized  
signal contact - Product standard**

Série aérospatiale - Disjoncteurs unipolaires  
compensés en température, intensités nominales 1 A à  
25 A - Partie 006 : Borne à lames de 6,3 mm et 2,8 mm  
avec contact de signalisation polarisé - Norme de  
produit

Luft- und Raumfahrt - Schutzschalter, einpolig,  
temperaturkompensiert, Nennströme von 1 A bis 25  
A - Teil 006: Flachsteckverbinder 6,3 mm & 2,8 mm mit  
polarisiertem signalkontakt - Produktnorm

This European Standard was approved by CEN on 22 October 2023.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels**

<b>Contents</b>	<b>Page</b>
European foreword .....	3
<b>1 Scope</b> .....	<b>4</b>
<b>2 Normative references</b> .....	<b>4</b>
<b>3 Terms and definitions</b> .....	<b>4</b>
<b>4 Dimensions and mass</b> .....	<b>4</b>
<b>4.1 Dimensional characteristics</b> .....	<b>4</b>
<b>4.2 Electrical diagram</b> .....	<b>7</b>
<b>4.3 Mass</b> .....	<b>8</b>
<b>4.4 Panel mounting</b> .....	<b>8</b>
<b>5 Characteristics</b> .....	<b>8</b>
<b>5.1 Material, surface treatment</b> .....	<b>8</b>
<b>5.2 Mechanical characteristics</b> .....	<b>9</b>
<b>5.2.1 Fasteners</b> .....	<b>9</b>
<b>5.2.2 Recommended tightening torque of attaching nut for installation</b> .....	<b>9</b>
<b>5.2.3 Tensile load of terminals</b> .....	<b>9</b>
<b>5.2.4 Recommended tools for auxiliary contact insertion and extraction</b> .....	<b>9</b>
<b>5.2.5 Resistance to vibrations</b> .....	<b>9</b>
<b>5.2.6 Resistance to shocks</b> .....	<b>9</b>
<b>5.2.7 Mechanical endurance</b> .....	<b>9</b>
<b>5.3 Environment characteristics</b> .....	<b>10</b>
<b>5.3.1 Humidity</b> .....	<b>10</b>
<b>5.3.2 Corrosion</b> .....	<b>10</b>
<b>5.3.3 Contaminating liquids</b> .....	<b>10</b>
<b>5.3.4 Overvoltage caused by lightning</b> .....	<b>10</b>
<b>5.4 Electrical characteristics</b> .....	<b>10</b>
<b>5.4.1 Nominal voltage of operational circuits</b> .....	<b>10</b>
<b>5.4.2 Diode of signal contact</b> .....	<b>10</b>
<b>5.4.3 Voltage drop at <math>I_n</math> and low current</b> .....	<b>10</b>
<b>5.4.4 Minimum and maximum tripping thresholds</b> .....	<b>11</b>
<b>5.4.5 Overload trip</b> .....	<b>12</b>
<b>5.4.6 Short-circuit values</b> .....	<b>12</b>
<b>5.4.7 No-load and load endurance</b> .....	<b>13</b>
<b>5.4.8 Dielectric rigidity</b> .....	<b>13</b>
<b>5.4.9 Insulation resistance</b> .....	<b>13</b>
<b>5.4.10 Overload endurance</b> .....	<b>13</b>
<b>6 Designation</b> .....	<b>14</b>
<b>6.1 Product designation</b> .....	<b>14</b>
<b>6.2 Procurement designation</b> .....	<b>14</b>
<b>7 Rated current code</b> .....	<b>15</b>
<b>8 Delivery hardware codes</b> .....	<b>15</b>
<b>9 Marking</b> .....	<b>15</b>
<b>10 Technical specification</b> .....	<b>15</b>
<b>Bibliography</b> .....	<b>16</b>

## European foreword

This document (EN 2995-006:2023) has been prepared by the Aerospace and Defence Industries Association of Europe — Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this document has received the approval of the National Associations and the Official Services of the member countries of ASD-STAN, prior to its presentation to CEN.

This document shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2024, and conflicting national standards shall be withdrawn at the latest by June 2024.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this document: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[SIST EN 2995-006:2024](https://standards.iteh.ai/catalog/standards/sist/878415ff-a797-401d-8adc-77673b961f11/sist-en-2995-006-2024)

<https://standards.iteh.ai/catalog/standards/sist/878415ff-a797-401d-8adc-77673b961f11/sist-en-2995-006-2024>

**EN 2995-006:2023 (E)****1 Scope**

This document specifies the characteristics of single-pole circuit breakers, temperature compensated with a rated current from 1 A to 25 A, used in aircraft on-board circuits at a temperature between -55 °C and 125 °C and at an altitude of 15 000 m max.

These circuit breakers are operated by a push-pull type single push button (actuator), with delayed action “trip-free” tripping with a polarized signal contact which is open when main contacts are closed, and inversely.

They will continue to function up to the short-circuit current.

**2 Normative references**

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2282<sup>1</sup>, *Aerospace series — Characteristics of aircraft electrical supplies*

EN 2995-001, *Aerospace series — Circuit breakers, single-pole, temperature compensated, rated currents 1 A to 25 A — Part 001: Technical specification*

TR 6083<sup>2</sup>, *Aerospace series — Cut-outs for installation of electrical components*

AMS-STD-595, *Colors Used in Government Procurement*

MIL-PRF-19500<sup>3</sup>, *Performance specification: Semiconductor devices, general specification for*

EN IEC 60934:2019, *Circuit Breakers for Equipment (CBE) (IEC 60934:2019)*

**3 Terms and definitions**

No terms and definitions are listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses: 995-006-2024

— ISO Online browsing platform: available at <https://www.iso.org/obp/>

— IEC Electropedia: available at <https://www.electropedia.org/>

**4 Dimensions and mass****4.1 Dimensional characteristics**

The circuit breakers do not have to correspond to the pictorial illustration, only the dimensions given shall be adhered to. The mounting surface is the contact surface with the circuit breaker panel.

See Figure 1.

<sup>1</sup> Published as ASD-STAN Standard at the date of publication of this document by AeroSpace and Defence industries Association of Europe — Standardization (ASD-STAN), <https://www.asd-stan.org/>.

<sup>2</sup> Published as ASD-STAN Technical Report at the date of publication of this document by AeroSpace and Defence industries Association of Europe — Standardization (ASD-STAN), <https://www.asd-stan.org/>.

<sup>3</sup> Published by: Department of Defense (DOD), the Pentagon, Washington D.C. 20301 USA.