

ETSI TS 129 283 V15.2.0 (2023-01)



Universal Mobile Telecommunications System (UMTS); LTE; Diameter data management applications (3GPP TS 29.283 version 15.2.0 Release 15)

[ETSI TS 129 283 V15.2.0 \(2023-01\)](https://standards.iteh.ai/catalog/standards/sist/4d1f28e1-e6da-4d81-9c2e-97504b5c3bdb/etsi-ts-129-283-v15-2-0-2023-01)

<https://standards.iteh.ai/catalog/standards/sist/4d1f28e1-e6da-4d81-9c2e-97504b5c3bdb/etsi-ts-129-283-v15-2-0-2023-01>



ReferenceRTS/TSGC-0429283vf20

KeywordsLTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards-portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.

All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	6
1 Scope	7
2 References	7
3 Definitions, symbols and abbreviations	8
3.1 Definitions	8
3.2 Abbreviations	8
4 Main Concept	8
4.1 Introduction	8
5 MC Service General Architecture	9
5.1 Introduction	9
5.2 Functional requirements of network entities	9
5.2.1 Functional Requirements of the MC Service Server.....	9
5.2.2 Functional Requirements of the Configuration Management Server.....	9
5.2.3 Functional requirements of MCPTT User Database.....	9
5.3 Functional classification of MC Service Server to MC Service User Database related interface procedures	10
5.4 Functional classification of CSC-13 interface procedures	10
6 Procedure Descriptions for MC Services	11
6.1 Introduction	11
6.2 MC Service User data handling procedures	11
6.2.1 Data Pull	11
6.2.1.1 General	11
6.2.1.2 Detailed behaviour of the requesting entity	12
6.2.1.3 Detailed behaviour of the MC Service User Database	12
6.2.2 Data Update	13
6.2.2.1 General	13
6.2.2.2 Detailed behaviour of the Configuration Management Server.....	14
6.2.2.3 Detailed behaviour of the MC Service User Database	15
6.2.3 Data Notification	16
6.2.3.1 General	16
6.2.3.2 Detailed behaviour of the MCPTT User Database.....	17
6.2.3.3 Detailed behaviour of the receiving entity	17
6.3 Requesting entity permissions list.....	18
6.3.1 General.....	18
7 Protocol Specification and Implementation for MC Service.....	19
7.1 General	19
7.1.1 Use of Diameter base protocol.....	19
7.1.2 Securing Diameter Messages	19
7.1.3 Accounting functionality	19
7.1.4 Use of sessions.....	20
7.1.5 Transport protocol	20
7.1.6 Routing considerations	20
7.1.7 Advertising Application Support	21
7.1.8 Diameter Application Identifier.....	21
7.1.9 Use of the Supported-Features AVP	21
7.1.10 MC Service ID to MC Service User Database resolution	21
7.2 Commands.....	23
7.2.1 Introduction.....	23
7.2.2 Command-Code values.....	23

7.2.3	Data-Pull-Request (DPR) Command	23
7.2.4	Data-Pull-Answer (DPA) Command	24
7.2.5	Data-Update-Request (DUR) Command	24
7.2.6	Data-Update-Answer (DUA) Command	24
7.2.7	Notification-Data-Request (PDR) Command	25
7.2.8	Notification-Data-Answer (PDA) Command	25
7.3	AVPs	26
7.3.1	General.....	26
7.3.2	MCPTT-ID	27
7.3.3	Data-Identification	27
7.3.4	DRMP	27
7.3.5	OC-OLR	27
7.3.6	OC-Supported-Features	27
7.3.7	User-Data	27
7.3.8	User-Identifier.....	28
7.3.9	Feature-List-ID AVP	28
7.3.10	Feature-List AVP	28
7.3.11	Data-Identification-Prefix.....	28
7.3.12	Data-Identification-Flags	28
7.3.13	DPR-Flags.....	29
7.3.14	DPA-Flags	29
7.3.15	DUR-Flags.....	29
7.3.16	DUA-Flags.....	29
7.3.17	NDR-Flags.....	30
7.3.18	NDA-Flags.....	30
7.3.19	User-Data-Id	30
7.3.20	MC-Service-User-Profile-Data	30
7.3.21	Sequence-Number.....	31
7.3.22	Data.....	31
7.3.23	Load.....	31
7.3.24	MCVideo-ID.....	31
7.3.25	MCDData-ID	31
7.4	Result-Code and Experimental-Result-Code Values.....	31
7.4.1	Introduction.....	31
7.4.2	Success.....	31
7.4.2.1	General	31
7.4.3	Permanent Failures	31
7.4.3.1	General	31
7.4.3.2	DIAMETER_ERROR_USER_UNKNOWN (5001).....	32
7.4.3.3	DIAMETER_ERROR_USER_DATA_NOT_RECOGNIZED (5100).....	32
7.4.3.4	DIAMETER_ERROR_OPERATION_NOT_ALLOWED (5101).....	32
7.4.3.5	DIAMETER_ERROR_USER_DATA_CANNOT_BE_READ (5102).....	32
7.4.3.6	DIAMETER_ERROR_USER_DATA_CANNOT_BE_MODIFIED (5103).....	32
7.4.3.7	DIAMETER_ERROR_USER_DATA_CANNOT_BE_NOTIFIED (5104).....	32
7.4.3.8	DIAMETER_ERROR_TOO_MUCH_DATA (5008)	32
7.4.3.9	DIAMETER_ERROR_DATA_OUT_OF_SYNC (5105)	32
7.4.3.10	DIAMETER_ERROR_FEATURE_UNSUPPORTED (5011).....	32
7.4.3.11	DIAMETER_ERROR_NO_SUBSCRIPTION_TO_DATA (5107).....	32
7.4.3.12	DIAMETER_ERROR_UNKNOWN_DATA (5670)	32
7.4.3.13	DIAMETER_ERROR_REQUIRED_KEY_NOT_PROVIDED (5671).....	32
7.4.4	Transient Failures	33
7.4.4.1	General	33
7.4.4.2	DIAMETER_USER_DATA_NOT_AVAILABLE (4100)	33
7.4.4.3	DIAMETER_PRIOR_UPDATE_IN_PROGRESS (4101).....	33
Annex A (normative):	Diameter overload control mechanism	34
A.1	General	34
A.2	MC Service User Database behaviour.....	34
A.3	MC Service Server and Configuration Management Server behaviour	34

Annex B (Informative):	Diameter overload node behaviour	35
B.1	Message prioritization	35
Annex C (normative):	Diameter message priority mechanism.....	36
C.1	General	36
C.2	MCPTT-2, MCVideo-2, MCData-2 and CSC-13 interfaces	36
C.2.1	General	36
C.2.2	MC Service Server and Configuration Management Server behaviour	36
C.2.3	MC Service User Database behaviour	37
Annex D (normative):	Diameter load control mechanism.....	38
D.1	General	38
D.2	MC Service User Database behaviour.....	38
D.3	MC Service Server and Configuration Management Server behaviour	38
Annex E (informative):	Change history	39
History		40

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ETSI TS 129 283 V15.2.0 (2023-01)

<https://standards.iteh.ai/catalog/standards/sist/4d1f28e1-e6da-4d81-9c2e-97504b5c3bdb/etsi-ts-129-283-v15-2-0-2023-01>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ETSI TS 129 283 V15.2.0 (2023-01)

<https://standards.iteh.ai/catalog/standards/sist/4d1f28e1-e6da-4d81-9c2e-97504b5c3bdb/etsi-ts-129-283-v15-2-0-2023-01>

1 Scope

The common functional architecture for support of Mission Critical (MC) services is specified in 3GPP TS 23.280 [21].

The functional architecture for support of Mission Critical Push To Talk (MCPTT) services is specified in 3GPP TS 23.379 [18].

The functional architecture for support of Mission Critical Video (MCVideo) services is specified in 3GPP TS 23.281 [19].

The functional architecture for support of Mission Critical Data (MCData) services is specified in 3GPP TS 23.282 [20].

This 3GPP Technical Specification (TS) specifies:

1. The interactions between the MC Service User Database and the MC Service Server:
 - This interface between the MCPTT User Database and the MCPTT Server is referred to as the MCPTT-2 reference point, as specified in 3GPP TS 23.379 [18].
 - This interface between the MCVideo User Database and the MCVideo Server is referred to as the MCVideo-2 reference point, as specified in 3GPP TS 23.281 [19].
 - This interface between the MCData User Database and the MCData Server is referred to as the MCData-2 reference point, as specified in 3GPP TS 23.282 [20].
 - This interface between the MCData User Database and the MCData Server is referred to as the MCVideo-2 reference point, as specified in 3GPP TS 23.282 [20].
2. The interactions between the MC Service User Database and the Configuration Management Server. This interface is referred to as the CSC-13 reference point.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- | | |
|-----|--|
| [1] | 3GPP TR 21.905: "Vocabulary for 3GPP Specifications". |
| [2] | Void. |
| [3] | Void. |
| [4] | 3GPP TS 33.210: "3G security; Network Domain Security (NDS); IP network layer security". |
| [5] | IETF RFC 4960: "Stream Control Transmission Protocol". |
| [6] | 3GPP TS 29.229: "Cx and Dx interfaces based on the Diameter protocol; Protocol details". |
| [7] | IETF RFC 5234: "Augmented BNF for Syntax Specifications: ABNF". |
| [8] | IETF RFC 7944: "Diameter Routing Message Priority". |
| [9] | 3GPP TS 29.329: "Sh interface based on the Diameter protocol; Protocol details". |

- [10] 3GPP TS 29.336: "Home Subscriber Server (HSS) diameter interfaces for interworking with packet data networks and applications".
- [11] IETF RFC 7683: "Diameter Overload Indication Conveyance".
- [12] 3GPP TS 23.003: "Numbering, addressing and identification".
- [13] 3GPP TS 24.229: "IP multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3".
- [14] 3GPP TS 29.228: "IP Multimedia (IM) Subsystem Cx and Dx Interfaces; Signalling flows and message contents".
- [15] IETF RFC 3986: "Uniform Resource Identifier (URI): Generic Syntax".
- [16] Void.
- [17] IETF RFC 8583: "Diameter Load Information Conveyance".
- [18] 3GPP TS 23.379: "Functional architecture and information flows to support Mission Critical Push To Talk (MCPTT); Stage 2".
- [19] 3GPP TS 23.281: "Functional architecture and information flows to support Mission Critical Video (MCVideo); Stage 2".
- [20] 3GPP TS 23.282: "Functional architecture and information flows to support Mission Critical Data (MCData); Stage 2".
- [21] 3GPP TS 23.280: "Common functional architecture to support mission critical services; Stage 2".
- [22] 3GPP TS 24.484: "Mission Critical Services (MCS) configuration management; Protocol specification".
- [23] IETF RFC 6733: "Diameter Base Protocol".

ETSI TS 129 283 V15.2.0 (2023-01)

<https://standards.iteh.ai/catalog/standards/sist/d1122831-cbda-4d81-9c2e-424410401000/etsi-ts-129-283-v15-2-0-2023-01>

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1], in 3GPP TS 23.281 [19], in 3GPP TS 23.282 [20], in 3GPP TS 23.280 [21], in 3GPP TS 23.379 [18] and the following apply, if any.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1], in 3GPP TS 23.281 [19], in 3GPP TS 23.282 [20], in 3GPP TS 23.280 [21], in 3GPP TS 23.379 [18] and the following apply, if any. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

4 Main Concept

4.1 Introduction

The MCPTT-2 reference point (between the MCPTT Server and the MCPTT User Database) is defined in the 3GPP TS 23.379 [18].

The MCVideo-2 reference point (between the MCVideo Server and the MCVideo User Database) is defined in the 3GPP TS 23.281 [19].

The MCDData-2 reference point (between the MCDData Server and the MCDData User Database) is defined in the 3GPP TS 23.282 [20].

The CSC-13 reference point (between the Configuration Management and the MC Service User Database) is defined in the 3GPP TS 23.280 [21].

This document describes the Diameter-based related procedures, message parameters and protocol specification for MCPTT-2, MDVideo-2, MCDData-2 and CSC-13 reference points.

This document specifies the Diameter Management Application used as protocol over the MCPTT-2, MDVideo-2, MCDData-2 and CSC-13 reference points.

5 MC Service General Architecture

5.1 Introduction

This clause further specifies the architectural assumptions associated with the MCPTT-2, MDVideo-2, MCDData-2 and CSC-13 reference points, building on respectively 3GPP TS 23.379 [18], 3GPP TS 23.281 [19], 3GPP TS 23.282 [20] and 3GPP TS 23.280 [21].

5.2 Functional requirements of network entities

5.2.1 Functional Requirements of the MC Service Server

Depending on the MC Service, the MC Server is:

- the MCPTT Server for MCPTT services, as defined in 3GPP TS 23.379 [18],
- the MCVideo Server for MCVideo services, as defined in 3GPP TS 23.281 [19],
- and the MCDData Server for MCDData services, as defined in 3GPP TS 23.282 [20].

The MC Service Server may communicate with the MC Service User Database over:

- the MCPTT-2 interface between the MCPTT Server and the MCPTT User Database;
- the MCVideo-2 interface between the MCVideo Server and the MCVideo User Database;
- the MCDData-2 interface between the MCDData Server and the MCPTT User Database.

For more details on the functionality of the MC Service Server, refer to 3GPP TS 23.379 [18], 3GPP TS 23.281 [19] and 3GPP TS 23.282 [20], depending on the MC Service.

5.2.2 Functional Requirements of the Configuration Management Server

The Configuration Management Server may communicate with the MC Service User Database over the CSC-13 interface.

For more details on the functionality of the Configuration Management Server, refer to 3GPP TS 23.280 [21].

5.2.3 Functional requirements of MCPTT User Database

Depending on the MC Service, the MC Service User Database is:

- the MCPTT user database for MCPTT services, as defined in 3GPP TS 23.379 [18],

- the MCVideo user database for MCVideo services, as defined in 3GPP TS 23.281 [19],
- and the MCDData user database for MCDData services, as defined in 3GPP TS 23.282 [20].

These MC service user databases can be co-located.

The MCPTT User Database may communicate with the MCPTT Server over the MCPTT-2 interface.

The MCVideo User Database may communicate with the MCVideo Server over the MCVideo-2 interface.

The MCDData User Database may communicate with the MCDData Server over the MCDData-2 interface.

Any MC Service User Database may communicate with the Configuration Management Server over the CSC-13 interface.

For more details on the functionality of the MC Service User Database, refer to 3GPP TS 23.280 [21], 3GPP TS 23.379 [18], 3GPP TS 23.281 [19] and 3GPP TS 23.282 [20] depending on the MC Service.

5.3 Functional classification of MC Service Server to MC Service User Database related interface procedures

MC Service Server to MC Service User Database interfaces are:

- The MCPTT-2 interface between the MCPTT User Database and the MCPTT Server;
- The MCVideo-2 interface between the MCVideo User Database and the MCVideo Server;
- The MCDData-2 interface between the MCDData User Database and the MCDData Server.

Operations on the MC Service Server to MC Service User Database interfaces are classified in functional groups:

1. Data handling procedures

- The download of data from the MC Service User Database to an MC Service Server.
- The subscription to notifications from the MC Service User Database when particular information about a specific MC Service User is updated.
- The MC Service User Database can notify an MC Service Server of changes in data for which the MC Service Server previously had subscribed.

5.4 Functional classification of CSC-13 interface procedures

Operations on the CSC-13 interface are classified in functional groups:

1. Data handling procedures

- The download of data from the MC Service User Database to a Configuration Management Server.
- The update of data in the MC Service User Database.
- The subscription to notifications from the MC Service User Database when particular information about a specific MC Service User is updated.
- The MC Service User Database can notify a Configuration Management Server of changes in data for which the Configuration Management Server previously had subscribed.

6 Procedure Descriptions for MC Services

6.1 Introduction

This clause describes the procedures invoked between MC Service Server(s) and the MC Service User Database(s), i.e.:

- between the MCPTT Server and the MCPTT User Database over the MCPTT-2 reference point;
- between the MCVideo Server and the MCVideo User Database over the MCVideo-2 reference point;
- between the MCDATA Server and the MCDATA User Database over the MCDATA-2 reference point.

This clause describes the procedures invoked between the Configuration Management Server and the MC Service User Database over the CSC-13 reference point.

In the tables that describe the Information Elements transported by each command, each Information Element is marked as (M) Mandatory, (C) Conditional or (O) Optional in the "Cat." column. For the correct handling of the Information Element according to the category type, see the description detailed in clause 6 of the 3GPP TS 29.228 [14].

6.2 MC Service User data handling procedures

6.2.1 Data Pull

6.2.1.1 General

This procedure is used between the MC Service Server or the Configuration Management Server and the MC Service User Database.

The procedure is invoked by the MC Service Server or the Configuration Management Server and is used:

- To obtain information for a specific MC Service ID from the MC Service User Database;
- To subscribe to notifications from the MC Service User Database for when particular information associated with a specific MC Service ID is updated.

This procedure is mapped to the commands Data-Pull-Request/Answer in the Diameter application specified in clause 7.2.3/7.2.4. The tables 6.2.1-1 and 6.2.1-2 detail the involved information elements.

Table 6.2.1-1: Data Pull Request

Information element name	Mapping to Diameter AVP	Cat.	Description
MC Service ID	User-Identifier (See 7.3.8)	M	This information element contains the MC Service ID of the MC Service user for whom the data is required. See 3GPP TS 23.280 [21]. See clause 7.3.8 for the content of this AVP.
Requested Data	Data-Identification (See 7.3.3)	M	This information element indicates the requested information. The set of valid values are defined in clause 7.3.3.
DPR Flags	DPR-Flags (See 7.3.13)	O	This information element contains one or several flags that define different command behaviours. The set of valid values are defined in clause 7.3.13.
User Data ID	User-Data-Id	O	This information element contain the unique identifier of a given MC Service User Profile defined for an MC Service User.

Table 6.2.1-2: Data Pull Response

Information element name	Mapping to Diameter AVP	Cat.	Description
Result	Result-Code / Experimental_Result (See 7.4)	M	Result of the request. Result-Code AVP shall be used for errors defined in the Diameter base protocol (see IETF RFC 6733 [23]). Experimental-Result AVP shall be used for Data Management application errors. This is a grouped AVP which contains the 3GPP Vendor ID in the Vendor-Id AVP, and the error code in the Experimental-Result-Code AVP.
Returned Data	Data (See 7.3.22)	C	This information element shall contain the requested data that is successfully returned. This information element shall be present when all requested data exist in the MC Service User Database, the requesting entity has permissions to read them and they are all successfully read. Otherwise, it shall be absent.
Failed Requested Data	Data-Identification (See 7.3.3)	C	This information element indicates the requested data that cannot be retrieved by the requesting entity, when the corresponding error only applies to some of the requested data. The set of valid values are defined in 7.3.3. This information element shall be present when the Experimental-Result-Code AVP is set to "DIAMETER_ERROR_USER_DATA_CANNOT_BE_READ" or "DIAMETER_ERROR_UNKNOWN_DATA" and more than one data was requested. Otherwise, it may be absent.
DPA Flags	DPA-Flags (See 7.3.14)	O	This information element contains one or several flags that define different command behaviours. The set of valid values are defined in clause 7.3.14.

6.2.1.2 Detailed behaviour of the requesting entity

The MC Service Server or the Configuration Management Server shall make use of this procedure to retrieve from the MC Service User Database the MC Service User Profile associated with an MC Service ID i.e. the user ID of a MC user within a specific MC Service. The request shall include the MC Service ID (e.g. MCPTT ID for MCPTT service) and the requested data. The MC Service Server or the Configuration Management Server may set the "Subscription to notifications" flag in the DPR-Flags to subscribe to the service of notifications for any change for the requested data is requested. Otherwise, the "Subscription to notifications" flag in the DPR-Flags shall be cleared.

The MC Service Server or the Configuration Management Server may make use of this procedure to unsubscribe to the notifications service for a given MC user within a specific MC Service. The request shall include the MC Service ID identifying the MC user within a specific MC Service. The "Subscription to notifications" flag shall be cleared in the DPR-Flags to unsubscribe to the service of notifications for any change for the requested data.

When receiving the Data Pull response with the Result Code set to "DIAMETER_SUCCESS" with the requested MC Service User data, the MC Service Server or the Configuration Management Server should store the received data if the subscription to the notifications service was requested and the "Notifications service status" flag is set by the MC Service User Database in the DPA-Flags AVP.

6.2.1.3 Detailed behaviour of the MC Service User Database

The MC Service User Database may prioritise the received request message according to priority level received within the DRMP AVP.

Upon reception of the Data Pull Request, the MC Service User Database shall check whether the MC Service ID for whom data is asked exists in the MC Service User Database. If not, Experimental-Result-Code shall be set to "DIAMETER_ERROR_USER_UNKNOWN" in the Data Pull Response.

The MC Service User Database shall check whether the requested data exist. If one or more requested data are not recognized or supported by the MC Service User Database, the MC Service User Database shall set the Experimental-