



SLOVENSKI STANDARD
SIST EN 301 419-2:2000

01-junij-2000

8 [[[HJb]W] b]hY_ca i b] UWg_]g]ghYa fUnU&ŽL!Df]_`4]hj YbY'nU H]j Y'nU
[`cVUb]g]ghYa `a cV]b]`_ca i b] UW^f] GAŁ!AcV]bYdcgHUY'nUdfYbcg]j cXcj bc
_ca i hfUb] `dcXU_cj `n]]gc_c`]fcgħc]b`i dcfUvc]j Y ` Ugcj b] `c_Yb`fk G7 G8Ł!
8 cglcd`f] GA`% " (žfUn]]WU) "\$" Ł

Digital cellular telecommunications system (Phase 2+); Attachment requirements for
Global System for Mobile communications (GSM); High Speed Circuit Switched Data
(HSCSD) multislots mobile stations; Access (GSM 13.34 version 5.0.3)

<https://standards.iteh.ai/catalog/standards/sist/40e3c339-c2b1-4126-8a8b-6520c49f4606/sist-en-301-419-2-2000>

Ta slovenski standard je istoveten z: EN 301 419-2 Version 5.0.3

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---------------------------------------------------	----------------------------------------------

SIST EN 301 419-2:2000 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 419-2:2000

<https://standards.iteh.ai/catalog/standards/sist/40e3c339-c2b1-4126-8a8b-6520c49f4606/sist-en-301-419-2-2000>

EN 301 419-2 V5.0.3 (1999-03)

European Standard (Telecommunications series)

**Digital cellular telecommunications system (Phase 2+);
Attachment requirements for Global System for Mobile
communications (GSM);
High Speed Circuit Switched Data (HSCSD) Multislot
Mobile Stations;
Access
(GSM 13.34 version 5.0.3)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

GSM®
GLOBAL SYSTEM FOR
MOBILE COMMUNICATIONS

SIST EN 301 419-2:2000

<https://standards.iteh.ai/catalog/standards/sist/40e3c339-c2b1-4126-8a8b-6520c49f4606/sist-en-301-419-2-2000>



Reference

DEN/SMG-071334Q (d50i2i20.PDF)

Keywords

Digital cellular telecommunications system,
Global System for Mobile communications
(GSM), HSCSD

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la
Sous-Prefecture de Grasse (06) N° 7803/88

<https://standards.etsi.org/standards-sist/en-301-419-2-2000>

Internet

secretariat@etsi.fr

Individual copies of this ETSI deliverable
can be downloaded from

<http://www.etsi.org>

If you find errors in the present document, send your
comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.
All rights reserved.

Contents

Intellectual Property Rights.....	4
Foreword	4
1 Scope.....	5
2 Normative references	5
3 Abbreviations.....	6
4 General requirements	6
5 Requirements	6
Annex A (normative): The Requirement Table (RT).....	13
A.1 Introduction to the RT.....	13
A.2 Format of the tables.....	13
A.3 References to EN 300 607-1 (GSM 11.10-1).....	14
A.4 Notations used in the RT.....	14
A.4.1 Status Notations	14
A.4.2 Support Answer Notations	14
A.5 The Requirement Tables.....	15
A.5.1 Static Requirements, RT A	15
A.5.1.1 Types of Mobile Stations	15
A.5.1.2 Mobile Station Features	15
A.5.1.3 Teleservices.....	15
A.5.1.4 Bearer Services.....	16
A.5.1.5 Supplementary Services	16
A.5.1.6 Bearer Capability Information.....	16
A.5.1.7 Additional Information.....	16
A.5.2 Dynamic Requirements, RT B	16
Annex B (informative): Document history.....	19
History	20

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Harmonised Standard has been produced by the Special Mobile Group (SMG) of the European Telecommunications Standards Institute (ETSI).

This standard covers the High Speed Circuit Switched Data Multislot (HSCSD) requirements for terminal equipment for the Global System for Mobile communications (GSM) mobile services.

This standard contains the procedures and requirements for the approval testing of GSM terminal equipment implementing the HSCSD optional feature for access.

The requirements of TBR 19 [3] and/or TBR-31 [5], apply in addition to this standard, for HSCSD terminal equipment, Access.

For each test, supplementary information is provided, giving a justification why this item has been selected for regulatory testing, and a reference to the relevant article of the Terminal Directive [1].

This document is based on EN 300 607-1 (GSM 11.10-1 version 5.5.0) [2].

The contents of this EN may be subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of this EN it will then be re-submitted for formal approval procedures by ETSI with an identifying change of release date and an increase in version number as follows:

Version 5.x.y

where:

- 5 GSM Phase 2+
- x the second digit is incremented for all other types of changes, i.e. technical enhancements, corrections, updates, etc.;
- y the third digit is incremented when editorial only changes have been incorporated in the specification.

Proposed national transposition dates

Date of adoption of this EN:	19 March 1999
Date of latest announcement of this EN (doa):	30 June 1999
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 1999
Date of withdrawal of any conflicting National Standard (dow):	31 December 1999

1 Scope

This Harmonised Standard specifies the technical requirements to be met by terminal equipment capable of connecting to a public telecommunications network and that support the GSM High Speed Circuit Switched Data Multislot (HSCSD) feature. These requirements apply to terminals for Phase 2+ of the public land mobile radio service, operating in the 900 MHz and 1800 MHz bands with a channel separation of 200 kHz, utilising constant envelope modulation and carrying traffic channels according to the Time Division Multiple Access (TDMA) principle.

This standard specifies the terminal equipment HSCSD requirements for the GSM 900 and the DCS 1800 versions of the Global System for Mobile communications (GSM).

This standard applies in addition to any regulatory requirements, eg. CTR 19/CTR 31, for HSCSD terminal equipment, Access.

For each test purpose and its corresponding conformance requirement, a reference is given to the test method in EN 300 607-1 (GSM 11.10-1) [2]. The requirements apply at the air interface and the Subscriber Identity Module - Mobile Equipment interface for the access requirements, which may be stimulated to perform the tests by additional equipment if necessary.

The measurement uncertainty is described in EN 300 607-1 (GSM 11.10-1) [2].

This standard covers the essential requirements of the Terminal Directive 98/13/EC [1] Articles 5d, 5e, 5f.

The Terminal Directive 98/13/EC [1] Articles 5a and 5b are covered by other directives, and, therefore, not by this standard.

In this standard, there are no Electromagnetic Compatibility technical requirements in terms of the Terminal Directive 98/18/EC [1], Article 5c.

NOTE 1: Technical Requirements for EMC performance and testing of the equipment are covered by the relevant standards applicable to the EMC Directive 89/336/EEC, annex A.

This standard specifies the HSCSD Terminal equipment additional requirements, Access.

EN 300 607-1 (GSM 11.10-1) [2] constitutes the conformance test suite for GSM. The verification of the conformance requirements in this standard is based on the tests described in this reference. The set of requirements in EN 300 607-1 (GSM 11.10-1) [2] and the set of requirements in this standard need not be identical.

All the requirements in this standard are specific to mobile stations supporting HSCSD.

An active accessory is covered by this standard if it modifies the terminal performance in an aspect which affects conformance to essential requirements.

NOTE 2: Only active devices are subject to this standard. Accessories may be tested with specific terminals, and either approved for use with those terminals only, or may possibly be approved for use with a wider range of terminals, depending on the nature and effect of the accessory.

2 Normative references

References may be made to:

- a) specific versions of publications (identified by date of publication, edition number, version number, etc.), in which case, subsequent revisions to the referenced document do not apply; or
- b) all versions up to and including the identified version (identified by "up to and including" before the version identity); or
- c) all versions subsequent to and including the identified version (identified by "onwards" following the version identity); or
- d) publications without mention of a specific version, in which case the latest version applies.

A non-specific reference to a standard shall also be taken to refer to later versions published as a standard with the same number.

- [1] Directive 98/13/EC of the European Parliament and of the Council of 12 February 1998 relating to telecommunications terminal equipment and satellite earth station equipment, including the mutual recognition of their conformity.
- [2] EN 300 607-1 (GSM 11.10-1 version 5.5.0): "Digital cellular telecommunications system (Phase 2+); Mobile station conformity specifications".
- [3] TBR 19: "European digital cellular telecommunications system; Attachment requirements for Global System for Mobile communications (GSM) mobile stations; Access".
- [4] GSM 01.04 (ETR 350): "Digital cellular telecommunication system (Phase 2+); Abbreviations and acronyms"
- [5] TBR 31: "European digital cellular telecommunications system (Phase2); Attachment requirements for mobile stations in the DCS 1800 band and additional GSM 900 band; Access".
- [6] TBR 20: "European digital cellular telecommunications system (Phase 20; Attachment requirements for Global System for Mobile communications (GSM) mobile stations; Telephony".
- [7] TBR 32: "European digital cellular telecommunications system (Phase2); Attachment requirements for mobile stations in the DCS 1800 band and additional GSM 900 band; Telephony".

3 Abbreviations

For the purposes of this standard the following additional abbreviations apply:

HSCSD	High Speed Circuit Switched Data
MO	Mobile Originated
MT	Mobile Terminated
T	Transparent
NT	Non Transparent
AIUR	Air Interface User Rate
FNUR	Fixed Network User Rate

Additional GSM related abbreviations can be found in GSM 01.04 (ETR 350) [4].

4 General requirements

HSCSD terminals shall conform to:

- a) the requirements of TBR 19/TBR 31 according to the frequency band(s) implemented in the terminal; and
- b) the requirements of clause 5 of this standard; and
- c) the requirements in Annex A of this standard; and
- d) if the terminal implements speech services, the requirements of TBR 20/TBR 32 according to the frequency band(s) implemented in the terminal.

5 Requirements

The following table contains all requirements that are needed to meet the essential requirements as defined in the Terminal Directive [1]. A justification according to article 5 of the Terminal Directive is given by stating the relevant categories (c to f) together with a text supporting the justification.

The entries are defined as follows:

- "EN 300 607-1 Item" defines the item number of the conformance requirement and also the reference to EN 300 607-1 (GSM 11.10-1) [2]. This reference is a normative reference to a subclause of EN 300 607-1 (GSM 11.10-1) [2] containing the conformance requirement text, and references to the base standard.
- "Description" contains a short description of the requirement.
- "Justification" contains supplementary information to explain the justification of the requirement according to article 5 of the Terminal Directive [1].
- "TD Cat" defines the category according to article 5 of the Terminal Directive [1].
- "Test Cat" defines whether the requirement is covered by a "special test situation" (e.g. a manufacturer's declaration of some form). An "X" indicates a special test situation, whilst, a blank entry indicates conformity is by the test referred to by this standard.

Table 1: Requirements and Justifications

EN 300 607-1 Item	Description	Justification	TD Cat	Test Cat
13.6	Transmitter - Frequency error and phase error in HSCSD multislot configuration	Non compliance in this area may cause interference to other spectrum users.	e	
13.7	Transmitter output power and burst timing in HSCSD multislot configurations	Non compliance in this area may cause interference to other spectrum users.	e	
13.8	Transmitter - Output RF spectrum in HSCSD multislot configuration	Non compliance in this area may cause interference to other spectrum users.	e	

(standards.iteh.ai)

Table 1 (continued): Requirements and Justifications

EN 300 607-1 Item	Description	Justification	TD Cat	Test Cat
14.2.8	Receiver / Reference sensitivity - full rate data channels in multislot configuration	Non Compliance in this area may impair establishment and the maintaining of the call.	f	X

Table 1 (continued): Requirements and Justifications

EN 300 607-1 Item	Description	Justification	TD Cat	Test Cat
18.2	Temporary reception gaps in HSCSD multislot configurations	Non Compliance in this area may impair the holding of the connection.	f	

Table 1 (continued): Requirements and Justifications

EN 300 607-1 Item	Description	Justification	TD Cat	Test Cat
21.5	Received signal measurements in HSCSD multislot configuration	Non compliance in this area may lead to ignore excessive values of RXLEV, under normal or extreme conditions.	e, f	

Table 1 (continued): Requirements and Justifications

EN 300 607-1 Item	Description	Justification	TD Cat	Test Cat
22.2	Transmit power control timing and confirmation in HSCSD mutlislot configurations.	Spectrum efficiency.	E	

Table 1 (continued): Requirements and Justifications

EN 300 607-1 Item	Description	Justification	TD Cat	Test Cat
26.13.1.1.1	Multislot signalling / RR / Measurement / symmetric	This test case verifies that the MS does not report about cells which are suitable from a radio propagation point of view but which could not accommodate the MS for other reasons. The measurement reports that are sent by the MS are used by the network to determine whether a handover procedure should be performed and towards which cell it can be performed (Article 5f). For its measurements, the MS has to follow the indications broadcasted by the network in the SYSTEM INFORMATION messages.	f	
26.13.1.1.2	Multislot signalling / RR / Measurement / asymmetric	This test case verifies that the MS does not report about cells which are suitable from a radio propagation point of view but which could not accommodate the MS for other reasons. The measurement reports that are sent by the MS are used by the network to determine whether a handover procedure should be performed and towards which cell it can be performed (Article 5f). For its measurements, the MS has to follow the indications broadcasted by the network in the SYSTEM INFORMATION messages.	f	
26.13.1.1.3	Multislot signalling / RR / Measurement / asymmetric / Change of the reported subchannel	This test guarantees the reliability of measurement reports	e, f	
26.13.1.2.1	Multislot signalling / RR / Dedicated assignment / successful case	If the assignment procedure is not correctly implemented by the MS, connections can not be established (Article 5f). If the correct power level is not applied this harms the network (Article 5d).	d, f	
26.13.1.2.2	Multislot signalling / RR / Dedicated assignment / failure / general case	If the assignment failure procedure is not correctly implemented by the MS, that MS can not be able to re-establish the old link.	f	
26.13.1.3.1	Multislot signalling / RR / Handover / successful / active call / non-synchronized	If the handover procedure is not correctly implemented by the MS, it is impossible to switch a call in progress from one cell to another cell.	f	
26.13.1.3.2	Multislot signalling / RR / Handover / successful / call under establishment / non synchronized / resource upgrading	If the handover procedure is not correctly implemented by the MS, it is impossible to switch a call in progress from one cell to another cell.	f	
(continued)				

Table 1 (continued): Requirements and Justifications

26.13.1.3.3	Multislot signalling / RR / Handover / successful / active call / finely synchronized / resource downgrading	If the handover procedure is not correctly implemented by the MS, it is impossible to switch a call in progress from one cell to another cell.	f	
26.13.1.3.4	Multislot signalling / RR / Handover / successful / call under establishment / finely synchronized / relocation of channels	If the handover procedure is not correctly implemented by the MS, it is impossible to switch a call in progress from one cell to another cell.	f	
26.13.1.3.5	Multislot signalling / RR / Handover / successful / call under establishment / pre-synchronized / resource upgrading	If the handover procedure is not correctly implemented by the MS, it is impossible to switch a call in progress from one cell to another cell.	d, f	
26.13.1.4	Multislot signalling / RR / Test of the channel mode modify procedure	Non Compliance in this area may impair the modification / holding of the call.	f	
26.13.1.5	Multislot signalling / RR / Early classmark sending	Networks may systematically use this procedure and, if it is incorrectly implemented in the MS, the basic connection establishment procedure may systematically fail.	f	
26.13.2.1.1	Multislot signalling / CC / In-call functions / User initiated service level upgrade / successful	Non Compliance in this area may impair the modification / holding of the call.	f	
26.13.2.1.2	Multislot signalling / CC / In-call functions / User initiated service level downgrade / successful	Non Compliance in this area may impair the modification / holding of the call.	f	
26.13.2.1.3	Multislot signalling / CC / In-call functions / User initiated service level upgrade / Time-out of timer T323	Non Compliance in this area may impair the modification / holding of the call.	f	
26.13.2.1.4	Multislot signalling / CC / In-call functions / User initiated service level upgrade / modify reject	Non Compliance in this area may impair the modification / holding of the call.	f	

(continued)