This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.



Designation: D5331–98 Designation: D 5331 – 03 (Reapproved 2009)^{ε1}

Standard Test Method for Evaluation of Mechanical Handling of Unitized Loads Secured with Stretch Wrap Films¹

This standard is issued under the fixed designation D 5331; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

 ε^1 Note—Paragraphs 3.2.2 and 7.2 were editorially corrected in March 2009.

1. Scope

1.1 This test method covers evaluation and comparison of the ability of unitizing films to survive various methods of mechanical handling.

1.2 The test method described is applicable to common means of material handling, including the following: forklift, push/pull, clamp truck, crane, and spade lift-type handling systems.

1.3 The test levels may be varied to reflect known levels of intensity accurately for the specific unit load under testing.

1.4 The methodology of performing the mechanical handling tests is described in detail in Test Methods <u>D1083D 6055 and Test</u> <u>Methods D 6179</u>. This test method will describe only sample preparation and evaluation in the special case of evaluating the performance of stretch film for load unitizing.

1.5The values stated in inch-pound units are to be regarded as the standard. The values given in parentheses are for information only.

1.5 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.6 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

2. Referenced Documents

2.1 ASTM Standards:²

- D1083Test Methods for Mechanical Handling of Unitized Loads and Large Shipping Cases and Crates <u>996</u> Terminology of Packaging and Distribution Environments
- D 4169 Practice for Performance Testing of Shipping Containers and Systems
- D 6055 Test Methods for Mechanical Handling of Unitized Loads and Large Shipping Cases and Crates D 6179 Test Methods for Rough Handling of Unitized Loads and Large Shipping Cases and Crates

3. Terminology

- 3.1 Definitions—General definitions for packaging and distribution environments are found in Terminology D 996.
- 3.2 Definitions of Terms Specific to This Standard:

3.2.1 *large shipping case or crate*—for the purposes of this test method, a shipping container constructed of any material, and of such size and weight, to require mechanical handling. A case or crate of this type may weigh from 100 lb (45 kg) to many tons and measure proportionally. The case or crate may be secured to or carried by a base or pallet. Frame members may be provided for rigidity throughout the container.

3.2.2 *spade lifelift attachment*—a lift truck attachment used for top handling products packaged in interlocking flange cartons (IFC) or folded cap or folded flap style cartons.

3.2.3 *unitized load*—for the purposes of this test method, consisting of a number of packages (two or more) wrapped or banded together as a shipping unit. When unitized, these packages typically weigh more than 100 lb (45 kg). The unitized method may

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.

¹ This test method is under the jurisdiction of ASTM Committee <u>D-10D10</u> on Packaging and is the direct responsibility of Subcommittee D10.25 on Palletizing and Unitizing of Loads.

Current edition approved April 10, 1998: March 15, 2009. Published February 1999: March 2009. Originally published as D5331–92: approved in 1992. Last previous edition D5331–95: approved in 2003 as D 5331–03.

² Annual Book of ASTM Standards, Vol 15.09.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.