

ETSI TS 123 501 V16.15.0 (2023-01)



5G; System architecture for the 5G System (5GS) (3GPP TS 23.501 version 16.15.0 Release 16)

[ETSI TS 123 501 V16.15.0 \(2023-01\)](#)

<https://standards.iteh.ai/catalog/standards/sist/e8c69f46-2ac9-4257-9a92-42c83e013d8a/etsi-ts-123-501-v16-15-0-2023-01>



Reference

RTS/TSGS-0223501vgf0

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the **GSM** logo are trademarks registered and owned by the **GSM Association**.

Legal Notice

(standards.iteh.ai)

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	16
1 Scope	17
2 References	17
3 Definitions and abbreviations.....	22
3.1 Definitions	22
3.2 Abbreviations	26
4 Architecture model and concepts	29
4.1 General concepts	29
4.2 Architecture reference model	29
4.2.1 General.....	29
4.2.2 Network Functions and entities	30
4.2.3 Non-roaming reference architecture	31
4.2.4 Roaming reference architectures.....	34
4.2.5 Data Storage architectures	38
4.2.5a Radio Capabilities Signalling optimisation.....	39
4.2.6 Service-based interfaces	40
4.2.7 Reference points	40
4.2.8 Support of non-3GPP access.....	42
4.2.8.0 General	42
4.2.8.1 General Concepts to Support Trusted and Untrusted Non-3GPP Access	42
4.2.8.1A General Concepts to support Wireline Access	44
4.2.8.2 Architecture Reference Model for Trusted and Untrusted Non-3GPP Acceses	44
4.2.8.2.1 http://Non-roaming Architecture.alcatel-stdards/sist/e8c69f46.2ac9.4257-9a92..	44
4.2.8.2.2 LBO Roaming Architecture.....	45
4.2.8.2.3 Home-routed Roaming Architecture	48
4.2.8.3 Reference Points for Non-3GPP Access	50
4.2.8.3.1 Overview	50
4.2.8.3.2 Requirements on Ta.....	50
4.2.8.4 Architecture Reference Model for Wireline Access network.....	51
4.2.8.5 Access to 5GC from devices that do not support 5GC NAS over WLAN access.....	52
4.2.8.5.1 General	52
4.2.8.5.2 Reference Architecture	53
4.2.8.5.3 Network Functions	53
4.2.8.5.4 Reference Points.....	53
4.2.9 Network Analytics architecture	54
4.2.10 Architecture Reference Model for ATSSS Support.....	54
4.3 Interworking with EPC	55
4.3.1 Non-roaming architecture	55
4.3.2 Roaming architecture.....	56
4.3.3 Interworking between 5GC via non-3GPP access and E-UTRAN connected to EPC.....	58
4.3.3.1 Non-roaming architecture	58
4.3.3.2 Roaming architecture	59
4.3.4 Interworking between ePDG connected to EPC and 5GS	61
4.3.4.1 Non-roaming architecture	61
4.3.4.2 Roaming architectures.....	62
4.3.5 Service Exposure in Interworking Scenarios	64
4.3.5.1 Non-roaming architecture	64
4.3.5.2 Roaming architectures.....	65
4.4 Specific services	66
4.4.1 Public Warning System	66
4.4.2 SMS over NAS	66

4.4.2.1	Architecture to support SMS over NAS	66
4.4.2.2	Reference point to support SMS over NAS	68
4.4.2.3	Service based interface to support SMS over NAS	68
4.4.3	IMS support	68
4.4.4	Location services	68
4.4.4.1	Architecture to support Location Services	68
4.4.4.2	Reference point to support Location Services	68
4.4.4.3	Service Based Interfaces to support Location Services	68
4.4.5	Application Triggering Services	69
4.4.6	5G LAN-type Services	69
4.4.6.1	User plane architecture to support 5G LAN-type service	69
4.4.6.2	Reference points to support 5G LAN-type service	69
4.4.7	MSISDN-less MO SMS Service	69
4.4.8	Time Sensitive Communication	70
4.4.8.1	General	70
4.4.8.2	Architecture to support Time Sensitive Communication	70
5	High level features	71
5.1	General	71
5.2	Network Access Control	71
5.2.1	General	71
5.2.2	Network selection	72
5.2.3	Identification and authentication	72
5.2.4	Authorisation	72
5.2.5	Access control and barring	72
5.2.6	Policy control	73
5.2.7	Lawful Interception	73
5.3	Registration and Connection Management	73
5.3.1	General	73
5.3.2	Registration Management	73
5.3.2.1	General	73
5.3.2.2	5GS Registration Management states	73
5.3.2.2.1	General	73
5.3.2.2.2	RM-DEREGISTERED state	73
5.3.2.2.3	RM-REGISTERED state	74
5.3.2.2.4	5GS Registration Management State models	75
5.3.2.3	Registration Area management	75
5.3.2.4	Support of a UE registered over both 3GPP and Non-3GPP access	76
5.3.3	Connection Management	78
5.3.3.1	General	78
5.3.3.2	5GS Connection Management states	78
5.3.3.2.1	General	78
5.3.3.2.2	CM-IDLE state	78
5.3.3.2.3	CM-CONNECTED state	79
5.3.3.2.4	5GS Connection Management State models	79
5.3.3.2.5	CM-CONNECTED with RRC Inactive state	80
5.3.3.3	NAS signalling connection management	82
5.3.3.3.1	General	82
5.3.3.3.2	NAS signalling connection establishment	82
5.3.3.3.3	NAS signalling connection Release	82
5.3.3.4	Support of a UE connected over both 3GPP and Non-3GPP access	82
5.3.4	UE Mobility	83
5.3.4.1	Mobility Restrictions	83
5.3.4.1.1	General	83
5.3.4.1.2	Management of Service Area Restrictions	85
5.3.4.2	Mobility Pattern	86
5.3.4.3	Radio Resource Management functions	86
5.3.4.4	UE mobility event notification	87
5.4	3GPP access specific aspects	88
5.4.1	UE reachability in CM-IDLE	88
5.4.1.1	General	88
5.4.1.2	UE reachability allowing mobile terminated data while the UE is CM-IDLE	89

5.4.1.3	Mobile Initiated Connection Only (MICO) mode.....	89
5.4.2	UE reachability in CM-CONNECTED.....	90
5.4.3	Paging strategy handling.....	90
5.4.3.1	General.....	90
5.4.3.2	Paging Policy Differentiation.....	91
5.4.3.3	Paging Priority	91
5.4.4	UE Radio Capability handling	92
5.4.4.1	UE radio capability information storage in the AMF.....	92
5.4.4.1a	UE radio capability signalling optimisation (RACS).....	93
5.4.4.2	Void.....	96
5.4.4.2a	UE Radio Capability Match Request	96
5.4.4.3	Paging assistance information.....	97
5.4.4a	UE MM Core Network Capability handling.....	97
5.4.4b	UE 5GSM Core Network Capability handling	98
5.4.5	DRX (Discontinuous Reception) framework.....	98
5.4.6	Core Network assistance information for RAN optimization.....	99
5.4.6.1	General.....	99
5.4.6.2	Core Network assisted RAN parameters tuning.....	99
5.4.6.3	Core Network assisted RAN paging information.....	100
5.4.7	NG-RAN location reporting	100
5.4.8	Support for identification and restriction of using unlicensed spectrum.....	101
5.4.9	Wake Up Signal Assistance	102
5.4.9.1	General.....	102
5.4.9.2	Group Wake Up Signal	102
5.5	Non-3GPP access specific aspects	102
5.5.0	General.....	102
5.5.1	Registration Management	103
5.5.2	Connection Management	103
5.5.3	UE Reachability	104
5.5.3.1	UE reachability in CM-IDLE	104
5.5.3.2	UE reachability in CM-CONNECTED	105
5.6	Session Management.....	105
5.6.1	Overview	105
5.6.2	Interaction between AMF and SMF.....	108
5.6.3	Roaming.....	110
5.6.4	Single PDU Session with multiple PDU Session Anchors	111
5.6.4.1	General	111
5.6.4.2	Usage of an UL Classifier for a PDU Session.....	112
5.6.4.3	Usage of IPv6 multi-homing for a PDU Session.....	113
5.6.5	Support for Local Area Data Network.....	115
5.6.6	Secondary authentication/authorization by a DN-AAA server during the establishment of a PDU Session	117
5.6.7	Application Function influence on traffic routing	118
5.6.7.1	General	118
5.6.7.2	Enhancement of UP path management based on the coordination with AFs	123
5.6.8	Selective activation and deactivation of UP connection of existing PDU Session	124
5.6.9	Session and Service Continuity	125
5.6.9.1	General	125
5.6.9.2	SSC mode.....	125
5.6.9.2.1	SSC Mode 1.....	125
5.6.9.2.2	SSC Mode 2.....	126
5.6.9.2.3	SSC Mode 3.....	126
5.6.9.3	SSC mode selection	126
5.6.10	Specific aspects of different PDU Session types	127
5.6.10.1	Support of IP PDU Session type	127
5.6.10.2	Support of Ethernet PDU Session type	128
5.6.10.3	Support of Unstructured PDU Session type	129
5.6.10.4	Maximum Transfer Unit size considerations	130
5.6.11	UE presence in Area of Interest reporting usage by SMF.....	131
5.6.12	Use of Network Instance.....	132
5.6.13	Always-on PDU session	133
5.6.14	Support of Framed Routing	133

5.7	QoS model.....	134
5.7.1	General Overview	134
5.7.1.1	QoS Flow	134
5.7.1.2	QoS Profile.....	134
5.7.1.2a	Alternative QoS Profile.....	135
5.7.1.3	Control of QoS Flows	135
5.7.1.4	QoS Rules	135
5.7.1.5	QoS Flow mapping	136
5.7.1.6	DL traffic.....	138
5.7.1.7	UL Traffic	138
5.7.1.8	AMBR/MFBR enforcement and rate limitation.....	139
5.7.1.9	Precedence Value.....	139
5.7.2	5G QoS Parameters.....	139
5.7.2.1	5QI	139
5.7.2.2	ARP	140
5.7.2.3	RQA	140
5.7.2.4	Notification control	140
5.7.2.4.1	General	140
5.7.2.4.1a	Notification Control without Alternative QoS Profiles	140
5.7.2.4.1b	Notification control with Alternative QoS Profiles	141
5.7.2.4.2	Usage of Notification control with Alternative QoS Profiles at handover	142
5.7.2.4.3	Usage of Notification control with Alternative QoS Profiles during QoS Flow establishment and modification.....	143
5.7.2.5	Flow Bit Rates.....	143
5.7.2.6	Aggregate Bit Rates	143
5.7.2.7	Default values	144
5.7.2.8	Maximum Packet Loss Rate.....	144
5.7.2.9	Wireline access network specific 5G QoS parameters.....	144
5.7.3	5G QoS characteristics.....	145
5.7.3.1	General	145
5.7.3.2	Resource Type.....	145
5.7.3.3	Priority Level	145
5.7.3.4	Packet Delay Budget.....	146
5.7.3.5	Packet Error Rate	147
5.7.3.6	Averaging Window	147
5.7.3.7	Maximum Data Burst Volume	147
5.7.4	Standardized 5QI to QoS characteristics mapping.....	147
5.7.5	Reflective QoS.....	151
5.7.5.1	General	151
5.7.5.2	UE Derived QoS Rule	152
5.7.5.3	Reflective QoS Control	153
5.7.6	Packet Filter Set	154
5.7.6.1	General	154
5.7.6.2	IP Packet Filter Set	154
5.7.6.3	Ethernet Packet Filter Set	154
5.8	User Plane Management.....	155
5.8.1	General.....	155
5.8.2	Functional Description.....	155
5.8.2.1	General	155
5.8.2.2	UE IP Address Management	155
5.8.2.2.1	General	155
5.8.2.2.2	Routing rules configuration	158
5.8.2.2.3	The procedure of Stateless IPv6 Address Autoconfiguration.....	158
5.8.2.3	Management of CN Tunnel Info	158
5.8.2.3.1	General	158
5.8.2.3.2	Void.....	159
5.8.2.3.3	Management of CN Tunnel Info in the UPF	159
5.8.2.4	Traffic Detection	159
5.8.2.4.1	General	159
5.8.2.4.2	Traffic Detection Information	159
5.8.2.5	Control of User Plane Forwarding	160
5.8.2.5.1	General	160

5.8.2.5.2	Data forwarding between the SMF and UPF.....	160
5.8.2.5.3	Support of Ethernet PDU Session type.....	160
5.8.2.6	Charging and Usage Monitoring Handling	161
5.8.2.6.1	General	161
5.8.2.6.2	Activation of Usage Reporting in UPF.....	162
5.8.2.6.3	Reporting of Usage Information towards SMF	162
5.8.2.7	PDU Session and QoS Flow Policing	163
5.8.2.8	PCC Related Functions	163
5.8.2.8.1	Activation/Deactivation of predefined PCC rules	163
5.8.2.8.2	Enforcement of Dynamic PCC Rules.....	163
5.8.2.8.3	Redirection	164
5.8.2.8.4	Support of PFD Management	164
5.8.2.9	Functionality of Sending of "End marker"	165
5.8.2.9.0	Introduction	165
5.8.2.9.1	UPF Constructing the "End marker" Packets	165
5.8.2.9.2	SMF Constructing the "End marker" Packets.....	165
5.8.2.10	UP Tunnel Management	165
5.8.2.11	Parameters for N4 session management.....	166
5.8.2.11.1	General	166
5.8.2.11.2	N4 Session Context	167
5.8.2.11.3	Packet Detection Rule	167
5.8.2.11.4	QoS Enforcement Rule.....	170
5.8.2.11.5	Usage Reporting Rule.....	173
5.8.2.11.6	Forwarding Action Rule	176
5.8.2.11.7	Usage Report generated by UPF	179
5.8.2.11.8	Multi-Access Rule.....	180
5.8.2.11.9	Bridge Information	181
5.8.2.11.10	Void.....	181
5.8.2.11.11	Session Reporting Rule	181
5.8.2.11.12	Session reporting generated by UPF.....	182
5.8.2.11.13	Void.....	182
5.8.2.11.14	TSC Management Information.....	182
5.8.2.11.15	Downlink Data Report generated by UPF	182
5.8.2.12	Reporting of the UE MAC addresses used in a PDU Session.....	183
5.8.2.13	Support for 5G VN group communication.....	183
5.8.2.13.0	General	183
5.8.2.13.1	Support for unicast traffic forwarding of a 5G VN.....	184
5.8.2.13.2	Support for unicast traffic forwarding update due to UE mobility	185
5.8.2.13.3	Support for user plane traffic replication in a 5G VN	186
5.8.2.14	Inter PLMN User Plane Security functionality	188
5.8.3	Explicit Buffer Management.....	188
5.8.3.1	General.....	188
5.8.3.2	Buffering at UPF.....	188
5.8.3.3	Buffering at SMF	189
5.8.4	SMF Pause of Charging.....	189
5.9	Identifiers	189
5.9.1	General.....	189
5.9.2	Subscription Permanent Identifier	189
5.9.2a	Subscription Concealed Identifier.....	190
5.9.3	Permanent Equipment Identifier	190
5.9.4	5G Globally Unique Temporary Identifier	190
5.9.5	AMF Name	191
5.9.6	Data Network Name (DNN)	191
5.9.7	Internal-Group Identifier.....	191
5.9.8	Generic Public Subscription Identifier.....	192
5.9.9	AMF UE NGAP ID	192
5.9.10	UE Radio Capability ID	192
5.10	Security aspects	193
5.10.1	General.....	193
5.10.2	Security Model for non-3GPP access	193
5.10.2.1	Signalling Security.....	193
5.10.3	PDU Session User Plane Security.....	193

5.11	Support for Dual Connectivity, Multi-Connectivity.....	195
5.11.1	Support for Dual Connectivity.....	195
5.12	Charging.....	195
5.12.1	General.....	195
5.12.2	Usage Data Reporting for Secondary RAT.....	196
5.12.3	Secondary RAT Periodic Usage Data Reporting Procedure	196
5.13	Support for Edge Computing.....	196
5.14	Policy Control	197
5.15	Network slicing	197
5.15.1	General.....	197
5.15.2	Identification and selection of a Network Slice: the S-NSSAI and the NSSAI	198
5.15.2.1	General	198
5.15.2.2	Standardised SST values	199
5.15.3	Subscription aspects.....	199
5.15.4	UE NSSAI configuration and NSSAI storage aspects.....	200
5.15.4.1	General	200
5.15.4.1.1	UE Network Slice configuration	200
5.15.4.1.2	Mapping of S-NSSAIs values in the Allowed NSSAI and in the Requested NSSAI to the S-NSSAIs values used in the HPLMN.....	202
5.15.4.2	Update of UE Network Slice configuration	202
5.15.5	Detailed Operation Overview	203
5.15.5.1	General.....	203
5.15.5.2	Selection of a Serving AMF supporting the Network Slices.....	203
5.15.5.2.1	Registration to a set of Network Slices.....	203
5.15.5.2.2	Modification of the Set of Network Slice(s) for a UE	207
5.15.5.2.3	AMF Re-allocation due to Network Slice(s) Support.....	209
5.15.5.3	Establishing a PDU Session in a Network Slice	209
5.15.6	Network Slicing Support for Roaming	210
5.15.7	Network slicing and Interworking with EPS	211
5.15.7.1	General	211
5.15.7.2	Idle mode aspects	211
5.15.7.3	Connected mode aspects	212
5.15.8	Configuration of Network Slice availability in a PLMN	212
5.15.9	Operator-controlled inclusion of NSSAI in Access Stratum Connection Establishment.....	213
5.15.10	Network Slice-Specific Authentication and Authorization.....	214
5.16	Support for specific services	215
5.16.1	Public Warning System	215
5.16.2	SMS over NAS	215
5.16.2.1	General	215
5.16.2.2	SMS over NAS transport	215
5.16.3	IMS support	215
5.16.3.1	General	215
5.16.3.2	IMS voice over PS Session Supported Indication over 3GPP access	216
5.16.3.2a	IMS voice over PS Session Supported Indication over non-3GPP access	217
5.16.3.3	Homogeneous support for IMS voice over PS Session supported indication	217
5.16.3.4	P-CSCF address delivery	217
5.16.3.5	Domain selection for UE originating sessions / calls	217
5.16.3.6	Terminating domain selection for IMS voice.....	218
5.16.3.7	UE's usage setting	218
5.16.3.8	Domain and Access Selection for UE originating SMS	219
5.16.3.8.1	UE originating SMS for IMS Capable UEs supporting SMS over IP	219
5.16.3.8.2	Access Selection for SMS over NAS	219
5.16.3.9	SMF support for P-CSCF restoration procedure	219
5.16.3.10	IMS Voice Service via EPS Fallback or RAT fallback in 5GS.....	219
5.16.3.11	P-CSCF discovery and selection	220
5.16.3.12	HSS discovery and selection	220
5.16.4	Emergency Services.....	220
5.16.4.1	Introduction	220
5.16.4.2	Architecture Reference Model for Emergency Services	223
5.16.4.3	Mobility Restrictions and Access Restrictions for Emergency Services.....	223
5.16.4.4	Reachability Management.....	223
5.16.4.5	SMF and UPF selection function for Emergency Services	224

5.16.4.6	QoS for Emergency Services	224
5.16.4.7	PCC for Emergency Services.....	224
5.16.4.8	IP Address Allocation	224
5.16.4.9	Handling of PDU Sessions for Emergency Services.....	224
5.16.4.9a	Handling of PDU Sessions for normal services for Emergency Registered UEs.....	224
5.16.4.10	Support of eCall Only Mode	225
5.16.4.11	Emergency Services Fallback	225
5.16.5	Multimedia Priority Services	226
5.16.6	Mission Critical Services	227
5.17	Interworking and Migration	228
5.17.1	Support for Migration from EPC to 5GC.....	228
5.17.1.1	General	228
5.17.1.2	User Plane management to support interworking with EPS.....	229
5.17.2	Interworking with EPC	230
5.17.2.1	General	230
5.17.2.2	Interworking Procedures with N26 interface	233
5.17.2.2.1	General	233
5.17.2.2.2	Mobility for UEs in single-registration mode	234
5.17.2.3	Interworking Procedures without N26 interface	235
5.17.2.3.1	General	235
5.17.2.3.2	Mobility for UEs in single-registration mode	235
5.17.2.3.3	Mobility for UEs in dual-registration mode	236
5.17.2.3.4	Redirection for UEs in connected state	237
5.17.2.4	Mobility between 5GS and GERAN/UTRAN	238
5.17.3	Interworking with EPC in presence of Non-3GPP PDU Sessions	238
5.17.4	Network sharing support and interworking between EPS and 5GS	238
5.17.5	Service Exposure in Interworking Scenarios	238
5.17.5.1	General	238
5.17.5.2	Support of interworking for Monitoring Events	239
5.17.5.2.1	Interworking with N26 interface	239
5.17.5.2.2	Interworking without N26 interface	240
5.17.5.3	Availability or expected level of a service API	240
5.17.6	Void	240
5.17.7	Configuration Transfer Procedure between NG-RAN and E-UTRAN	241
5.17.7.1	Architecture Principles for Configuration Transfer between NG-RAN and E-UTRAN	241
5.17.7.2	Addressing, routing and relaying	242
5.17.7.2.1	Addressing	242
5.17.7.2.2	Routing	242
5.17.7.2.3	Relaying	242
5.18	Network Sharing	242
5.18.1	General concepts	242
5.18.2	Broadcast system information for network sharing	243
5.18.2a	PLMN list handling for network sharing	243
5.18.3	Network selection by the UE	244
5.18.4	Network selection by the network	244
5.18.5	Network Sharing and Network Slicing	244
5.19	Control Plane Load Control, Congestion and Overload Control	245
5.19.1	General	245
5.19.2	TNLA Load Balancing and TNLA Load Re-Balancing	245
5.19.3	AMF Load Balancing	245
5.19.4	AMF Load Re-Balancing	245
5.19.5	AMF Control Of Overload	246
5.19.5.1	General	246
5.19.5.2	AMF Overload Control	246
5.19.6	SMF Overload Control	247
5.19.7	NAS level congestion control	247
5.19.7.1	General	247
5.19.7.2	General NAS level congestion control	247
5.19.7.3	DNN based congestion control	249
5.19.7.4	S-NSSAI based congestion control	250
5.19.7.5	Group specific NAS level congestion control	251
5.19.7.6	Control Plane data specific NAS level congestion control	251

5.20	External Exposure of Network Capability.....	252
5.20a	Data Collection from an AF	253
5.21	Architectural support for virtualized deployments	253
5.21.0	General.....	253
5.21.1	Architectural support for N2	254
5.21.1.1	TNL associations.....	254
5.21.1.2	NGAP UE-TNLA-binding	254
5.21.1.3	N2 TNL association selection	254
5.21.2	AMF Management.....	254
5.21.2.1	AMF Addition/Update	254
5.21.2.2	AMF planned removal procedure	255
5.21.2.2.1	AMF planned removal procedure with UDSF deployed	255
5.21.2.2.2	AMF planned removal procedure without UDSF.....	257
5.21.2.3	Procedure for AMF Auto-recovery	258
5.21.3	Network Reliability support with Sets	260
5.21.3.1	General	260
5.21.3.2	NF Set and NF Service Set.....	260
5.21.3.3	Reliability of NF instances within the same NF Set.....	260
5.21.3.4	Reliability of NF Services	261
5.21.4	Network Function/NF Service Context Transfer	261
5.21.4.1	General	261
5.22	System Enablers for priority mechanism.....	261
5.22.1	General.....	261
5.22.2	Subscription-related Priority Mechanisms.....	261
5.22.3	Invocation-related Priority Mechanisms	262
5.22.4	QoS Mechanisms applied to established QoS Flows.....	263
5.23	Supporting for Asynchronous Type Communication.....	264
5.24	3GPP PS Data Off	264
5.25	Support of OAM Features	265
5.25.1	Support of Tracing: Signalling Based Activation/Deactivation of Tracing	265
5.25.2	Support of OAM-based 5G VN group management.....	265
5.26	Configuration Transfer Procedure	265
5.26.1	Architecture Principles for Configuration Transfer	266
5.26.2	Addressing, routing and relaying	266
5.26.2.1	Addressing	266
5.26.2.2	Routing.....	266
5.26.2.3	Relaying	267
5.27	Time Sensitive Communications	267
5.27.0	General.....	267
5.27.1	TSN Time Synchronization	267
5.27.1.1	General	267
5.27.1.2	Distribution of timing information	268
5.27.1.2.1	Distribution of 5G internal system clock	268
5.27.1.2.2	Distribution of TSN grandmaster clock and time-stamping	268
5.27.1.3	Support for multiple TSN working domains	269
5.27.1.4	Periodic deterministic QoS	269
5.27.2	TSC Assistance Information (TSCAI)	270
5.27.3	Support for TSC QoS Flows	271
5.27.4	Hold and Forward Buffering mechanism.....	272
5.27.5	5G System Bridge delay	272
5.28	Support of integration with TSN	273
5.28.1	5GS TSN bridge management	273
5.28.2	5GS Bridge configuration	275
5.28.3	Port and bridge management information exchange in 5GS	276
5.28.3.1	General	276
5.28.3.2	Transfer of port or bridge management information	283
5.28.3.3	VLAN Configuration Information	284
5.28.4	QoS mapping tables	284
5.29	Support for 5G LAN-type service	286
5.29.1	General.....	286
5.29.2	5G VN group management	286
5.29.3	PDU Session management.....	287

5.29.4	User Plane handling	288
5.30	Support for non-public networks	289
5.30.1	General	289
5.30.2	Stand-alone non-public networks	289
5.30.2.0	General	289
5.30.2.1	Identifiers	289
5.30.2.2	Broadcast system information	290
5.30.2.3	UE configuration and subscription aspects	290
5.30.2.4	Network selection in SNPN access mode	291
5.30.2.5	Network access control	291
5.30.2.6	Cell (re-)selection in SNPN access mode	291
5.30.2.7	Access to PLMN services via stand-alone non-public networks	291
5.30.2.8	Access to stand-alone non-public network services via PLMN	292
5.30.3	Public Network Integrated NPN	292
5.30.3.1	General	292
5.30.3.2	Identifiers	293
5.30.3.3	UE configuration, subscription aspects and storage	293
5.30.3.4	Network and cell (re-)selection, and access control	294
5.30.3.5	Support of emergency services in CAG cells	295
5.31	Support for Cellular IoT	295
5.31.1	General	295
5.31.2	Preferred and Supported Network Behaviour	296
5.31.3	Selection, steering and redirection between EPS and 5GS	297
5.31.4	Control Plane CIoT 5GS Optimisation	297
5.31.4.1	General	297
5.31.4.2	Establishment of N3 data transfer during Data Transport in Control Plane CIoT 5GS Optimisation	298
5.31.4.3	Control Plane Relocation Indication procedure	299
5.31.5	Non-IP Data Delivery (NIDD)	299
5.31.6	Reliable Data Service	299
5.31.7	Power Saving Enhancements	300
5.31.7.1	General	300
5.31.7.2	Extended Discontinuous Reception (DRX) for CM-IDLE and CM-CONNECTED with RRC-INACTIVE	300
5.31.7.2.1	Overview	300
5.31.7.2.2	Paging for extended idle mode DRX in E-UTRA connected to 5GC	302
5.31.7.2.3	Paging for a UE registered in a tracking area with heterogeneous support of extended idle mode DRX	303
5.31.7.3	MICO mode with Extended Connected Time	303
5.31.7.4	MICO mode with Active Time	303
5.31.7.5	MICO mode and Periodic Registration Timer Control	303
5.31.8	High latency communication	304
5.31.9	Support for Monitoring Events	305
5.31.10	NB-IoT UE Radio Capability Handling	305
5.31.11	Inter-RAT idle mode mobility to and from NB-IoT	305
5.31.12	Restriction of use of Enhanced Coverage	306
5.31.13	Paging for Enhanced Coverage	307
5.31.14	Support of rate control of user data	307
5.31.14.1	General	307
5.31.14.2	Serving PLMN Rate Control	307
5.31.14.3	Small Data Rate Control	308
5.31.15	Control Plane Data Transfer Congestion Control	309
5.31.16	Service Gap Control	309
5.31.17	Inter-UE QoS for NB-IoT	311
5.31.18	User Plane CIoT 5GS Optimisation	311
5.31.19	QoS model for NB-IoT	312
5.31.20	Category M UEs differentiation	312
5.32	Support for ATSSS	313
5.32.1	General	313
5.32.2	Multi Access PDU Sessions	313
5.32.3	Policy for ATSSS Control	316
5.32.4	QoS Support	316

5.32.5	Access Network Performance Measurements.....	318
5.32.5.1	General principles	318
5.32.5.2	Round Trip Time Measurements.....	318
5.32.5.3	Access Availability/Unavailability Report.....	319
5.32.5.4	Protocol stack for user plane measurements and measurement reports.....	320
5.32.6	Support of Steering Functionalities	321
5.32.6.1	General	321
5.32.6.2	High-Layer Steering Functionalities	322
5.32.6.2.1	MPTCP Functionality.....	322
5.32.6.3	Low-Layer Steering Functionalities	323
5.32.6.3.1	ATSSS-LL Functionality.....	323
5.32.7	Interworking with EPS.....	324
5.32.7.1	General	324
5.32.7.2	Interworking with N26 Interface.....	324
5.32.7.3	Interworking without N26 Interface.....	325
5.32.8	ATSSS Rules	325
5.33	Support for Ultra Reliable Low Latency Communication.....	327
5.33.1	General.....	327
5.33.2	Redundant transmission for high reliability communication	327
5.33.2.1	Dual Connectivity based end to end Redundant User Plane Paths.....	327
5.33.2.2	Support of redundant transmission on N3/N9 interfaces	329
5.33.2.3	Support for redundant transmission at transport layer	330
5.33.3	QoS Monitoring to Assist URLLC Service	331
5.33.3.1	General	331
5.33.3.2	Per QoS Flow per UE QoS Monitoring.....	331
5.33.3.3	GTP-U Path Monitoring.....	332
5.34	Support of deployments topologies with specific SMF Service Areas.....	333
5.34.1	General.....	333
5.34.2	Architecture	334
5.34.2.1	SBA architecture	334
5.34.2.2	Non-roaming architecture	334
5.34.2.3	Roaming architecture	335
5.34.3	I-SMF selection, V-SMF reselection	335
5.34.4	Usage of an UL Classifier for a PDU Session controlled by I-SMF.....	336
5.34.5	Usage of IPv6 multi-homing for a PDU Session controlled by I-SMF.....	337
5.34.6	Interaction between I-SMF and SMF for the support of traffic offload by UPF controlled by the I-SMF	338
5.34.6.1	General	338
5.34.6.2	N4 information sent from SMF to I-SMF for local traffic offload.....	338
5.34.7	Event Management	339
5.34.7.1	UE's Mobility Event Management	339
5.34.7.2	SMF event exposure service	339
5.34.7.3	AMF implicit subscription about events related with the PDU Session	340
5.34.8	Support for Cellular IoT	340
5.34.9	Support of the Deployment Topologies with specific SMF Service Areas feature within and between PLMN(s).....	340
5.34.10	Support for 5G LAN-type service.....	340
5.35	Support for Integrated access and backhaul (IAB).....	340
5.35.1	IAB architecture and functional entities	340
5.35.2	5G System enhancements to support IAB	342
5.35.3	Data handling and QoS support with IAB	342
5.35.4	Mobility support with IAB	342
5.35.5	Charging support with IAB.....	343
5.35.6	IAB operation involving EPC	343
5.36	RIM Information Transfer.....	343
6	Network Functions	343
6.1	General	343
6.2	Network Function Functional description	343
6.2.1	AMF.....	343
6.2.2	SMF	345
6.2.3	UPF.....	346

6.2.4	PCF	347
6.2.5	NEF.....	347
6.2.5.0	NEF functionality.....	347
6.2.5.1	Support for CAPIF.....	348
6.2.5a	Void	348
6.2.6	NRF	348
6.2.6.1	General.....	348
6.2.6.2	NF profile.....	349
6.2.6.3	SCP profile.....	350
6.2.7	UDM.....	351
6.2.8	AUSF	351
6.2.9	N3IWF.....	351
6.2.9A	TNGF.....	352
6.2.10	AF	352
6.2.11	UDR.....	352
6.2.12	UDSF	353
6.2.13	SMSF	353
6.2.14	NSSF.....	353
6.2.15	5G-EIR.....	353
6.2.16	LMF	353
6.2.16A	GMLC.....	354
6.2.17	SEPP	354
6.2.18	Network Data Analytics Function (NWDAF)	354
6.2.19	SCP	354
6.2.20	W-AGF	355
6.2.21	UE radio Capability Management Function (UCMF).....	355
6.2.22	TWIF	355
6.2.23	NSSAAF	355
6.3	Principles for Network Function and Network Function Service discovery and selection	356
6.3.1	General.....	356
6.3.1.0	Principles for Binding, Selection and Reselection	357
6.3.1.1	NF Discovery and Selection aspects relevant with indirect communication.....	359
6.3.1.2	Location information.....	359
6.3.2	SMF discovery and selection.....	360
6.3.3	User Plane Function Selection.....	362
6.3.3.1	Overview	362
6.3.3.2	SMF Provisioning of available UPF(s)	362
6.3.3.3	Selection of an UPF for a particular PDU Session	362
6.3.4	AUSF discovery and selection.....	364
6.3.5	AMF discovery and selection	364
6.3.6	N3IWF selection	366
6.3.6.1	General	366
6.3.6.2	Stand-alone N3IWF selection	367
6.3.6.2a	SNPN N3IWF selection	368
6.3.6.3	Combined N3IWF/ePDG Selection	369
6.3.6.4	PLMN Selection for emergency services	371
6.3.7	PCF discovery and selection	371
6.3.7.0	General principles	371
6.3.7.1	PCF discovery and selection for a UE or a PDU Session	372
6.3.7.2	Providing policy requirements that apply to multiple UE and hence to multiple PCF.....	374
6.3.7.3	Binding an AF request targeting a UE address to the relevant PCF.....	374
6.3.8	UDM discovery and selection.....	374
6.3.9	UDR discovery and selection.....	375
6.3.10	SMSF discovery and selection.....	375
6.3.11	CHF discovery and selection	376
6.3.12	Trusted Non-3GPP Access Network selection	377
6.3.12.1	General	377
6.3.12.2	Access Network Selection Procedure.....	378
6.3.12a	Access Network selection for devices that do not support 5GC NAS over WLAN	380
6.3.12a.1	General	380
6.3.12a.2	Access Network Selection Procedure.....	380
6.3.13	NWDAF discovery and selection	382

6.3.14	NEF Discovery	382
6.3.15	UCMF Discovery and Selection	382
6.3.16	SCP discovery and selection	382
6.3.17	NSSAAF discovery and selection	383
6.3.18	5G-EIR discovery and selection	383
7	Network Function Services and descriptions	383
7.1	Network Function Service Framework.....	383
7.1.1	General.....	383
7.1.2	NF Service Consumer - NF Service Producer interactions.....	384
7.1.3	Network Function Service discovery	386
7.1.4	Network Function Service Authorization	386
7.1.5	Network Function and Network Function Service registration and de-registration.....	387
7.2	Network Function Services	387
7.2.1	General.....	387
7.2.2	AMF Services	388
7.2.3	SMF Services.....	389
7.2.4	PCF Services.....	389
7.2.5	UDM Services	390
7.2.6	NRF Services	391
7.2.7	AUSF Services.....	392
7.2.8	NEF Services	392
7.2.8A	Void	393
7.2.9	SMSF Services.....	393
7.2.10	UDR Services	394
7.2.11	5G-EIR Services	394
7.2.12	NWDAF Services	394
7.2.13	UDSF Services.....	394
7.2.14	NSSF Services	395
7.2.15	BSF Services	395
7.2.16	LMF Services.....	395
7.2.16A	GMLC Services	395
7.2.17	CHF Services.....	396
7.2.18	UCMF Services	396
7.2.19	AF Services.....	397
7.2.20	NSSAAF Services	397
7.3	Exposure.....	397
8	Control and User Plane Protocol Stacks.....	397
8.1	General	397
8.2	Control Plane Protocol Stacks	397
8.2.1	Control Plane Protocol Stacks between the 5G-AN and the 5G Core: N2	397
8.2.1.1	General	397
8.2.1.2	5G-AN - AMF	398
8.2.1.3	5G-AN - SMF	399
8.2.2	Control Plane Protocol Stacks between the UE and the 5GC	399
8.2.2.1	General	399
8.2.2.2	UE - AMF	401
8.2.2.3	UE – SMF	401
8.2.3	Control Plane Protocol Stacks between the network functions in 5GC	402
8.2.3.1	The Control Plane Protocol Stack for the service based interface.....	402
8.2.3.2	The Control Plane protocol stack for the N4 interface between SMF and UPF.....	402
8.2.4	Control Plane for untrusted non 3GPP Access	402
8.2.5	Control Plane for trusted non-3GPP Access	403
8.2.6	Control Plane for W-5GAN Access.....	404
8.3	User Plane Protocol Stacks.....	404
8.3.1	User Plane Protocol Stack for a PDU Session	404
8.3.2	User Plane for untrusted non-3GPP Access.....	406
8.3.3	User Plane for trusted non-3GPP Access.....	406
8.3.4	User Plane for W-5GAN Access	406
8.3.5	User Plane for N19-based forwarding of a 5G VN group.....	407