

---

---

**Mechanical vibration — Measurement  
and evaluation of human exposure  
to hand transmitted vibration —  
Supplementary method for assessing  
risk of vascular disorders**

*Vibrations mécaniques — Mesurage et évaluation de l'exposition  
des individus aux vibrations transmises par la main — Méthode  
supplémentaire pour l'évaluation du risque de blessure vasculaire*

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[ISO/TR 18570:2017](https://standards.iteh.ai/catalog/standards/sist/8fb1d45e-6792-4b20-8d15-0efa1405974e/iso-tr-18570-2017)

<https://standards.iteh.ai/catalog/standards/sist/8fb1d45e-6792-4b20-8d15-0efa1405974e/iso-tr-18570-2017>



**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/TR 18570:2017](https://standards.iteh.ai/catalog/standards/sist/8fb1d45e-6792-4b20-8d15-0efa1405974e/iso-tr-18570-2017)

<https://standards.iteh.ai/catalog/standards/sist/8fb1d45e-6792-4b20-8d15-0efa1405974e/iso-tr-18570-2017>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
[copyright@iso.org](mailto:copyright@iso.org)  
[www.iso.org](http://www.iso.org)

# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms, definitions and symbols</b> .....	<b>1</b>
<b>4 Characterization of hand-transmitted vibration</b> .....	<b>2</b>
4.1 General considerations.....	2
4.2 Measuring equipment for hand-transmitted vibration.....	2
4.2.1 General.....	2
4.2.2 Vibration transducers.....	2
4.2.3 Location and orientation of transducers.....	2
4.2.4 Mounting of transducers.....	2
4.2.5 Coupling of the hand to the vibration source.....	2
4.3 Quantity to be measured.....	3
4.4 Multi-axis vibration.....	3
<b>5 Characterization of hand-transmitted vibration exposure for vascular disorders</b> .....	<b>3</b>
5.1 General.....	3
5.2 Daily exposure duration.....	3
5.3 Vibration exposure.....	3
<b>6 Information to be reported</b> .....	<b>4</b>
<b>Annex A (informative) Biomechanical and epidemiological basis for weighting <math>W_p</math></b> .....	<b>5</b>
<b>Annex B (informative) Frequency weighting definitions</b> .....	<b>7</b>
<b>Annex C (informative) Examples of vibration magnitudes</b> .....	<b>12</b>
<b>Bibliography</b> .....	<b>14</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html). (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 108, *Mechanical vibration, shock and condition monitoring*, Subcommittee SC 4, *Human exposure to mechanical vibration and shock*.

ISO/TR 18570:2017  
<https://standards.iteh.ai/catalog/standards/sist/8fb1d45e-6792-4b20-8d15-0ef1405974e/iso-tr-18570-2017>

## Introduction

This document is a result of analyses of application of the  $W_h$  frequency weighting defined by ISO 5349-1 to the risk of vascular hand-arm vibration disorders. For vibration exposures dominated by particularly high or particularly low frequencies of vibration, there is evidence that weightings based on the (20 to 400) Hz frequency range may give an improved prediction of risk of vascular disorders over the weighting  $W_h$ .

This document proposes a frequency weighting and risk assessment parameter that can be used to supplement the method defined in ISO 5349-1. The purpose of this document is to

- a) define a supplementary evaluation methodology that can be used in addition to that given in ISO 5349-1, and
- b) ensure that additional data are collected in a common format to help to improve knowledge and understanding of vascular vibration risks.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/TR 18570:2017](https://standards.iteh.ai/catalog/standards/sist/8fb1d45e-6792-4b20-8d15-0efa1405974e/iso-tr-18570-2017)

<https://standards.iteh.ai/catalog/standards/sist/8fb1d45e-6792-4b20-8d15-0efa1405974e/iso-tr-18570-2017>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO/TR 18570:2017](#)

<https://standards.iteh.ai/catalog/standards/sist/8fb1d45e-6792-4b20-8d15-0efa1405974e/iso-tr-18570-2017>

# Mechanical vibration — Measurement and evaluation of human exposure to hand transmitted vibration — Supplementary method for assessing risk of vascular disorders

## 1 Scope

This document provides guidance on a supplementary method to that defined in ISO 5349-1 for measuring and reporting hand-transmitted vibration exposures. The method defined in this document provides an improved assessment methodology for evaluating vascular hand-arm vibration risks (vibration white finger). This document does not apply for other health effects (e.g. sensorineural and musculoskeletal disorders) induced from hand-transmitted vibration exposure (see ISO 5349-1:2001, Annex B).

This document is intended to facilitate future research on hand-arm vibration risks. It can be used to supplement the data given by the ISO 5349-1 methodology.

This document cannot be used as an alternative to ISO 5349-1. Data derived from this document cannot be used in place of ISO 5349-1 data for fulfilling duties under national regulations, guidance or recommendations for either workplace vibration exposures or machinery vibration emissions.

The methodology defined in this document is based on biomechanical and epidemiological studies which are reviewed in [Annex A](#). Also provided in [Annex A](#) is tentative information on a relationship between vibration exposure and risk of developing vascular hand-arm vibration disorders.

<https://standards.iteh.ai/catalog/standards/sist/8fb1d45e-6792-4b20-8d15-0efa1405974e/iso-tr-18570-2017>

## 2 Normative references

There are no normative references in this document.

## 3 Terms, definitions and symbols

For the purposes of this document, the terms and definitions given in ISO 2041 and ISO 5349-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

Symbol	Definition
$a_{pi}(t)$	instantaneous value of the hand-transmitted vibration for the axis $i$ at time $t$ , in metres per second squared ( $m/s^2$ ) frequency-weighted according to the hand-arm vascular weighting $W_p$ ;
$a_{pi}$	root-mean-square (r.m.s.) value of the hand-transmitted vibration for the axis $i$ in metres per second squared ( $m/s^2$ ) frequency-weighted according to the hand-arm vascular weighting $W_p$ ;
$a_{pv}(t)$	instantaneous value of the hand-transmitted vibration total value at time $t$ , in metres per second squared ( $m/s^2$ ) frequency-weighted according to the hand-arm vascular weighting $W_p$ : $a_{pv}(t) = \sqrt{a_{px}^2(t) + a_{py}^2(t) + a_{pz}^2(t)}$ ;
$a_{pv}$	r.m.s. vibration total value of the hand-transmitted vibration, in metres per second squared ( $m/s^2$ ) frequency-weighted according to the hand-arm vascular weighting $W_p$ ;

Symbol	Definition
$A_p(8)$	daily vibration exposure normalized to an 8-hour day, frequency-weighted according to the hand-arm vascular weighting $W_p$ ;
$E_p$	vibration exposure value, frequency-weighted according to the hand-arm vascular weighting $W_p$ ;
$E_{p,d}$	vibration exposure value determined over a working day;
$E_{p,l}$	vibration exposure value determined over a working lifetime;
$W_p$	frequency weighting characteristic for the vascular component of the hand-transmitted vibration syndrome.

## 4 Characterization of hand-transmitted vibration

### 4.1 General considerations

The method specified in this document takes account of the following factors which are believed to influence the vascular effects of human exposure to hand-transmitted vibration in working conditions:

- the frequency spectrum of vibration;
- the magnitude of vibration;
- the duration of exposure per working day.

Other factors which may influence the effects of vibration exposure, but for which standardized methods for reporting do not yet exist, are listed in ISO 5349-1:2001, Annex D.

### 4.2 Measuring equipment for hand-transmitted vibration

#### 4.2.1 General

ISO/TR 18570:2017  
<https://standards.iteh.ai/catalog/standards/sist/8fb1d45e-6792-4b20-8d15-0efa1405974e/iso-tr-18570-2017>

Measurement of hand-transmitted vibration should be undertaken using instrumentation conforming as far as is possible to the requirements of ISO 8041-1. This equipment should be checked for correct operation before and after use. The calibration should be traceable to a recognized standard maintained by an accredited laboratory.

ISO 8041-1:2017 does not provide specifications for the  $W_p$  frequency weighting. Where possible, measurement equipment should conform to the basic requirements of ISO 8041-1.

#### 4.2.2 Vibration transducers

The vibration transducer requirements should be the same as those specified in ISO 5349-1:2001, 4.2.2.

#### 4.2.3 Location and orientation of transducers

The location and orientation of vibration transducers should be the same as those specified in ISO 5349-1:2001, 4.2.3.

#### 4.2.4 Mounting of transducers

The mounting requirements for vibration transducers should be the same as those specified in ISO 5349-1:2001, 4.2.4.

NOTE The consequence of poor mounting may be more noticeable with  $W_p$  than with  $W_h$ .

#### 4.2.5 Coupling of the hand to the vibration source

The coupling of the hand requirements should be the same as those specified in ISO 5349-1:2001, 4.3.



### 4.3 Quantity to be measured

The primary quantity used to describe the magnitude of the vibration shall be the root-mean-square (r.m.s.) frequency-weighted acceleration expressed in metres per second squared (m/s<sup>2</sup>).

The measurement of frequency-weighted acceleration requires the application of a frequency weighting and band-limiting filters. The frequency weighting  $W_p$  reflects the assumed importance of different frequencies in causing vascular disorders of the hand. The characteristics of the  $W_p$  frequency weighting and methods for band-limiting are given in [Annex B](#).

The r.m.s. value is measured using a linear integration method. The integration time should be chosen such that a representative sample of the vibration signal is used (see ISO 5349-2).

### 4.4 Multi-axis vibration

It is known that on most power tools the vibration entering the hand contains contributions from all three measurement directions. It is assumed that vibration in each of the three directions is equally detrimental. Measurements should therefore be made for all three directions. The frequency-weighted r.m.s. acceleration values for the x-, y- and z-axes,  $a_{px}$ ,  $a_{py}$  and  $a_{pz}$ , should be reported separately.

The evaluation of vibration exposure (see [Clause 5](#)), however, is based on a quantity that combines all three axes. This is the vibration total value,  $a_{pv}$ , and is defined as the root-sum-of-squares of the three component values, as shown by [Formula \(1\)](#):

$$a_{pv} = \sqrt{a_{px}^2 + a_{py}^2 + a_{pz}^2} \quad (1)$$

[Annex C](#) provides some example values for  $a_{pv}$  and compares these with equivalent values  $a_{hv}$  using the ISO 5349-1 frequency weighting.

## 5 Characterization of hand-transmitted vibration exposure for vascular disorders

### 5.1 General

Vibration exposure is dependent on the magnitude of the vibration and on the duration of the exposure. In order to apply the guidance on the vascular health effects given in [Annex A](#), the vibration magnitude is represented by a frequency-weighted vibration total value  $a_{pv}$ .

### 5.2 Daily exposure duration

The requirements for assessing daily vibration exposure times should be the same as those specified in ISO 5349-1:2001, 5.2.

### 5.3 Vibration exposure

A value for an individual's vibration exposure in a working day is derived from the magnitude of the vibration (vibration total values) and the daily exposure durations.

The daily vibration exposure should be expressed in terms of the frequency-weighted exposure vibration value,  $E_p$ , as shown by [Formula \(2\)](#):

$$E_p = \sqrt{\int_{t_1}^{t_2} a_{pv}^2(t) dt} \quad (\text{m/s}^{1,5}) \quad (2)$$

where

$t_1$  is the time at the start of vibration exposure, expressed in seconds (s);

$t_2$  is the time at the end of vibration exposure, expressed in seconds (s).

If the work is such that the vibration exposure consists of several operations with different vibration magnitudes, then the vibration exposure,  $E_p$ , should be obtained using [Formula \(3\)](#):

$$E_p = \sqrt{\sum_{i=1}^n a_{pvi}^2 T_i} \quad (\text{m/s}^{1,5}) \quad (3)$$

where

$a_{pvi}$  is the vibration total value for the  $i^{\text{th}}$  operation;

$n$  is the number of individual vibration exposures;

$T_i$  is the duration of the  $i^{\text{th}}$  operation, expressed in seconds (s).

When the  $E_p$  value is determined over a single working day it should be denoted as,  $E_{p,d}$ . The  $E_p$  value may also be estimated for a lifetime exposure, where it is denoted as  $E_{p,l}$ , as shown by [Formula \(4\)](#):

$$E_{p,l} = \sqrt{\sum_{j=1}^m E_{p,d,j}^2} \quad (\text{m/s}^{1,5}) \quad (4)$$

where

$E_{p,d,j}$  is the daily vibration exposure for the  $j^{\text{th}}$  day;

$m$  is the number of days with vibration exposure in a lifetime.

To prevent confusion with the  $W_h$  weighted  $A(8)$  as defined by ISO 5349-1, it is recommended that  $W_p$  weighted exposures are expressed as exposure values  $E_{p,d}$ . However, if necessary, the  $W_p$  weighted daily vibration exposure  $A_p(8)$  may be obtained using [Formula \(5\)](#):

$$A_p(8) = \sqrt{\sum_{i=1}^n a_{pvi}^2 \frac{T_i}{T_0}} \quad (\text{m/s}^2) \quad (5)$$

where  $T_0$  is the reference time of 8 h (28 800 s).

Therefore:

$$A_p(8) = \frac{E_{p,d}}{\sqrt{T_0}}$$

## 6 Information to be reported

In addition to the information to be reported in accordance with ISO 5349-1:2001, Clause 6, the following information should be reported:

- a) the individual root-mean-square, single-axis frequency-weighted accelerations measured with the  $W_p$  weighting;
- b) the vibration total value,  $a_{pv}$ , for each operation;
- c) the calculated vibration exposure,  $E_{p,d}$ , for a working day.

Additionally, the lifetime vibration exposure,  $E_{p,l}$ , may also be reported.

## Annex A (informative)

### Biomechanical and epidemiological basis for weighting $W_p$

A frequency weighting is required to quantify the risk of developing symptoms of vibration white finger (VWF) from exposing the hands to vibration. The frequency weighting accounts for the relative hazard posed by vibration at different frequencies. Predictions of risk using the procedures described in annexes to ISO 5349:1986 and ISO 5349-1:2001 have been found to agree with the observed latencies of finger blanching (i.e. the years of exposure to vibration prior to the appearance of the first white finger) for some occupationally-exposed population groups, as well as to underestimate or overestimate the risk for some situations.<sup>[1],[2]</sup> The risk of developing VWF is overestimated for power tools such as rock drills, pavement breakers and sand rammers, and underestimated for riveting tools.<sup>[1-7]</sup> The discrepancies between predictions of the risk of developing VWF and the experience of population groups occupationally exposed to vibration have been attributed, in part, to the frequency weighting recommended in ISO 5349-1.

Frequency weightings can be derived, in principle, from physiological or patho-physiological responses to vibration in humans or animals, from biodynamic models characterizing vibration entering the hand-arm system, or from epidemiological studies of population groups in which vibration exposures have been measured or can be estimated. Attempts to construct frequency weightings from physiological responses of humans or animals, while informative, have not so far proved to be definitive. Most information on the form of frequency weighting necessary to characterize the development of VWF has come from biodynamic models contained in ISO 10068:2012, and from analyses of epidemiological studies using trial frequency weightings.<sup>[8-12]</sup>

The results of the three most definitive studies are summarized in [Figure A.1](#), see Reference [\[12\]](#). The frequency weightings derived by Tominaga ( $W_{HT}$ ) and Dong et al. ( $W_{hf}$ ) are presented in the form used in analyses by Pitts et al. and Bovenzi, see Reference [\[13\]](#), alongside the  $W_h$  weightings. The weighting derived by Brammer and Pitts defines a range of frequencies that lies between the black dots. Each frequency weighting applies to vibration expressed as either the dominant single axis r.m.s. acceleration or vibration total value (i.e. vector sum acceleration).  $W_p$  is compatible with the results of all these studies and provides the best estimate of the frequency weighting required to quantify the risk of developing symptoms of VWF from exposing the hands to vibration.

The analysis of Brammer and Pitts<sup>[12]</sup> also permits an estimate to be made of the least daily vibration exposure,  $E_{p,d}$ , at which symptoms of VWF may be expected to occur. The daily exposure threshold for the onset and continuing development of VWF is in the range for  $E_{p,d}$ , of 1150  $m/s^{1.5}$  to 1750  $m/s^{1.5}$ .

Some variation in the threshold can be expected for different exposure conditions. Upper values in the range pertain to exposures for a working day evaluated using vibration total values according to [5.3](#). Lower values in the range pertain to situations in which it is not possible to obtain vibration total values, and exposures have to be constructed from dominant single-axis accelerations. It should be noted that the threshold range pertains only to the risk of developing vascular hand-arm vibration disorders.