

---

---

**Road vehicles — Compressed natural  
gas (CNG) fuel system components —  
Part 15:  
Gas-tight housing and ventilation hose**

*Véhicules routiers — Composants des systèmes de combustible gaz  
naturel comprimé (GNC) —*

*Partie 15: Compartiment étanche pour gaz et tuyaux de ventilation*  
**(standards.iteh.ai)**

[ISO 15500-15:2015](https://standards.iteh.ai/catalog/standards/sist/cd00ef95-1406-426a-b9ec-601eea7ed983/iso-15500-15-2015)

<https://standards.iteh.ai/catalog/standards/sist/cd00ef95-1406-426a-b9ec-601eea7ed983/iso-15500-15-2015>



**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 15500-15:2015

<https://standards.iteh.ai/catalog/standards/sist/cd00ef95-1406-426a-b9ec-601eea7ed983/iso-15500-15-2015>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Marking</b> .....	<b>2</b>
<b>5 Construction and assembly</b> .....	<b>2</b>
<b>6 Tests</b> .....	<b>2</b>
6.1 Applicability .....	2
6.2 Leakage .....	3
6.2.1 External leakage .....	3
6.2.2 External Leakage, of pressure retaining ventilation passages .....	3
6.2.3 Venting ability and pressure retention .....	4
6.3 Pull-off .....	4
<b>Bibliography</b> .....	<b>5</b>

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 15500-15:2015](https://standards.iteh.ai/catalog/standards/sist/cd00ef95-1406-426a-b9ec-601eea7ed983/iso-15500-15-2015)

<https://standards.iteh.ai/catalog/standards/sist/cd00ef95-1406-426a-b9ec-601eea7ed983/iso-15500-15-2015>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 41, *Specific aspects for gaseous fuels*.

This second edition cancels and replaces the first edition (ISO 15500-15:2001), which has been technically revised.

ISO 15500 consists of the following parts, under the general title *Road vehicles — Compressed natural gas (CNG) fuel system components* :

- *Part 1: General requirements and definitions*
- *Part 2: Performance and general test methods*
- *Part 3: Check valve*
- *Part 4: Manual valve*
- *Part 5: Manual cylinder valve*
- *Part 6: Automatic valve*
- *Part 7: Gas injector*
- *Part 8: Pressure indicator*
- *Part 9: Pressure regulator*
- *Part 10: Gas-flow adjuster*
- *Part 11: Gas/air mixer*
- *Part 12: Pressure relief valve (PRV)*
- *Part 13: Pressure relief device (PRD)*

- *Part 14: Excess flow valve*
- *Part 15: Gas-tight housing and ventilation hose*
- *Part 16: Rigid fuel line in stainless steel*
- *Part 17: Flexible fuel line*
- *Part 18: Filter*
- *Part 19: Fittings*
- *Part 20: Rigid fuel line in material other than stainless steel*

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[ISO 15500-15:2015](https://standards.iteh.ai/catalog/standards/sist/cd00ef95-1406-426a-b9ec-601eea7ed983/iso-15500-15-2015)

<https://standards.iteh.ai/catalog/standards/sist/cd00ef95-1406-426a-b9ec-601eea7ed983/iso-15500-15-2015>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 15500-15:2015

<https://standards.iteh.ai/catalog/standards/sist/cd00ef95-1406-426a-b9ec-601eea7ed983/iso-15500-15-2015>

# Road vehicles — Compressed natural gas (CNG) fuel system components —

## Part 15: Gas-tight housing and ventilation hose

### 1 Scope

This part of ISO 15500 specifies tests and requirements for the gas-tight housing and ventilation hose, compressed natural gas fuel system components intended for use on the types of motor vehicles defined in ISO 3833.

This part of ISO 15500 is applicable to vehicles using natural gas in accordance with ISO 15403-1 (mono-fuel, bi-fuel, or dual-fuel applications). It is not applicable to the following:

- a) liquefied natural gas (LNG) fuel system components located upstream of, and including, the vaporizer;
- b) fuel containers;
- c) stationary gas engines;
- d) container mounting hardware;
- e) electronic fuel management;
- f) refuelling receptacles.

NOTE 1 It is recognized that miscellaneous components not specifically covered herein can be examined to meet the criteria of this part of ISO 15500 and tested according to the appropriate functional tests.

NOTE 2 All references to pressure in this part of ISO 15500 are to be considered gauge pressures unless otherwise specified.

NOTE 3 This part of ISO 15500 is based upon a service pressure for natural gas as a fuel of 20 MPa (200 bar<sup>1</sup>) settled at 15 °C. Other service pressures can be accommodated by adjusting the pressure by the appropriate factor (ratio). For example, a 25 MPa (250 bar) service pressure system will require pressures to be multiplied by 1,25.

### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 15500-1, *Road vehicles — Compressed natural gas (CNG) fuel system components — Part 1: General requirements and definitions*

ISO 15500-2, *Road vehicles — Compressed natural gas (CNG) fuel system components — Part 2: Performance and general test methods*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 15500-1 apply.

1) 1 bar = 0,1 MPa = 10<sup>5</sup> Pa; 1 MPa = 1 N/mm<sup>2</sup>.

## 4 Marking

Marking of the component shall provide sufficient information to allow the following to be traced:

- a) the manufacturer's or agent's name, trademark or symbol;
- b) the model designation (part number);
- c) the temperature range.

The following additional markings are recommended:

- the direction of flow (when necessary for correct installation);
- the type of fuel;
- electrical ratings (if applicable);
- the symbol of the certification agency;
- the type approval number;
- the serial number or date code;
- a reference to this part of ISO 15500.

NOTE This information can be provided by a suitable identification code on at least one part of the component when it consists of more than one part.

## 5 Construction and assembly

The gas-tight housing and ventilation hose shall comply with the applicable provisions of ISO 15500-1 and ISO 15500-2, and with the tests specified in [Clause 6](#).

The gas-tight housing and ventilation hose are intended to contain and vent to a safe place permeation gas and small leaks from the primary pressure retaining components.

The gas-tight housing shall be assembled in such a way that the function of the pressure relief device or devices (PRD) will not be affected.

## 6 Tests

### 6.1 Applicability

The tests required to be carried out are indicated in [Table 1](#).



Table 1 — Tests applicable

Test	Applicable	Test procedure as required by ISO 15500-2	Specific test requirements of this part of ISO 15500
Leakage	X	X	X (see 6.2)
Excess torque resistance	X <sup>a</sup>	X	
Bending moment			
Continued operation			
Corrosion resistance	X <sup>b</sup>	X	
Oxygen ageing	X	X	
Ozone ageing	X	X	
Heat Ageing	X	X	
Automotive Fluids	X	X	
Electrical over-voltages			
Non-metallic synthetic immersion	X	X	
Vibration resistance	X <sup>a</sup>	X	
Brass material compatibility			
Pull-off	X		X (see 6.3)

<sup>a</sup> Applicable only to rigid components.  
<sup>b</sup> Applicable to metallic parts or components.

## 6.2 Leakage

ISO 15500-15:2015

<https://standards.iteh.ai/catalog/standards/sist/cd00ef95-1406-426a-b9ec-601eea7ed983/iso-15500-15-2015>

Test the gas-tight housing according to the procedure for leakage specified in ISO 15500-2, at the temperatures and pressures given in Table 2.

Table 2 — Test temperatures and pressures

Temperature °C	Pressure MPa [bar]
-40 or -20 (as applicable)	0,05 [0,5]
20	0,05 [0,5]
85	0,05 [0,5]

### 6.2.1 External leakage

This external leakage test is intended for ventilation hoses and gas-tight housings. Ventilation hoses and gas-tight housings shall be leak-tight when tested at the pressures and temperatures given in Table 2. Atmospheric passages and other connections shall be connected or plugged as recommended by the manufacturer for normal service.

### 6.2.2 External Leakage, of pressure retaining ventilation passages

This external leakage test is intended for ventilation passages of pressure retaining components. Ventilation passages of pressure retaining components shall meet the requirements of the following tests.

**6.2.2.1** Plug the ventilation passage outlets and pressurize the ventilation passages to the maximum pressure the vent passage is expected to be exposed to in service as specified by the manufacturer. The component shall be leak-tight other than through the intended vent passage.