
Specifikacije za posebne vrste navijalnih žic - 21. del: S poliuretanom emajlirana okrogla bakrena žica, prevlečena s poliamidom, za spajkanje, razred 155 - Dopolnilo A1

Specifications for particular types of winding wires - Part 21: Solderable polyurethane enamelled round copper wire overcoated with polyamide, class 155

Technische Lieferbedingungen für bestimmte Typen von Wickeldrähten - Teil 21: Runddrähte aus Kupfer, verzinnbar, lackisoliert mit Polyurethan und darüber mit Polyamid, Klasse 155

Spécifications pour types particuliers de fils de bobinage - Partie 21: Fil brasable de section circulaire en cuivre émaillé avec polyuréthane et avec surcouche polyamide, classe 155

Ta slovenski standard je istoveten z: EN 60317-21:2014/A1:2019

ICS:

29.060.10	Žice	Wires
77.150.30	Bakreni izdelki	Copper products

SIST EN 60317-21:2014/A1:2019 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 60317-21:2014/A1:2019](https://standards.iteh.ai/catalog/standards/sist/4cf19fd7-4f29-4fc3-8e11-a4b5cab70f4f/sist-en-60317-21-2014-a1-2019)

<https://standards.iteh.ai/catalog/standards/sist/4cf19fd7-4f29-4fc3-8e11-a4b5cab70f4f/sist-en-60317-21-2014-a1-2019>

EUROPEAN STANDARD

EN 60317-21:2014/A1

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2019

ICS 29.060.10

English Version

Specifications for particular types of winding wires - Part 21:
Solderable polyurethane enamelled round copper wire
overcoated with polyamide, class 155
(IEC 60317-21:2013/A1:2019)

Spécifications pour types particuliers de fils de bobinage -
Partie 21: Fil brasable de section circulaire en cuivre
émaillé avec polyuréthane et avec surcouche polyamide,
classe 155
(IEC 60317-21:2013/A1:2019)

Technische Lieferbedingungen für bestimmte Typen von
Wickeldrähten - Teil 21: Runddrähte aus Kupfer,
verzinnbar, lackisoliert mit Polyurethan und darüber mit
Polyamid, Klasse 155
(IEC 60317-21:2013/A1:2019)

This amendment A1 modifies the European Standard EN 60317-21:2014; it was approved by CENELEC on 2019-07-17. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this amendment the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This amendment exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

EN 60317-21:2014/A1:2019 (E)**European foreword**

The text of document 55/1690/CDV, future IEC 60317-21/A1, prepared by IEC/TC 55 "Winding wires" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 60317-21:2014/A1:2019.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2020-04-17
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2022-07-17

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

iTeh STANDARD PREVIEW
Endorsement notice
(standards.itih.ai)

The text of the International Standard IEC 60317-21:2013/A1:2019 was approved by CENELEC as a European Standard without any modification.



IEC 60317-21

Edition 3.0 2019-06

INTERNATIONAL STANDARD

NORME INTERNATIONALE

AMENDMENT 1
AMENDEMENT 1

**Specifications for particular types of winding wires –
Part 21: Solderable polyurethane enamelled round copper wire overcoated with
polyamide, class 155**

**Spécifications pour types particuliers de fils de bobinage –
Partie 21: Fil brasable de section circulaire en cuivre émaillé avec polyuréthane
et avec surcouche polyamide, classe 155**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.060.10

ISBN 978-2-8322-6962-6

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

FOREWORD

This amendment to International Standard IEC 60317-21 has been prepared by IEC technical committee 55: Winding wires.

The text of this amendment is based on the following documents:

CDV	Report on voting
55/1690/CDV	55/1739/RVC

Full information on the voting for the approval of this amendment can be found in the report on voting indicated in the above table.

The committee has decided that the contents of this amendment and the base publication will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 60317-21:2014/A1:2019

<https://standards.iteh.ai/catalog/standards/sist/4cfl9fd7-4f29-4fc3-8e11-a4b5cab70f4f/sist-en-60317-21-2014-a1-2019>

17 Solderability

Replace the content of this clause by the following:

17.1 General

The temperature of the solder bath shall be (390 ± 5) °C. The surface of the tinned wire shall be smooth and free from holes and enamel residues.

17.2 Nominal conductor diameters up to and including 0,100 mm

The maximum immersion time shall be 2 s.

17.3 Nominal conductor diameters over 0,100 mm

The maximum immersion time (in seconds) shall be the following multiple of the nominal conductor diameter (in millimetres) with a minimum of 2 s.

Grade 1	Grade 2
8 s/mm	12 s/mm