

Second edition
2012-04-15

AMENDMENT 1
2016-04-01

**Road vehicles — Compressed natural
gas (CNG) fuel system components —**

**Part 9:
Pressure regulator**

AMENDMENT 1

iTeh STANDARD PREVIEW
(standards.iteh.ai)

*Véhicules routiers — Composants des systèmes de combustible gaz
naturel comprimé (GNC) —*

Partie 9: Régulateur de pression

ISO 15500-9:2012/Amd 1:2016

AMENDEMENT 1

<https://standards.iteh.ai/catalog/standards/sist/defa3846-f4d1-4eec-a49d-fa5ca147067e/iso-15500-9-2012-amd-1-2016>



Reference number
ISO 15500-9:2012/Amd.1:2016(E)

© ISO 2016

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 15500-9:2012/Amd.1:2016

<https://standards.iteh.ai/catalog/standards/sist/defa3846-f4d1-4eec-a49d-fa5ca147067e/iso-15500-9-2012-amd-1-2016>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](http://standards.iteh.ai/Foreword-Supplementary-information)

Amendment 1 to ISO 15500-9:2012 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 41, *Specific aspects for gaseous fuels*.

[ISO 15500-9:2012/Amd 1:2016](https://standards.iteh.ai/catalog/standards/sist/defa3846-f4d1-4eec-a49d-fa5ca147067e/iso-15500-9-2012-amd-1-2016)

<https://standards.iteh.ai/catalog/standards/sist/defa3846-f4d1-4eec-a49d-fa5ca147067e/iso-15500-9-2012-amd-1-2016>

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

ISO 15500-9:2012/Amd 1:2016

<https://standards.iteh.ai/catalog/standards/sist/defa3846-f4d1-4eec-a49d-fa5ca147067e/iso-15500-9-2012-amd-1-2016>

Road vehicles — Compressed natural gas (CNG) fuel system components —

Part 9: Pressure regulator

AMENDMENT 1

Page 2, Clause 5

Replace Clause 5 with the following:

5 Construction and assembly

The pressure regulator shall comply with the applicable provisions of ISO 15500-1 and ISO 15500-2, and with the tests specified in Clause 6. Tolerances should follow the specifications of ISO 15500-2.

The components downstream of the pressure regulator shall be protected from exposure to full upstream pressure. The pressure relief valve used for this purpose shall reset after relieving.

A pressure relief valve may be integral to the pressure regulator.

The pressure regulator shall have a factory-set maximum outlet pressure. The maximum outlet pressure rating and the inlet working pressure rating shall be marked on the regulator.

Page 3, Table 1

<https://standards.iteh.ai/catalog/standards/sist/defa3846-f4d1-4eec-a49d-fa5ca147067e/iso-15500-9-2012-amd-1-2016>

Replace [Table 1](#) with the following:

Table 1 — Applicable tests

Test	Applicable	Test procedure as required by ISO 15500-2	Specific test requirements of this part of ISO 15500
Hydrostatic strength	X	X	X (see 6.2)
Leakage	X (external)	X	X (see 6.3)
Excess torque resistance	X	X	
Bending moment	X	X	
Continued operation	X	X	X (see 6.4)
Corrosion resistance	X	X	
Oxygen ageing	X	X	
Ozone ageing	X	X	
Heat ageing	X	X	
Automotive fluids	X	X	
Electrical over-voltages	X	X	
Non-metallic material immersion	X	X	
Vibration resistance	X	X	
Brass material compatibility	X	X	
Insulation resistance	X		X (see 6.5)

Table 1 (continued)

Test	Applicable	Test procedure as required by ISO 15500-2	Specific test requirements of this part of ISO 15500
Minimum opening voltage	X		X (see 6.6)
Pressure impulse	X		X (see 6.7)
Water jacket freezing	X		X (see 6.8)

Page 4, 6.4

Replace list item a) with the following:

- a) Cycle the regulator for 95 % of the total number of cycles at room temperature and at the working pressure. Each cycle shall consist of flow until stable outlet pressure has been obtained, after which the gas flow shall be shut off by a downstream valve within 1 s, until the downstream lock-up pressure has stabilized. Stabilized outlet pressures are defined as set pressure ± 15 % for at least 5 s. The regulator shall comply with 6.3 at room temperature at intervals of 20 %, 40 %, 60 %, 80 % and 100 % of room temperature cycles.

Page 5, 6.7.2

Replace 6.7.2 with the following:

6.7.2 External impulse

The pressure regulator shall withstand 100 inlet pressure pulses, as follows.

- a) If the regulator has an integrated solenoid valve, it shall be opened by application of the rated voltage.
- b) The outlet of the regulator shall be vented until the inlet fuel line is at atmospheric pressure and then closed.
- c) Working pressure shall be instantaneously applied to the regulator inlet.

The pressure regulator shall contain or vent the pressure without any permanent deformation. The pressure regulator shall meet the requirements of the external leakage in accordance with 6.3, and the lock-up pressure shall not exceed the manufacturer's rated lock-up pressure.

The external impulse test in this subclause tests the resistance of the inlet valve to pulses on the high pressure side, for example, a pressure regulator with normal working pressure inside but with no pressure in the fuel line and there is a sudden opening of the cylinder valve filled with service pressure.

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

ISO 15500-9:2012/Amd 1:2016

<https://standards.iteh.ai/catalog/standards/sist/defa3846-f4d1-4eec-a49d-fa5ca147067e/iso-15500-9-2012-amd-1-2016>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15500-9:2012/Amd 1:2016
<https://standards.iteh.ai/catalog/standards/sist/defa3846-f4d1-4eec-a49d-fa5ca147067e/iso-15500-9-2012-amd-1-2016>