

ETSI TS 138 101-1 V17.8.0 (2023-01)



5G;
NR;
iTech STANDARD PREVIEW
User Equipment (UE) radio transmission and reception;
Part 1: Range 1 Standalone
(3GPP TS 38.101-1 version 17.8.0 Release 17)

<https://standards.iteh.ai/catalog/standards/sist/d697aceb-d0cc-46b9-b2d6-043bb1f3a1c/etsi-ts-138-101-1-v17-8-0-2023-01>



Reference

RTS/TSGR-0438101-1vh80

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards-portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document **"shall"**, **"shall not"**, **"should"**, **"should not"**, **"may"**, **"need not"**, **"will"**, **"will not"**, **"can"** and **"cannot"** are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and **"must not"** are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	18
1 Scope	20
2 References	20
3 Definitions, symbols and abbreviations	21
3.1 Definitions	21
3.2 Symbols.....	22
3.3 Abbreviations	24
4 General	25
4.1 Relationship between minimum requirements and test requirements	25
4.2 Applicability of minimum requirements	25
4.3 Specification suffix information.....	25
5 Operating bands and channel arrangement.....	27
5.1 General	27
5.2 Operating bands.....	27
5.2A Operating bands for CA	29
5.2A.0 General.....	29
5.2A.1 Intra-band CA	29
5.2A.2 Inter-band CA	30
5.2A.2.1 Inter-band CA (two bands).....	30
5.2A.2.2 Inter-band CA (three bands).....	34
5.2A.2.3 Inter-band CA (four bands)	37
5.2A.2.4 Inter-band CA (five bands)	38
5.2B Operating bands for DC	38
5.2C Operating band combination for SUL	38
5.2D Operating bands for UL MIMO	40
5.2E Operating band for V2X.....	41
5.2E.1 V2X operating bands	41
5.2E.2 V2X operating bands for con-current operation	41
5.3 UE channel bandwidth	42
5.3.1 General.....	42
5.3.2 Maximum transmission bandwidth configuration	43
5.3.3 Minimum guardband and transmission bandwidth configuration.....	43
5.3.4 RB alignment.....	45
5.3.5 UE channel bandwidth per operating band	45
5.3.6 Asymmetric channel bandwidths	49
5.3A UE channel bandwidth for CA	50
5.3A.1 General.....	50
5.3A.2 Maximum transmission bandwidth configuration for CA	50
5.3A.3 Minimum guardband and transmission bandwidth configuration for CA	50
5.3A.4 Void	52
5.3A.5 UE channel bandwidth per operating band for CA.....	52
5.3E Channel bandwidth for V2X	53
5.3E.1 General.....	53
5.3E.2 Channel bandwidth for V2X concurrent operation.....	54
5.3I Channel bandwidth for RedCap	55
5.4 Channel arrangement.....	55
5.4.1 Channel spacing.....	55
5.4.1.1 Channel spacing for adjacent NR carriers.....	55
5.4.2 Channel raster	55
5.4.2.1 NR-ARFCN and channel raster.....	55

5.4.2.2	Channel raster to resource element mapping.....	56
5.4.2.3	Channel raster entries for each operating band	56
5.4.3	Synchronization raster	59
5.4.3.1	Synchronization raster and numbering.....	59
5.4.3.3	Synchronization raster entries for each operating band.....	59
5.4.4	TX–RX frequency separation	61
5.4A	Channel arrangement for CA.....	62
5.4A.1	Channel spacing for CA.....	62
5.4A.2	Channel raster for CA	62
5.4A.3	Synchronization raster for CA	62
5.4A.4	Tx-Rx frequency separation for CA.....	62
5.4B	Reserved	63
5.4C	Reserved	63
5.4D	Reserved	63
5.4E	Channel arrangement for V2X	63
5.4E.1	Channel spacing.....	63
5.4E.2	Channel raster	63
5.4E.2.1	NR-ARFCN and channel raster.....	63
5.4E.2.2	Channel raster to resource element mapping.....	63
5.4E.2.3	Channel raster entries for each operating band	63
5.4E.3	Synchronization raster for V2X	63
5.5	Void.....	64
5.5A	Configurations for CA.....	64
5.5A.0	General.....	64
5.5A.1	Configurations for intra-band contiguous CA.....	64
5.5A.2	Configurations for intra-band non-contiguous CA	67
5.5A.3	Configurations for inter-band CA.....	71
5.5A.3.1	Configurations for inter-band CA (two bands)	71
5.5A.3.2	Configurations for inter-band CA (three bands)	100
5.5A.3.3	Configurations for inter-band CA (four bands).....	159
5.5A.3.4	Configurations for inter-band CA (five bands).....	192
5.5B	Configurations for DC.....	195
5.5C	Configurations for SUL.....	199
6	Transmitter characteristics	205
6.1	General	205
6.1A	General	205
6.1F	General	205
6.2	Transmitter power	205
6.2.1	UE maximum output power.....	205
6.2.1I	Void.....	207
6.2.2	UE maximum output power reduction.....	207
6.2.3	UE additional maximum output power reduction.....	209
6.2.3.1	General.....	209
6.2.3.2	A-MPR for NS_04	213
6.2.3.3	A-MPR for NS_10	214
6.2.3.4	A-MPR for NS_05 and NS_05U.....	214
6.2.3.5	A-MPR for NS_40	218
6.2.3.6	A-MPR for NS_43 and NS_43U.....	218
6.2.3.7	A-MPR for NS_03 and NS_03U.....	219
6.2.3.8	A-MPR for NS_37	220
6.2.3.9	A-MPR for NS_38	221
6.2.3.10	A-MPR for NS_39	221
6.2.3.11	A-MPR for NS_41	221
6.2.3.12	A-MPR for NS_42	222
6.2.3.13	A-MPR for NS_18	222
6.2.3.14	A-MPR for NS_21	223
6.2.3.15	A-MPR for NS_24	224
6.2.3.16	A-MPR for NS_27	224
6.2.3.17	A-MPR for NS_46	226
6.2.3.18	A-MPR for NS_47	226
6.2.3.19	A-MPR for NS_50	227

6.2.3.20	A-MPR for NS_44	229
6.2.3.21	A-MPR for NS_12	229
6.2.3.22	A-MPR for NS_13	230
6.2.3.23	A-MPR for NS_14	230
6.2.3.24	A-MPR for NS_15	230
6.2.3.25	A-MPR for NS_45	231
6.2.3.26	A-MPR for NS_48	231
6.2.3.27	A-MPR for NS_49	233
6.2.3.28	A-MPR for NS_51	235
6.2.3.29	A-MPR for NS_07	236
6.2.3.30	A-MPR for NS_56	236
6.2.4	Configured transmitted power	237
6.2A	Transmitter power for CA	240
6.2A.1	UE maximum output power for CA	240
6.2A.1.1	UE maximum output power for Intra-band contiguous CA	240
6.2A.1.2	UE maximum output power for Intra-band non-contiguous CA	240
6.2A.1.3	UE maximum output power for Inter-band CA	240
6.2A.1.4	Void	244
6.2A.1.5	Void	244
6.2A.2	UE maximum output power reduction for CA	244
6.2A.2.1	UE maximum output power reduction for Intra-band contiguous CA	244
6.2A.2.2	UE maximum output power reduction for Intra-band non-contiguous CA	247
6.2A.2.2.0	General	247
6.2A.2.2.1	MPR to meet -30dBm/MHz	248
6.2A.2.2.1.1	PC3 with indicating dualPA-Architecture supported	248
6.2A.2.2.1.2	PC2 with indicating dualPA-Architecture supported	249
6.2A.2.2.1.3	PC3 without indicating dualPA-Architecture supported	249
6.2A.2.2.1.4	PC2 without indicating dualPA-Architecture supported	249
6.2A.2.2.2	MPR to meet -13dBm/MHz	250
6.2A.2.2.2.1	PC3 with indicating dualPA-Architecture supported	250
6.2A.2.2.2.2	PC2 with indicating dualPA-Architecture supported	250
6.2A.2.2.2.3	PC3 without indicating dualPA-Architecture supported	250
6.2A.2.2.2.4	PC2 without indicating dualPA-Architecture supported	251
6.2A.2.3	UE maximum output power reduction for Inter-band CA	251
6.2A.2.4	Void	251
6.2A.3	UE additional maximum output power reduction for CA	251
6.2A.3.1	UE additional maximum output power reduction for Intra-band CA	251
6.2A.3.1.1	UE additional maximum output power reduction for Intra-band contiguous CA	251
6.2A.3.1.1.1	A-MPR for CA_NS_04	252
6.2A.3.1.1.1.2	Non-contiguous allocations	253
6.2A.3.1.2	UE additional maximum output power reduction for Intra-band non-contiguous CA	258
6.2A.3.1.3	UE additional maximum output power reduction for Inter-band CA	261
6.2A.4	Configured output power for CA	263
6.2A.4.1	Configured transmitted power level	263
6.2A.4.1.1	Configured transmitted power for Intra-band contiguous CA	263
6.2A.4.1.2	Configured transmitted power for Intra-band non-contiguous CA	265
6.2A.4.1.3	Configured transmitted power for Inter-band CA	268
6.2A.4.1.4	Void	271
6.2A.4.2	$\Delta T_{IB,c}$ for CA	271
6.2A.4.2.1	Void	271
6.2A.4.2.2	Void	271
6.2A.4.2.3	$\Delta T_{IB,c}$ for Inter-band CA (two bands)	271
6.2A.4.2.4	$\Delta T_{IB,c}$ for Inter-band CA (three bands)	277
6.2A.4.2.5	$\Delta T_{IB,c}$ for Inter-band CA (four bands)	286
6.2A.4.2.6	$\Delta T_{IB,c}$ for Inter-band CA (five bands)	291
6.2B	Transmitter power for NR-DC	291
6.2B.0	General	291
6.2B.1	UE maximum output power for NR-DC	291
6.2B.2	UE maximum output power reduction for NR-DC	292
6.2B.3	UE additional maximum output power reduction for NR-DC	292
6.2B.4.1	Configured transmitted power level for NR-DC	292
6.2B.4.2	$\Delta T_{IB,c}$ for NR-DC	296

6.2C	Transmitter power for SUL	297
6.2C.1	Configured transmitted power for SUL	297
6.2C.2	$\Delta T_{IB,c}$	297
6.2D	Transmitter power for UL MIMO	299
6.2D.1	UE maximum output power for UL MIMO	299
6.2D.2	UE maximum output power reduction for UL MIMO	301
6.2D.3	UE additional maximum output power reduction for UL MIMO	302
6.2D.4	Configured transmitted power for UL MIMO	302
6.2E	Transmitter power for V2X	303
6.2E.1	UE maximum output power for V2X	303
6.2E.1.1	General	303
6.2E.1.2	UE maximum output power for V2X con-current operation	304
6.2E.2	UE maximum output power reduction for V2X	305
6.2E.2.1	General	305
6.2E.2.2	MPR for Power class 2 and Power class 3 V2X UE	305
6.2E.2.3	MPR for Power class 2 and Power class 3 V2X con-current operation	307
6.2E.2.4	MPR for Power class 1 UE in Band n14	309
6.2E.3	UE additional maximum output power reduction for V2X	309
6.2E.3.1	General	309
6.2E.3.2	A-MPR for V2X UE by NS_33	310
6.2E.3.3	A-MPR for Power class 3 V2X UE by NS_52	313
6.2E.3.4	A-MPR for V2X con-current operation	314
6.2E.4	Configured transmitted power for V2X	314
6.2E.4.1	General	314
6.2E.4.2	Configured transmitted power for inter-band V2X con-current operation	315
6.2E.4.3	Configured transmitted power for intra-band V2X con-current operation	316
6.2F	Transmitter power for shared spectrum channel access	318
6.2F.1	UE maximum output power	318
6.2F.1A	UE maximum output power for CA	319
6.2F.1A.1	UE maximum output power for inter-band CA	319
6.2F.1A.2	UE maximum output power for intra-band contiguous CA	320
6.2F.1B	UE maximum output power for NR-DC	320
6.2F.1D	UE maximum output power for UL MIMO	320
6.2F.2	UE maximum output power reduction	321
6.2F.2A	UE maximum output power reduction for CA	322
6.2F.2A.1	UE maximum output power reduction for inter-band CA	322
6.2F.2A.2	UE maximum output power reduction for intra-band contiguous CA	322
6.2F.2D	UE maximum output power reduction for UL MIMO	323
6.2F.3	UE additional maximum output power reduction	324
6.2F.3.1	General	324
6.2F.3.2	A-MPR for NS_28	325
6.2F.3.3	A-MPR for NS_29	325
6.2F.3.4	A-MPR for NS_30	325
6.2F.3.5	A-MPR for NS_31	326
6.2F.3.6	A-MPR for NS_53	326
6.2F.3.7	A-MPR for NS_54	327
6.2F.3.8	A-MPR for NS_58	327
6.2F.3.9	A-MPR for NS_59	328
6.2F.3.10	A-MPR for NS_60	328
6.2F.3.11	A-MPR for NS_61	329
6.2F.3A	UE additional maximum output power reduction for CA	330
6.2F.3A.1	UE additional maximum output power reduction for inter-band CA	330
6.2F.3D	UE additional maximum output power reduction for UL MIMO	330
6.2F.4	Configured transmitted power	330
6.2F.4D	Configured transmitted power UL MIMO	330
6.2G	Transmitter power for Tx Diversity	331
6.2G.1	UE maximum output power for Tx Diversity	331
6.2G.2	UE maximum output power reduction for Tx Diversity	331
6.2G.3	UE additional maximum output power reduction for Tx Diversity	331
6.2G.4	Configured transmitted power for Tx Diversity	331
6.2H	Transmitter power for CA with UL MIMO	332
6.2H.1	Transmitter power for intra-band UL contiguous CA with UL MIMO	332

6.2H.1.1	UE maximum output power for intra-band UL contiguous CA with UL MIMO	332
6.2H.1.2	UE maximum output power reduction for intra-band UL contiguous CA with UL MIMO	332
6.2H.1.3	UE additional maximum output power reduction for intra-band UL contiguous CA with UL MIMO	333
6.2H.1.4	Configured transmitted power for intra-band UL contiguous CA with UL MIMO	333
6.2I	Transmitter power for RedCap	333
6.2I.1	Maximum output power for RedCap	333
6.3	Output power dynamics	334
6.3.1	Minimum output power	334
6.3.2	Transmit OFF power	334
6.3.3	Transmit ON/OFF time mask	334
6.3.3.1	General	334
6.3.3.2	General ON/OFF time mask	335
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries	335
6.3.3.4	PRACH time mask	335
6.3.3.5	Void	337
6.3.3.6	SRS time mask	337
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	338
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	339
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	340
6.3.4	Power control	341
6.3.4.1	General	341
6.3.4.2	Absolute power tolerance	341
6.3.4.3	Relative power tolerance	341
6.3.4.4	Aggregate power tolerance	342
6.3A	Output power dynamics for CA	342
6.3A.1	Minimum output power for CA	342
6.3A.1.1	Minimum output power for intra-band contiguous CA	342
6.3A.1.2	Minimum output power for intra-band non-contiguous CA	342
6.3A.1.3	Minimum output power for inter-band CA	342
6.3A.1.4	Void	343
6.3A.2	Transmit OFF power for CA	343
6.3A.2.1	Transmit OFF power for intra-band contiguous CA	343
6.3A.2.2	Transmit OFF power for intra-band non-contiguous CA	343
6.3A.2.3	Transmit OFF power for inter-band CA	343
6.3A.2.4	Void	343
6.3A.3	Transmit ON/OFF time mask for CA	343
6.3A.3.1	Transmit ON/OFF time mask for intra-band contiguous CA	343
6.3A.3.2	Transmit ON/OFF time mask for intra-band non-contiguous CA	343
6.3A.3.3	Transmit ON/OFF time mask for inter-band CA	344
6.3A.3.3.1	General	344
6.3A.3.3.2	Time mask for switching between two uplink carriers	344
6.3A.3.3.3	Time mask for switching between two uplink carriers with two transmit antenna connectors	345
6.3A.3.3.4	Time mask for switching between one uplink band with one transmit antenna connector and one uplink band with two transmit antenna connectors	346
6.3A.3.3.5	Time mask for switching between two uplink bands with two transmit antenna connectors	347
6.3A.3.4	Void	348
6.3A.4	Power control for CA	348
6.3A.4.1	Power control for intra-band contiguous CA	348
6.3A.4.1.1	Absolute power tolerance	348
6.3A.4.1.2	Relative power tolerance	348
6.3A.4.1.3	Aggregate power control tolerance	349
6.3A.4.2	Power control for intra-band non-contiguous CA	349
6.3A.4.2.1	Absolute power tolerance	349
6.3A.4.2.1.1	Minimum requirements	349
6.3A.4.2.2	Relative power tolerance	349
6.3A.4.2.2.1	Minimum requirements	349
6.3A.4.2.3	Aggregate power control tolerance	349
6.3A.4.3	Power control for inter-band CA	349
6.3A.4.4	Void	349
6.3B	Output power dynamics for NR-DC	349

6.3C	Output power dynamics for SUL	350
6.3C.1	Void	350
6.3C.2	Void	350
6.3C.3	Transmit ON/OFF time mask for SUL	350
6.3C.3.1	Time mask for switching between two uplink carriers.....	350
6.3C.3.2	Time mask for switching between two uplink carriers with two transmit antenna connectors	351
6.3C.3.3	Time mask for switching between one uplink band with one transmit antenna connector and one uplink band with two transmit antenna connectors	351
6.3C.3.4	Time mask for switching between two uplink bands with two transmit antenna connectors.....	352
6.3D	Output power dynamics for UL MIMO	353
6.3D.1	Minimum output power for UL MIMO	353
6.3D.2	Transmit OFF power for UL MIMO.....	353
6.3D.3	Transmit ON/OFF time mask for UL MIMO	353
6.3D.4	Power control for UL MIMO.....	354
6.3E	Output power dynamics for V2X	354
6.3E.1	Minimum output power for V2X	354
6.3E.1.1	General	354
6.3E.1.2	Minimum output power for V2X con-current operation	354
6.3E.2	Transmit OFF power for V2X	355
6.3E.2.1	General	355
6.3E.2.2	Transmit OFF power for V2X con-current operation	355
6.3E.3	Transmit ON/OFF time mask for V2X.....	355
6.3E.3.1	General	355
6.3E.3.2	General time mask.....	355
6.3E.3.3	S-SSB time mask	356
6.3E.3.4	Transmit ON/OFF time mask for V2X con-current operation.....	356
6.3E.4	Power control for V2X	357
6.3E.4.1	General	357
6.3E.4.2	Absolute power tolerance.....	358
6.3E.4.3	Power control for V2X con-current operation.....	358
6.3F	Output power dynamics for shared spectrum channel access.....	358
6.3F.1	Minimum output power	358
6.3F.2	Transmit OFF power.....	358
6.3F.3	Transmit ON/OFF time mask	358
6.3F.3.1	General	358
6.3F.3.2	General ON/OFF time mask	358
6.3F.3A	General ON/OFF mask for CA	359
6.3F.3A.1	General ON/OFF mask for inter-band CA	359
6.3F.4	Power control.....	359
6.3F.4.1	General	359
6.3F.4.2	Absolute power tolerance.....	359
6.3F.4.3	Relative power tolerance.....	359
6.3F.4.4	Aggregate power tolerance.....	359
6.3F.4A	Power control for inter-band CA	359
6.3G	Output power dynamics for Tx Diversity.....	360
6.3G.1	Minimum output power for Tx Diversity	360
6.3G.2	Transmit OFF power for Tx Diversity.....	360
6.3G.3	Transmit ON/OFF time mask for Tx Diversity	360
6.3G.4	Power control for Tx Diversity	360
6.3H	Output power dynamics for CA with UL MIMO	360
6.3H.1	Output power dynamics for intra-band UL contiguous CA with UL MIMO	360
6.3H.1.1	Minimum output power for intra-band UL contiguous CA with UL MIMO	360
6.3H.1.2	Transmit OFF power for intra-band UL contiguous CA with UL MIMO	360
6.3H.1.3	Transmit ON/OFF time mask for intra-band UL contiguous CA with UL MIMO.....	360
6.3H.1.4	Power control for intra-band UL contiguous CA with UL MIMO	361
6.4	Transmit signal quality	361
6.4.1	Frequency error.....	361
6.4.2	Transmit modulation quality.....	361
6.4.2.0	General	361
6.4.2.1	Error Vector Magnitude	361
6.4.2.1a	Error Vector Magnitude including symbols with transient period	362
6.4.2.2	Carrier leakage	363

6.4.2.3	In-band emissions	363
6.4.2.4	EVM equalizer spectrum flatness	364
6.4.2.4.1	Requirements for Pi/2 BPSK modulation.....	365
6.4.2.5	Phase continuity requirements for DMRS bundling	366
6.4A	Transmit signal quality for CA.....	367
6.4A.1	Frequency error for CA.....	367
6.4A.1.1	Frequency error for intra-band contiguous CA	367
6.4A.1.2	Frequency error for intra-band non-contiguous CA.....	367
6.4A.1.3	Frequency error for inter-band CA.....	367
6.4A.1.4	Void.....	368
6.4A.2	Transmit modulation quality for CA.....	368
6.4A.2.1	Transmit modulation quality for intra-band contiguous CA	368
6.4A.2.1.0	General	368
6.4A.2.1.1	Error Vector Magnitude.....	368
6.4A.2.1.2	In-band emissions.....	368
6.4A.2.1.3	Carrier leakage.....	370
6.4A.2.2	Transmit modulation quality for intra-band non-contiguous CA	371
6.4A.2.2.0	General	371
6.4A.2.2.1	Error Vector Magnitude.....	371
6.4A.2.2.2	In-band emissions	371
6.4A.2.2.3	Carrier leakage.....	371
6.4A.2.3	Transmit modulation quality for inter-band CA.....	372
6.4A.2.4	Void.....	372
6.4B	Transmit signal quality for NR-DC	372
6.4C	Transmit signal quality for SUL.....	372
6.4D	Transmit signal quality for UL MIMO.....	373
6.4D.0	General.....	373
6.4D.1	Frequency error for UL MIMO.....	373
6.4D.2	Transmit modulation quality for UL MIMO.....	373
6.4D.2.0	General	373
6.4D.2.1	Error Vector Magnitude	373
6.4D.2.2	Carrier leakage	374
6.4D.2.3	In-band emissions	374
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO	374
6.4D.3	Time alignment error for UL MIMO	374
6.4D.4	Requirements for coherent UL MIMO	374
6.4E	Transmit signal quality for V2X.....	375
6.4E.1	Frequency error for V2X	375
6.4E.1.1	General	375
6.4E.1.2	Frequency error for V2X con-current operation	375
6.4E.2	Transmit modulation quality for V2X	375
6.4E.2.1	General	375
6.4E.2.2	Error Vector Magnitude for V2X.....	375
6.4E.2.3	Carrier leakage for V2X.....	375
6.4E.2.4	In-band emissions for V2X	376
6.4E.2.5	EVM equalizer spectrum flatness for V2X	376
6.4E.2.6	Transmit modulation quality for V2X con-current operation	376
6.4F	Transmit signal quality for shared spectrum channel access.....	376
6.4F.1	Frequency error.....	376
6.4F.2	Transmit modulation quality.....	376
6.4F.2.0	General	376
6.4F.2.1	Error Vector Magnitude	376
6.4F.2.2	Carrier leakage	376
6.4F.2.3	In-band emissions	377
6.4F.2.4	EVM equalizer spectrum flatness	377
6.4F.2A	Transmit modulation quality for CA.....	378
6.4F.2A.1	Transmit modulation quality for inter-band CA.....	378
6.4G	Transmit signal quality for Tx Diversity	378
6.4G.1	Frequency error for Tx Diversity.....	378
6.4G.2	Transmit modulation quality for Tx Diversity	378
6.4G.2.0	General	378
6.4H	Transmit signal quality for CA with UL MIMO	379

6.4H.1	Transmit signal quality for intra-band UL contiguous CA with UL MIMO.....	379
6.4H.1.1	Frequency error for intra-band UL contiguous CA with UL MIMO	379
6.4H.1.2	Transmit modulation quality for intra-band UL contiguous CA with UL MIMO	379
6.4H.1.2.0	General	379
6.4H.1.2.1	Error Vector Magnitude.....	379
6.4H.1.2.2	Carrier leakage.....	380
6.4H.1.2.3	In-band emissions	380
6.4H.1.3	Time alignment error for intra-band UL contiguous CA with UL MIMO	380
6.4H.1.4	Coherent UL MIMO requirement for intra-band UL contiguous CA with UL MIMO.....	380
6.5	Output RF spectrum emissions.....	380
6.5.1	Occupied bandwidth	380
6.5.2	Out of band emission	380
6.5.2.1	General	380
6.5.2.2	Spectrum emission mask.....	380
6.5.2.3	Additional spectrum emission mask	381
6.5.2.3.1	Requirements for network signalling value "NS_35"	381
6.5.2.3.2	Requirements for network signalling value "NS_04"	381
6.5.2.3.3	Requirements for network signalling values "NS_03" and "NS_03U"	382
6.5.2.3.4	Requirements for network signalling value "NS_06" or "NS_07"	383
6.5.2.3.5	Void	383
6.5.2.3.6	Void	383
6.5.2.3.7	Void	383
6.5.2.3.8	Requirements for network signalling value "NS_27"	383
6.5.2.3.9	Requirements for network signalling value "NS_21"	384
6.5.2.4	Adjacent channel leakage ratio	384
6.5.2.4.1	NR ACLR	384
6.5.2.4.2	UTRA ACLR	385
6.5.3	Spurious emissions	385
6.5.3.0	General	385
6.5.3.1	General spurious emissions	386
6.5.3.2	Spurious emissions for UE co-existence	386
6.5.3.3	Additional spurious emissions	393
6.5.3.3.1	Requirement for network signalling value "NS_04"	393
6.5.3.3.2	Requirement for network signalling value "NS_17"	394
6.5.3.3.3	Requirement for network signalling value "NS_18"	394
6.5.3.3.4	Requirement for network signalling values "NS_05" and "NS_05U"	394
6.5.3.3.5	Requirement for network signalling values "NS_43" and "NS_43U"	394
6.5.3.3.6	Requirement for network signalling value "NS_37"	395
6.5.3.3.7	Requirement for network signalling value "NS_38"	395
6.5.3.3.8	Requirement for network signalling value "NS_39"	395
6.5.3.3.9	Requirement for network signalling value "NS_40"	395
6.5.3.3.10	Requirement for network signalling value "NS_41"	396
6.5.3.3.11	Requirement for network signalling value "NS_42"	396
6.5.3.3.12	Requirement for network signalling value "NS_21"	396
6.5.3.3.13	Requirement for network signalling value "NS_24"	396
6.5.3.3.14	Requirement for network signalling value "NS_27"	397
6.5.3.3.15	Requirement for network signalling value "NS_47"	397
6.5.3.3.16	Requirement for network signalling value "NS_50"	397
6.5.3.3.17	Requirement for network signalling value "NS_12"	398
6.5.3.3.18	Requirement for network signalling value "NS_13"	398
6.5.3.3.19	Requirement for network signalling value "NS_14"	398
6.5.3.3.20	Requirement for network signalling value "NS_15"	398
6.5.3.3.21	Requirement for network signalling value "NS_45"	399
6.5.3.3.22	Requirement for network signalling values "NS_48" and "NS_51"	399
6.5.3.3.23	Requirement for network signalling value "NS_49"	399
6.5.3.3.24	Requirement for network signalling value "NS_44"	400
6.5.3.3.25	Requirement for network signalling value "NS_46"	400
6.5.3.3.26	Requirement for network signalling value "NS_07"	400
6.5.3.3.27	Requirement for network signalling value "NS_56"	401
6.5.4	Transmit intermodulation	401
6.5A	Output RF spectrum emissions for CA.....	402
6.5A.0	General.....	402

6.5A.1	Occupied bandwidth for CA	402
6.5A.1.1	Void.....	402
6.5A.1.1a	Occupied bandwidth for Intra-band contiguous CA	402
6.5A.1.2	Occupied bandwidth for Intra-band non-contiguous CA	402
6.5A.1.3	Occupied bandwidth for Inter-band CA.....	402
6.5A.2	Out of band emission for CA.....	402
6.5A.2.1	General.....	402
6.5A.2.2	Spectrum emission mask.....	402
6.5A.2.2.1	Spectrum emission mask for intra-band contiguous CA	402
6.5A.2.2.2	Spectrum emission mask for intra-band non-contiguous CA	403
6.5A.2.2.3	Spectrum emission mask for Inter-band CA.....	403
6.5A.2.2.4	Void.....	403
6.5A.2.3	Additional spectrum emission mask for CA	403
6.5A.2.3.1	Additional spectrum emission mask for intra-band contiguous CA	403
6.5A.2.3.2	Additional spectrum emission mask for Intra-band non-contiguous CA.....	404
6.5A.2.3.3	Additional spectrum emission mask for Inter-band CA	404
6.5A.2.4	Adjacent channel leakage ratio	404
6.5A.2.4.1	NR ACLR.....	404
6.5A.2.4.2	UTRA ACLR	406
6.5A.3	Spurious emission for CA.....	406
6.5A.3.1	General spurious emissions.....	406
6.5A.3.2	Spurious emissions for UE co-existence	407
6.5A.3.2.1	Spurious emissions for UE co-existence for intra-band contiguous CA.....	407
6.5A.3.2.2	Spurious emissions for UE co-existence for intra-band non-contiguous CA	408
6.5A.3.2.3	Spurious emissions for UE co-existence for Inter-band CA.....	409
6.5A.3.2.4	Void.....	427
6.5A.3.2.5	Void.....	427
6.5A.3.2.6	Void.....	427
6.5A.3.3	Additional spurious emissions for CA	427
6.5A.3.3.1	Additional spurious emissions for intra-band contiguous CA	427
6.5A.3.3.2	Additional spurious emissions for intra-band non-contiguous CA.....	428
6.5A.4	Transmit intermodulation for CA	428
6.5A.4.2.1	Transmit intermodulation for intra-band contiguous CA	428
6.5A.4.2.2	Void.....	428
6.5B	Output RF spectrum emissions for NR-DC.....	428
6.5D	Output RF spectrum emissions for UL MIMO.....	429
6.5D.1	Occupied bandwidth for UL MIMO	429
6.5D.2	Out of band emission for UL MIMO	429
6.5D.3	Spurious emission for UL MIMO.....	429
6.5D.4	Transmit intermodulation for UL MIMO	429
6.5E	Output RF spectrum emissions for V2X	430
6.5E.1	Occupied bandwidth for V2X.....	430
6.5E.1.1	General.....	430
6.5E.1.2	Occupied bandwidth for V2X con-current operation.....	430
6.5E.2	Out of band emission for V2X.....	430
6.5E.2.1	General.....	430
6.5E.2.2	Spectrum emission mask.....	430
6.5E.2.2.1	General	430
6.5E.2.2.2	Spectrum emission mask for V2X con-current operation.....	430
6.5E.2.3	Additional Spectrum emission mask.....	431
6.5E.2.3.1	Requirements for network signalling value "NS_33".....	431
6.5E.2.3.2	Requirements for network signalling value "NS_52".....	431
6.5E.2.3.3	Requirements for network signalling value "NS_06".....	432
6.5E.2.4	Adjacent channel leakage ratio	432
6.5E.2.4.1	General	432
6.5E.2.4.2	ACLR for V2X con-current operation.....	432
6.5E.3	Spurious emissions for V2X	432
6.5E.3.1	General spurious emissions.....	432
6.5E.3.2	Spurious emissions for UE co-existence	432
6.5E.3.3	Spurious emissions for UE co-existence for V2X con-current operation	433
6.5E.3.4	Additional spurious emissions requirements for V2X	434
6.5E.3.4.1	General	434

6.5E.3.4.2	Requirements for network signalling value "NS_33"	434
6.5E.3.4.3	Void	434
6.5E.4	Transmit intermodulation	434
6.5E.4.1	General	434
6.5E.4.2	Transmit intermodulation for V2X con-current operation	435
6.5F	Output RF spectrum emissions for shared spectrum channel access.....	435
6.5F.1	Occupied bandwidth	435
6.5F.2	Out of band emission	435
6.5F.2.1	General	435
6.5F.2.2	Spectrum emission mask for operation with shared spectrum channel access.....	435
6.5F.2.2.0	General	435
6.5F.2.2.1	Spectrum emission mask for non-transmitted channels.....	436
6.5F.2.3	Additional spectrum emission mask	436
6.5F.2.4	Adjacent channel leakage ratio	436
6.5F.2.4.0	General	436
6.5F.2.4.1	Shared spectrum channel access ACLR	436
6.5F.2.4.2	Additional requirement for network signalled value "NS_29"	436
6.5F.2A	Out of band emission for CA	437
6.5F.2A.1	Spectrum emission mask for CA.....	437
6.5F.2A.1.1	Spectrum emission mask for Inter-band CA.....	437
6.5F.2A.1.2	Spectrum emission mask for Intra-band contiguous CA	437
6.5F.2A.1.2.1	General.....	437
6.5F.2A.1.2.2	Intra-band contiguous CA spectrum emission mask for non-transmitted channels	438
6.5F.2A.2	Adjacent channel leakage ratio for CA	438
6.5F.2A.2.1	Adjacent channel leakage ratio for inter-band CA	438
6.5F.2A.2.2	Adjacent channel leakage ratio for intra-band contiguous CA	438
6.5F.3	Spurious emissions	439
6.5F.3.0	General	439
6.5F.3.1	General spurious emissions	439
6.5F.3.2	Spurious emissions for UE co-existence	439
6.5F.3.3	Additional spurious emissions	439
6.5F.3.3.0	General	439
6.5F.3.3.1	Requirement for network signalling value "NS_28"	439
6.5F.3.3.2	Requirement for network signalling value "NS_29"	440
6.5F.3.3.3	Requirement for network signalling value "NS_30"	441
6.5F.3.3.4	Requirement for network signalling value "NS_31"	442
6.5F.3.3.5	Requirements for network signalling value "NS_53" or "NS_54" or "NS_60".....	443
6.5F.3.3.6	Requirements for network signalling value "NS_58"	443
6.5F.3.3.7	Requirements for network signalling value "NS_61"	443
6.5F.4	Transmit intermodulation	443
6.5G	Output RF spectrum emissions for Tx Diversity	444
6.5G.1	Occupied bandwidth for Tx Diversity	444
6.5G.2	Out of band emission for Tx Diversity	444
6.5G.3	Spurious emission for Tx Diversity	444
6.5G.4	Transmit intermodulation for Tx Diversity.....	444
6.5H	Output RF spectrum emissions for CA with UL MIMO	444
6.5H.1	Output RF spectrum emissions for intra-band UL contiguous CA with UL MIMO	444
6.5H.1.1	Occupied bandwidth for intra-band UL contiguous CA with UL MIMO.....	444
6.5H.1.2	Out of band emission for intra-band UL contiguous CA with UL MIMO.....	444
6.5H.1.3	Spurious emission for intra-band UL contiguous CA with UL MIMO.....	445
6.5H.1.4	Transmit intermodulation for intra-band UL contiguous CA with UL MIMO	445
6.6	Void.....	445
6.6E	Time alignment error.....	445
7	Receiver characteristics.....	446
7.1	General	446
7.1A	General	446
7.1F	General	447
7.1I	General	447
7.2	Diversity characteristics	447
7.3	Reference sensitivity	447
7.3.1	General.....	447

7.3.2	Reference sensitivity power level	447
7.3.3	$\Delta R_{IB,c}$	456
7.3A	Reference sensitivity for CA	456
7.3A.1	General	456
7.3A.2	Reference sensitivity power level for CA	456
7.3A.2.1	Reference sensitivity power level for Intra-band contiguous CA	456
7.3A.2.2	Reference sensitivity power level for Intra-band non-contiguous CA	457
7.3A.2.3	Reference sensitivity power level for Inter-band CA	458
7.3A.2.4	Void	458
7.3A.3	$\Delta R_{IB,c}$ for CA	458
7.3A.3.1	General	458
7.3A.3.2	$\Delta R_{IB,c}$ for Inter-band CA	458
7.3A.3.2.1	$\Delta R_{IB,c}$ for two bands	459
7.3A.3.2.2	Void	461
7.3A.3.2.3	$\Delta R_{IB,c}$ for three bands	461
7.3A.3.2.4	$\Delta R_{IB,c}$ for four bands	469
7.3A.3.2.5	$\Delta R_{IB,c}$ for five bands	474
7.3A.3.3	$\Delta R_{IB,c}$ for Intra-band CA	474
7.3A.4	Reference sensitivity exceptions due to UL harmonic interference for CA	475
7.3A.5	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA	483
7.3A.6	Reference sensitivity exceptions due to cross band isolation for CA	505
7.3B	Reference sensitivity for NR-DC	508
7.3C	Reference sensitivity for SUL	508
7.3C.1	General	508
7.3C.2	Reference sensitivity power level for SUL	508
7.3C.3	$\Delta R_{IB,c}$ for SUL	511
7.3C.3.1	General	511
7.3C.3.2	SUL band combination	511
7.3C.3.2.1	$\Delta R_{IB,c}$ for two bands	511
7.3C.3.2.2	$\Delta R_{IB,c}$ for three bands	512
7.3C.3.2.3	$\Delta R_{IB,c}$ for four bands	512
7.3D	Reference sensitivity for UL MIMO	513
7.3E	Reference sensitivity for V2X	513
7.3E.1	General	513
7.3E.2	Minimum requirements	513
7.3E.3	Reference sensitivity power level for V2X con-current operation	514
7.3F	Reference sensitivity for shared spectrum channel access	515
7.3F.1	General	515
7.3F.2	Reference sensitivity power level	516
7.3F.3	Void	516
7.3F.4	Void	517
7.3F.4A	Shared spectrum channel access CA	517
7.3F.4A.1	Intra-band contiguous shared spectrum channel access CA	517
7.3F.5	Void	517
7.3F.5.1	Void	517
7.3F.5.2	Void	517
7.3F.5.3	Void	517
7.3G	Reference sensitivity for Tx Diversity	517
7.3G.5	Void	517
7.3G.5.0	Void	517
7.3I	Reference sensitivity for RedCap	517
7.3I.1	General	517
7.3I.2	Reference sensitivity power level	517
7.4	Maximum input level	521
7.4A	Maximum input level for CA	522
7.4A.1	Maximum input level for Intra-band contiguous CA	522
7.4A.2	Maximum input level for Intra-band non-contiguous CA	522
7.4A.3	Maximum input level for Inter-band CA	522
7.4B	Maximum input level for NR-DC	523
7.4D	Maximum input level for UL MIMO	523
7.4E	Maximum input level for V2X	523
7.4E.1	General	523

7.4E.2	Maximum input level for V2X con-current operation	523
7.5	Adjacent channel selectivity	523
7.5A	Adjacent channel selectivity for CA	525
7.5A.1	Adjacent channel selectivity for Intra-band contiguous CA	525
7.5A.2	Adjacent channel selectivity Intra-band non-contiguous CA	527
7.5A.3	Adjacent channel selectivity Inter-band CA	528
7.5B	Adjacent channel selectivity for NR-DC	528
7.5D	Adjacent channel selectivity for UL MIMO	528
7.5E	Adjacent channel selectivity for V2X	528
7.5E.1	General	528
7.5E.2	Adjacent channel selectivity for V2X con-current operation	530
7.5F	Adjacent channel selectivity for shared spectrum channel access	530
7.5F.1	General	530
7.5F.1A	Adjacent channel selectivity for shared spectrum channel access CA	531
7.5F.1A.1	Intra-band contiguous shared spectrum channel access CA	531
7.5F.2	Void	531
7.6	Blocking characteristics	531
7.6.1	General	531
7.6.2	In-band blocking	532
7.6.3	Out-of-band blocking	533
7.6.4	Narrow band blocking	536
7.6A	Blocking characteristics for CA	537
7.6A.1	General	537
7.6A.2	In-band blocking for CA	537
7.6A.2.1	In-band blocking for Intra-band contiguous CA	537
7.6A.2.2	In-band blocking for Intra-band non-contiguous CA	538
7.6A.2.3	In-band blocking for Inter-band CA	538
7.6A.3	Out-of-band blocking for CA	539
7.6A.3.1	Out-of-band blocking for Intra-band contiguous CA	539
7.6A.3.2	Out-of-band blocking for Intra-band non-contiguous CA	540
7.6A.3.3	Out-of-band blocking for Inter-band CA	540
7.6A.4	Narrow band blocking for CA	542
7.6A.4.1	Narrow band blocking for Intra-band contiguous CA	542
7.6A.4.2	Narrow band blocking for Intra-band non-contiguous CA	543
7.6A.4.3	Narrow band blocking for Inter-band CA	543
7.6B	Blocking characteristics for NR-DC	543
7.6C	Blocking characteristics for SUL	543
7.6C.1	General	543
7.6C.2	In-band blocking for SUL	543
7.6C.3	Out-of-band blocking for SUL	543
7.6C.4	Narrow band blocking for SUL	544
7.6D	Blocking characteristics for UL MIMO	544
7.6E	Blocking characteristics for V2X	544
7.6E.1	General	544
7.6E.2	In-band blocking	544
7.6E.2.1	General	544
7.6E.2.2	In-band blocking for V2X con-current operation	545
7.6E.3	Out-of-band blocking	546
7.6E.3.1	General	546
7.6E.3.2	Out-of-band blocking for V2X con-current operation	546
7.6F	Blocking characteristics for shared spectrum channel access	546
7.6F.1	General	546
7.6F.2	In-band blocking	547
7.6F.2.1	General	547
7.6F.2.2	Void	547
7.6F.2A	In-band blocking for shared spectrum CA	547
7.6F.2A.1	Intra-band contiguous shared spectrum channel access CA	547
7.6F.3	Out-of-band blocking	548
7.6F.3.1	General	548
7.6F.3.2	Void	549
7.6F.3A	Out-of-band blocking for shared spectrum CA	549
7.6F.3A.1	Intra-band contiguous shared spectrum channel access CA	549