

ETSI TS 138 141-2 v15.16.0 (2023-01)



iTeh STANDA~~D~~ 5G; NR; D PREVIEW

Base Station (BS) conformance testing
Part 2: Radiated conformance testing

(3GPP TS 38.141-2 version 15.16.0 Release 15)

<https://standards.iteh.ai/catalog/standards/sist/5d079b07-31dd-42ef-a8de-132727dbc868/etsi-ts-138-141-2-v15-16-0-2023-01>



Reference

RTS/TSGR-0438141-2vfg0

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the **GSM** logo are trademarks registered and owned by the **GSM Association**.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	13
1 Scope	15
2 References	15
3 Definitions, symbols and abbreviations	16
3.1 Definitions.....	16
3.2 Symbols.....	20
3.3 Abbreviations	22
4 General radiated test conditions and declarations	23
4.1 Measurement uncertainties and test requirements	23
4.1.1 General.....	23
4.1.2 Acceptable uncertainty of OTA Test System	25
4.1.2.1 General	25
4.1.2.2 Measurement of transmitter	26
4.1.2.3 Measurement of receiver	28
4.1.2.4 Measurement of performance requirement	30
4.1.3 Interpretation of measurement results.....	31
4.2 Radiated requirement reference points	32
4.3 Base station classes	33
4.4 Regional requirements.....	33
4.5 BS configurations	34
4.5.1 Transmit configurations	34
4.5.2 Receive configurations	35
4.5.3 Power supply options.....	36
4.5.4 BS with integrated Iuant BS modem	36
4.6 Manufacturer's declarations.....	36
4.7 Test configurations	44
4.7.1 General.....	44
4.7.2 Test signal configurations	45
4.7.2.1 Test signal used to build Test Configurations	45
4.7.2.2 NRTC1: Contiguous spectrum operation	45
4.7.2.2.1 NRTC1 generation.....	45
4.7.2.2.2 NRTC1 power allocation.....	45
4.7.2.3 NRTC2: Contiguous CA occupied bandwidth	46
4.7.2.3.1 NRTC2 generation.....	46
4.7.2.3.2 NRTC2 power allocation.....	46
4.7.2.4 NRTC3: Non-contiguous spectrum operation	46
4.7.2.4.1 NRTC3 generation.....	47
4.7.2.4.2 NRTC3 power allocation.....	47
4.7.2.5 NRTC4: Multi-band test configuration for full carrier allocation	47
4.7.2.5.1 NRTC4 generation.....	47
4.7.2.5.2 NRTC4 power allocation.....	48
4.7.2.6 NRTC5: Multi-band test configuration with high PSD per carrier	48
4.7.2.6.1 NRTC5 generation.....	48
4.7.2.6.2 NRTC5 power allocation.....	48
4.8 Applicability of requirements	49
4.8.1 Requirement set applicability	49
4.8.2 Applicability of test configurations for <i>single-band RIB</i>	49
4.8.3 Applicability of test configurations for <i>multi-band RIB</i>	50
4.8.4 Additional conformance	51
4.9 RF channels and test models	52
4.9.1 RF channels	52

4.9.2	Test models	53
4.9.2.1	General	53
4.9.2.2	NR FR2 test models	53
4.9.2.2.1	NR FR2 test model 1.1 (NR-FR2-TM1.1)	54
4.9.2.2.2	NR FR2 test model 2 (NR-FR2-TM2)	55
4.9.2.2.3	NR FR2 test model 3.1 (NR-FR2-TM3.1)	55
4.9.2.3	Data content of physical channels and signals for NR-FR2-TM	56
4.9.2.3.1	PDCCH	56
4.9.2.3.2	PDSCH	56
4.10	Requirements for contiguous and non-contiguous spectrum	57
4.11	Requirements for BS capable of multi-band operation	58
4.12	Co-location requirements	58
4.12.1	General	58
4.12.2	Co-location test antenna	59
4.12.2.1	General	59
4.12.2.2	Co-location test antenna characteristics	59
4.12.2.3	Co-location test antenna alignment	59
4.13	Format and interpretation of tests	60
4.14	Reference coordinate system	61
5	Operating bands and channel arrangement	63
6	Radiated transmitter characteristics	64
6.1	General	64
6.2	Radiated transmit power	64
6.2.1	Definition and applicability	64
6.2.2	Minimum requirement	64
6.2.3	Test purpose	65
6.2.4	Method of test	65
6.2.4.1	Initial conditions	65
6.2.4.2	Procedure	65
6.2.5	Test requirement	66
6.3	OTA base station output power	66
6.3.1	Definition and applicability	66
6.3.2	Minimum requirement	66
6.3.3	Test purpose	67
6.3.4	Method of test	67
6.3.4.1	Initial conditions	67
6.3.4.2	Procedure	67
6.3.5	Test requirement	68
6.3.5.1	<i>BS type 1-O</i>	68
6.3.5.2	<i>BS type 2-O</i>	68
6.4	OTA output power dynamics	68
6.4.1	General	68
6.4.2	OTA RE power control dynamic range	68
6.4.2.1	Definition and applicability	68
6.4.2.2	Minimum requirement	68
6.4.2.3	Method of test	68
6.4.3	OTA total power dynamic range	69
6.4.3.1	Definition and applicability	69
6.4.3.2	Minimum requirement	69
6.4.3.3	Test purpose	69
6.4.3.4	Method of test	69
6.4.3.4.1	Initial conditions	69
6.4.3.4.2	Procedure	69
6.4.3.5	Test requirement	70
6.4.3.5.1	<i>BS type 1-O</i>	70
6.4.3.5.2	<i>BS type 2-O</i>	71
6.5	OTA transmit ON/OFF power	71
6.5.1	OTA transmitter OFF power	71
6.5.1.1	Definition and applicability	71
6.5.1.2	Minimum requirement	71

6.5.1.3	Test purpose	71
6.5.1.4	Method of test	71
6.5.1.5	Test requirements	71
6.5.2	OTA transmitter transient period	72
6.5.2.1	Definition and applicability.....	72
6.5.2.2	Minimum requirement	72
6.5.2.3	Test purpose	72
6.5.2.4	Method of test	72
6.5.2.4.1	Initial conditions.....	72
6.5.2.4.2	Procedure.....	73
6.5.2.5	Test requirements	74
6.5.2.5.1	<i>BS type 1-O</i>	74
6.5.2.5.2	<i>BS type 2-O</i>	74
6.6	OTA transmitted signal quality	74
6.6.1	General.....	74
6.6.2	OTA frequency error	74
6.6.2.1	Definition and applicability.....	74
6.6.2.2	Minimum Requirement	74
6.6.2.3	Test purpose	75
6.6.2.4	Method of test	75
6.6.2.4.1	Initial conditions.....	75
6.6.2.5	Test Requirements.....	75
6.6.3	OTA modulation quality	75
6.6.3.1	Definition and applicability.....	75
6.6.3.2	Minimum Requirement	75
6.6.3.3	Test purpose	75
6.6.3.4	Method of test	75
6.6.3.4.1	Initial conditions.....	75
6.6.3.4.2	Procedure.....	76
6.6.3.5	Test requirements	77
6.6.3.5.1	<i>BS type 1-O</i>	77
6.6.3.5.2	<i>BS type 2-O</i>	78
6.6.4	OTA time alignment error	79
6.6.4.1	Definition and applicability.....	79
6.6.4.2	Minimum requirement	79
6.6.4.3	Test purpose	80
6.6.4.4	Method of test	80
6.6.4.4.1	Initial conditions.....	80
6.6.4.4.2	Procedure.....	80
6.6.4.5	Test Requirement	81
6.6.4.5.1	<i>BS type 1-O</i>	81
6.6.4.5.2	<i>BS type 2-O</i>	81
6.7	OTA unwanted emissions	81
6.7.1	General.....	81
6.7.2	OTA occupied bandwidth	82
6.7.2.1	Definition and applicability.....	82
6.7.2.2	Minimum requirement	82
6.7.2.3	Test purpose	82
6.7.2.4	Method of test	82
6.7.2.4.1	Initial conditions.....	82
6.7.2.4.2	Procedure.....	82
6.7.2.5	Test requirement	84
6.7.2.5.1	<i>BS type 1-O</i>	84
6.7.2.5.2	<i>BS type 2-O</i>	84
6.7.3	OTA Adjacent Channel Leakage Power Ratio (ACLR)	84
6.7.3.1	Definition and applicability.....	84
6.7.3.2	Minimum requirement	84
6.7.3.3	Test purpose	84
6.7.3.4	Method of test	84
6.7.3.4.1	Initial conditions.....	84
6.7.3.4.2	Procedure.....	85
6.7.3.5	Test requirements	86

6.7.3.5.1	<i>BS type 1-O</i>	86
6.7.3.5.2	<i>BS type 2-O</i>	88
6.7.4	OTA operating band unwanted emissions	91
6.7.4.1	Definition and applicability.....	91
6.7.4.2	Minimum requirement	91
6.7.4.3	Test purpose	91
6.7.4.4	Method of test	91
6.7.4.4.1	Initial conditions.....	91
6.7.4.4.2	Procedure.....	91
6.7.4.5	Test requirements	92
6.7.4.5.1	<i>BS type 1-O</i>	92
6.7.4.5.2	<i>BS type 2-O</i>	103
6.7.5	OTA transmitter spurious emissions.....	105
6.7.5.1	General	105
6.7.5.2	General OTA transmitter spurious emissions requirements	105
6.7.5.2.1	Definition and applicability	105
6.7.5.2.2	Minimum requirement.....	105
6.7.5.2.3	Test purpose	105
6.7.5.2.4	Method of test.....	106
6.7.5.2.5	Test requirement.....	107
6.7.5.3	Protection of the BS receiver of own or different BS	109
6.7.5.3.1	Definition and applicability	109
6.7.5.3.2	Minimum requirements	109
6.7.5.3.3	Test purpose	109
6.7.5.3.4	Method of test.....	109
6.7.5.3.5	Test requirements	110
6.7.5.4	Additional spurious emissions requirements	111
6.7.5.4.1	Definition and applicability	111
6.7.5.4.2	Minimum Requirement	111
6.7.5.4.3	Test purpose	111
6.7.5.4.4	Method of test.....	111
6.7.5.4.5	Test requirement	113
6.7.5.5	Co-location requirements	119
6.7.5.5.1	Definition and applicability	119
6.7.5.5.2	Minimum requirements	119
6.7.5.5.3	Test purpose	119
6.7.5.5.4	Method of test.....	119
6.7.5.5.5	Test requirements	120
6.8	OTA transmitter intermodulation	124
6.8.1	Definition and applicability	124
6.8.2	Minimum requirement	125
6.8.3	Test purpose	125
6.8.4	Method of test	125
6.8.4.1	Initial conditions	125
6.8.4.2	Procedure	125
6.8.5	Test requirements	127
6.8.5.1	Requirement for BS type 1-O.....	127
7	Radiated receiver characteristics	128
7.1	General	128
7.2	OTA sensitivity	128
7.2.1	Definition and applicability	128
7.2.2	Minimum requirement	129
7.2.3	Test Purpose.....	129
7.2.4	Method of test	129
7.2.4.1	Initial conditions	129
7.2.4.2	Procedure	130
7.2.5	Test requirements	130
7.2.5.1	General	130
7.2.5.2	Test requirements for <i>BS type 1-H</i> and <i>BS type 1-O</i>	130
7.2.5.3	Test requirements for <i>BS type 2-O</i>	131
7.3	OTA reference sensitivity level	131

7.3.1	Definition and applicability	131
7.3.2	Minimum requirement	131
7.3.3	Test Purpose.....	131
7.3.4	Method of test	131
7.3.4.1	Initial conditions	131
7.3.4.2	Procedure	131
7.3.5	Test requirements.....	132
7.3.5.1	General	132
7.3.5.2	Test requirements for <i>BS type 1-O</i>	132
7.3.5.3	Test requirements for <i>BS type 2-O</i>	133
7.4	OTA dynamic range	134
7.4.1	Definition and applicability	134
7.4.2	Minimum requirement	134
7.4.3	Test purpose.....	134
7.4.4	Method of test	134
7.4.4.1	Initial conditions	134
7.4.4.2	Procedure	134
7.4.5	Test requirement	135
7.4.5.1	General	135
7.4.5.2	Test requirements for <i>BS type 1-O</i>	135
7.5	OTA in-band selectivity and blocking.....	144
7.5.1	OTA adjacent channel selectivity	144
7.5.1.1	Definition and applicability.....	144
7.5.1.2	Minimum requirement	144
7.5.1.3	Test purpose	144
7.5.1.4	Method of test	144
7.5.1.4.1	Initial conditions	144
7.5.1.4.2	Procedure	144
7.5.1.5	Test requirement	145
7.5.1.5.1	General	145
7.5.1.5.2	Test requirements for <i>BS type 1-O</i>	145
7.5.1.5.3	Test requirements for <i>BS type 2-O</i>	146
7.5.2	OTA in-band blocking.....	147
7.5.2.1	Definition and applicability.....	147
7.5.2.2	Minimum requirement	147
7.5.2.3	Test purpose	147
7.5.2.4	Method of test	147
7.5.2.4.1	Initial conditions	147
7.5.2.4.2	Procedure	148
7.5.2.5	Test requirement	149
7.5.2.5.1	General	149
7.5.2.5.2	Test requirements for <i>BS type 1-O</i>	149
7.5.2.5.3	Test requirements for <i>BS type 2-O</i>	152
7.6	OTA out-of-band blocking	153
7.6.1	Definition and applicability	153
7.6.2	Minimum requirement	153
7.6.3	Test purpose.....	153
7.6.4	Method of test	153
7.6.4.1	Initial conditions	153
7.6.4.2	Procedure	154
7.6.4.2.1	<i>BS type 1-O</i> procedure for out-of-band blocking.....	154
7.6.4.2.2	<i>BS type 1-O</i> procedure for co-location blocking	154
7.6.4.2.3	<i>BS type 2-O</i> procedure for out-of-band blocking.....	155
7.6.5	Test requirements.....	156
7.6.5.1	Requirement for <i>BS type 1-O</i>	156
7.6.5.1.1	General	156
7.6.5.1.2	Co-location requirement	156
7.6.5.2	Requirement for <i>BS type 2-O</i>	157
7.6.5.2.1	General requirement	157
7.7	OTA receiver spurious emissions.....	157
7.7.1	Definition and applicability	157
7.7.2	Minimum requirement	158

7.7.3	Test purpose.....	158
7.7.4	Method of test	158
7.7.4.1	Initial conditions	158
7.7.4.2	Procedure	159
7.7.5	Test requirement	159
7.7.5.1	Test requirement for <i>BS type 1-O</i>	159
7.7.5.2	Test requirement for <i>BS type 2-O</i>	160
7.8	OTA receiver intermodulation	161
7.8.1	Definition and applicability	161
7.8.2	Minimum requirement	161
7.8.3	Test purpose.....	161
7.8.4	Method of test	161
7.8.4.1	Initial conditions	161
7.8.4.2	Procedure	161
7.8.5	Test requirement	162
7.8.5.1	<i>BS type 1-O</i>	162
7.8.5.2	<i>BS type 2-O</i>	167
7.9	OTA in-channel selectivity.....	167
7.9.1	Definition and applicability	167
7.9.2	Minimum requirement	167
7.9.3	Test purpose.....	168
7.9.4	Method of test	168
7.9.4.1	Initial conditions	168
7.9.4.2	Procedure	168
7.9.5	Test requirement	169
7.9.5.1	<i>BS type 1-O</i>	169
7.9.5.2	<i>BS type 2-O</i>	171
8	Radiated performance requirements.....	173
8.1	General	173
8.1.0	Scope and definitions.....	173
8.1.1	OTA demodulation branches	173
8.1.2	Applicability rule	174
8.1.2.0	General	174
8.1.2.1	Applicability of PUSCH performance requirements.....	174
8.1.2.1.1	Applicability of requirements for different subcarrier spacings	174
8.1.2.1.2	Applicability of requirements for different channel bandwidths	174
8.1.2.1.3	Applicability of requirements for different configurations.....	174
8.1.2.1.4	Applicability of requirements for uplink carrier aggregation	174
8.1.2.1.5	Applicability of requirements for TDD with different UL-DL patterns	174
8.1.2.2	Applicability of PUCCH performance requirements	175
8.1.2.2.1	Applicability of requirements for different formats.....	175
8.1.2.2.2	Applicability of requirements for different subcarrier spacings	175
8.1.2.2.3	Applicability of requirements for different channel bandwidths	175
8.1.2.2.4	Applicability of requirements for different configurations.....	175
8.1.2.2.5	Applicability of requirements for multi-slot PUCCH.....	175
8.1.2.3	Applicability of PRACH performance requirements	175
8.1.2.3.1	Applicability of requirements for different formats.....	175
8.1.2.3.2	Applicability of requirements for different subcarrier spacings	175
8.1.2.3.3	Applicability of requirements for different channel bandwidths	175
8.2	OTA performance requirements for PUSCH	176
8.2.1	Performance requirements for PUSCH with transform precoding disabled	176
8.2.1.1	Definition and applicability.....	176
8.2.1.2	Minimum Requirement	176
8.2.1.3	Test purpose	176
8.2.1.4	Method of test	176
8.2.1.4.1	Initial conditions.....	176
8.2.1.4.2	Procedure.....	176
8.2.1.5	Test Requirement	178
8.2.1.5.1	Test requirement for <i>BS type 1-O</i>	178
8.2.1.5.2	Test requirement for <i>BS type 2-O</i>	181
8.2.2	Performance requirements for PUSCH with transform precoding enabled	184

8.2.2.1	Definition and applicability.....	184
8.2.2.2	Minimum Requirement	184
8.2.2.3	Test Purpose	184
8.2.2.4	Method of test	184
8.2.2.4.1	Initial Conditions	184
8.2.2.4.2	Procedure.....	185
8.2.2.5	Test Requirement	186
8.2.2.5.1	Test requirement for <i>BS type 1-O</i>	186
8.2.2.5.2	Test requirement for <i>BS type 2-O</i>	187
8.2.3	Performance requirements for UCI multiplexed on PUSCH	187
8.2.3.1	Definition and applicability.....	187
8.2.3.2	Minimum Requirement	188
8.2.3.3	Test purpose	188
8.2.3.4	Method of test	188
8.2.3.4.1	Initial conditions.....	188
8.2.3.4.2	Procedure.....	188
8.2.3.5	Test Requirement	190
8.2.3.5.1	Test requirement for <i>BS type 1-O</i>	190
8.2.3.5.2	Test requirement for <i>BS type 2-O</i>	191
8.3	OTA performance requirements for PUCCH	192
8.3.1	Performance requirements for PUCCH format 0.....	192
8.3.1.1	Definition and applicability.....	192
8.3.1.2	Minimum Requirement	192
8.3.1.3	Test purpose	192
8.3.1.4	Method of test	193
8.3.1.4.1	Initial conditions.....	193
8.3.1.4.2	Procedure.....	193
8.3.1.5	Test Requirement	194
8.3.1.5.1	Test requirement for <i>BS type 1-O</i>	194
8.3.1.5.2	Test requirement for <i>BS type 2-O</i>	195
8.3.2	Performance requirements for PUCCH format 1.....	195
8.3.2.1	NACK to ACK detection	195
8.3.2.1.1	Definition and applicability.....	195
8.3.2.1.2	Minimum Requirement	195
8.3.2.1.3	Test purpose	196
8.3.2.1.4	Method of test.....	196
8.3.2.1.5	Test Requirement.....	197
8.3.2.2	ACK missed detection.....	198
8.3.2.2.1	Definition and applicability.....	198
8.3.2.2.2	Minimum Requirement	198
8.3.2.2.3	Test purpose	198
8.3.2.2.4	Method of test.....	198
8.3.2.2.5	Test Requirement.....	200
8.3.3	Performance requirements for PUCCH format 2.....	201
8.3.3.1	ACK missed detection performance requirements.....	201
8.3.3.1.1	Definition and applicability.....	201
8.3.3.1.2	Minimum Requirement	201
8.3.3.1.3	Test Purpose	201
8.3.3.1.4	Method of test.....	202
8.3.3.1.5	Test requirement.....	203
8.3.3.2	UCI BLER performance requirements.....	204
8.3.3.2.1	Definition and applicability.....	204
8.3.3.2.2	Minimum Requirement	204
8.3.3.2.3	Test Purpose	204
8.3.3.2.4	Method of test.....	204
8.3.3.2.5	Test requirement.....	206
8.3.4	Performance requirements for PUCCH format 3	207
8.3.4.1	Definition and applicability.....	207
8.3.4.2	Minimum requirement	207
8.3.4.3	Test purpose	207
8.3.4.4	Method of test	207
8.3.4.4.1	Initial conditions.....	207

8.3.4.4.2	Procedure	208
8.3.4.5	Test requirement	209
8.3.4.5.1	Test requirement for BS type 1-O	209
8.3.4.5.2	Test requirement for BS type 2-O	210
8.3.5	Performance requirements for PUCCH format 4	210
8.3.5.1	Definition and applicability	210
8.3.5.2	Minimum requirement	211
8.3.5.3	Test purpose	211
8.3.5.4	Method of test	211
8.3.5.4.1	Initial conditions	211
8.3.5.4.2	Procedure	211
8.3.5.5	Test requirement	212
8.3.5.5.1	Test requirement for BS type 1-O	212
8.3.5.5.2	Test requirement for BS type 2-O	213
8.3.6	Performance requirements for multi-slot PUCCH format	213
8.3.6.1	Performance requirements for multi-slot PUCCH format 1	213
8.3.6.1.1	NACK to ACK detection	213
8.3.6.1.2	ACK missed detection	215
8.4	OTA performance requirements for PRACH	217
8.4.1	PRACH false alarm probability and missed detection	217
8.4.1.1	Definition and applicability	217
8.4.1.2	Minimum requirement	218
8.4.1.3	Test purpose	218
8.4.1.4	Method of test	218
8.4.1.4.1	Initial conditions	218
8.4.1.4.2	Procedure	218
8.4.1.5	Test requirement	220
8.4.1.5.1	Test requirement for BS type 1-O	220
8.4.1.5.2	Test requirement for BS type 2-O	221

Annex A (normative): Reference measurement channels222

A.1	Fixed Reference Channels for OTA sensitivity, OTA reference sensitivity level, OTA ACS, OTA in-band blocking, OTA out-of-band blocking, OTA receiver intermodulation and OTA in-channel selectivity (QPSK, R=1/3)	222
A.2	Fixed Reference Channels for OTA dynamic range (16QAM, R=2/3)	223
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	223
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	228
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	232
A.6	PRACH Test preambles	234

Annex B (normative): Environmental requirements for the BS equipment235

B.1	General	235
B.2	Normal test environment	235
B.3	Extreme test environment	235
B.3.1	Extreme temperature	235
B.4	Vibration	236
B.5	Power supply	236
B.6	Measurement of test environments	236
B.7	OTA extreme test methods	237
B.7.1	Direct far field method	237
B.7.2	Relative method	237

Annex C (informative): Test tolerances and derivation of test requirements.....239

C.1	Measurement of transmitter.....	240
C.2	Measurement of receiver.....	244
C.3	Measurement of performance requirements	246
Annex D (normative):	Calibration.....	248
Annex E (informative):	OTA measurement system set-up.....	249
E.1	Transmitter	249
E.1.1	Radiated transmit power, OTA output power dynamics, OTA transmitted signal quality, OTA occupied bandwidth, and OTA transmit ON/OFF power (<i>BS type 2-O</i>)	249
E.1.2	OTA base station output power, OTA ACLR, OTA operating band unwanted emissions	250
E.1.3	OTA spurious emissions	250
E.1.4	OTA co-location emissions, OTA transmit ON/OFF power (<i>BS type 1-O</i>)	251
E.1.5	OTA transmitter intermodulation	252
E.2	Receiver.....	253
E.2.1	OTA sensitivity and OTA reference sensitivity level.....	253
E.2.2	OTA dynamic range	253
E.2.3	OTA adjacent channel selectivity, general OTA blocking, and OTA narrowband blocking	254
E.2.4	OTA blocking.....	255
E.2.4.1	General OTA out-of-band blocking	255
E.2.4.2	OTA co-location blocking	255
E.2.5	OTA receiver spurious emissions.....	256
E.2.6	OTA receiver intermodulation	256
E.2.7	OTA in-channel selectivity.....	257
E.3	Performance requirements.....	257
Annex F (normative):	Void	259
Annex G (informative):	Transmitter spatial emissions declaration.....	260
G.1	General	260
G.2	Declarations.....	260
Annex H (normative):	Characteristics of the interfering signals.....	262
Annex I (normative):	TRP measurement procedures	263
I.1	General	263
I.2	Spherical equal angle grid	263
I.2.1	General	263
I.2.2	Reference angular step criteria	263
I.3	Spherical equal area grid	265
I.4	Spherical Fibonacci grid.....	266
I.5	Orthogonal cut grid	266
I.5.1	General	266
I.5.2	Operating band unwanted emissions	267
I.5.3	Spurious unwanted emissions.....	267
I.6	Wave vector space grid	268
I.7	Void.....	268
I.8	Void.....	268
I.9	Full sphere with sparse sampling	268
I.10	Beam-based directions	269
I.11	Peak method	269

I.12	Equal sector with peak average	269
I.13	Pre-scan	270
Annex J (normative):	Propagation conditions.....	271
J.1	Static propagation condition.....	271
J.2	Multi-path fading propagation conditions	271
J.2.1	Delay profiles	271
J.2.1.1	Delay profiles for FR1	272
J.2.1.2	Delay profiles for FR2	273
J.2.2	Combinations of channel model parameters	274
J.2.3	MIMO channel correlation matrices.....	274
J.2.3.1	MIMO correlation matrices using Uniform Linear Array	274
J.2.3.1.1	Definition of MIMO correlation matrices	274
J.2.3.1.2	MIMO correlation matrices at high, medium and low level	276
J.2.3.2	Multi-antenna channel models using cross polarized antennas.....	278
J.2.3.2.1	Definition of MIMO correlation matrices using cross polarized antennas.....	278
J.2.3.2.2	Spatial correlation matrices at UE and gNB sides.....	279
J.2.3.2.2.1	Spatial correlation matrices at UE side	279
J.2.3.2.2.2	Spatial correlation matrices at gNB side	279
J.2.3.2.3	MIMO correlation matrices using cross polarized antennas	279
Annex K (informative):	Measuring noise close to noise-floor.....	281
Annex L (normative):	In-channel TX tests.....	282
L.1	General	282
L.2	Basic principles	282
L.2.1	Output signal of the TX under test	282
L.2.2	Ideal signal	282
L.2.3	Measurement results.....	283
L.2.4	Measurement points	283
L.3	Pre-FFT minimization process	284
L.4	Timing of the FFT window	285
L.5	Resource element TX power	286
L.6	Post-FFT equalisation.....	286
L.7	EVM.....	288
L.7.0	General.....	288
L.7.1	Averaged EVM (FDD)	288
L.7.2	Averaged EVM (TDD).....	289
Annex M (informative):	Change history	290
History	301	

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

shall indicates a mandatory requirement to do something

shall not indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

should indicates a recommendation to do something

should not indicates a recommendation not to do something

may indicates permission to do something

need not indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

can indicates that something is possible

cannot indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

will indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

will not indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

might indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ETSI TS 138 141-2 V15.16.0 \(2023-01\)](#)

<https://standards.iteh.ai/catalog/standards/sist/5d079b07-3fdd-42ef-a8de-132727dbc868/etsi-ts-138-141-2-v15-16-0-2023-01>