ETSI EN 301 489-52 V1.3.1 (2024-11)



ElectroMagnetic Compatibility (EMC)
standard for radio equipment and services;
Part 52: Specific conditions for Cellular Communication
User Equipment (UE) radio and ancillary equipment;
Harmonised Standard for ElectroMagnetic Compatibility

2131 EN 301 409-32 V1.3.1 (2024-11

Reference

REN/ERM-EMC-420

Keywords

EMC, GSM, harmonised standard, LTE, MSR, NR, OFDMA, radio, WCDMA, WMAN

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the ETSI Search & Browse Standards application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on ETSI deliver repository.

Users should be aware that the present document may be revised or have its status changed, this information is available in the Milestones listing.

If you find errors in the present document, please send your comments to the relevant service listed under Committee Support Staff.

If you find a security vulnerability in the present document, please report it through our Coordinated Vulnerability Disclosure (CVD) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied. In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024. All rights reserved.

Contents

Intellectual Property Rights		5
Forev	5	
Mod	6	
1 Scope		7
2	References	7
2.1	Normative references	
2.2	Informative references.	9
3	Definition of terms, symbols and abbreviations	10
3.1	Terms	
3.2	Symbols	
3.3	Abbreviations	
4	Test conditions	
4.1	General	
4.2	Arrangements for test signals	
4.2.1	General	
4.2.2	Arrangements for test signals for GSM	
4.2.3	Arrangements for test signals for UTRA and E-UTRA	
4.2.4	Arrangements for test signals for NR	
4.2.4.	1 General for NR	14
4.2.4.	2 NR FR1 SA	14
4.2.4.	3 NR FR1 NSA	15
4.2.4.	4 NR FR2 SA MITTING STORM STOR	15
4.2.4.	5 NR FR2 NSA	16
4.3	Exclusion bands.	16
4.3.1	General Ducument Freyew	16
4.3.2	GSM exclusion band	
4.3.2.		
4.3.2.		
4.3.3	UTRA and E-UTRA exclusion band	
4.5.5		
4.3.3.		
4.3.3.		
4.3.4	NR exclusion band	
4.3.4.		
4.3.4.		
4.3.4.		17
4.3.4.		
4.4	Narrow band responses of receivers and receivers of duplex transceivers	17
4.4.1	GSM Narrow band responses on receivers	
4.4.2	UTRA and E-UTRA Narrow band responses on receivers	18
4.4.2.	1 UTRA	18
4.4.2.	2 E-UTRA	18
4.4.3	NR Narrow band responses on receivers	19
5	Ancillary equipment	19
6	Performance criteria	19
6.1	Performance criteria for Continuous phenomena	
6.1.1	GSM and voice call	
6.1.1.		
6.1.1.		
6.1.2	UTRA	
6.1.3	E-UTRA, E-UTRA with LAA, inband or guard band NB-IoT, Standalone NB-IoT	
6.1.4	NR	
6.2	Performance criteria for Transient phenomena	20

7	Requirements		20
7.1	General		20
7.2			
7.2.1			
7.2.2	-	ns	
7.3			
7.3.1			
7.3.2	Special condition	ns	22
Anno	ex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	23
Anno	ex B (normative):	Performance assessment voice call, Audio breakthrough	25
B.1	Calibration of audio l	evels	25
B.2	Measurement of audi	o levels	26
Anna	ex C (normative):	Performance assessment of data transfer call, Error Ratios	27
АШ	ex C (normative):	1 01101 maniet appending of the transfer the Life 1 through mining	••••••
C.1	` '	ansfer	
	Calibration of data tra		27
C.1	Calibration of data tra	ansfer	27 27
C.1 C.1.1	Calibration of data tra UTRA E-UTRA and NR	ansfer	27 27
C.1 C.1.1 C.1.2	Calibration of data tra UTRA E-UTRA and NR Assessment of data tr	ansfer	27 27 27
C.1 C.1.1 C.1.2 C.2	Calibration of data tra UTRA E-UTRA and NR Assessment of data tr UTRA, Derivation of	ansferansfer	27 27 27 27
C.1 C.1.1 C.1.2 C.2 C.2.1	Calibration of data tra UTRA E-UTRA and NR Assessment of data tr UTRA, Derivation of E-UTRA and NR, E	ansfer	27 27 27 27 27
C.1 C.1.1 C.1.2 C.2 C.2.1 C.2.2	Calibration of data tra UTRA E-UTRA and NR Assessment of data tr UTRA, Derivation of E-UTRA and NR, E EUT without data app	ansfer	2727272727272727
C.1 C.1.1 C.1.2 C.2 C.2.1 C.2.2 C.3 C.4	Calibration of data tra UTRA E-UTRA and NR Assessment of data tr UTRA, Derivation of E-UTRA and NR, E EUT without data applic	ansfer	27272727272727
C.1 C.1.1 C.1.2 C.2 C.2.1 C.2.2 C.3 C.4	Calibration of data tra UTRA E-UTRA and NR Assessment of data tr UTRA, Derivation of E-UTRA and NR, E EUT without data application of the company	ansfer	272727272727272728

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI IPR online database.

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP**TM, **LTE**TM and **5G logo** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M**TM logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**[®] and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.4] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 52 of a multi-part deliverable. Full details of the entire series can be found in part 1 [1].

National transposition dates	
Date of adoption of this EN:	6 November 2024
Date of latest announcement of this EN (doa):	28 February 2025
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 2025
Date of withdrawal of any conflicting National Standard (dow):	31 August 2026

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

iTeh Standards (https://standards.iteh.ai) Document Preview

<u>ETSI EN 301 489-52 V1.3.1 (2024-11)</u>

https://standards.iteh.ai/catalog/standards/etsi/16da6ae5-4908-42a7-9b03-d8fd916a3fdc/etsi-en-301-489-52-v1-3-1-2024

1 Scope

The present document specifies the applicable test conditions, performance assessment, and performance criteria for Cellular Communication User Equipment (UE), including Customer Premise Equipment (CPE), Set Top Box (STB) containing cellular communication technologies, and the associated ancillary equipment in respect of ElectroMagnetic Compatibility (EMC) for equipment utilizing the technologies in table 1.

Table 1: Technologies User Equipment (UE) radio and ancillary equipment Cellular Communication

Cellular Mobile Communication Technology	Technology Generation	Standard Set	ETSI Deliverable
Global System for Mobile communications (GSM)	2G/3G	IMT-2000 SC single carrier	ETSI EN 301 511 [i.9]
CDMA Multi-Carrier (cdma2000)	2G/3G	IS-95/CDMA2000 - IMT-MC multi-carrier	ETSI EN 301 908-4 [i.10]
CDMA Direct Spread (UTRA FDD)	3G	IMT-2000 Direct Spread	ETSI EN 301 908-2 [i.11]
Evolved Universal Terrestrial Radio Access (E-UTRA)	4G	IMT-advanced	ETSI EN 301 908-13 [i.12]
New Radio (NR)	5G	IMT-2020	ETSI TS 138 521-1 [15] ETSI TS 138 521-2 [19] ETSI TS 138 521-3 [16]

Technical specifications related to the antenna port of radio equipment, radiated emissions from the enclosure port of radio equipment, and combinations of radio and associated ancillary equipment are not included in the present document. Such technical specifications are normally found in the relevant product standards for the effective use of the radio spectrum.

- NOTE 1: The relationship between the present document and the essential requirements of article 3.1(b) of Directive 2014/53/EU [i.2] is given in annex A.
- NOTE 2: The present document does not cover the radio base stations as specified in ETSI EN 301 489-50 [i.13].

Technical specifications related to conducted emission EMC requirements below 9 kHz on the AC mains port of radio equipment are not included in the present document.

https://standa NOTE 3: Such technical specifications are normally found in the relevant product family standards for AC mains 1-3-1-2024-powered equipment (e.g. EN 61000-3-2 [i.14] and EN 61000-3-3 [i.15]).

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at https://docbox.etsi.org/Reference/.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

[1] <u>ETSI EN 301 489-1 (V2.2.3) (11-2019)</u>: "ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements; Harmonised Standard for ElectroMagnetic Compatibility".



2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1]	ETSI TR 121 905 (V17.1.0) (05-2022): "Digital cellular telecommunications system (Phase 2+)
	(GSM); Universal Mobile Telecommunications System (UMTS); LTE; 5G; Vocabulary for 3GPP
	Specifications (3GPP TR 21.905 version 17.1.0 Release 17)".

- [i.2] <u>Directive 2014/53/EU</u> of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] ETSI TR 125 990 (V3.0.0): "Universal Mobile Telecommunications System (UMTS); Vocabulary (3G TR 25.990 version 3.0.0 Release 1999)".
- [i.4] Commission Implementing Decision C (2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.5] ETSI GTS 05.08 (V3.8.0) (01-1995): "European digital cellular telecommunications system (Phase 1); Radio Subsystem Link Control (GSM 05.08)".
- NOTE: The technical content of ETSI I-ETS 300 034-1 has been transferred into ETSI GTS 05.08 (V3.8.0).
- [i.6] ETSI GTS 05.08-DCS (V3.0.0) (01-1995): "European digital cellular telecommunications system (Phase 1); Radio Subsystem Link Control; (GSM 05.08 DCS-1800)".
- NOTE: The technical content of ETSI I-ETS 300 034-2 has been transferred into ETSI GTS 05.08-DCS (V3.0.0).
- [i.7] ETSI ETS 300 578 (Edition 13) (03-1999): "Digital cellular telecommunications system (Phase 2) (GSM); Radio subsystem link control (GSM 05.08 version 4.22.1)".
- [i.8] Void.
- [i.9] ETSI EN 301 511 (V12.5.1) (03-2017): "Global System for Mobile communications (GSM); Mobile Stations (MS) equipment; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU".
- [i.10] ETSI EN 301 908-4 (V6.2.1) (06-2013): "IMT cellular networks; Harmonized EN covering the essential requirements of article 3.2 of the R&TTE Directive; Part 4: CDMA Multi-Carrier (cdma2000) User Equipment (UE)".
- [i.11] <u>ETSI EN 301 908-2 (V13.1.1) (06-2020)</u>: "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 2: CDMA Direct Spread (UTRA FDD) User Equipment (UE)".
- [i.12] <u>ETSI EN 301 908-13 (V13.2.1) (02-2022)</u>: "IMT cellular networks; Harmonised Standard for access to radio spectrum; Part 13: Evolved Universal Terrestrial Radio Access (E-UTRA) User Equipment (UE)".
- [i.13] ETSI EN 301 489-50 (V2.3.1) (03-2021): "ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 50: Specific conditions for Cellular Communication Base Station (BS), repeater and ancillary equipment; Harmonised Standard for ElectroMagnetic Compatibility".

[i.14]	EN 61000-3-2 (2019) + A1(2021): "ELECTROMAGNETIC COMPATIBILITY (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current \leq 16 A per phase)".
[i.15]	EN 61000-3-3 (2013) + A2 (2021): "Electromagnetic compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current \leq 16 A per phase and not subject to conditional connection".
[i.16]	ETSI TS 100 910 (V8.20.0) (11-2005): "Digital cellular telecommunications system (Phase 2+);

Radio Transmission and Reception (3GPP TS 05.05 version 8.20.0 Release 1999)".

[i.17] <u>Recommendation ITU-T P.76 (11/1988)</u>: "Determination of loudness ratings; fundamental principles".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 301 489-1 [1] and the following apply:

ancillary equipment: electrical or electronic equipment that is intended to be used with a receiver or transmitter

NOTE 1: It is considered as an ancillary equipment if:

- the equipment is intended for use with a receiver or transmitter to provide additional operational and/or control features to the radio equipment (e.g. to extend control to another position or location);
- the ancillary equipment cannot be used without being connected to radio equipment to provide user functions independently of a receiver or transmitter; and
- the receiver or transmitter, to which it is connected, is capable of providing some intended operation such as transmitting and/or receiving without the ancillary equipment (i.e. it is not a sub-unit of the main equipment essential to the main equipment basic functions).

NOTE 2: An example of ancillary equipment would be a docking station for radio equipment whose interface is dedicated to a particular product or range of products.

bearer: information transmission path of defined characteristics for transfer of user data or predefined test data

camped on a cell: UE is in idle mode and has completed the cell selection/reselection process and has chosen a cell

NOTE 1: The UE monitors system information and (in most cases) paging information.

NOTE 2: The services may be limited, and the PLMN may not be aware of the existence of the UE within the chosen cell.

channel bandwidth: RF bandwidth supporting a single E-UTRA RF carrier with the transmission bandwidth configured in the uplink or downlink of a cell

NOTE: The channel bandwidth is measured in MHz and is used as a reference for transmitter and receiver RF requirements.

critical stored data: data that is essential for an EUT to perform a primary function in accordance with that EUT's specification

NOTE: This may include data previously stored by the user.

data application ancillary: ancillary which provides, sends and/or receives data access to UMTS services via UE

end-user data: manufacturer-defined data patterns for data transfer testing

NOTE: Represents EUT's typical user application data pattern (e.g. photo, video, text file, message) in its characteristics.

fixed equipment: equipment intended for use in a fixed location and fitted with one or more antennas

NOTE: The equipment may be fitted with either antenna socket(s) or, integral antenna(s) or both.

idle mode:

- For UTRA/EUTRA equipment: state of User Equipment (UE) when switched on but with no Radio Resource Control (RRC) connection.
- For GSM: mode of operation of a receiver or a transceiver, where the Equipment Under Test (EUT) is powered, available for service and available to respond to a request to set up a call.
- For NR equipment: state of User Equipment (UE) when switched on but with no Radio Resource Control (RRC) connection.

International Mobile Telecommunications 2000 (IMT-2000): third generation mobile systems which provide access, by means of one or more radio links, to a wide range of telecommunications services supported by the fixed telecommunication networks (e.g. PSTN, ISDN or IP) and to other services which are specific to mobile users

License Assisted Access (LAA): LTE based base station operating in unlicensed frequency spectrum

maximum average power: average transmitter output power obtained over any specified time interval, including periods with no transmission, when the transmit time slots are at the maximum power setting

maximum throughput: maximum achievable throughput for a reference measurement channel

NB-IoT guard band operation: operation of NB-IoT guard band utilizing the unused resource block(s) within an E-UTRA carrier's guard-band

NB-IoT In-band operation: operation of NB-IoT in-band utilizing the resource block(s) within a normal E-UTRA carrier

NB-IoT standalone operation: operation of NB-IoT standalone utilizing its own spectrum, for example the spectrum currently being used by GERAN systems as a replacement of one or more GSM carriers, as well as scattered spectrum for potential IoT deployment

necessary bandwidth: for a given class of emission, width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions

portable equipment: radio equipment intended for portable use and powered by integral batteries or battery

NOTE: Devices will typically be handheld.

RXQUAL: measure of the received signal quality, which is generated by the mobile or portable equipment, for use as a criterion in the Radio Frequency (RF) power control and handover processes

NOTE: For more information, see:

- ETSI GTS 05.08 [i.5], clause 8.2 for Phase 1 GSM 900 equipment;
- ETSI GTS 05.08-DCS [i.6], clause 8.2 for Phase 1 GSM 1800 equipment;
- ETSI ETS 300 578 [i.7], clause 8.2 for Phase 2 GSM 900 or Phase 2 GSM 1800 equipment;
- ETSI TS 100 910 [i.16], clause 8.2 for Phase 2+ GSM 900 or Phase 2+ GSM 1800 equipment.

throughput: number of payload bits successfully received per second for a reference measurement channel in a specified reference condition

traffic mode: state of User Equipment (UE) when switched on and with Radio Resource Control (RRC) connection established