

ISO/TC 45/SC 1

Secretariat: DSM

Voting begins
on: 2015-07-08

Voting terminates
on: 2015-09-08

Rubber hoses and hose assemblies — Rubber-covered spiral-wire- reinforced hydraulic types for oil-based or water-based fluids — Specification

*Tuyaux et flexibles en caoutchouc — Types hydrauliques avec
armature hélicoïdale de fils métalliques pour fluides à base d'huile ou
à base d'eau — Spécifications*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 3862

<https://standards.iteh.ai/catalog/standards/sist/4ed827fa-f288-4ba3-9e69-a45f31d5244d/iso-fdis-3862>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number
ISO/FDIS 3862:2015(E)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/FDIS 3862](https://standards.iteh.ai/catalog/standards/sist/4ed827fa-f288-4ba3-9e69-a45f31d5244d/iso-fdis-3862)

<https://standards.iteh.ai/catalog/standards/sist/4ed827fa-f288-4ba3-9e69-a45f31d5244d/iso-fdis-3862>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Classification	2
5 Materials and construction	2
5.1 Hoses	2
5.2 Hose assemblies	2
6 Dimensions	2
6.1 Hose diameters and hose concentricity	2
6.2 Length	4
7 Performance requirements	4
7.1 General	4
7.2 Hydrostatic requirements	4
7.3 Minimum bend radius	5
7.4 Resistance to impulse	6
7.4.1 Resistance to impulse with oil-based fluids	6
7.4.2 Resistance to impulse with water-based fluids	6
7.4.3 Optional impulse test	7
7.5 Leakage of hose assemblies	7
7.6 Cold flexibility	7
7.7 Adhesion between components	7
7.8 Fluid resistance	7
7.8.1 General	7
7.8.2 Oil resistance	7
7.8.3 Water resistance	8
7.9 Ozone resistance	8
7.10 Visual examination	8
8 Marking	8
8.1 Hoses	8
8.2 Hose assemblies	8
Annex A (normative) Type and routine testing of production hoses	10
Annex B (informative) Production acceptance testing	11
Annex C (informative) Recommendations for lengths of supplied hoses and tolerances on lengths of hose assemblies	12

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 1, *Rubber and plastics hoses and hose assemblies*.

This fourth edition cancels and replaces the third edition (ISO 3862:2009), of which it constitutes a minor revision. The following changes have been made:

- ISO 4672:1997 has been updated to ISO 10619-2:2011 in [Clause 2](#) and in [7.6](#);
- a requirement to provide the maximum working pressure in bar has been added in [8.1](#) and [8.2](#).

Rubber hoses and hose assemblies — Rubber-covered spiral-wire-reinforced hydraulic types for oil-based or water-based fluids — Specification

1 Scope

This International Standard specifies requirements for five types of spiral-wire-reinforced hydraulic hose and hose assembly of nominal size from 6,3 to 51. They are suitable for use with water-based hydraulic fluids HFC, HFAE, HFAS and HFB as defined in ISO 6743-4 at temperatures ranging from $-40\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$ and oil-based hydraulic fluids HH, HL, HM, HR and HV as defined in ISO 6743-4 at temperatures ranging from $-40\text{ }^{\circ}\text{C}$ to $+100\text{ }^{\circ}\text{C}$ for types 4SP and 4SH and $-40\text{ }^{\circ}\text{C}$ to $+120\text{ }^{\circ}\text{C}$ for types R12, R13 and R15.

NOTE 1 This temperature rating is related to the water-based hydraulic fluids defined in ISO 6743-4.

This International Standard does not include requirements for end fittings. It is limited to requirements for hoses and hose assemblies.

NOTE 2 It is the responsibility of the user, in consultation with the hose manufacturer, to establish the compatibility of the hose with the fluid to be used.

iTeh STANDARD PREVIEW

2 Normative references

(standards.iteh.ai)

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1307, *Rubber and plastics hoses — Hose sizes, minimum and maximum inside diameters, and tolerances on cut-to-length hoses*

ISO 1402, *Rubber and plastics hoses and hose assemblies — Hydrostatic testing*

ISO 1817, *Rubber, vulcanized or thermoplastic — Determination of the effect of liquids*

ISO 4671, *Rubber and plastics hoses and hose assemblies — Methods of measurement of the dimensions of hoses and the lengths of hose assemblies*

ISO 6605, *Hydraulic fluid power — Hoses and hose assemblies — Test methods*

ISO 6743-4, *Lubricants, industrial oils and related products (class L) — Classification — Part 4: Family H (Hydraulic systems)*

ISO 6803, *Rubber or plastics hoses and hose assemblies — Hydraulic-pressure impulse test without flexing*

ISO 7326:2006, *Rubber and plastics hoses — Assessment of ozone resistance under static conditions*

ISO 8033:2006, *Rubber and plastics hoses — Determination of adhesion between components*

ISO 8330, *Rubber and plastics hoses and hose assemblies — Vocabulary*

ISO 10619-2:2011, *Rubber and plastics hoses and tubing — Measurement of flexibility and stiffness — Part 2: Bending tests at sub-ambient temperatures*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8330 apply.

4 Classification

Five types of hose are specified, distinguished by their construction, working pressure and oil resistance:

- Type 4SP: medium-pressure hoses with four plies of steel wire spiral.
- Type 4SH: high-pressure hoses with four plies of steel wire spiral.
- Type R12: heavy-duty high-temperature hoses with a medium-pressure rating having four plies of steel wire spiral.
- Type R13: heavy-duty high-temperature hoses with a high-pressure rating having a multiple-steel-wire spiral.
- Type R15: heavy-duty high-temperature hoses with an extra-high-pressure rating having a multiple-steel-wire spiral.

5 Materials and construction

5.1 Hoses

Hoses shall consist of a rubber lining resistant to oil- or water-based hydraulic fluids, spiral plies of steel wire wrapped in alternating directions, and an oil- and weather-resistant rubber cover. Each spiral wire ply shall be separated by an insulating layer.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

5.2 Hose assemblies

Hose assemblies shall be manufactured using hoses conforming to the requirements of this International Standard.

[ISO/FDIS 3862](https://standards.iteh.ai/catalog/standards/sist/4ed827fa-f288-4ba3-9e69-445f3145244d/iso-fdis-3862)

Hose assemblies shall be manufactured only with those hose fittings whose correct functioning has been verified in accordance with [7.2](#), [7.4](#), [7.5](#) and [7.6](#) of this International Standard. The manufacturer's instructions shall be followed for the preparation and fabrication of hose assemblies.

6 Dimensions

6.1 Hose diameters and hose concentricity

When measured in accordance with ISO 4671, the inside diameter of hoses shall conform to the values given in [Table 1](#).

When measured in accordance with ISO 4671, the diameter over reinforcement and outside diameter of hoses shall conform to the values given in [Table 2](#).

When measured in accordance with ISO 4671, the concentricity of hoses shall conform to the values given in [Table 3](#).

Table 1 — Inside diameters of hoses

Nominal size	Inside diameter									
	mm									
	Type 4SP		Type 4SH		Type R12		Type R13		Type R15	
	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.
6,3	6,2	7,0	—	—	—	—	—	—	—	—
10	9,3	10,1	—	—	9,3	10,1	—	—	9,3	10,1
12,5	12,3	13,5	—	—	12,3	13,5	—	—	12,3	13,5
16	15,5	16,7	—	—	15,5	16,7	—	—	—	—
19	18,6	19,8	18,6	19,8	18,6	19,8	18,6	19,8	18,6	19,8
25	25,0	26,4	25,0	26,4	25,0	26,4	25,0	26,4	25,0	26,4
31,5	31,4	33,0	31,4	33,0	31,4	33,0	31,4	33,0	31,4	33,0
38	37,7	39,3	37,7	39,3	37,7	39,3	37,7	39,3	37,7	39,3
51	50,4	52,0	50,4	52,0	50,4	52,0	50,4	52,0	—	—

Table 2 — Diameter over reinforcement and outside diameter

Nominal size ^a	Type 4SP				Type 4SH				Type R12				Type R13				Type R15			
	Diameter over outside reinforcement		Outside diameter of hose		Diameter over outside reinforcement		Outside diameter of hose		Diameter over outside reinforcement		Outside diameter of hose		Diameter over outside reinforcement		Outside diameter of hose		Diameter over outside reinforcement		Outside diameter of hose	
	mm		mm		mm		mm		mm		mm		mm		mm		mm		mm	
	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.	min.	max.
6,3	14,1	15,3	17,1	18,7	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
10	16,9	18,1	20,6	22,2	—	—	—	—	16,6	17,8	19,5	21,0	—	—	—	—	—	20,3	—	23,3
12,5	19,4	21,0	23,8	25,4	—	—	—	—	19,9	21,5	23,0	24,6	—	—	—	—	—	24,0	—	26,8
16	23,0	24,6	27,4	29,0	—	—	—	—	23,8	25,4	26,6	28,2	—	—	—	—	—	—	—	—
19	27,4	29,0	31,4	33,0	27,6	29,2	31,4	33,0	26,9	28,7	29,9	31,7	28,2	29,8	31,0	33,2	—	32,9	—	36,1
25	34,5	36,1	38,5	40,9	34,4	36,0	37,5	39,9	34,1	36,0	36,8	39,4	34,9	36,4	37,6	39,8	—	38,9	—	42,9
31,5	45,0	47,0	49,2	52,4	40,9	42,9	43,9	47,1	42,7	45,1	45,4	48,6	45,6	48,0	48,3	51,3	—	48,4	—	51,5
38	51,4	53,4	55,6	58,8	47,8	49,8	51,9	55,1	49,2	51,6	51,9	55,0	53,1	55,5	55,8	58,8	—	56,3	—	59,6
51	64,3	66,3	68,2	71,4	62,2	64,2	66,5	69,7	62,5	64,8	65,1	68,3	66,9	69,3	69,5	72,7	—	—	—	—

^a The nominal sizes correspond to those given in ISO 1307.

Table 3 — Concentricity of hoses

Nominal size	Maximum variation in wall thickness	
	mm	
	Between inside diameter and outside diameter	Between inside diameter and reinforcement outside diameter
6,3	0,8	0,5
Over 6,3 and up to and including 19	1,0	0,7
Over 19	1,3	0,9

6.2 Length

The length of supplied hoses and hose assemblies shall be the subject of agreement between the manufacturer and the purchaser.

NOTE Recommendations for supplied lengths of hoses and hose assemblies are given in [Annex C](#).

7 Performance requirements

7.1 General

The requirements for type and routine testing are given in [Annex A](#) and recommendations for production acceptance testing in [Annex B](#).

7.2 Hydrostatic requirements

7.2.1 When tested in accordance with ISO 1402 or ISO 6605 at the relevant proof pressure given in [Table 4](#) and the relevant minimum burst pressure given in [Table 5](#), the hoses and hose assemblies shall not leak.

7.2.2 When determined in accordance with ISO 1402 or ISO 6605, the change in length of hoses at the maximum working pressure (see [Table 6](#)) shall not exceed +2 % or -4 % for types 4SP and 4SH, or +2 % or -2 % for types R12, R13 and R15.

iTeh STANDARD PREVIEW
Table 4 — Proof pressure
(standards.iteh.ai)

Nominal size	Type				
	4SP	4SH	R12	R13	R15
	MPa (bar)	MPa (bar)	MPa (bar)	MPa (bar)	MPa (bar)
6,3	90,0 (900)	—	—	—	—
10	89,0 (890)	—	56,0 (560)	—	84,0 (840)
12,5	83,0 (830)	—	56,0 (560)	—	84,0 (840)
16	70,0 (700)	—	56,0 (560)	—	—
19	70,0 (700)	84,0 (840)	56,0 (560)	70,0 (700)	84,0 (840)
25	56,0 (560)	76,0 (760)	56,0 (560)	70,0 (700)	84,0 (840)
31,5	42,0 (420)	65,0 (650)	42,0 (420)	70,0 (700)	84,0 (840)
38	37,0 (370)	58,0 (580)	35,0 (350)	70,0 (700)	84,0 (840)
51	33,0 (330)	50,0 (500)	35,0 (350)	70,0 (700)	—

Table 5 — Minimum burst pressure

Nominal size	Type				
	4SP	4SH	R12	R13	R15
	MPa (bar)	MPa (bar)	MPa (bar)	MPa (bar)	MPa (bar)
6,3	180,0 (1 800)	—	—	—	—
10	178,0 (1 780)	—	112,0 (1 120)	—	168,0 (1 680)
12,5	166,0 (1 660)	—	112,0 (1 120)	—	168,0 (1 680)
16	140,0 (1 400)	—	112,0 (1 120)	—	—
19	140,0 (1 400)	168,0 (1 680)	112,0 (1 120)	140,0 (1 400)	168,0 (1 680)
25	112,0 (1 120)	152,0 (1 520)	112,0 (1 120)	140,0 (1 400)	168,0 (1 680)
31,5	84,0 (840)	130,0 (1 300)	84,0 (840)	140,0 (1 400)	168,0 (1 680)
38	74,0 (740)	116,0 (1 160)	70,0 (700)	140,0 (1 400)	168,0 (1 680)
51	66,0 (660)	100,0 (1 000)	70,0 (700)	140,0 (1 400)	—

Table 6 — Maximum working pressure

Nominal size	Type				
	4SP	4SH	R12	R13	R15
	MPa (bar)	MPa (bar)	MPa (bar)	MPa (bar)	MPa (bar)
6,3	45,0 (450)	—	—	—	—
10	44,5 (445)	—	28,0 (280)	—	42,0 (420)
12,5	41,5 (415)	—	28,0 (280)	—	42,0 (420)
16	35,0 (350)	—	28,0 (280)	—	—
19	35,0 (350)	42,0 (420)	28,0 (280)	35,0 (350)	42,0 (420)
25	28,0 (280)	38,0 (380)	28,0 (280)	35,0 (350)	42,0 (420)
31,5	21,0 (210)	32,5 (325)	21,0 (210)	35,0 (350)	42,0 (420)
38	18,5 (185)	29,0 (290)	17,5 (175)	35,0 (350)	42,0 (420)
51	16,5 (165)	25,0 (250)	17,5 (175)	35,0 (350)	—

7.3 Minimum bend radius

Use a test piece having a length at least four times the minimum bend radius.

When bent to the minimum bend radius given in [Table 7](#), measured on the inside of the bend, the hose shall conform, in the bent state, to the impulse and cold flexibility requirements of [7.4](#) and [7.6](#).