



SLOVENSKI STANDARD

oSIST prEN 16603-20-21:2019

01-november-2019

Vesoljska tehnika - Zahteve vmesnika za električne pogone

Space engineering - Interface requirements for electrical actuators

Raumfahrttechnik - Anforderungen an Schnittstellen für elektrische Aktuatoren

Ingénierie spatiale - Exigences d'interface pour les actionneurs électriques

Ta slovenski standard je istoveten z: prEN 16603-20-21

<https://standards.iteh.ai/catalog/standards/sist/a6eaaceb-880f-4005-81c9-b2dc08cfla49/sist-en-16603-20-21-2020>

ICS:

49.140	Vesoljski sistemi in operacije	Space systems and operations
--------	--------------------------------	------------------------------

oSIST prEN 16603-20-21:2019

en,fr,de

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN 16603-20-21

September 2019

ICS 49.140

English version

Space engineering - Interface requirements for electrical actuators

Ingénierie spatiale - Exigences d'interface pour les
actuateurs électriques

Raumfahrttechnik - Anforderungen an Schnittstellen
für elektrische Aktuatoren

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/CLC/JTC 5.

If this draft becomes a European Standard, CEN and CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN and CENELEC in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN and CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN and CENELEC members are the national standards bodies and national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation. Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



CEN-CENELEC Management Centre:
Rue de la Science 23, B-1040 Brussels

Table of contents

European Foreword.....	4
Introduction.....	5
1 Scope.....	6
2 Normative references	7
3 Terms, definitions and abbreviated terms.....	8
3.1 Terms from other standards.....	8
3.2 Terms specific to the present standard	8
3.3 Abbreviated terms.....	10
3.4 Nomenclature	10
4 Principles	11
4.1 Standard assumptions	11
4.2 Verification.....	11
5 Requirements.....	12
5.1 Functional general interface requirements	12
5.1.1 General	12
5.1.2 Reliability	12
5.2 Functional source interface requirements	13
5.2.1 General	13
5.2.2 Reliability	13
5.2.3 Commands	14
5.2.4 Telemetry.....	15
5.3 Functional load interface requirements	16
5.3.1 General	16
5.3.2 Reliability	16
5.4 Performance general interface requirements	16
5.4.1 General	16
5.5 Performance source interface requirements	17
5.5.1 General	17
5.5.2 Reliability	17

5.5.3	Telemetry.....	18
5.5.4	Recurrent products.....	18
5.6	Performance load interface requirements	18
5.6.1	General	18
5.6.2	Reliability	19
5.6.3	Recurrent products.....	19
Annex A (informative) Requirements mapping.....		20
Bibliography.....		37

Tables

Table A-1 : Functional general requirements list.....	21
Table A-2 : Functional source requirements list.....	23
Table A-3 : Functional load requirements list.....	30
Table A-4 : Performance general requirements list.....	31
Table A-5 : Performance source requirements list.....	32
Table A-6 : Performance load requirements list.....	35

ITEH STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 16603-20-21:2020

<https://standards.iteh.ai/catalog/standards/sist/a6eaaceb-880f-4005-81c9-b2dc08cfla49/sist-en-16603-20-21-2020>

European Foreword

This document (prEN 16603-20-21:2019) has been prepared by Technical Committee CEN/CLC/TC 5 “Space”, the secretariat of which is held by DIN (Germany).

This document (prEN 16603-20-21:2019) originates from ECSS-E-ST-20-21C.

This document is currently submitted to the ENQUIRY.

This document has been developed to cover specifically space systems and will therefore have precedence over any EN covering the same scope but with a wider do-main of applicability (e.g. : aerospace).

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 16603-20-21:2020

<https://standards.iteh.ai/catalog/standards/sist/a6eaaceb-880f-4005-81c9-b2dc08cfla49/sist-en-16603-20-21-2020>

Introduction

This standard identifies the requirements needed to specify, procure or develop the electronics needed for driving release actuators (both explosive like pyrotechnic devices or non-explosive like thermal knives) and gives the relevant electrical interface specification, both from source and load perspective.

The present standard covers explosive or non-explosive actuators electronics required to comply with single fault tolerance with respect to actuation success.

For a reference architecture description, it is possible to refer to ECSS-E-HB-20-21.

ECSS-E-HB-20-21 includes a clarification of the principles of operation of the actuator electronics, identifies important issues related to actuators and explains the requirements of the present standard.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 16603-20-21:2020

<https://standards.iteh.ai/catalog/standards/sist/a6eaaceb-880f-4005-81c9-b2dc08cf1a49/sist-en-16603-20-21-2020>

1

Scope

In general terms, the scope of the consolidation of the electrical interface requirements for electrical (hold down and release or deployment) actuators in the present ECSS-E-ST-20-21 and the relevant explanation in the handbook ECSS-E-HB-20-21 is to allow a more recurrent approach both for actuator electronics (power source) and electrical actuators (power load) offered by the relevant manufacturers, at the benefit of the system integrators and of the Agency, thus ensuring:

- better quality,
- stability of performances, and
- independence of the products from specific mission targets.

A recurrent approach enables manufacturing companies to concentrate on products and a small step improvement approach that is the basis of a high quality industrial output.

[SIST EN 16603-20-21:2020](https://standards.iteh.ai/catalog/standards/sist/a6eaaceb-880f-4005-81c9-b2dc08cfla49/sist-en-16603-20-21-2020)

<https://standards.iteh.ai/catalog/standards/sist/a6eaaceb-880f-4005-81c9-b2dc08cfla49/sist-en-16603-20-21-2020>

2

Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this ECSS Standard. For dated references, subsequent amendments to, or revision of any of these publications do not apply. However, parties to agreements based on this ECSS Standard are encouraged to investigate the possibility of applying the more recent editions of the normative documents indicated below. For undated references, the latest edition of the publication referred to applies.

EN reference	Reference in text	Title
EN 16601-00-01	ECSS-S-ST-00-01	ECSS system - Glossary of terms
EN 16602-30-02	ECSS-Q-ST-30-02	Space product assurance - Failure modes, effects (and criticality) analysis (FMEA/FMECA)
EN 16603-33-11	ECSS-E-ST-33-11	Space engineering - Explosive subsystems and devices

[SIST EN 16603-20-21:2020](https://standards.iteh.ai/catalog/standards/sist/a6eaaceb-880f-4005-81c9-b2dc08cfla49/sist-en-16603-20-21-2020)

<https://standards.iteh.ai/catalog/standards/sist/a6eaaceb-880f-4005-81c9-b2dc08cfla49/sist-en-16603-20-21-2020>

Terms, definitions and abbreviated terms

3.1 Terms from other standards

- a. For the purpose of this document, the terms and definitions from ECSS-S-ST-00-01 apply, in particular for the following terms:
 1. redundancy
 2. active redundancy
 3. hot redundancy
 4. cold redundancy
 5. fault
 6. fault tolerance
- b. For the purpose of this document, the terms and definitions ECSS-Q-ST-30-02 apply, in particular for the following terms:
 1. failure propagation
- c. For the purpose of this document, the terms and definitions from ECSS-E-ST-33-11 apply, in particular for the following terms:
 1. no fire
 2. all fire

3.2 Terms specific to the present standard

3.2.1 actuator

<CONTEXT: electrical actuator> component of a machine that is responsible for triggering the movement of a mechanism or a system

3.2.2 actuator electronics

electronics supplying an actuator

3.2.3 actuators group

set of actuators sharing the same ARM and the same FIRE block

NOTE The term “actuators group” is synonymous to the term “group” in this standard

3.2.4 all-fire current

current giving a probability of actuation higher than a specified limit, at a confidence level higher of a specified limit

3.2.5 no-fire current

current giving a probability of actuation lower than a specified limit, at a confidence level higher than a specified limit

3.2.6 maximum fire current

maximum current allowed in an actuator in nominal conditions

3.2.7 minimum actuation current

all-fire current plus a margin defined by the system integrator

NOTE The current margin is calculated to guarantee in worst case the required reliability with a given confidence level when the actuation time is above the minimum actuation time.

3.2.8 minimum actuation time

actuation time in the all-fire current reference conditions, plus a margin established by the manufacturer or by the system integrator

NOTE The margin is calculated to guarantee in worst case the required reliability with a given confidence level when the actuation current is above the minimum actuation current.

3.2.9 inhibition strap

hardware feature that does not allow firing of the actuator

NOTE The inhibition strap typically contains a connector and one of more wires to ensure continuity until strap is opened.

3.2.10 current-driven actuator

actuator that is commanded by a current pulse within a certain range of values and duration

3.2.11 voltage-driven actuator

actuator that is commanded by a voltage pulse within a certain range of values and duration

3.2.12 short duration actuator

actuator with actuation duration lasting less than or equal to 1 s

3.2.13 long duration actuator

actuator with actuation duration lasting more than 1 s

3.3 Abbreviated terms

For the purpose of this Standard, the abbreviated terms and symbols from ECSS-S-ST-00-01 and the following apply:

Abbreviation	Meaning
DC	direct current
EEE	electrical, electronic and electromechanical
FMEA	failure modes and effects analysis
FMECA	failure modes, effects and criticality analysis
RoD	review of design
SSE	space segment element
SSS	space segment subsystem

3.4 Nomenclature

The following nomenclature applies throughout this document:

- a. The word “shall” is used in this Standard to express requirements. All the requirements are expressed with the word “shall”.
- b. The word “should” is used in this Standard to express recommendations. All the recommendations are expressed with the word “should”.

NOTE It is expected that, during tailoring, recommendations in this document are either converted into requirements or tailored out.

- c. The words “may” and “need not” are used in this Standard to express positive and negative permissions, respectively. All the positive permissions are expressed with the word “may”. All the negative permissions are expressed with the words “need not”.
- d. The word “can” is used in this Standard to express capabilities or possibilities, and therefore, if not accompanied by one of the previous words, it implies descriptive text.

NOTE In ECSS “may” and “can” have completely different meanings: “may” is normative (permission), and “can” is descriptive.

- e. The present and past tenses are used in this Standard to express statements of fact, and therefore they imply descriptive text.