
**Rubber, vulcanized or
thermoplastic — Determination of
resistance to abrasion using a driven,
vertical abrasive disc**

*Caoutchouc, vulcanisé ou thermoplastique — Détermination de la
résistance à l'abrasion au moyen d'un disque abrasif vertical, motorisé*

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 23233:2016](https://standards.iteh.ai/catalog/standards/iso/039292a1-94ea-4629-b339-bf64df48a3f6/iso-23233-2016)

<https://standards.iteh.ai/catalog/standards/iso/039292a1-94ea-4629-b339-bf64df48a3f6/iso-23233-2016>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 23233:2016](https://standards.iteh.ai/catalog/standards/iso/039292a1-94ea-4629-b339-bf64df48a3f6/iso-23233-2016)

<https://standards.iteh.ai/catalog/standards/iso/039292a1-94ea-4629-b339-bf64df48a3f6/iso-23233-2016>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Apparatus	2
5.1 Abrasion test machine.....	2
5.2 Balance.....	4
6 Test pieces	5
6.1 Type and preparation.....	5
6.2 Number.....	5
6.3 Time interval between vulcanization or forming and testing.....	5
7 Conditioning	5
8 Test temperature	5
9 Test conditions	6
9.1 Preliminary abrasion.....	6
9.2 Run-in.....	6
9.3 Test conditions.....	6
10 Procedure	7
10.1 Order of the test pieces.....	7
10.2 Marking of the test pieces.....	8
10.3 Abrasion testing.....	8
11 Expression of results [2] to [6].....	8
12 Test report	9
Bibliography	10

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](http://www.iso.org/foreword)

The committee responsible for this document is ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 2, *Testing and analysis*.

This second edition cancels and replaces the first edition (ISO 23233:2009), which has been technically revised to update the dimensions of the test piece and the test conditions.

[ISO 23233:2016](https://standards.iteh.ai/catalog/standards/iso/039292a1-94ea-4629-b339-bf64df48a3f6/iso-23233-2016)

<https://standards.iteh.ai/catalog/standards/iso/039292a1-94ea-4629-b339-bf64df48a3f6/iso-23233-2016>

Rubber, vulcanized or thermoplastic — Determination of resistance to abrasion using a driven, vertical abrasive disc

WARNING 1 — Persons using this International Standard should be familiar with normal laboratory practice. This International Standard does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices and to ensure compliance with any national regulatory conditions.

WARNING 2 — Certain procedures specified in this International Standard may involve the use or generation of substances, or the generation of waste, that could constitute a local environmental hazard. Reference should be made to appropriate documentation on safe handling and disposal after use.

1 Scope

This International Standard specifies a method for the determination of the resistance of rubber to abrasion using a driven, vertical abrasive disc.

The loss in mass on abrasion is determined through the slip caused by setting different slip angles and rotational speeds between a wheel-shaped rubber test piece and an abrasive disc which are rotating in planes at right angles to each other and pressed against each other with a specified load. The test result can be reported as the loss in mass per unit running distance and/or as an abrasion resistance index compared to a reference compound.

This International Standard is applicable to comparative testing, quality control, specification compliance testing, referee testing and research and development work.

As the test device described is capable of setting each abrasion parameter, such as slip angle, rotational speed of the abrasive disc and load, independently, the method is suitable for carrying out a wide range of abrasion tests for various rubber products, especially tyres.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 525, *Bonded abrasive products — General requirements*

ISO 8486-1, *Bonded abrasives — Determination and designation of grain size distribution — Part 1: Macrogrits F4 to F220*

ISO 23529, *Rubber — General procedures for preparing and conditioning test pieces for physical test methods*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

abrasion

loss of material from a surface due to frictional forces

[SOURCE: ISO 23794:2015, 3.1]

3.2

abrasion resistance

resistance to wear resulting from mechanical action upon a surface

[SOURCE: ISO 23794:2015, 3.2]

Note 1 to entry: Abrasion resistance can be expressed as a loss in mass or an abrasion resistance index.

3.3

abrasion resistance index

ratio of the loss in volume of a reference compound to the loss in volume of a test rubber measured under the same specified conditions and expressed as a percentage

[SOURCE: ISO 23794:2015, 3.3]

Note 1 to entry: The smaller the number, the lower the abrasion resistance.

3.4

slip angle

angle made by the plane of the test piece with the radius of the abrasive disc which passes through the point of contact between the test piece and the abrasive disc

3.5

running distance

total distance travelled by a point on the circumference of the test piece relative to the abrasive disc

3.6

reference compound

compound of known abrasion resistance which is compared with that of the test rubber

4 Principle

A wheel-shaped test piece and an abrasive disc are pressed against each other at right angles by a specified load. The abrasive disc is driven so that it rotates, causing the test piece to rotate with it. Wear occurs due to slip between the test piece and the abrasive disc.

Different angles of slip between the abrasive disc and the test piece can be used to give different speeds of rotation of the test piece.

A powder consisting of a mixture of MgO and Al₂O₃ is used to prevent smearing of the test piece on the surface of the abrasive disc.

The loss in mass of the test piece is measured and the loss per unit running distance calculated. The abrasion resistance index can also be determined by comparing the loss in mass of the test piece per unit running distance with the loss in mass per unit running distance of a reference compound tested under the same conditions.

5 Apparatus

5.1 Abrasion test machine

The abrasion test machine (see [Figure 1](#)) consists of an abrasive electro-corundum disc, a test piece holder with test piece mounting facilities (see [Figure 2](#)), a feed device for anti-smearing powder, an infrared thermometer, a load application device, a slip angle adjustment device and a side force measurement device.