



**Universal Mobile Telecommunications System (UMTS);  
LTE; 5G; (standard.iteh.ai)**

**Characteristics of the Universal Subscriber  
Identity Module (USIM) application  
(3GPP TS 31.102 version 17.9.0 Release 17)**



---

Reference

RTS/TSGC-0631102vh90

---

Keywords

5G,LTE,UMTS

***ETSI***

650 Route des Lucioles  
 F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
 Association à but non lucratif enregistrée à la  
 Sous-Préfecture de Grasse (06) N° w061004871

---

***Important notice***

The present document can be downloaded from:  
<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](https://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our  
 Coordinated Vulnerability Disclosure Program:  
<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

***Notice of disclaimer & limitation of liability***

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use or inability to use the software.

---

***Copyright Notification***

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™, PLUGTESTS™, UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the **GSM** logo are trademarks registered and owned by the **GSM Association**.

---

## Legal Notice

(standards.iteh.ai)

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

## Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	13
Introduction .....	14
1    Scope .....	15
2    References .....	15
3    Definitions, symbols, abbreviations and coding conventions .....	20
3.1    Definitions .....	20
3.2    Symbols.....	20
3.3    Abbreviations .....	20
3.4    Coding Conventions .....	23
4    Contents of the Files .....	23
4.1    Contents of the EFs at the MF level .....	23
4.2    Contents of files at the USIM ADF (Application DF) level .....	23
4.2.1    EFLI (Language Indication).....	24
4.2.2    EFIMSI (IMSI) .....	24
4.2.3    EFKeys (Ciphering and Integrity Keys) .....	25
4.2.4    EFKeysPS (Ciphering and Integrity Keys for Packet Switched domain) .....	26
4.2.5    EFPLMNwAcT (User controlled PLMN selector with Access Technology) .....	26
4.2.6    EFHPLMN (Higher Priority PLMN search period).....	28
4.2.7    EFACMmax (ACM maximum value).....	29
4.2.8    EFUST (USIM Service Table) .....	30
4.2.9    EFACM (Accumulated Call Meter).....	34
4.2.10    EFGID1 (Group Identifier Level 1).....	34
4.2.11    EFGID2 (Group Identifier Level 2).....	34
4.2.12    EFSPN (Service Provider Name) .....	35
4.2.13    EFPUCT (Price per Unit and Currency Table).....	36
4.2.14    EFCBMI (Cell Broadcast Message identifier selection) .....	37
4.2.15    EFACC (Access Control Class).....	37
4.2.16    EFFPLMN (Forbidden PLMNs) .....	38
4.2.17    EFLOCI (Location Information).....	38
4.2.18    EFAD (Administrative Data) .....	39
4.2.19    Void .....	42
4.2.20    EFCBMID (Cell Broadcast Message Identifier for Data Download).....	42
4.2.21    EFECC (Emergency Call Codes) .....	42
4.2.22    EFCBMR (Cell Broadcast Message Identifier Range selection) .....	43
4.2.23    EFPSLOCI (Packet Switched location information) .....	44
4.2.24    EFDN (Fixed Dialling Numbers) .....	45
4.2.25    EFSMS (Short messages) .....	46
4.2.26    EFMSISDN (MSISDN) .....	47
4.2.27    EFSMSP (Short message service parameters).....	48
4.2.28    EFMSSS (SMS status) .....	49
4.2.29    EFSDN (Service Dialling Numbers).....	50
4.2.30    EFEXT2 (Extension2).....	51
4.2.31    EFEXT3 (Extension3).....	51
4.2.32    EFMSR (Short message status reports) .....	51
4.2.33    EFICI (Incoming Call Information) .....	52
4.2.34    EFOCI (Outgoing Call Information) .....	55
4.2.35    EFICT (Incoming Call Timer) .....	56
4.2.36    EFOCT (Outgoing Call Timer) .....	57
4.2.37    EFEXT5 (Extension5).....	57
4.2.38    EFCCP2 (Capability Configuration Parameters 2) .....	58

4.2.39	EF <sub>e</sub> MLPP (enhanced Multi Level Precedence and Pre-emption).....	58
4.2.40	EF <sub>AaeM</sub> (Automatic Answer for eMLPP Service).....	59
4.2.41	Void .....	60
4.2.42	EF <sub>Hiddenkey</sub> (Key for hidden phone book entries) .....	60
4.2.43	Void .....	61
4.2.44	EF <sub>BDN</sub> (Barred Dialling Numbers) .....	61
4.2.45	EF <sub>EXT4</sub> (Extension4).....	61
4.2.46	EF <sub>CMI</sub> (Comparison Method Information) .....	62
4.2.47	EF <sub>EST</sub> (Enabled Services Table).....	62
4.2.48	EF <sub>ACL</sub> (Access Point Name Control List) .....	63
4.2.49	EF <sub>DCK</sub> (Depersonalisation Control Keys) .....	63
4.2.50	EF <sub>CNL</sub> (Co-operative Network List) .....	64
4.2.51	EF <sub>START-HFN</sub> (Initialisation values for Hyperframe number).....	65
4.2.52	EF <sub>THRESHOLD</sub> (Maximum value of START).....	66
4.2.53	EF <sub>OPLMNwACT</sub> (Operator controlled PLMN selector with Access Technology).....	66
4.2.54	EF <sub>HPLMNwAcT</sub> (HPLMN selector with Access Technology).....	67
4.2.55	EF <sub>ARR</sub> (Access Rule Reference).....	67
4.2.56	Void .....	68
4.2.57	EF <sub>NETPAR</sub> (Network Parameters) .....	68
4.2.58	EF <sub>PNN</sub> (PLMN Network Name) .....	70
4.2.59	EF <sub>OPL</sub> (Operator PLMN List).....	71
4.2.60	EF <sub>MBDN</sub> (Mailbox Dialling Numbers) .....	72
4.2.61	EF <sub>EXT6</sub> (Extension6).....	73
4.2.62	EF <sub>MBI</sub> (Mailbox Identifier).....	73
4.2.63	EF <sub>MWIS</sub> (Message Waiting Indication Status) .....	74
4.2.64	EF <sub>CFIS</sub> (Call Forwarding Indication Status).....	75
4.2.65	EF <sub>EXT7</sub> (Extension7).....	76
4.2.66	EF <sub>SPDI</sub> (Service Provider Display Information) .....	77
4.2.67	EF <sub>MMSN</sub> (MMS Notification) .....	78
4.2.68	EF <sub>EXT8</sub> (Extension 8) .....	79
4.2.69	EF <sub>MMSICP</sub> (MMS Issuer Connectivity Parameters) .....	80
4.2.70	EF <sub>MMSUP</sub> (MMS User Preferences) .....	82
4.2.71	EF <sub>MMSUCP</sub> (MMS User Connectivity Parameters) .....	83
4.2.72	EF <sub>NIA</sub> (Network's Indication of Alerting) .....	83
4.2.73	EF <sub>VGCS</sub> (Voice Group Call Service).....	84
4.2.74	EF <sub>VGCCS</sub> (Voice Group Call Service Status).....	86
4.2.75	EF <sub>VBS</sub> (Voice Broadcast Service).....	86
4.2.76	EF <sub>VBSS</sub> (Voice Broadcast Service Status).....	88
4.2.77	EF <sub>VGCSA</sub> (Voice Group Call Service Ciphering Algorithm).....	89
4.2.78	EF <sub>VBSCA</sub> (Voice Broadcast Service Ciphering Algorithm).....	90
4.2.79	EF <sub>GBABP</sub> (GBA Bootstrapping parameters) .....	90
4.2.80	EF <sub>MSK</sub> (MBMS Service Keys List) .....	91
4.2.81	EF <sub>MUK</sub> (MBMS User Key) .....	92
4.2.82	Void .....	93
4.2.83	EF <sub>GBANL</sub> (GBA NAF List).....	93
4.2.84	EF <sub>EHPLMN</sub> (Equivalent HPLMN) .....	94
4.2.85	EF <sub>EHPLMNPI</sub> (Equivalent HPLMN Presentation Indication) .....	94
4.2.86	EF <sub>LRPLMNSI</sub> (Last RPLMN Selection Indication).....	95
4.2.87	EF <sub>NAFKCA</sub> (NAF Key Centre Address) .....	95
4.2.88	EF <sub>SPNI</sub> (Service Provider Name Icon) .....	96
4.2.89	EF <sub>PNNI</sub> (PLMN Network Name Icon) .....	97
4.2.90	EF <sub>NCPIP</sub> (Network Connectivity Parameters for USIM IP connections).....	97
4.2.91	EF <sub>EPSLOCI</sub> (EPS location information) .....	100
4.2.92	EF <sub>EPNSC</sub> (EPS NAS Security Context) .....	103
4.2.93	EF <sub>UFC</sub> (USAT Facility Control).....	104
4.2.94	EF <sub>NASCONFIG</sub> (Non Access Stratum Configuration) .....	105
4.2.95	EF <sub>UICCIARI</sub> (UICC IARI).....	110
4.2.96	EF <sub>PWS</sub> (Public Warning System).....	111
4.2.97	EF <sub>FDNURI</sub> (Fixed Dialling Numbers URI).....	111
4.2.98	EF <sub>BDNURI</sub> (Barred Dialling Numbers URI).....	112
4.2.99	EF <sub>SDNURI</sub> (Service Dialling Numbers URI) .....	113

4.2.101	EF <sub>IPS</sub> (IMEI(SV) Pairing Status).....	115
4.2.102	EF <sub>IPD</sub> (IMEI(SV) of Pairing Device) .....	116
4.2.103	EF <sub>ePDGId</sub> (Home ePDG Identifier) .....	117
4.2.104	EF <sub>ePDGSelection</sub> (ePDG Selection Information).....	118
4.2.104a	EF <sub>ePDGIdEm</sub> (Emergency ePDG Identifier) .....	120
4.2.105	EF <sub>ePDGSelectionEm</sub> (ePDG Selection Information for Emergency Services).....	120
4.2.106	EF <sub>FromPreferred</sub> (From Preferred) .....	120
4.2.107	EF <sub>IMSCfgData</sub> (IMS Configuration Data) .....	121
4.2.108	EF <sub>TVCONFIG</sub> (TV Configuration) .....	121
4.2.109	EF <sub>3GPPPSDATAOFF</sub> (3GPP PS Data Off) .....	123
4.2.110	EF <sub>3GPPPSDATAOFFservicelist</sub> (3GPP PS Data Off Service List).....	124
4.2.111	EF <sub>XCAPConfigData</sub> (XCAP Configuration Data).....	124
4.2.112	EF <sub>EARFCNList</sub> (EARFCN list for MTC/NB-IOT UEs).....	125
4.2.113	EF <sub>MuDMiDConfigData</sub> (MuD and MiD Configuration Data) .....	126
4.3	DFs at the USIM ADF (Application DF) Level .....	126
4.4	Contents of DFs at the USIM ADF (Application DF) level .....	127
4.4.1	Contents of files at the DF SoLSA level.....	127
4.4.1.1	EF <sub>SAI</sub> (SoLSA Access Indicator).....	127
4.4.1.2	EF <sub>SLL</sub> (SoLSA LSA List) .....	128
4.4.1.3	LSA Descriptor files .....	130
4.4.2	Contents of files at the DF PHONEBOOK level .....	131
4.4.2.1	EF <sub>PBR</sub> (Phone Book Reference file) .....	132
4.4.2.2	EF <sub>IAP</sub> (Index Administration Phone book) .....	134
4.4.2.3	EF <sub>ADN</sub> (Abbreviated dialling numbers) .....	134
4.4.2.4	EF <sub>EXT1</sub> (Extension1) .....	137
4.4.2.5	EF <sub>PBC</sub> (Phone Book Control).....	139
4.4.2.6	EF <sub>GRP</sub> (Grouping file).....	140
4.4.2.7	EF <sub>AAS</sub> (Additional number Alpha String) .....	140
4.4.2.8	EF <sub>GAS</sub> (Grouping information Alpha String) .....	141
4.4.2.9	EF <sub>ANR</sub> (Additional Number).....	141
4.4.2.10	EF <sub>SNE</sub> (Second Name Entry).....	143
4.4.2.11	EF <sub>CCP1</sub> (Capability Configuration Parameters 1).....	144
4.4.2.12	Phone Book Synchronisation .....	144
4.4.2.12.1	EF <sub>UID</sub> (Unique Identifier).....	144
4.4.2.12.2	EF <sub>PSC</sub> (Phone book Synchronisation Counter).....	145
4.4.2.12.3	EF <sub>CC</sub> (Change Counter) .....	146
4.4.2.12.4	EF <sub>PUID</sub> (Previous Unique Identifier) .....	147
4.4.2.13	EF <sub>EMAIL</sub> (e-mail address) .....	147
4.4.2.14	Phonebook restrictions .....	148
4.4.2.15	EF <sub>PURI</sub> (Phonebook URIs) .....	148
4.4.3	Contents of files at the DF GSM-ACCESS level (Files required for GSM Access).....	149
4.4.3.1	EF <sub>Kc</sub> (GSM Ciphering key Kc) .....	150
4.4.3.2	EF <sub>KcGPRS</sub> (GPRS Ciphering key KcGPRS) .....	150
4.4.3.3	Void.....	151
4.4.3.4	EF <sub>CPBCCH</sub> (CPBCCH Information) .....	151
4.4.3.5	EF <sub>InvScan</sub> (Investigation Scan) .....	152
4.4.4	Contents of files at the MexE level.....	152
4.4.4.1	EF <sub>MexE-ST</sub> (MexE Service table).....	153
4.4.4.2	EF <sub>ORPK</sub> (Operator Root Public Key).....	153
4.4.4.3	EF <sub>ARPK</sub> (Administrator Root Public Key).....	155
4.4.4.4	EF <sub>TPRPK</sub> (Third Party Root Public Key).....	156
4.4.4.5	EF <sub>TKCDF</sub> (Trusted Key/Certificates Data Files) .....	156
4.4.5	Contents of files at the DF WLAN level.....	157
4.4.5.1	EF <sub>Pseudo</sub> (Pseudonym) .....	157
4.4.5.2	EF <sub>UPLMNWLAN</sub> (User controlled PLMN selector for I-WLAN Access) .....	158
4.4.5.3	EF <sub>OPLMNWLAN</sub> (Operator controlled PLMN selector for I-WLAN Access) .....	158
4.4.5.4	EF <sub>UWSIDL</sub> (User controlled WLAN Specific Identifier List).....	159
4.4.5.5	EF <sub>OwsIDL</sub> (Operator controlled WLAN Specific IdentifierList) .....	160
4.4.5.6	EF <sub>WRI</sub> (WLAN Reauthentication Identity) .....	160
4.4.5.7	EF <sub>HWSIDL</sub> (Home I-WLAN Specific Identifier List) .....	161
4.4.5.8	EF <sub>WEHPLMNP1</sub> (I-WLAN Equivalent HPLMN Presentation Indication).....	162
4.4.5.9	EF <sub>WHPI</sub> (I-WLAN HPLMN Priority Indication) .....	162

4.4.5.10	EF <sub>WLRPLMN</sub> (I-WLAN Last Registered PLMN) .....	163
4.4.5.11	EF <sub>HPLMNDAI</sub> (HPLMN Direct Access Indicator) .....	163
4.4.6	Contents of files at the DF HNB level .....	164
4.4.6.1	Introduction .....	164
4.4.6.2	EF <sub>ACSGL</sub> (Allowed CSG Lists) .....	164
4.4.6.3	EF <sub>CSGT</sub> (CSG Type) .....	167
4.4.6.4	EF <sub>HNBN</sub> (Home NodeB Name) .....	169
4.4.6.5	EF <sub>OCSGL</sub> (Operator CSG Lists) .....	169
4.4.6.6	EF <sub>OCSTG</sub> (Operator CSG Type) .....	171
4.4.6.7	EF <sub>OHNBN</sub> (Operator Home NodeB Name) .....	172
4.4.7	Void .....	172
4.4.8	Contents of files at the DF ProSe level .....	172
4.4.8.1	Introduction .....	172
4.4.8.2	EF <sub>PROSE_MON</sub> (ProSe Monitoring Parameters) .....	172
4.4.8.3	EF <sub>PROSE_ANN</sub> (ProSe Announcing Parameters) .....	173
4.4.8.4	EF <sub>PROSEFUNC</sub> (HPLMN ProSe Function) .....	174
4.4.8.5	EF <sub>PROSE_RADIO_COM</sub> (ProSe Direct Communication Radio Parameters) .....	175
4.4.8.6	EF <sub>PROSE_RADIO_MON</sub> (ProSe Direct Discovery Monitoring Radio Parameters) .....	177
4.4.8.7	EF <sub>PROSE_RADIO_ANN</sub> (ProSe Direct Discovery Announcing Radio Parameters) .....	178
4.4.8.8	EF <sub>PROSE_POLICY</sub> (ProSe Policy Parameters) .....	179
4.4.8.9	EF <sub>PROSE_PLMN</sub> (ProSe PLMN Parameters) .....	181
4.4.8.10	EF <sub>PROSE_GC</sub> (ProSe Group Counter) .....	182
4.4.8.11	EF <sub>PST</sub> (ProSe Service Table) .....	184
4.4.8.12	EF <sub>PROSE_UIRC</sub> (ProSe UsageInformationReportingConfiguration) .....	184
4.4.8.12	EF <sub>PROSE_GM_DISCOVERY</sub> (ProSe Group Member Discovery Parameters) .....	188
4.4.8.13	EF <sub>PROSE_RELAY</sub> (ProSe Relay Parameters) .....	189
4.4.8.14	EF <sub>PROSE_RELAY_DISCOVERY</sub> (ProSe Relay Discovery Parameters) .....	190
4.4.9	Contents of files at the DF ACDC level .....	193
4.4.9.1	Introduction .....	193
4.4.9.2	EF <sub>ACDC_LIST</sub> (ACDC List) .....	193
4.4.9.3	EF <sub>ACDC_OS_CONFIG</sub> (ACDC OS configuration) .....	194
4.4.10	Contents of files at the DF TV level .....	195
4.4.10.1	Introduction .....	195
4.4.10.2	EF <sub>TVUSD</sub> (TV User Service Description) .....	195
4.4.11	Contents of files at the DF <sub>5GS</sub> level .....	196
4.4.11.1	Introduction .....	196
4.4.11.2	EF <sub>5GS3GPPLOCI</sub> (5GS 3GPP location information) .....	197
4.4.11.3	EF <sub>5GSN3GPPLOCI</sub> (5GS non-3GPP location information) .....	198
4.4.11.4	EF <sub>5GS3GPNSC</sub> (5GS 3GPP Access NAS Security Context) .....	199
4.4.11.5	EF <sub>5GSN3GPNSC</sub> (5GS non-3GPP Access NAS Security Context) .....	202
4.4.11.6	EF <sub>5GAUTHKEYS</sub> (5G authentication keys) .....	202
4.4.11.7	EF <sub>UAC_AIC</sub> (UAC Access Identities Configuration) .....	204
4.4.11.8	EF <sub>SUCL_Calc_Info</sub> (Subscription Concealed Identifier Calculation Information EF) .....	205
4.4.11.9	EF <sub>OPL5G</sub> (5GS Operator PLMN List) .....	207
4.4.11.10	EF <sub>SUPI_NAI</sub> (SUPI as Network Access Identifier) .....	208
4.4.11.11	EF <sub>Routing_Indicator</sub> (Routing Indicator EF) .....	209
4.4.11.12	EF <sub>URSP</sub> (URSP) .....	210
4.4.11.13	EF <sub>TN3GPPSN</sub> (Trusted non-3GPP Serving network names list) .....	211
4.4.11.14	EF <sub>CAG</sub> (Pre-configured CAG information list EF) .....	212
4.4.11.15	EF <sub>SOR-CMCI</sub> (Steering Of Roaming - Connected Mode Control Information) .....	213
4.4.11.16	Void .....	214
4.4.11.16.1	Void .....	214
4.4.11.16.2	Void .....	214
4.4.11.16.3	Void .....	214
4.4.11.16.4	Void .....	214
4.4.11.16.5	Void .....	214
4.4.11.16.6	Void .....	214
4.4.11.17	EF <sub>DRI</sub> (Disaster roaming information EF) .....	214
4.4.11.18	EF <sub>5GSEDRX</sub> (5GS eDRX Parameters) .....	215
4.4.11.19	EF <sub>5GNSWO_CONF</sub> (5G Non-Seamless WLAN Offload configuration) .....	216
4.4.11.20	EF <sub>MCHPPLMN</sub> (Multiplier Coefficient for Higher Priority PLMN search) .....	217
4.4.11.21	EF <sub>KAUSF_DERIVATION</sub> (K <sub>AUSF</sub> derivation configuration) .....	218

4.4.12	Contents of files at the DF SNP level .....	218
4.4.12.1	Introduction .....	218
4.4.12.2	EF <sub>PWS_SNPN</sub> (Public Warning System in SNPNs).....	218
4.4.12.3	EF <sub>NID</sub> (Network Identifier for SNPN) .....	219
4.4.13	Contents of files at the DF 5G ProSe level .....	220
4.4.13.1	Introduction .....	220
4.4.13.2	EF <sub>5G_PROSE_ST</sub> (5G ProSe Service Table) .....	220
4.4.13.3	EF <sub>5G_PROSE_DD</sub> (5G ProSe configuration data for direct discovery) .....	220
4.4.13.4	EF <sub>5G_PROSE_DC</sub> (5G ProSe configuration data for direct communication) .....	224
4.4.13.5	EF <sub>5G_PROSE_U2NRU</sub> (5G ProSe configuration data for UE-to-network relay UE).....	226
4.4.13.6	EF <sub>5G_PROSE_RU</sub> (5G ProSe configuration data for remote UE).....	230
4.4.13.7	EF <sub>5G_PROSE_UIR</sub> (5G ProSe configuration data for usage information reporting).....	233
4.5	Contents of Efs at the TELECOM level .....	235
4.5.1	EF <sub>ADN</sub> (Abbreviated dialling numbers).....	235
4.5.2	EF <sub>EXT1</sub> (Extension1).....	235
4.5.3	EF <sub>ECCP</sub> (Extended Capability Configuration Parameter).....	236
4.5.4	EF <sub>SUME</sub> (SetUpMenu Elements).....	236
4.5.5	EF <sub>AARR</sub> (Access Rule Reference).....	236
4.5.6	EF <sub>ICE_DN</sub> (In Case of Emergency – Dialling Number) .....	236
4.5.7	EF <sub>ICE_FF</sub> (In Case of Emergency – Free Format).....	237
4.5.8	EF <sub>RMA</sub> (Remote Management Actions).....	238
4.5.9	EF <sub>PSISMSC</sub> (Public Service Identity of the SM-SC).....	238
4.6	Contents of DFs at the TELECOM level.....	238
4.6.0	List of DFs at the TELECOM level .....	238
4.6.1	Contents of files at the DF <sub>GRAPHICS</sub> level.....	239
4.6.1.1	EF <sub>IMG</sub> (Image) .....	239
4.6.1.2	EF <sub>IIDF</sub> (Image Instance Data Files).....	240
4.6.1.3	EF <sub>ICE_graphics</sub> (In Case of Emergency – Graphics).....	241
4.6.1.4	Void.....	242
4.6.1.5	Void.....	242
4.6.2	Contents of files at the DF <sub>PHONEBOOK</sub> under the DF <sub>TELECOM</sub> .....	242
4.6.3	Contents of files at the DF <sub>MULTIMEDIA</sub> level.....	242
4.6.3.1	EF <sub>MML</sub> (Multimedia Messages List).....	242
4.6.3.2	EF <sub>MMDF</sub> (Multimedia Messages Data File).....	244
4.6.4	Contents of files at the DF <sub>MCS</sub> level.....	245
4.6.4.1	EF <sub>MST</sub> (MCS Service Table).....	245
4.6.4.2	EF <sub>MCS_CONFIG</sub> (MCS configuration data).....	246
4.6.4.3	Void.....	247
4.6.4.4	Void.....	247
4.6.4.5	Void.....	247
4.6.5	Contents of files at the DF <sub>V2X</sub> level .....	247
4.6.5.1	V2X configuration data related files .....	247
4.6.5.2	EF <sub>VST</sub> (V2X Service Table).....	247
4.6.5.3	EF <sub>V2X_CONFIG</sub> (V2X configuration data).....	248
4.6.5.4	EF <sub>V2XP_PC5</sub> (V2X data policy over PC5).....	248
4.6.5.5	EF <sub>V2XP_Uu</sub> (V2X data policy over Uu) .....	250
4.7	Files of USIM.....	253
5	Application protocol.....	260
5.1	USIM management procedures .....	260
5.1.1	Initialisation .....	261
5.1.1.1	USIM application selection.....	261
5.1.1.2	USIM initialisation.....	261
5.1.1.3	GSM related initialisation procedures.....	262
5.1.2	Session termination.....	262
5.1.2.1	3G session termination.....	262
5.1.2.1.1	GSM termination procedures.....	263
5.1.2.2	3G session reset.....	263
5.1.3	USIM application closure .....	263
5.1.4	Emergency call codes .....	263
5.1.5	Language indication.....	263
5.1.6	Administrative information request .....	263

5.1.7	USIM service table request .....	263
5.1.8	Void .....	263
5.1.9	UICC presence detection .....	263
5.1.10	UICC interface in PSM .....	264
5.1.11	UICC interface during eDRX .....	264
5.1.12	UICC interface during MICO .....	265
5.2	USIM security related procedures .....	265
5.2.1	Authentication algorithms computation .....	265
5.2.2	IMSI request .....	265
5.2.3	Access control information request .....	265
5.2.4	Higher Priority PLMN search period request .....	266
5.2.5	Location information .....	266
5.2.6	Cipher and Integrity key .....	266
5.2.7	Forbidden PLMN .....	266
5.2.8	Void .....	266
5.2.9	User Identity Request .....	266
5.2.10	GSM Cipher key .....	266
5.2.11	GPRS Cipher key .....	266
5.2.12	Initialisation value for Hyperframe number .....	266
5.2.13	Maximum value of START .....	267
5.2.14	HPLMN selector with Access Technology request .....	267
5.2.15	Packet Switched Location information .....	267
5.2.16	Cipher and Integrity key for Packet Switched domain .....	267
5.2.17	LSA information .....	267
5.2.18	Voice Group Call Services .....	267
5.2.19	Voice Broadcast Services .....	267
5.2.20	Generic Bootstrapping architecture (Bootstrap) .....	267
5.2.21	Generic Bootstrapping architecture (NAF Derivation) .....	268
5.2.22	MSK MIKEY Message Reception .....	268
5.2.23	MTK MIKEY Message Reception .....	268
5.2.24	Void .....	268
5.2.25	EHPLMN request .....	268
5.2.26	Last RPLMN Selection Indication request .....	268
5.2.29	Non Access Stratum Configuration .....	268
5.2.30	PWS Configuration .....	269
5.2.33	SUPI_NAI request .....	269
5.2.34	URSP request .....	269
5.2.35	Trusted non-3GPP Serving network name list request .....	269
5.2.36	Steering of roaming connected mode control information request .....	269
5.3	Subscription related procedures .....	270
5.3.1	Phone book procedures .....	270
5.3.1.1	Initialisation .....	270
5.3.1.2	Creation/Deletion of information .....	270
5.3.1.3	Hidden phone book entries .....	270
5.3.2	Dialling numbers .....	270
5.3.3	Short messages .....	272
5.3.4	Advice of charge .....	272
5.3.5	Capability configuration parameters .....	273
5.3.6	User controlled PLMN selector with Access Technology .....	273
5.3.7	Cell broadcast message identifier .....	273
5.3.8	Group identifier level 1 .....	273
5.3.9	Group identifier level 2 .....	273
5.3.10	Service provider name .....	273
5.3.11	Enhanced multi level precedence and pre-emption service .....	274
5.3.12	Cell broadcast message identifier ranges .....	274
5.3.13	Short message status report .....	274
5.3.14	APN Control List .....	274
5.3.15	Depersonalisation Control Keys .....	275
5.3.16	Co-operative Network List .....	275
5.3.17	CPBCCH information .....	275
5.3.18	Investigation Scan .....	275
5.3.19	Enabled Services Table Request .....	275

5.3.20	Operator controlled PLMN selector with Access Technology .....	275
5.3.21	HPLMN selector with Access Technology.....	275
5.3.22	Automatic Answer on eMLPP service.....	276
5.3.23	Network Parameter information .....	276
5.3.24	PLMN network name.....	276
5.3.25	Operator PLMN List.....	276
5.3.26	Message Waiting Indication .....	276
5.3.27	Call Forwarding Indication Status .....	276
5.3.28	Service Provider Display Information .....	276
5.3.29	MMS Notifications .....	276
5.3.30	MMS Issuer Connectivity Parameters .....	277
5.3.31	MMS User Preferences .....	277
5.3.32	MMS User Connectivity Parameters .....	277
5.3.33	Network's indication of alerting.....	277
5.3.34	Multimedia Messages Storage .....	277
5.3.35	Equivalent HPLMN Presentation Indication request.....	278
5.3.36	NAF Key Centre Address request.....	278
5.3.37	Service provider name Icon .....	278
5.3.38	PLMN network name Icon .....	278
5.3.39	ICE Information request .....	278
5.3.40	eCall Related Procedures .....	279
5.3.40.1	eCall Only support .....	279
5.3.40.2	eCall and Normal call support.....	279
5.3.40.3	Change of eCall mode .....	280
5.3.41	SM-over-IP .....	280
5.3.42	UICC access to IMS .....	280
5.3.43	TV Configuration.....	280
5.3.44	3GPP PS Data Off related procedures .....	280
5.3.45	3GPP PS Data Off service list related procedures .....	280
5.3.46	EARFCN list for MTC/NB-IOT UEs .....	280
5.3.47	SUCI Calculation information procedure .....	281
5.3.48	SUCI Calculation by the USIM procedure .....	281
5.3.49	Control plane-based Steering of Roaming related procedures.....	281
5.3.50	5GS Operator PLMN List.....	281
5.3.51	Routing Indicator procedure for ME.....	281
5.3.52	5GS eDRX procedure for ME.....	281
5.3.53	5G NSWO procedure.....	282
5.4	USAT related procedures .....	282
5.4.1	Data Download via SMS-PP.....	282
5.4.2	Image Request .....	282
5.4.3	Data Download via SMS-CB .....	282
5.4.4	Call Control by USIM.....	282
5.4.5	MO-SMS control by USIM .....	282
5.4.6	Data Download via USSD and USSD application mode.....	282
5.4.7	Additional TERMINAL PROFILE after UICC activation .....	282
5.4.8	Terminal Applications .....	283
5.4.9	Call control on EPS PDN connection by USIM .....	283
5.4.10	Communication Control for IMS by USIM .....	283
5.4.11	USAT Facility Control.....	283
5.4.12	Extended Terminal Applications .....	283
5.4.13	USAT application pairing procedure .....	283
5.4.14	Call control on PDU Session by USIM .....	284
5.5	MxEx related procedures.....	284
5.5.1	MxEx ST .....	284
5.5.2	Operator root public key .....	284
5.5.3	Administrator root public key .....	284
5.5.4	Third Party root public key(s).....	284
5.5.5	Trusted Key/Certificates Data Files.....	284
5.6	WLAN related procedures.....	285
5.6.1	WLAN Selection related Procedures .....	285
5.6.2	WLAN PLMN Selection related procedures .....	285
5.6.3	WLAN access authentication related procedures .....	285

5.6.4	WLAN access re-authentication related procedures .....	285
5.7	Network Connectivity Parameters for UICC IP connections related procedures.....	285
5.8	H(e)NB related procedures.....	285
5.8.1	CSG Access Control procedures.....	285
5.8.2	CSG Type related procedures .....	286
5.8.3	HNB name display related procedures.....	286
5.9	ProSe related procedures .....	287
5.9.1	ProSe Direct Discovery Provisioning parameters.....	287
5.9.2	HPLMN ProSe Function address.....	287
5.9.3	ProSe direct communication related Procedures.....	287
5.9.4	ProSe direct discovery related Procedures.....	287
5.9.5	ProSe direct communication related Procedures.....	287
5.9.6	ProSe direct communication related Procedures.....	287
5.9.7	ProSe Group Counter related Procedures .....	287
5.9.8	ProSe Usage Information Reporting Configuration related Procedures .....	288
5.9.9	ProSe Group Member Discovery related Procedures .....	288
5.9.10	ProSe Relay related Procedures .....	288
5.10	ePDG Selection related procedures .....	288
5.10.1	Home ePDG Identifier .....	288
5.10.2	ePDG Selection Information.....	288
5.10.3	ePDG configuration information configured but empty .....	288
5.11	ACDC related procedures .....	289
5.11.1	ACDC Configuration.....	289
5.12	MCS related procedures .....	289
5.12.1	MCS configuration .....	289
5.12.2	Void .....	289
5.12.3	Void .....	289
5.12.4	Void .....	289
5.13	ePDG Selection for Emergency Services related procedures .....	289
5.13.1	Emergency ePDG Identifier.....	289
5.13.2	ePDG Selection Information for Emergency Services.....	289
5.13.3	ePDG configuration information for Emergency Services configured but empty .....	290
5.13.4	From Preferred related procedures.....	290
5.13.5	IMS Configuration Data related procedures.....	290
5.13.6	XCAP Configuration Data related procedures.....	290
5.13.7	Multi-device and multi-identity related procedures .....	290
5.14	V2X related procedures.....	290
5.14.1	V2X configuration .....	290
5.14.2	V2X data policy over PC5 .....	290
5.14.3	V2X data policy over Uu .....	290
5.15	UAC Access Identities related procedures .....	291
5.15.1	UAC Access Identities Configuration.....	291
5.16	CAG selection related procedures .....	291
5.16.1	Pre-configured CAG information list reading procedure for ME.....	291
5.17	5G ProSe related procedures .....	291
5.17.1	5G ProSe configuration data for direct discovery .....	291
5.17.2	5G ProSe configuration data for direct communication.....	291
5.17.3	5G ProSe configuration data for UE-to-network relay UE .....	291
5.17.4	5G ProSe configuration data for remote UE.....	291
5.17.5	5G ProSe configuration data for usage information reporting .....	291
5.18	Disaster roaming related procedures .....	292
5.18.1	Disaster roaming information reading procedure for ME .....	292
5.19	SNPN (Standalone NPN) related procedures .....	292
5.19.1	PWS configuration in SNPN. ....	292
5.19.2	K <sub>AUSF</sub> derivation configuration .....	292
5.20	NG-RAN satellite access related procedures.....	292
5.20.1	Multiplier coefficient for Higher Priority PLMN search via NG-RAN satellite access for ME .....	292
6	Security features .....	292
6.1	Authentication and key agreement procedure .....	292
6.2	Cryptographic Functions .....	293
6.3	GSM Conversion Functions .....	293

6.4	User verification and file access conditions .....	293
7	<b>USIM Commands.....</b>	294
7.1	AUTHENTICATE .....	294
7.1.1	Command description .....	294
7.1.1.1	3G/EPS/5G security context.....	294
7.1.1.2	GSM security context.....	295
7.1.1.3	VGCS/VBS security context.....	295
7.1.1.4	GBA security context (Bootstrapping Mode) .....	296
7.1.1.5	GBA security context (NAF Derivation Mode) .....	297
7.1.1.6	MBMS security context (MSK Update Mode) .....	297
7.1.1.7	Void.....	299
7.1.1.8	MBMS security context (MTK Generation Mode) .....	299
7.1.1.9	MBMS security context (MSK Deletion Mode) .....	299
7.1.1.10	MBMS security context (MUK Deletion Mode).....	300
7.1.1.11	Local Key Establishment security context (Key Derivation mode) .....	300
7.1.1.12	Local Key Establishment security context (Key Availability Check mode) .....	301
7.1.2	Command parameters and data.....	301
7.1.2.1	GSM/3G/EPS/5G security context.....	303
7.1.2.2	VGCS/VBS security context.....	304
7.1.2.3	GBA security context (Bootstrapping Mode) .....	304
7.1.2.4	GBA security context (NAF Derivation Mode) .....	305
7.1.2.5	MBMS security context (All Modes).....	305
7.1.2.6	Local Key Establishment security context (All Modes).....	306
7.1.2.6.1	Local Key Establishment security context (Key Derivation mode).....	306
7.1.2.6.2	Local Key Establishment security context (Key Availability Check mode) .....	308
7.2	Void.....	309
7.3	<b>Status Conditions Returned by the USIM .....</b>	309
7.3.1	Security management.....	309
7.3.2	Status Words of the Commands.....	310
7.4	Optional commands.....	311
7.5	<b>GET IDENTITY .....</b>	311
7.5.1	Command description .....	311
7.5.1.1	SUCI context.....	311
7.5.1.2	SUCI 5G NSW context .....	312
7.5.2	Command parameters and data.....	313
7.5.2.1	SUCI context.....	313
7.5.2.2	SUCI 5G NSW context .....	315
8	Void.....	316
<b>Annex A (informative): EF changes via Data Download or USAT applications .....</b>		317
<b>Annex B (normative): Image Coding Schemes.....</b>		322
B.1	Basic Image Coding Scheme.....	322
B.2	Colour Image Coding Scheme .....	323
B.3	Colour Image Coding Scheme with Transparency.....	324
<b>Annex C (informative): Structure of the Network parameters TLV objects.....</b>		325
<b>Annex D (informative): Tags defined in 31.102 .....</b>		326
<b>Annex E (informative): Suggested contents of the EFs at pre-personalization .....</b>		334
<b>Annex F (informative): Examples of coding of LSA Descriptor files for SoLSA .....</b>		339
<b>Annex G (informative): Phonebook Example .....</b>		340
<b>Annex H (normative): List of SFI Values.....</b>		344
H.1	List of SFI Values at the USIM ADF Level.....	344

H.2	List of SFI Values at the DF GSM-ACCESS Level.....	344
H.3	List of SFI Values at the DF WLAN Level.....	345
H.4	List of SFI Values at the DF HNB Level .....	345
H.5	List of SFI Values at the DF ProSe Level .....	345
H.6	List of SFI Values at the DF ACDC Level.....	345
H.7	List of SFI Values at the DF MCS Level .....	346
H.8	List of SFI Values at the DF V2X Level.....	346
H.9	List of SFI Values at the DF 5GS Level .....	346
H.10	List of SFI Values at the DF 5G ProSe Level .....	347
H.11	List of SFI Values at the DF SNPN Level .....	347
<b>Annex I (informative):</b>	<b>USIM Application Session Activation/Termination .....</b>	<b>348</b>
<b>Annex J (informative):</b>	<b>Example of MMS coding.....</b>	<b>349</b>
J.1	Coding example for MMS User Preferences.....	349
J.2	Coding Example for MMS Issuer/User Connectivity Parameters.....	349
<b>Annex K (informative):</b>	<b>Examples of VService_Id coding.....</b>	<b>351</b>
<b>Annex L (normative):</b>	<b>USIM-INI and USIM-RN for Relay Nodes .....</b>	<b>352</b>
L.1	Introduction .....	352
L.2	Application selection procedure.....	352
L.3	Secure channel operation.....	353
L.4	Support of commands.....	353
L.5	Storage of certificates.....	353
L.6	Relay Node files support .....	353
L.6.1	USIM-INI Files .....	353
L.6.1.1	EFCERT (UICC Certificate) .....	353
L.6.2	USIM-RN Files .....	354
L.6.2.1	eFRNid (Relay Node identifier).....	354
L.6.2.2	EFSCCmax (maximum value of Secure Channel Counter).....	355
<b>Annex M (normative):</b>	<b>USIM application dedicated for IOPS .....</b>	<b>356</b>
M.1	Introduction .....	356
M.2	Features of the USIM dedicated for IOPS.....	356
M.3	Selection mechanisms .....	356
<b>Annex N (normative):</b>	<b>USIM supporting non-IMSI SUPI Type.....</b>	<b>357</b>
N.1	Introduction .....	357
N.2	Features of USIM supporting non-IMSI SUPI type.....	357
N.3	Application selection procedure .....	357
<b>Annex O (informative):</b>	<b>Examples of NAS security contexts management in multiple registrations.....</b>	<b>358</b>
<b>Annex P (informative):</b>	<b>Change history .....</b>	<b>360</b>
History .....	367	

## Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

**shall** indicates a mandatory requirement to do something

**shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

**should** indicates a recommendation to do something

**should not** indicates a recommendation not to do something

**may** indicates permission to do something

**need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

**can** indicates that something is possible

**cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

**will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

**will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document

**might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

**might not** indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

**is** (or any other verb in the indicative mood) indicates a statement of fact

**is not** (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

---

## Introduction

The present document defines the Universal Subscriber Identity Module (USIM) application. This application resides on the UICC, an IC card specified in TS 31.101 [11]. In particular, TS 31.101 [11] specifies the application independent properties of the UICC/terminal interface such as the physical characteristics and the logical structure.

TS 31.101 [11] is one of the core documents for this specification and is therefore referenced in many places in the present document.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ETSI TS 131 102 V17.9.0 \(2023-04\)](#)

<https://standards.iteh.ai/catalog/standards/sist/45b27c31-d843-4925-995a-e5de9216a75e/etsi-ts-131-102-v17-9-0-2023-04>