

---

---

**Road vehicles — Compressed gaseous  
hydrogen (CGH<sub>2</sub>) and hydrogen/  
natural gas blends fuel system  
components —**

Part 5:

**Manual cylinder valve**

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

*Véhicules routiers — Composants des circuits d'alimentation pour  
hydrogène gazeux comprimé (CGH<sub>2</sub>) et mélanges de gaz naturel et  
hydrogène —*

ISO 12619-5:2016

*Partie 5: Valve manuelle du cylindre*

<https://standards.iteh.ai/catalog/standards/sist/17185724-4948-4003-b27e-a9d3e9b1710a/iso-12619-5-2016>



**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

ISO 12619-5:2016

<https://standards.iteh.ai/catalog/standards/sist/f7f83724-484b-4003-b27e-a9d3e9b1710a/iso-12619-5-2016>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

# Contents

	Page
Foreword .....	iv
<b>1 Scope .....</b>	<b>1</b>
<b>2 Normative references .....</b>	<b>1</b>
<b>3 Terms and definitions .....</b>	<b>2</b>
<b>4 Markings .....</b>	<b>2</b>
<b>5 Construction and assembly .....</b>	<b>2</b>
<b>6 Tests .....</b>	<b>3</b>
6.1 Applicability .....	3
6.2 Hydrostatic strength .....	3
6.3 Leakage .....	3
6.4 Continued operation .....	4
<b>Bibliography .....</b>	<b>5</b>

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 12619-5:2016

<https://standards.iteh.ai/catalog/standards/sist/f7f83724-484b-4003-b27e-a9d3e9b1710a/iso-12619-5-2016>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword — Supplementary information](#).

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 41, *Specific aspects for gaseous fuels*.

ISO 12619 consists of the following parts, under the general title *Road vehicles — Compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blends fuel system components*:

- *Part 1: General requirements and definitions*
- *Part 2: Performance and general test methods*
- *Part 3: Pressure regulator*
- *Part 4: Check valve*
- *Part 5: Manual cylinder valve*
- *Part 6: Automatic valve*

# Road vehicles — Compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blends fuel system components —

## Part 5: Manual cylinder valve

### 1 Scope

This part of ISO 12619 specifies general requirements and definitions of compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blends fuel system components, intended for use on the types of motor vehicles defined in ISO 3833. It also provides general design principles and specifies requirements for instructions and markings.

It is applicable to vehicles using compressed gaseous hydrogen (CGH<sub>2</sub>) in accordance with ISO 14687-1 or ISO 14687-2 and hydrogen/natural gas blends using natural gas in accordance with ISO 15403-1 and ISO/TR 15403-2. It is not applicable to the following:

- a) liquefied hydrogen (LH<sub>2</sub>) fuel system components located upstream of, and including, the vaporizer;
- b) fuel containers;
- c) stationary gas engines;
- d) container mounting hardware;
- e) electronic fuel management;
- f) refuelling receptacles.

NOTE 1 It is recognized that miscellaneous components not specifically covered herein can be examined to meet the criteria of this part of ISO 12619 and tested according to the appropriate functional tests.

NOTE 2 All references to pressure in this part of ISO 12619 are to be considered gauge pressures unless otherwise specified.

NOTE 3 This part of ISO 12619 may not apply to fuel cell vehicles in compliance with international regulations.

### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12619-1, *Road vehicles — Compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blend fuel system components — Part 1: General requirements and definitions*

ISO 12619-2, *Road vehicles — Compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blend fuel system components — Part 2: Performance and general test methods*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12619-1 apply.

### 4 Markings

Marking of the component shall provide sufficient information to allow the following details to be traced:

- manufacturer's or agent's name, trademark or symbol;
- model designation (part number);
- working pressure or pressure and temperature range.

The following additional markings are recommended:

- direction of flow (when necessary for correct installation);
- type of fuel;
- electrical ratings (if applicable);
- symbol of the certification agency (if applicable);
- type approval number;
- serial number or date code;
- reference to this International Standard (i.e. ISO 12619).

**STANDARD PREVIEW**  
(standards.iteh.ai)

Markings shall remain legible for the life of the component and shall not be removed without destroying or defacing the marking. Permanent adhesive labels are permissible, or markings may be etched, stamped, or moulded into the component.

NOTE 1 Specific information required for each component can be found in ISO 12619-4 and subsequent parts of ISO 12619.

NOTE 2 This information can be provided by a suitable identification code on at least one part of the component when it consists of more than one part.

### 5 Construction and assembly

The manual cylinder valve shall comply with the applicable provisions of ISO 12619-1 and ISO 12619-2, and with the tests specified in [Clause 6](#).

## 6 Tests

### 6.1 Applicability

The tests required to be carried out are indicated in [Table 1](#).

**Table 1 — Tests applicable**

Test	Applicable	Test procedure as required by ISO 12619-2	Specific test requirements of this part of ISO 12619
Hydrostatic strength	X	X	X (see <a href="#">6.2</a> )
Leakage	X	X	X (see <a href="#">6.3</a> )
Excess torque resistance	X	X	—
Bending moment	X	X	—
Continued operation	X	X	X (see <a href="#">6.4</a> )
Corrosion resistance	X	X	—
Oxygen ageing	X	X	—
Ozone ageing	X	X	—
N-pentane	X	X	—
Heat ageing	X	X	—
Electrical over-voltages	—	—	—
Non-metallic material immersion	X	X	—
Pre-cooled hydrogen exposure test	X	—	X
Material requirements	X	—	—
Non-metallic material compatibility to hydrogen	X	—	X
Automotive fluid exposure	X	—	X
Vibration resistance	X	X	—
Brass material compatibility	X	X	—

### 6.2 Hydrostatic strength

Test the manual cylinder valve according to the procedure for testing hydrostatic strength specified in ISO 12619-2. The test pressure shall be twice the working pressure.

### 6.3 Leakage

Test the manual cylinder valve at the temperatures and pressures given in [Table 2](#).

**Table 2 — Test temperatures and pressures**

Temperature °C	Pressure MPa (bar)	
	First	Second
-40 or -20 as applicable	0,75 × WP	0,025 × WP
20	0,025 × WP	1,5 × WP
85	0,05 × WP	

## 6.4 Continued operation

**6.4.1** Test the manual cylinder valve in accordance with the procedure for testing continued operation given in ISO 12619-2, for 2 000 cycles, but lower the downstream pressure of the test fixture to less than 0,5 MPa (5 bar), and perform the leakage test in accordance with [6.3](#).

**6.4.2** Following cycling and leakage re-testing, the manual cylinder valve shall be capable of completely opening and closing when a torque no greater than the appropriate one specified in [Table 3](#) is applied to the component handle in a direction that opens it completely and in the opposite direction. The test shall be conducted with the valve pressurized at service pressure

**Table 3 — Torque test**

Test Temperature	Ambient Temperature	-40 °C
Component inlet size mm	Max. torque N·m	Max. torque N·m
6	1,7	3,4
8 or 10	2,3	4,5
12	2,8	11,3

**6.4.3** Conduct the test at the appropriate maximum temperature according to ISO 12619-1:2014, 4.4, then repeat the test at a temperature of -40 °C and with the appropriate maximum torque specified in [Table 3](#) above

**6.4.4** Following cycling and leakage re-testing and the torque testing, perform the hydrostatic test in accordance with [6.2](#).

iTeH STANDARD PREVIEW  
(standards.iteh.ai)  
ISO 12619-5:2016  
<https://standards.iteh.ai/catalog/standards/sist/f7f83724-484b-4003-b27e-a9d3e9b1710a/iso-12619-5-2016>



## Bibliography

- [1] ISO 3833, *Road vehicles — Types — Terms and definitions*
- [2] ISO 6722-1, *Road vehicles — 60 V and 600 V single-core cables — Part 1: Dimensions, test methods and requirements for copper conductor cables*
- [3] ISO 6722-2, *Road vehicles — 60 V and 600 V single-core cables — Part 2: Dimensions, test methods and requirements for aluminium conductor cables*
- [4] ISO 6722-3<sup>1)</sup>, *Road vehicles — Unscreened low-tension cables — Part 3: Conductor sizes and dimensions for thick-wall insulated cables*
- [5] ISO 6722-4<sup>2)</sup>, *Road vehicles — Unscreened low-tension cables — Part 4: Conductor sizes and dimensions for thin-wall insulated cables*
- [6] ISO 12619-3, *Road vehicles — Compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blend fuel system components — Part 3: Pressure regulator*
- [7] ISO 14687-1, *Hydrogen fuel — Product specification — Part 1: All applications except proton exchange membrane (PEM) fuel cell for road vehicles*
- [8] ISO 14687-2, *Hydrogen fuel — Product specification — Part 2: Proton exchange membrane (PEM) fuel cell applications for road vehicles*
- [9] ISO 15403-1, *Natural gas — Natural gas for use as a compressed fuel for vehicles — Part 1: Designation of the quality*
- [10] ISO/TR 15403-2, *Natural gas - Natural gas for use as a compressed fuel for vehicles — Part 2: Specification of the quality*
- [11] ISO/TS 15869, *Gaseous hydrogen and hydrogen blends — Land vehicle fuel tanks*

---

1) Withdrawn.

2) Withdrawn.