

---

---

**Ships and marine technology —  
Navigation and ship operations —  
Electronic inclinometers**

*Navires et technologie maritime — Navigation et opérations  
maritimes — Inclinomètres électroniques*

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

ISO 19697:2016

<https://standards.iteh.ai/catalog/standards/iso/2b12f39c-b664-47aa-9b4f-3aa2b15e492a/iso-19697-2016>



iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

ISO 19697:2016

<https://standards.iteh.ai/catalog/standards/iso/2b12f39c-b664-47aa-9b4f-3aa2b15e492a/iso-19697-2016>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
[copyright@iso.org](mailto:copyright@iso.org)  
[www.iso.org](http://www.iso.org)

# Contents

Page

<b>Foreword</b>	<b>v</b>
<b>Introduction</b>	<b>vi</b>
<b>1 Scope</b>	<b>1</b>
<b>2 Normative references</b>	<b>1</b>
<b>3 Terms and definitions</b>	<b>2</b>
<b>4 Requirements</b>	<b>3</b>
4.1 General	3
4.2 Functionality	3
4.3 Information	3
4.3.1 Actual heel angle and roll amplitude	3
4.3.2 Roll period	3
4.3.3 Roll peak hold value	3
4.4 Display	4
4.5 Alerts	4
4.5.1 Operational alerts	5
4.5.2 Functional alerts	5
4.6 Interface	6
4.7 Power supply	6
<b>5 Accuracy</b>	<b>6</b>
5.1 Actual heel angle, roll amplitude and roll period	6
5.2 Acceleration condition	6
<b>6 Test methods and required results</b>	<b>6</b>
6.1 General	6
6.2 Static actual heel angle test	7
6.2.1 Method of testing and required results	7
6.3 Dynamic actual heel angle test	7
6.3.1 Method of testing and required results	7
6.4 Long-term actual heel angle test	7
6.4.1 Method of testing and required results	7
6.5 Roll period test	8
6.5.1 Method of testing and required results	8
6.6 Connections to other equipment test	8
6.6.1 Method of testing and required results	8
6.7 Display test	8
6.7.1 Method of testing and required results	8
6.8 Operational alert test	10
6.8.1 Method of testing and required results	10
6.9 Functional alert test	11
6.9.1 Method of testing and required results	11
6.10 Roll peak hold value test	11
6.10.1 Method of testing and required results	11
6.11 Reset function of roll peak hold value test	11
6.11.1 Method of testing and required results	12
6.12 Power supply test	12
<b>7 Installation position</b>	<b>12</b>
<b>8 Information</b>	<b>12</b>
<b>Annex A (informative) Relationship between transverse metacentric stability and measured natural roll period of ships in waves</b>	<b>13</b>
<b>Annex B (informative) Test facility type test methodology</b>	<b>16</b>
<b>Annex C (informative) IEC 61162-1 interface for VDR and other systems</b>	<b>17</b>

**iTeh Standards**  
**(<https://standards.itih.ai>)**  
**Document Preview**

ISO 19697:2016

<https://standards.itih.ai/catalog/standards/iso/2b12f39c-b664-47aa-9b4f-3aa2b15e492a/iso-19697-2016>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

The committee responsible for this document is ISO/TC 8, *Ships and marine technology*, Subcommittee SC 6, *Navigation and ship operations*.

This first edition cancels and replaces ISO/PAS 19697:2014.

ISO 19697:2016

<https://standards.iteh.ai/catalog/standards/iso/2b12f39c-b664-47aa-9b4f-3aa2b15e492a/iso-19697-2016>

## Introduction

An electronic inclinometer is an electronic device that provides information about roll period, roll amplitude and the heel angle of the ship. *Electronic inclinometers are intended to support the decision-making process on board in order to avoid dangerous situations, as well as assist in and facilitate maritime casualty investigation.* The requirements in this document take into account human factors, ergonomic principles and advances in technology.

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

ISO 19697:2016

<https://standards.iteh.ai/catalog/standards/iso/2b12f39c-b664-47aa-9b4f-3aa2b15e492a/iso-19697-2016>

# Ships and marine technology — Navigation and ship operations — Electronic inclinometers

## 1 Scope

This document specifies the performance requirements, methods of testing and test results of electronic inclinometers required by the performance standard, IMO resolution MSC.363 (92), in addition to the general requirements contained in resolution A.694 (17) and is associated with IEC 60945.

The electronic inclinometers provide information about actual heel angle, roll amplitude, roll period to support decision-making process on board in order to avoid dangerous situations, in stability (see [Annex A](#) for information), as well as to assist in maritime casualty investigation. The electronic inclinometers are mainly composed of a set of sensors, a signal processor, a display, an input device and an interface to other systems.

It does not apply to the electronic inclinometers installed for purposes which are outside the scope of this document, e.g. monitoring of cargo status.

Where a requirement in this document is different from IEC 60945, the requirement in this document takes precedence.

**NOTE** All requirements that are extracted from the recommendations of IMO Resolution MSC.363 (92), performance standards for electronic inclinometers, are printed in italics and the resolution and paragraph numbers are indicated in brackets.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems — General requirements — Methods of testing and required test results*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems — Digital interfaces — Part 1: Single talker and multiple listeners*

IEC 61162-2, *Maritime navigation and radiocommunication equipment and systems — Digital interfaces — Part 2: Single talker and multiple listeners, high-speed transmission*

IEC 61924-2, *Maritime navigation and radiocommunication equipment and systems — Integrated navigation systems — Part 2: Modular structure for INS — Operational and performance requirements, methods of testing and required test results*

IEC 62288, *Maritime navigation and radiocommunication equipment and systems — Presentation of navigation-related information on shipborne navigational displays — General requirements, methods of testing and required test results*

IMO resolution MSC.191 (79), *Performance standard for the presentation of navigation-related information on shipborne navigational displays*

IMO resolution MSC.252 (83), *Performance standards for Integrated Navigation Systems (INS)*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp/>

#### 3.1 actual heel angle

*momentary angle of roll referenced to a levelled ship to port or starboard side*

[SOURCE: IMO MSC.363 (92), Par. 3.1]

#### 3.2 analogue type display

*display (3.3) that shows actual heel angle (3.1), roll amplitudes (3.7) and roll peak hold values (3.9) in a continuous way, such as by means of an arrow pointer and graduated scale*

#### 3.3 digital type display

*display (3.3) that shows actual heel angle (3.1), roll amplitudes (3.7) and roll peak hold values (3.9) in the form of numbers*

#### 3.4 display

*means by which the roll behaviour of the ship and the state of the electronic inclinometer system are presented to an observer*

#### 3.5 inspection equipment

*equipment for testing the performance of the electronic inclinometer*

#### 3.6 reset function for roll peak hold value

*function for resetting roll peak hold values (3.9) to zero and for recording reset date (month, day and year) and time*

#### 3.7 roll amplitude

*maximum values of heel angle to port or starboard side*

[SOURCE: IMO MSC.363 (92), Par. 3.1]

#### 3.8 roll period

*time between two successive maximum values of heel angle on the same side of the ship*

[SOURCE: IMO MSC.363 (92), Par. 3.1]

#### 3.9 roll peak hold value

*maximum values of roll amplitude (3.7) to port or starboard side from the last reset*

#### 3.10 rolling

*motion around the longitudinal axis of the ship*

Note 1 to entry: Positive roll is starboard down.



[SOURCE: IMO MSC.363 (92), Par. 3.1]

### 3.11

#### **zero crossing method**

way for measuring wave period by using a zero crossing which is a point where the sign of a measured value (roll angle) changes

EXAMPLE From positive to negative.

## 4 Requirements

### 4.1 General

Users of this document shall note that while attempting to implement the requirements, they shall ensure compliance with such statutory requirements, rules and regulations so as to be applicable to the individual ship concerned.

### 4.2 Functionality

[IMO MSC.363 (92) Par. 1.2] *The electronic inclinometers shall in a reliable form*

- a) *determine the actual heel angle with the required accuracy,*
- b) *determine the roll amplitude with the required accuracy,*
- c) *determine the roll period with the required accuracy,*
- d) *present the information on a bridge display, and*
- e) *provide a standardized interface to instantaneous heel angle to the voyage data recorder (VDR).*

### 4.3 Information

#### 4.3.1 Actual heel angle and roll amplitude

[IMO MSC.363 (92) Par. 4] *Electronic inclinometers shall be capable of measuring the actual heel angle and determining the amplitude of the rolling oscillation of the ship over a range of  $\pm 90^\circ$ .*

#### 4.3.2 Roll period

[IMO MSC.363 (92) Par. 5] *Electronic inclinometers shall be capable of measuring the time between the maximum values of the rolling oscillation and determining the roll period over a minimum range of 4 s to 40 s.*

If enough precision is not attained, the period may be measured by the “zero crossing method”.

#### 4.3.3 Roll peak hold value

Electronic inclinometers may optionally record the roll peak hold values on both sides and present them on any kind of display.

If optional recording of the roll peak hold values is provided, electronic inclinometers shall have a mean of manually resetting the roll peak hold values by a single operator action.

If necessary, the following sentences may be provided for the reset of roll peak hold value:

\$-TXT,01,01,01,EI\_RPHVReset\_yyyy\_mm\_dd oo\_nn\_ss\*hh < CR > < LF > (see IEC 61162-1)

where:

- “yyyy” is the reset year;
- “mm” is the reset month;
- “dd” is the reset day;
- “oo” is the reset hour;
- “nn” is the reset minute;
- “ss” is the reset second;
- “hh” is the check sum;
- TXT (see IEC 61162-1).

#### 4.4 Display

[IMO MSC.363 (92) Par. 7.2] *The actual heel angle to port or starboard shall be indicated in an analogue form between the limits of  $\pm 45^\circ$ . When the actual heel angle exceeds  $45^\circ$  to either side, the analogue display is permitted to remain at  $45^\circ$ .*

[IMO MSC.363 (92) Par. 7.1.2] *Electronic inclinometers shall display the roll amplitude to both port and starboard side with a minimum resolution of  $1^\circ$ .*

Electronic inclinometers may optionally display the roll peak hold value for both sides, port and starboard, with a minimum resolution of  $1^\circ$ . They may also optionally display its reset date/time or relative time from the reset, if the roll peak hold value function is installed.

[IMO MSC.363 (92) Par. 7.1.1] *Electronic inclinometers shall display the latest roll period with a minimum resolution of 1 s.*

[IMO MSC.363 (92) Par. 7.3] *The display may be implemented as a dedicated display or integrated into other bridge systems.*

#### 4.5 Alerts

Electronic inclinometer may provide operational alerts as described in [4.5.1](#) and shall provide functional alerts as described in [4.5.2](#).

The alerts shall conform to protocol requirements of [IMO MSC.252 (83)] as specified in IEC 61924-2. The presentation of alerts shall conform to the presentation requirements of [IMO MSC.191 (79)] as specified in IEC 62288.

[IMO MSC.363 (92) Par. 10.2] *Electronic inclinometers shall have a bidirectional interface to facilitate communication, to transfer alerts from inclinometers to external systems, and to acknowledge and silence alerts from external systems.*

All alerts provided in the electronic inclinometer shall be output via alert communications interface.

The following sentences shall be provided for the alert communications interface.

Sentences transmitted by the electronic inclinometers:

- ALC and ALF (see IEC 61924-2).

Sentences received by the electronic inclinometers:

- ACN (see IEC 61924-2).