

SLOVENSKI STANDARD
oSIST prEN ISO 8222:2019
01-maj-2019

Naftni merilni sistemi - Umerjanje - Temperaturne korekcije pri kalibriranju prostornine etalonskih posod (ISO/DIS 8222:2019)

Petroleum measurement systems - Calibration - Temperature corrections for use when calibrating volumetric proving tanks (ISO/DIS 8222:2019)

Messsysteme für Mineralölerzeugnisse - Kalibrierung - Temperaturkorrekturen zur Anwendung auf volumetrische Bezugsmessbehälter (ISO/DIS 8222:2019)

Systèmes de mesure du pétrole - Étalonnage - Corrections de température à utiliser lors de l'étalonnage des jauges étalons (ISO/DIS 8222:2019)

Ta slovenski standard je istoveten z: prEN ISO 8222

ICS:

75.180.30	Oprema za merjenje prostornine in merjenje	Volumetric equipment and measurements
-----------	--	---------------------------------------

oSIST prEN ISO 8222:2019

en,fr,de

ITeH STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/14bd797-13e4-4088-842a-e434a3fb2c3/osist-pr-en-iso-8222-2019>

DRAFT INTERNATIONAL STANDARD

ISO/DIS 8222

ISO/TC 28/SC 2

Secretariat: BSI

Voting begins on:
2019-03-19Voting terminates on:
2019-06-11

Petroleum measurement systems — Calibration — Temperature corrections for use when calibrating volumetric proving tanks

*Systèmes de mesure du pétrole — Étalonnage — Corrections de température à utiliser lors de l'étalonnage
des jauges étalons*

ICS: 75.180.30

ITEH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/14bd797-13e4-44b8-842a-e4344a3fb2c3/osist-pr-en-iso-8222-2019>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

This document is circulated as received from the committee secretariat.

ISO/CEN PARALLEL PROCESSING



Reference number
ISO/DIS 8222:2019(E)

© ISO 2019

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/14bd797-13e4-4088-842a-e4344a3fb2c3/osist-pr-en-iso-8222-2019>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Foreword.....	3
Introduction.....	4
1 Scope.....	5
2 Normative references.....	5
3 Definitions and symbols.....	6
3.1 Definitions.....	6
3.2 Symbols and units.....	12
4 Traceability.....	13
5 General design characteristics of volumetric measures.....	15
5.1 General design.....	15
5.2 Design to indicate the volume. Resolution.....	16
5.3 Additional design aspects.....	20
5.4 Filling and drainage.....	22
5.5 Markings.....	25
6 Test measures.....	25
6.1 Overview.....	25
6.2 Construction.....	28
7 Proving tanks.....	29
7.1 Overview.....	29
7.2 General construction.....	34
7.3 Bottom neck.....	34
7.4 Strength.....	34
7.5 Support.....	34
7.6 Size.....	34
7.7 Mobility.....	34
7.8 Overflow and vapour recovery.....	35
7.9 Filling and drainage.....	35
8 Alternative designs.....	35
8.1 High accuracy designs.....	35
8.2 Automatic pipettes.....	35
8.3 Proving tanks with bottom sight gauge.....	36
9 Calibration.....	36
9.1 General.....	36
9.2 Gravimetric calibration.....	38
9.3 Volumetric calibration.....	40
9.4 Calibration by reference meter.....	43
9.5 Calibration of neck scales.....	45
10 Calculations.....	46

ISO/DIS 8222:2019(E)

10.1	Overview	46
10.2	Reference volume	46
10.3	Transferred volume (volumetric method)	47
10.4	Transferred volume (gravimetric method)	48
10.5	Calibrated volume of test device	48
10.6	Multiple fills	50
10.7	Calibration of a measure using a reference measure	50
10.8	Calibrations using a flowmeter	50
10.9	Calibration of a small volume prover	51
11	Calibrating and setting the neck and scale	51
11.1	Calibrating the neck	51
11.2	Setting the scales	52
12	Safety	52
	Bibliography	52
ANNEX A.	(Normative) Properties of fluids and materials	54
ANNEX B.	(Informative) Temperature measurement and thermometers	68
ANNEX C.	(Informative) Standard glass contents measures	69
ANNEX D.	(Informative) Meniscus reading	71
ANNEX E.	(Informative) Accuracy and uncertainty of volumetric measures	73

Error! Reference source not found.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 28, *Petroleum products and lubricants*, Subcommittee SC 2, *Dynamic petroleum measurement*.

This third edition cancels and replaces the second edition (ISO 8222:2002: Petroleum measurement systems — Calibration — Temperature corrections for use when calibrating volumetric proving tanks), which has been extensively revised in both scope and content.

This revision extends the scope of ISO 8222:2002 to cover the design calibration and use of a wide range of volumetric measures and proving tanks. This revision is based on the draft TC 28 SC2 ISO DIS 12916:1998. This document was balloted to proceed to FDIS but no further action was taken and the document dropped from the programme.

Annex A of this document forms an integral part of this International Standard and contains the revised, extended and updated content from ISO 8222:2002. This provides options for formulae covering the properties of pure through to saline water, and also includes other materials and fluids used with volumetric measurement. Annex A provides formulae and updated formulae for other standards and measurements currently referring to ISO 8222:2002.

Introduction

Volumetric, or capacity, measures are used to provide an accurate measure of a volume hence providing a calibration reference for other volume measuring devices e.g. pipe displacement provers or flowmeters.

Volume measures are categorized in terms of capacity, test measures being below 20 l. Measures above 20 l are categorised as prover tanks. Standard measures are designed to comply with regulatory guidance and hence have specified volumes. Many measures have non-standard volumes specifically designed to suit an application e.g. measures to accompany a small volume prover.

Volumetric measures can be used to calibrate flowmeters, both duty and reference meters. They may also be used to calibrate secondary volume measures, pipe provers and storage tanks.

This document provides guidance for the design, calibration and use of volumetric measures in general, applies to all suitable liquids and is not restricted to hydrocarbon liquid applications.

Annex A provides the recommended formulae used in the calibration and use of volumetric measures and other volumetric measurements. This annex supersedes and extends the scope of ISO 8222:2002 by including pure and saline water properties. It now also includes the properties of hydrocarbon liquids and materials of construction of volumetric measuring devices.

This document gives guidance on both standard and non-standard measures. The requirements for regulatory or contractual requirements such as those given in OIML and National regulations will take precedence over the guidance given in this document.

ITEH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/14bd797-13e4-44b8-842a-e4344a3fb2c3/osist-pr-en-iso-8222-2019>

Error! Reference source not found.

WARNING — The use of this document may involve hazardous materials, operations and equipment. This International Standard does not purport to address all of the safety problems associated with its use. It is the responsibility of the user of this document to establish appropriate safety and health practices.

1 Scope

1.1 This document describes the design, use and calibration of volumetric measures (capacity measures) which are intended for use in fixed locations in a laboratory or in the field. It also covers portable and mobile measures. The scope covers applications particularly, but not exclusively, in the petroleum industry. Volumetric measures are classified as test measures or prover tanks depending on capacity and design.

1.2 The document excludes pressurised measures as used for LPG and LNG and measures for cryogenic liquids. Measures described in this document are primarily designed, calibrated and used to measure volumes "to deliver", i.e. wetted and drained for a specified time before use. Many of the provisions will however apply equally to measures which are used "to contain", i.e. to measure a volume using a clean and dry measure.

1.3 Annex A provides a reference for formulae describing the properties of water and other materials used to define volume. This includes density, thermal expansion, compressibility and viscosity for pure, impure and saline water. It also provides property information for hydrocarbon liquids and materials used to construct measures.

1.4 Guidance is given regarding commonly expected uncertainties and calibration specifications.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 4006:1991, *Measurement of fluid flow in closed conduits — Vocabulary and symbols*

JCGM 200:2012, *International vocabulary of metrology — Basic and general concepts and associated terms (VIM 2012)*

3 Definitions and symbols

3.1 Definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1.1

accuracy

closeness of the agreement between the measured quantity value and a true quantity value of a measurand

[SOURCE: VIM:2012]

Note 1 to entry: The concept "measurement accuracy" is not a quantity and should not be given a numerical value. The quantitative expression of accuracy should be in terms of uncertainty. "Good accuracy" or "more accurate" implies small measurement error. Any given numerical value should be taken as indicative of this.

3.1.2

adjustment

set of operations carried out on a measuring system so that it provides prescribed indications corresponding to given values of the quantity measured

[SOURCE: VIM:2012^[1]]

EXAMPLE This entails bringing a measuring instrument (meter) into a satisfactory performance and accuracy.

Note 1 to entry: Adjustment should not be confused with calibration which will be prerequisite for adjustment.

Note 2 to entry: After adjustment a recalibration is usually required.

3.1.3

automatic pipette overflow pipette

high precision measure, where the volume withdrawn is defined by a top overflow weir rather than a gauge scale

3.1.4

brim measure

field measure where the volume is defined by an overflow from the top edge of the neck

3.1.5

calibration

set of operations that establish, under specified conditions, the relationship between quantities indicated by an instrument and the corresponding values realized by standards

[SOURCE: VIM 1993^[1] and VIM:2012^[2]]

Note 1 to entry: Calibration should not be confused with adjustment of a measuring system.

Note 2 to entry: The term "proving" is used in the oil industry and has the same meaning but will include a check of the results against specified acceptance criteria.

3.1.6

calibrated volume

volume of a measure between a top and bottom datum as determined by calibration and expressed at a standard temperature

3.1.7

clingage

film of liquid that adheres to the inside surface of a volumetric measure after it has been emptied resulting in a residual volume

Error! Reference source not found.

3.1.8

correction factor

numerical factor by which the uncorrected result of a measurement at the measured conditions is multiplied

Note 1 to entry: Correction factors to standard conditions are used to convert a volume at observed conditions to the volume at another (standard) condition.

3.1.9

displacement plunger plunger

device consisting of a piston which is used for adjusting the volume of a volumetric measure

3.1.10

drain time

total time taken to empty the measure or tank to leave a consistent residual volume

Note 1 to entry: Drain time commences when the drain valve is opened and ceases when closed after a defined time or condition. Drain time may be divided into two parts; first drain time and final drain time.

3.1.11

drain time (final)

in a two stage emptying process it follows the cessation of the first drain time and finishes at a defined time or condition e.g. rate of dripping

3.1.12

drain time (first)

in a two stage emptying process it is the time to drain the majority of the fluid from the measure

Note 1 to entry: The first drainage flow commences when the drain valve is opened and ends at a defined level or when flow breaks into a defined trickle or drip rate. This will be prior to the start of the final drain time.

Note 2 to entry: A dry measure may be employed where the product evaporates quickly e.g. petrol. These measures are usually specified elsewhere however many of the provisions and methods described in this document may apply.

3.1.13

dry measure

contents measure which is calibrated and used with the internal surface completely dry (i.e no clingage or residual volume)

Note 1 to entry: A dry measure is marked "to contain" the specified volume.

3.1.14

error

measured value minus a reference value

[SOURCE: VIM:2012]

Note 1 to entry: Relative error is error divided by a reference value. This can be expressed as a percentage.

3.1.15

field measure

a measure designed to be used in the regular calibration of other devices

Note 1 to entry: While most field measures are portable, some may be in a fixed location.

3.1.16

gauge glass

clear tube in parallel with, or a window set into, the neck to show the level of liquid in the neck

Note 1 to entry: There will be an associated scale to indicate the measured volume.

3.1.17

nominal volume

design volume of a volumetric measure

ISO/DIS 8222:2019(E)

3.1.18**Primary measure**

A reference measure calibrated gravimetrically, normally by a National standard or suitably accredited laboratory.

3.1.19 proving

calibration with comparison to defined acceptance criteria

Note 1 to entry: Proving is a term used in the oil industry and is similar to "verification".

Note 2 to entry: Proving is a calibration, sometimes of limited measurement range, according to methods defined by standards, regulation or procedures providing a determination of the errors of a device and showing (proving) it performs to defined acceptance criteria.

3.1.20**proving tank**

volumetric measure which generally has capacity greater than 20 L and has a bottom drain

Note 1 to entry: A prover tank may be free standing or mounted on a truck or trailer.

3.1.21**pour**

individual quantities of liquid poured from, or received into, a volumetric measure

3.1.22**range****range of values**

difference between the maximum and minimum values of a set of values

Note 1 to entry: This can be expressed as a half range (\pm) number. Relative range will normally be expressed as a percentage of a specified value e.g. mean, minimum or other calculated value.

3.1.23**reference (operating) conditions**

operating conditions prescribed for evaluating the performance of the measure

Note 1 to entry: This is the range of ambient and fluid conditions with which the measure is evaluated, verified or operated.

3.1.24**reference measure**

volumetric measure calibrated, used and maintained to provide traceability to other volume measures and devices, including pipe provers and reference flowmeters

Note 1 to entry: A reference measure should be calibrated gravimetrically (primary measure) or volumetrically by means of a primary measure which itself has been calibrated gravimetrically.

3.1.25**repeatability**

(measurement precision)

closeness of agreement between indications or measured quantity values obtained by replicate measurements under specified conditions

[SOURCE: VIM:2012]

Note 1 to entry: Specified conditions will normally imply the same reference, same conditions, same operators and procedures and that the data are obtained sequentially over a short period of time.

Note 2 to entry: Repeatability can be expressed as the range (difference between the maximum and minimum) values of error or K-factor. Alternatively, repeatability can be expressed as a function of the standard deviation of the values.

Note 3 to entry: Dividing repeatability by the mean will give the relative value which can be expressed as a percentage. It is noted some standards suggest dividing by the minimum value.

Error! Reference source not found.

3.1.26

residual volume

volume or quantity remaining in the measure after draining for the defined drain time

3.1.27

resolution

quantitative expression of the ability of an indicating device to distinguish meaningfully between closely adjacent values of the quantity indicated

3.1.28

scale datum

fixed reference point or mark, established at manufacture or initial calibration, from which subsequent adjustments to the scale can be referred

Note 1 to entry: This may be an engraved mark on the neck or another defined fixed point such as a support bracket. The location should be referenced on calibration certificates.

3.1.29

secondary measure

volumetric measure which is calibrated by a primary measure

3.1.30

standard conditions

conditions of temperature and pressure to which measurements of volume or density are referred to standardize the quantity

Note 1 to entry: These are the specified values of the conditions to which the measured quantity is converted.

Note 2 to entry: For the petroleum industry, these are usually 15 °C, 20 °C or 60 °F and 101.325 kPa.

Note 3 to entry: Standard conditions may refer to the liquid or the volume of the measure. These may be different.

Note 4 to entry: Quantities expressed at standard conditions are shown by prefixing the volume unit by "S", e.g. 4 Sm³ or 700 kg/Sm³.

Note 5 to entry: Definition taken from Energy Institute HM 0 and OIML R 117. Some other petroleum standards employ the term "base" conditions.

Note 6 to entry: "Reference" conditions are conditions of use (influence quantities) prescribed for testing the performance of a measuring instrument [SOURCE: VIM:1993].

3.1.31

standard measure

volumetric measure which is designed to meet the requirements of regulatory standards (e.g. OIML R 120, NIST 105-3)

3.1.32

standard volume (base volume)

volume expressed as being at standard conditions

3.1.33

strike measure

brim measure where the volume is defined from the top edge of the neck which has been designed to be "struck" by sliding a ground glass disk over it to leave a consistent volume within the measure

3.1.34

test measure

hand portable volumetric measure up to 20 l capacity

Note 1 to entry: A test measure may be inverted to drain or fitted with a bottom drain.

Note 2 to entry: A test measure may also be non-portable, in a fixed frame or on a vehicle. It may in some cases be classified as a prover tank.