

ETSI TS 136 101 V12.31.0 (2023-05)



LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 12.31.0 Release 12)

[ETSI TS 136 101 V12.31.0 \(2023-05\)](https://standards.iteh.ai/catalog/standards/sist/6a472564-3992-4bac-a9b5-cla1b3ea17d2/etsi-ts-136-101-v12-31-0-2023-05)

<https://standards.iteh.ai/catalog/standards/sist/6a472564-3992-4bac-a9b5-cla1b3ea17d2/etsi-ts-136-101-v12-31-0-2023-05>



Reference

RTS/TSGR-0436101Vcv0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards-portal.etsi.org/standards-portal> <https://portal.etsi.org/People/CommitteeSupportStaff.aspx> 4bac-a9b5-4b4c-4b4c-4b4c@etsi.org

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	19
1 Scope	20
2 References	20
3 Definitions, symbols and abbreviations	20
3.1 Definitions	20
3.2 Symbols.....	22
3.3 Abbreviations	24
4 General	25
4.1 Relationship between minimum requirements and test requirements	25
4.2 Applicability of minimum requirements	26
4.3 Void.....	26
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0).....	26
4.4 RF requirements in later releases	27
5 Operating bands and channel arrangement.....	27
5.1 General	27
5.2 Void.....	27
5.3 Void.....	27
5.4 Void.....	27
5.5 Operating bands.....	27
5.5A Operating bands for CA	29
5.5B Operating bands for UL-MIMO	33
5.5C Operating bands for Dual Connectivity.....	33
5.5D Operating bands for ProSe.....	34
5.5E Operating bands for UE category 0	35
5.6 Channel bandwidth.....	35
5.6.1 Channel bandwidths per operating band.....	36
5.6A Channel bandwidth for CA.....	37
5.6A.1 Channel bandwidths per operating band for CA.....	39
5.6B Channel bandwidth for UL-MIMO	48
5.6B.1 Void	48
5.6C Channel bandwidth for Dual Connectivity	48
NOTE 2: For TDD inter-band dual connectivity configurations, requirements are applicable only for synchronous operation.5.6C.1.....	Void
5.6D Channel bandwidth for ProSe.....	48
5.6D.1 Channel bandwidths per operating band for ProSe.....	48
5.7 Channel arrangement.....	49
5.7.1 Channel spacing	49
5.7.1A Channel spacing for CA.....	49
5.7.2 Channel raster	49
5.7.2A Channel raster for CA	49
5.7.3 Carrier frequency and EARFCN.....	49
5.7.4 TX–RX frequency separation	50
5.7.4A TX–RX frequency separation for CA	51
6 Transmitter characteristics	51
6.1 General	51
6.2 Transmit power	51
6.2.1 Void	51

6.2.2	UE maximum output power.....	51
6.2.2A	UE maximum output power for CA.....	52
6.2.2B	UE maximum output power for UL-MIMO.....	54
6.2.3	UE maximum output power for modulation / channel bandwidth.....	55
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA.....	56
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO.....	57
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe.....	57
6.2.4	UE maximum output power with additional requirements.....	58
6.2.4A	UE maximum output power with additional requirements for CA.....	66
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C.....	67
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C.....	68
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C.....	68
6.2.4A.4	A-MPR for CA_NS_04.....	69
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C.....	70
6.2.4A.6	A-MPR for CA_NS_06.....	70
6.2.4A.7	A-MPR for CA_NS_07.....	71
6.2.4A.8	A-MPR for CA_NS_08.....	72
6.2.4B	UE maximum output power with additional requirements for UL-MIMO.....	73
6.2.4D	UE maximum output power with additional requirements for ProSe.....	73
6.2.5	Configured transmitted power.....	73
6.2.5A	Configured transmitted power for CA.....	80
6.2.5B	Configured transmitted power for UL-MIMO.....	81
6.2.5C	Configured transmitted power for Dual Connectivity.....	82
6.2.5D	Configured transmitted power for ProSe.....	83
6.3	Output power dynamics.....	84
6.3.1	(Void).....	84
6.3.2	Minimum output power.....	84
6.3.2.1	Minimum requirement.....	84
6.3.2A	UE Minimum output power for CA.....	84
6.3.2A.1	Minimum requirement for CA.....	84
6.3.2B	UE Minimum output power for UL-MIMO.....	85
6.3.2B.1	Minimum requirement.....	85
6.3.3	Transmit OFF power.....	85
6.3.3.1	Minimum requirement.....	85
6.3.3A	UE Transmit OFF power for CA.....	86
6.3.3A.1	Minimum requirement for CA.....	86
6.3.3B	UE Transmit OFF power for UL-MIMO.....	86
6.3.3B.1	Minimum requirement.....	86
6.3.3D	Transmit OFF power for ProSe.....	86
6.3.4	ON/OFF time mask.....	87
6.3.4.1	General ON/OFF time mask.....	87
6.3.4.2	PRACH and SRS time mask.....	87
6.3.4.2.1	PRACH time mask.....	87
6.3.4.2.2	SRS time mask.....	88
6.3.4.3	Slot / Sub frame boundary time mask.....	89
6.3.4.4	PUCCH / PUSCH / SRS time mask.....	89
6.3.4A	ON/OFF time mask for CA.....	90
6.3.4B	ON/OFF time mask for UL-MIMO.....	90
6.3.4D	ON/OFF time mask for ProSe.....	91
6.3.4D.1	General time mask for ProSe.....	91
6.3.4D.2	PSSS/SSSS time mask.....	91
6.3.4D.3	PSSS / SSSS / PSBCH time mask.....	92
6.3.4D.4	PSSCH / SRS time mask.....	93
6.3.5	Power Control.....	93
6.3.5.1	Absolute power tolerance.....	93
6.3.5.1.1	Minimum requirements.....	93
6.3.5.2	Relative Power tolerance.....	94
6.3.5.2.1	Minimum requirements.....	94
6.3.5.3	Aggregate power control tolerance.....	95
6.3.5.3.1	Minimum requirement.....	95
6.3.5A	Power control for CA.....	95
6.3.5A.1	Absolute power tolerance.....	95

6.3.5A.1.1	Minimum requirements	95
6.3.5A.2	Relative power tolerance	95
6.3.5A.2.1	Minimum requirements	95
6.3.5A.3	Aggregate power control tolerance	96
6.3.5A.3.1	Minimum requirements	96
6.3.5B	Power control for UL-MIMO	96
6.3.5D	Power Control for ProSe.....	97
6.3.5D.1	Absolute power tolerance.....	97
6.4	Void.....	97
6.5	Transmit signal quality	97
6.5.1	Frequency error.....	97
6.5.1A	Frequency error for CA.....	97
6.5.1B	Frequency error for UL-MIMO	97
6.5.1D	Frequency error for ProSe.....	97
6.5.2	Transmit modulation quality.....	97
6.5.2.1	Error Vector Magnitude	98
6.5.2.1.1	Minimum requirement.....	98
6.5.2.2	Carrier leakage	98
6.5.2.2.1	Minimum requirements	98
6.5.2.3	In-band emissions	99
6.5.2.3.1	Minimum requirements	99
6.5.2.4	EVM equalizer spectrum flatness	100
6.5.2.4.1	Minimum requirements	100
6.5.2A	Transmit modulation quality for CA.....	101
6.5.2A.1	Error Vector Magnitude	101
6.5.2A.2	Carrier leakage for CA	101
6.5.2A.2.1	Minimum requirements.....	101
6.5.2A.3	In-band emissions	102
6.5.2A.3.1	Minimum requirement for CA.....	102
6.5.2B	Transmit modulation quality for UL-MIMO	103
6.5.2B.1	Error Vector Magnitude	104
6.5.2B.2	Carrier leakage	104
6.5.2B.3	In-band emissions	104
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	104
6.5.2D	Transmit modulation quality for ProSe.....	104
6.5.2D.1	Error Vector Magnitude	104
6.5.2D.2	Carrier leakage	104
6.5.2D.3	In-band emissions	104
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	104
6.6	Output RF spectrum emissions.....	105
6.6.1	Occupied bandwidth	105
6.6.1A	Occupied bandwidth for CA	105
6.6.1B	Occupied bandwidth for UL-MIMO.....	105
6.6.2	Out of band emission	106
6.6.2.1	Spectrum emission mask.....	106
6.6.2.1.1	Minimum requirement.....	106
6.6.2.1A	Spectrum emission mask for CA.....	106
6.6.2.2	Additional spectrum emission mask	107
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21")..	107
6.6.2.2.2	Minimum requirement (network signalled value "NS_04")	108
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	108
6.6.2.2A	Additional Spectrum Emission Mask for CA.....	109
6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04").....	109
6.6.2.3	Adjacent Channel Leakage Ratio.....	109
6.6.2.3.1	Minimum requirement E-UTRA	110
6.6.2.3.1A	Void.....	111
6.6.2.3.1Aa	Void.....	111
6.6.2.3.2	Minimum requirements UTRA	111
6.6.2.3.2A	Minimum requirement UTRA for CA.....	111
6.6.2.3.3A	Minimum requirements for CA E-UTRA.....	113
6.6.2.4	Void.....	113
6.6.2.4.1	Void.....	113

6.6.2A	Void	113
6.6.2B	Out of band emission for UL-MIMO.....	114
6.6.3	Spurious emissions	114
6.6.3.1	Minimum requirements.....	114
6.6.3.1A	Minimum requirements for CA.....	114
6.6.3.2	Spurious emission band UE co-existence	115
6.6.3.2A	Spurious emission band UE co-existence for CA	120
6.6.3.3	Additional spurious emissions	125
6.6.3.3.1	Minimum requirement (network signalled value "NS_05")	125
6.6.3.3.2	Minimum requirement (network signalled value "NS_07").....	125
6.6.3.3.3	Minimum requirement (network signalled value "NS_08").....	126
6.6.3.3.4	Minimum requirement (network signalled value "NS_09").....	126
6.6.3.3.5	Minimum requirement (network signalled value "NS_12").....	126
6.6.3.3.6	Minimum requirement (network signalled value "NS_13").....	127
6.6.3.3.7	Minimum requirement (network signalled value "NS_14").....	127
6.6.3.3.8	Minimum requirement (network signalled value "NS_15").....	127
6.6.3.3.9	Minimum requirement (network signalled value "NS_16").....	127
6.6.3.3.10	Minimum requirement (network signalled value "NS_17").....	128
6.6.3.3.11	Minimum requirement (network signalled value "NS_18").....	128
6.6.3.3.12	Minimum requirement (network signalled value "NS_19").....	128
6.6.3.3.13	Minimum requirement (network signalled value "NS_11").....	128
6.6.3.3.14	Minimum requirement (network signalled value "NS_20").....	129
6.6.3.3.15	Minimum requirement (network signalled value "NS_21").....	129
6.6.3.3.16	Minimum requirement (network signalled value "NS_22").....	129
6.6.3.3.17	Minimum requirement (network signalled value "NS_23").....	130
6.6.3.3.18	Void.....	130
6.6.3.3.19	Minimum requirement (network signalled value "NS_04").....	130
6.6.3.3.20	Void.....	132
6.6.3.3.21	Void.....	132
6.6.3.3.22	Void.....	132
6.6.3.3.23	Void.....	132
6.6.3.3.24	Void.....	132
6.6.3.3.25	Void.....	132
6.6.3.3.26	Void.....	132
6.6.3.3.27	Void.....	132
6.6.3.3.28	Void.....	132
6.6.3.3.29	Void.....	132
6.6.3.3.30	Void.....	132
6.6.3.3.31	Void.....	132
6.6.3.3.32	Void.....	133
6.6.3.3.33	Void.....	133
6.6.3.3.34	Void.....	133
6.6.3.3.35	Minimum requirement (network signalled value "NS_56").....	133
6.6.3.3A	Additional spurious emissions for CA	133
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01").....	133
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02").....	134
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03").....	134
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05").....	134
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06").....	135
6.6.3.3A.6	Minimum requirement for CA_39C (network signalled value "CA_NS_07").....	135
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08").....	135
6.6.3.3A.8	Minimum requirement for CA_41C (network signalled value "CA_NS_04").....	136
6.6.3A	Void.....	136
6.6.3B	Spurious emission for UL-MIMO	136
6.6A	Void.....	136
6.6B	Void.....	136
6.7	Transmit intermodulation.....	136
6.7.1	Minimum requirement	136
6.7.1A	Minimum requirement for CA	137
6.7.1B	Minimum requirement for UL-MIMO.....	137
6.8	Void.....	138
6.8.1	Void.....	138

6.8A	Void.....	138
6.8B	Time alignment error for UL-MIMO	138
6.8B.1	Minimum Requirements	138
7	Receiver characteristics.....	138
7.1	General	138
7.2	Diversity characteristics	139
7.3	Reference sensitivity power level.....	139
7.3.1	Minimum requirements (QPSK).....	139
7.3.1A	Minimum requirements (QPSK) for CA.....	147
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	158
7.3.1D	Minimum requirements (QPSK) for ProSe.....	158
7.3.1E	Minimum requirements (QPSK) for UE category 0	159
7.3.2	Void	160
7.4	Maximum input level	160
7.4.1	Minimum requirements.....	160
7.4.1A	Minimum requirements for CA	161
7.4.1B	Minimum requirements for UL-MIMO	162
7.4.1D	Minimum requirements for ProSe	162
7.4A	Void.....	162
7.4A.1	Void	162
7.5	Adjacent Channel Selectivity (ACS).....	162
7.5.1	Minimum requirements.....	162
7.5.1A	Minimum requirements for CA	163
7.5.1B	Minimum requirements for UL-MIMO	165
7.5.1D	Minimum requirements for ProSe	165
7.6	Blocking characteristics	166
7.6.1	In-band blocking.....	166
7.6.1.1	Minimum requirements.....	166
7.6.1.1A	Minimum requirements for CA.....	167
7.6.1.1D	Minimum requirements for ProSe.....	169
7.6.2	Out-of-band blocking.....	170
7.6.2.1	Minimum requirements.....	170
7.6.2.1A	Minimum requirements for CA.....	171
7.6.2.1D	Minimum requirements for ProSe.....	173
7.6.3	Narrow band blocking	174
7.6.3.1	Minimum requirements.....	174
7.6.3.1A	Minimum requirements for CA.....	175
7.6.3.1D	Minimum requirements for ProSe.....	176
7.6A	Void.....	176
7.6B	Blocking characteristics for UL-MIMO	176
7.7	Spurious response.....	177
7.7.1	Minimum requirements.....	177
7.7.1A	Minimum requirements for CA	177
7.7.1B	Minimum requirements for UL-MIMO	178
7.7.1D	Minimum requirements for ProSe	179
7.8	Intermodulation characteristics	179
7.8.1	Wide band intermodulation.....	179
7.8.1.1	Minimum requirements.....	179
7.8.1A	Minimum requirements for CA	180
7.8.1B	Minimum requirements for UL-MIMO	181
7.8.1D	Minimum requirements for ProSe	181
7.8.2	Void	182
7.9	Spurious emissions	182
7.9.1	Minimum requirements.....	182
7.9.1A	Minimum requirements.....	183
7.10	Receiver image	183
7.10.1	Void	183
7.10.1A	Minimum requirements for CA	183
8	Performance requirement	184
8.1	General	184

8.1.1	Receiver antenna capability	184
8.1.1.1	Simultaneous unicast and MBMS operations.....	185
8.1.1.2	Dual-antenna receiver capability in idle mode	185
8.1.2	Applicability of requirements	185
8.1.2.1	Applicability of requirements for different channel bandwidths.....	185
8.1.2.2	Definition of CA capability	185
8.1.2.2A	Definition of dual connectivity capability	186
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets.....	187
8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	188
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets.....	189
8.1.2.4	Test coverage for different number of component carriers	190
8.1.2.5	Applicability of performance requirements for Type B receiver	191
8.1.3	UE category and UE DL category	191
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	191
8.2.1	FDD (Fixed Reference Channel)	191
8.2.1.1	Single-antenna port performance	191
8.2.1.1.1	Minimum Requirement	192
8.2.1.1.2	Void	194
8.2.1.1.3	Void	194
8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	194
8.2.1.2	Transmit diversity performance	195
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port	195
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	196
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	196
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	198
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	199
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	200
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	201
8.2.1.3	Open-loop spatial multiplexing performance.....	202
8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	202
8.2.1.3.1B	Enhanced Performance Requirement Type C –2Tx Antenna Ports	206
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	206
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	207
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	208
8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	210
8.2.1.4	Closed-loop spatial multiplexing performance	212
8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port.....	212
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	213
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	213
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	215
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	216
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	217
8.2.1.4.2A	Enhanced Performance Requirement Type C – Multi-layer Spatial Multiplexing 2Tx Antenna Ports.....	218
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	219
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	221
8.2.1.5	MU-MIMO.....	222
8.2.1.6	[Control channel performance: D-BCH and PCH]	222
8.2.1.7	Carrier aggregation with power imbalance	222

8.2.1.7.1	Minimum Requirement	222
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset	223
8.2.1.8.1	Minimum Requirement	223
8.2.2	TDD (Fixed Reference Channel)	224
8.2.2.1	Single-antenna port performance	225
8.2.2.1.1	Minimum Requirement	225
8.2.2.1.2	Void	228
8.2.2.1.3	Void	228
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN	228
8.2.2.2	Transmit diversity performance	228
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	228
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	229
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	229
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	231
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model	232
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	233
8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	234
8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	235
8.2.2.3	Open-loop spatial multiplexing performance	236
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port	236
8.2.2.3.1A	Soft buffer management test	238
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	239
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	239
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	240
8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS)	241
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	243
8.2.2.4	Closed-loop spatial multiplexing performance	245
8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	245
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	246
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	246
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	248
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	249
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	250
8.2.2.4.2A	Enhanced Performance Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	251
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	252
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	254
8.2.2.4.4	Void	255
8.2.2.5	MU-MIMO	255
8.2.2.6	[Control channel performance: D-BCH and PCH]	255
8.2.2.7	Carrier aggregation with power imbalance	255
8.2.2.7.1	Minimum Requirement	256
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing	256
8.2.2.8.1	Minimum Requirement	257
8.2.3	TDD FDD CA (Fixed Reference Channel)	257
8.2.3.1	Single-antenna port performance	258
8.2.3.1.1	Minimum Requirement for FDD PCell	258
8.2.3.1.2	Minimum Requirement for TDD PCell	260
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port	261
8.2.3.2.1	Minimum Requirement for FDD PCell	261

8.2.3.2.1A	Soft buffer management test for FDD PCell	263
8.2.3.2.2	Minimum Requirement for TDD PCell	264
8.2.3.2.2A	Soft buffer management test for TDD PCell	266
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port	267
8.2.3.3.1	Minimum Requirement for FDD PCell	267
8.2.3.3.2	Minimum Requirement for TDD PCell	268
8.3	Demodulation of PDSCH (User-Specific Reference Symbols).....	270
8.3.1	FDD	270
8.3.1.1	Single-layer Spatial Multiplexing	271
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	272
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	274
8.3.1.1C	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference model.....	276
8.3.1.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	277
8.3.1.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference model.....	278
8.3.1.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	279
8.3.1.2	Dual-Layer Spatial Multiplexing	280
8.3.1.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	281
8.3.1.3	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	282
8.3.1.3.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	282
8.3.1.3.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources).....	284
8.3.1.3.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	286
8.3.2	TDD	287
8.3.2.1	Single-layer Spatial Multiplexing	287
8.3.2.1A	Single-layer Spatial Multiplexing (with multiple CSI-RS configurations)	289
8.3.2.1B	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	291
8.3.2.1C	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	292
8.3.2.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference.....	294
8.3.2.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	296
8.3.2.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference.....	297
8.3.2.1G	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	298
8.3.2.2	Dual-Layer Spatial Multiplexing	299
8.3.2.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	300
8.3.2.3	Dual-Layer Spatial Multiplexing (with multiple CSI-RS configurations)	301
8.3.2.4	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	302
8.3.2.4.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	302
8.3.2.4.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources).....	304
8.3.2.4.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	305
8.4	Demodulation of PDCCH/PCFICH	307
8.4.1	FDD	307
8.4.1.1	Single-antenna port performance	307
8.4.1.2	Transmit diversity performance	307
8.4.1.2.1	Minimum Requirement 2 Tx Antenna Port	307
8.4.1.2.2	Minimum Requirement 4 Tx Antenna Port	308
8.4.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	308
8.4.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	311
8.4.2	TDD	313
8.4.2.1	Single-antenna port performance	314

8.4.2.2	Transmit diversity performance	314
8.4.2.2.1	Minimum Requirement 2 Tx Antenna Port	314
8.4.2.2.2	Minimum Requirement 4 Tx Antenna Port	315
8.4.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	315
8.4.2.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	317
8.5	Demodulation of PHICH	320
8.5.1	FDD	320
8.5.1.1	Single-antenna port performance	321
8.5.1.2	Transmit diversity performance	321
8.5.1.2.1	Minimum Requirement 2 Tx Antenna Port	321
8.5.1.2.2	Minimum Requirement 4 Tx Antenna Port	321
8.5.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	321
8.5.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	323
8.5.2	TDD	325
8.5.2.1	Single-antenna port performance	325
8.5.2.2	Transmit diversity performance	325
8.5.2.2.1	Minimum Requirement 2 Tx Antenna Port	325
8.5.2.2.2	Minimum Requirement 4 Tx Antenna Port	326
8.5.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	326
8.5.2.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	327
8.6	Demodulation of PBCH	329
8.6.1	FDD	329
8.6.1.1	Single-antenna port performance	329
8.6.1.2	Transmit diversity performance	329
8.6.1.2.1	Minimum Requirement 2 Tx Antenna Port	329
8.6.1.2.2	Minimum Requirement 4 Tx Antenna Port	330
8.6.1.2.3	Minimum Requirement 2 Tx Antenna Port under Time Domain Measurement Resource Restriction with CRS Assistance Information	330
8.6.2	TDD	331
8.6.2.1	Single-antenna port performance	331
8.6.2.2	Transmit diversity performance	331
8.6.2.2.1	Minimum Requirement 2 Tx Antenna Port	331
8.6.2.2.2	Minimum Requirement 4 Tx Antenna Port	332
8.6.2.2.3	Minimum Requirement 2 Tx Antenna Port under Time Domain Measurement Resource Restriction with CRS Assistance Information	332
8.7	Sustained downlink data rate provided by lower layers	333
8.7.1	FDD (single carrier and CA)	333
8.7.2	TDD (single carrier and CA)	337
8.7.3	FDD (EPDCCH scheduling)	340
8.7.4	TDD (EPDCCH scheduling)	341
8.7.5	TDD FDD CA	343
8.7.5.1	Minimum Requirement FDD PCell	344
8.7.5.2	Minimum Requirement TDD PCell	345
8.7.6	FDD (DC)	346
8.7.7	TDD (DC)	349
8.8	Demodulation of EPDCCH	351
8.8.1	Distributed Transmission	351
8.8.1.1	FDD	351
8.8.1.1.1	Void	352
8.8.1.2	TDD	352
8.8.1.2.1	Void	353
8.8.2	Localized Transmission with TM9	353
8.8.2.1	FDD	353
8.8.2.1.1	Void	354
8.8.2.1.2	Void	354
8.8.2.2	TDD	355

8.8.2.2.1	Void.....	356
8.8.2.2.2	Void.....	356
8.8.3	Localized transmission with TM10 Type B quasi co-location type.....	356
8.8.3.1	FDD.....	356
8.8.3.2	TDD.....	358
8.9	Demodulation (single receiver antenna).....	359
8.9.1	PDSCH.....	360
8.9.1.1	FDD and half-duplex FDD (Fixed Reference Channel).....	360
8.9.1.1.1	Transmit diversity performance (Cell-Specific Reference Symbols).....	360
8.9.1.1.2	Closed-loop spatial multiplexing performance (Cell-Specific Reference Symbols).....	361
8.9.1.1.3	Closed-loop spatial multiplexing performance (User-Specific Reference Symbols).....	361
8.9.1.2	TDD (Fixed Reference Channel).....	362
8.9.1.2.1	Transmit diversity performance (Cell-Specific Reference Symbols).....	363
8.9.1.2.2	Closed-loop spatial multiplexing performance (Cell-Specific Reference Symbols).....	363
8.9.1.2.3	Closed-loop spatial multiplexing performance (User-Specific Reference Symbols).....	364
8.9.2	PHICH.....	365
8.9.2.1	FDD and half-duplex FDD.....	365
8.9.2.1.1	Transmit diversity performance.....	365
8.9.2.2	TDD.....	365
8.9.2.2.1	Transmit diversity performance.....	365
8.9.3	PBCH.....	366
8.9.3.1	FDD and half-duplex FDD.....	366
8.9.3.1.1	Transmit diversity performance.....	366
8.9.3.2	TDD.....	366
8.9.3.2.1	Transmit diversity performance.....	366
9	Reporting of Channel State Information.....	366
9.1	General.....	366
9.1.1	Applicability of requirements.....	367
9.1.1.1	Applicability of requirements for different channel bandwidths.....	367
9.1.1.2	Applicability and test rules for different CA configurations and bandwidth combination sets.....	367
9.1.1.2A	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets.....	368
9.1.1.3	Test coverage for different number of component carriers.....	368
9.2	CQI reporting definition under AWGN conditions.....	369
9.2.1	Minimum requirement PUCCH 1-0 (Cell-Specific Reference Symbols).....	369
9.2.1.1	FDD.....	369
9.2.1.2	TDD.....	370
9.2.1.3	FDD (CSI measurements in case two CSI subframe sets are configured).....	371
9.2.1.4	TDD (CSI measurements in case two CSI subframe sets are configured).....	372
9.2.1.5	FDD (CSI measurements in case two CSI subframe sets are configured and with CRS assistance information).....	374
9.2.1.6	TDD (CSI measurements in case two CSI subframe sets are configured and with CRS assistance information).....	376
9.2.1.7	FDD (Modulation and TBS index Table 2 and 4-bit CQI Table 2 are used).....	377
9.2.1.8	TDD (Modulation and TBS index Table 2 and 4-bit CQI Table 2 are used).....	378
9.2.2	Minimum requirement PUCCH 1-1 (Cell-Specific Reference Symbols).....	379
9.2.2.1	FDD.....	379
9.2.2.2	TDD.....	380
9.2.3	Minimum requirement PUCCH 1-1 (CSI Reference Symbols).....	380
9.2.3.1	FDD.....	381
9.2.3.2	TDD.....	382
9.2.4	Minimum requirement PUCCH 1-1 (With Single CSI Process).....	383
9.2.4.1	FDD.....	383
9.2.4.2	TDD.....	384
9.2.5	Minimum requirement PUCCH 1-1 (when <i>csi-SubframeSet-r12</i> and <i>EIMTA-MainConfigServCell-r12</i> are configured).....	386
9.3	CQI reporting under fading conditions.....	387
9.3.1	Frequency-selective scheduling mode.....	387
9.3.1.1	Minimum requirement PUSCH 3-0 (Cell-Specific Reference Symbols).....	388
9.3.1.1.1	FDD.....	388
9.3.1.1.2	TDD.....	389

9.3.1.1.3	FDD (CSI measurements in case two CSI subframe sets are configured and with CRS assistance information)	390
9.3.1.1.4	TDD (CSI measurements in case two CSI subframe sets are configured and with CRS assistance information)	391
9.3.1.1.5	TDD (when <i>csi-SubframeSet-r12</i> is configured)	393
9.3.1.2	Minimum requirement PUSCH 3-1 (CSI Reference Symbol)	395
9.3.1.2.1	FDD	395
9.3.1.2.2	TDD	396
9.3.1.2.3	FDD (Modulation and TBS index Table 2 and 4-bit CQI Table 2 are used)	397
9.3.1.2.4	TDD (Modulation and TBS index Table 2 and 4-bit CQI Table 2 are used)	398
9.3.1.2.5	Void	399
9.3.1.2.6	TDD (when <i>csi-SubframeSet-r12</i> is configured with one CSI process)	399
9.3.2	Frequency non-selective scheduling mode	401
9.3.2.1	Minimum requirement PUCCH 1-0 (Cell-Specific Reference Symbol)	401
9.3.2.1.1	FDD	401
9.3.2.1.2	TDD	403
9.3.2.2	Minimum requirement PUCCH 1-1 (CSI Reference Symbol)	404
9.3.2.2.1	FDD	404
9.3.2.2.2	TDD	405
9.3.3	Frequency-selective interference	407
9.3.3.1	Minimum requirement PUSCH 3-0 (Cell-Specific Reference Symbol)	407
9.3.3.1.1	FDD	407
9.3.3.1.2	TDD	408
9.3.3.2	Void	409
9.3.3.2.1	Void	409
9.3.3.2.2	Void	409
9.3.4	UE-selected subband CQI	409
9.3.4.1	Minimum requirement PUSCH 2-0 (Cell-Specific Reference Symbols)	409
9.3.4.1.1	FDD	409
9.3.4.1.2	TDD	410
9.3.4.2	Minimum requirement PUCCH 2-0 (Cell-Specific Reference Symbols)	411
9.3.4.2.1	FDD	411
9.3.4.2.2	TDD	412
9.3.5	Additional requirements for enhanced receiver Type A	413
9.3.5.1	Minimum requirement PUCCH 1-0 (Cell-Specific Reference Symbol)	414
9.3.5.1.1	FDD	414
9.3.5.1.2	TDD	415
9.3.5.2	Minimum requirement PUCCH 1-1 (CSI Reference Symbol)	416
9.3.5.2.1	FDD	416
9.3.5.2.2	TDD	417
9.3.6	Minimum requirement (With multiple CSI processes)	419
9.3.6.1	FDD	419
9.3.6.2	TDD	422
9.3.7	Minimum requirement PUSCH 3-2	425
9.3.7.1	FDD	425
9.3.7.2	TDD	426
9.3.8	Additional requirements for enhanced receiver Type B	427
9.3.8.1	Minimum requirement PUCCH 1-1 (Cell-Specific Reference Symbols)	427
9.3.8.1.1	FDD	427
9.3.8.1.2	TDD	428
9.3.8.2	Minimum requirement PUCCH 1-1 (CSI Reference Symbols)	430
9.3.8.2.1	FDD	430
9.3.8.2.2	TDD	431
9.3.8.3	Minimum requirement with CSI process	432
9.3.8.3.1	FDD	432
9.3.8.3.2	TDD	434
9.4	Reporting of Precoding Matrix Indicator (PMI)	435
9.4.1	Single PMI	436
9.4.1.1	Minimum requirement PUSCH 3-1 (Cell-Specific Reference Symbols)	436
9.4.1.1.1	FDD	436
9.4.1.1.2	TDD	437
9.4.1.2	Minimum requirement PUCCH 2-1 (Cell-Specific Reference Symbols)	438

9.4.1.2.1	FDD	438
9.4.1.2.2	TDD	439
9.4.1.3	Minimum requirement PUSCH 3-1 (CSI Reference Symbol)	440
9.4.1.3.1	FDD	440
9.4.1.3.2	TDD	441
9.4.1.4	Minimum requirement PUCCH 1-1 (CSI Reference Symbol)	442
9.4.1.4.1	FDD (with 4Tx enhanced codebook)	442
9.4.1.4.2	TDD (with 4Tx enhanced codebook)	443
9.4.1a	Void	445
9.4.1a.1	Void	445
9.4.1a.1.1	Void	445
9.4.1a.1.2	Void	445
9.4.2	Multiple PMI	445
9.4.2.1	Minimum requirement PUSCH 1-2 (Cell-Specific Reference Symbols)	445
9.4.2.1.1	FDD	445
9.4.2.1.2	TDD	446
9.4.2.2	Minimum requirement PUSCH 2-2 (Cell-Specific Reference Symbols)	447
9.4.2.2.1	FDD	447
9.4.2.2.2	TDD	448
9.4.2.3	Minimum requirement PUSCH 1-2 (CSI Reference Symbol)	448
9.4.2.3.1	FDD	448
9.4.2.3.2	TDD	450
9.4.2.3.3	FDD (with 4Tx enhanced codebook)	451
9.4.2.3.4	TDD (with 4Tx enhanced codebook)	452
9.4.3	Void	453
9.4.3.1	Void	453
9.4.3.1.1	Void	453
9.4.3.1.2	Void	453
9.5	Reporting of Rank Indicator (RI)	453
9.5.1	Minimum requirement (Cell-Specific Reference Symbols)	454
9.5.1.1	FDD	454
9.5.1.2	TDD	455
9.5.2	Minimum requirement (CSI Reference Symbols)	456
9.5.2.1	FDD	456
9.5.2.2	TDD	457
9.5.3	Minimum requirement (CSI measurements in case two CSI subframe sets are configured)	458
9.5.3.1	FDD	458
9.5.3.2	TDD	460
9.5.4	Minimum requirement (CSI measurements in case two CSI subframe sets are configured and CRS assistance information are configured)	462
9.5.4.1	FDD	462
9.5.4.2	TDD	464
9.5.5	Minimum requirement (with CSI process)	466
9.5.5.1	FDD	467
9.5.5.2	TDD	468
9.6	Additional requirements for carrier aggregation	470
9.6.1	Periodic reporting on multiple cells (Cell-Specific Reference Symbols)	470
9.6.1.1	FDD	470
9.6.1.2	TDD	472
9.6.1.3	TDD-FDD CA with FDD PCell	473
9.6.1.4	TDD-FDD CA with TDD PCell	475
9.7	CSI reporting (Single receiver antenna)	477
9.7.1	CQI reporting definition under AWGN conditions	477
9.7.1.1	FDD and half-duplex FDD	477
9.7.1.2	TDD	477
9.7.2	CQI reporting under fading conditions	478
9.7.2.1	FDD and half-duplex FDD	478
9.7.2.2	TDD	479
10	Performance requirement (MBMS)	480
10.1	FDD (Fixed Reference Channel)	480
10.1.1	Minimum requirement	481